

## Exercise (Instructions): Grunt Part 2

### Objectives and Outcomes

In this exercise, you will continue to learn to use Grunt, the task runner. You will configure the Grunt file with a set of additional tasks to build your web project. At the end of this exercise, you will be able to:

- Configure a Grunt file with a set of tasks to build your web project from a source.

### Copying the Files and Cleaning Up the Dist Folder

- Next you will install the Grunt modules to copy over files to a distribution folder named dist, and clean up the dist folder when needed. To do this, install the following Grunt modules:

```
1 npm install grunt-contrib-copy --save-dev
2 npm install grunt-contrib-clean --save-dev
```

- You will now add the code to perform the copying of files to the dist folder, and cleaning up the dist folder. To do this, add the following code to *Gruntfile.js*. This should be added right after the configuration of the SASS task.:

```

1  ,
2
3      copy: {
4          html: {
5              files: [
6                  {
7                      //for html
8                      expand: true,
9                      dot: true,
10                     cwd: './',
11                     src: ['*.html'],
12                     dest: 'dist'
13                 }
14             ],
15             fonts: {
16                 files: [
17                     {
18                         //for font-awesome
19                         expand: true,
20                         dot: true,
21                         cwd: 'node_modules/font-awesome',
22                         src: ['fonts/*.'],
23                         dest: 'dist'
24                     }
25                 ]
26             },
27             clean: {
28                 build: {
29                     src: [ 'dist/' ]
30                 }
31             }
32         }

```

- Remember to add the comma after the end of the SASS task.

## Compressing and Minifying Images

- Next we install the grunt-contrib-imagemin module and use it to process the images. To install this module type at the prompt:

```
1  npm install grunt-contrib-imagemin --save-dev
```

- Then, configure the imagemin task as shown below in the Gruntfile:

```

1  ,
2      imagemin: {
3          dynamic: {
4              files: [{
5                  expand: true,                // Enable dynamic expansion
6                  cwd: './',                  // Src matches are relative to
5                  this path
7                  src: ['img/*.{png,jpg,gif}'], // Actual patterns to match
8                  dest: 'dist/'               // Destination path prefix
9              }
10             ]
11         }

```

## Preparing the Distribution Folder and Files

- We are now going to use the Grunt *usemin* module together with *concat*, *cssmin*, *uglify* and *filerev* to prepare the distribution folder. To do this, install the following Grunt modules:

```
1  npm install grunt-contrib-concat --save-dev
2  npm install grunt-contrib-cssmin --save-dev
3  npm install grunt-contrib-uglify --save-dev
4  npm install grunt-filerev --save-dev
5  npm install grunt-usemin --save-dev
```

- Add the following line to the scripts block in *aboutus.html* and *contactus.html*:

```
1      <script src="js/scripts.js"></script>
```

- Next, update the task configuration within the Gruntfile.js with the following additional code to introduce the new tasks:

```

1  ,
2
3      useminPrepare: {
4          foo: {
5              dest: 'dist',
6              src: ['contactus.html','aboutus.html','index.html']
7          },
8          options: {
9              flow: {
10                 steps: {
11                     css: ['cssmin'],
12                     js:['uglify']
13                 },
14                 post: {
15                     css: [{
16                         name: 'cssmin',
17                         createConfig: function (context, block) {
18                             var generated = context.options.generated;
19                             generated.options = {
20                                 keepSpecialComments: 0, rebase: false
21                             };
22                         }
23                     }]
24                 }
25             }
26         }
27     },
28
29     // Concat
30     concat: {
31         options: {
32             separator: ';'
33         },
34
35         // dist configuration is provided by useminPrepare
36         dist: {}
37     },
38
39     // Uglify
40     uglify: {
41         // dist configuration is provided by useminPrepare
42         dist: {}
43     },
44
45     cssmin: {
46         dist: {}
47     },
48
49     // Filerev
50     filerev: {
51         options: {
52             encoding: 'utf8',
53             algorithm: 'md5',
54             length: 20
55         },
56
57         release: {
58             // filerev:release hashes(md5) all assets (images, js and css )
59             // in dist directory
60             files: [{
61                 src: [
62                     'dist/js/*.js',
63                     'dist/css/*.css',

```

```

64         ]
65     }
66 },
67 // Usemin
68 // Replaces all assets with their revved version in html and css files.
69 // options.assetDirs contains the directories for finding the assets
70 // according to their relative paths
71 usemin: {
72     html: ['dist/contactus.html', 'dist/aboutus.html', 'dist/index.html'],
73     options: {
74         assetsDirs: ['dist', 'dist/css', 'dist/js']
75     }
76 }
77 }
78 }

```

- Next, update the jit-grunt configuration as follows, to inform it that useminPrepare task depends on the usemin package:

```

1  require('jit-grunt')(grunt, {
2    useminPrepare: 'grunt-usemin'
3  });

```

- Next, update the Grunt build task as follows:

```

1  grunt.registerTask('build', [
2    'clean',
3    'copy',
4    'imagemin',
5    'useminPrepare',
6    'concat',
7    'cssmin',
8    'uglify',
9    'filerev',
10   'usemin'
11  ]);

```

- Now if you run Grunt, it will create a dist folder with the files structured correctly to be distributed to a server to host your website. To do this, type the following at the prompt:

```

1  grunt build

```

## Conclusions

In this exercise you have learnt how to configure a Grunt file to perform several tasks. You were able to build a distribution folder for your web project.

Mark as completed

