

Core JavaScript

Fundamentals of the Language

April 3, 2018

Peter J. Jones

✉ pjones@devalot.com

🐦 @devalot

<http://devalot.com>



What's In Store

Before Lunch	After Lunch
JavaScript Basics	Object-Oriented Programming
Control Flow	Debugging in the Browser
Object Basics	Exception Handling
Arrays and Builtin Objects	Serialization w/ JSON
Functions and Closures	Best Practices

Approaching JavaScript

- JavaScript might be an object-oriented language with “Java” in the title, but it’s not Java.
- I find that it’s best to approach JavaScript as a functional (yet imperative) language with some object-oriented features.

A Little Bit About JavaScript

- Standardized as ECMAScript
 - ▶ 5th Edition, 2009 (widely supported)
 - ▶ 6th Edition, 2015 (not so much)
 - ▶ 7th Edition, 2016
 - ▶ 8th Edition, 2017
- Special-purpose language
- Dynamically typed (with weak typing)
- Interpreted and single threaded
- Prototype-based inheritance (vs. class-based)
- Nothing really to do with Java
- Weird but fun

Not a General Purpose Language

- JavaScript is **not** a general-purpose language
- There are no functions for reading from or writing to files
- I/O is heavily restricted

But, It's Not Just for the Browser

- Outside of the browser there are libraries that help make JavaScript act like a general purpose language.
- Tools such as Node.js add missing features to JS
- Weigh the pros and cons of using JS outside the browser

Why JavaScript?

- It's the language of the web
- Runs in the browser, options to run on server
- Easy to learn partially
- Harder to learn completely

JavaScript Syntax Basics

- Part of the “C” family of languages
- Whitespace is insignificant (including indentation)
- Blocks of code are wrapped with curly braces: `{ ... }`
- Expressions are terminated by a semicolon: `;`

A Note About Semicolons

- Semicolons are used to terminate expressions.
- They are optional in JavaScript.
- Due to the minification process and other subtle features of the language, you should always use semicolons.
- When in doubt, use a semicolon.

The Browser's JavaScript Console

- Open your browser's debugging console:
 - ▶ Command-Option-J on a Mac
 - ▶ F12 on Windows and Linux
- Enter the following JavaScript:

```
console.log("Hello World");
```

Simple Console Debugging

- The browser's "console" is a line interpreter (REPL)
- All major browsers are converging to the same API for console debugging
- Can use it to set breakpoints
- Lets you see scoped variables and context
- Can set a conditional breakpoint
- `console.log` is equivalent to `printf`

Primitive Values vs. Objects

- Primitive Values:

```
"Hello World"; // Strings
42;             // Numbers
true && false;  // Boolean
null;           // No value
undefined;      // Unset
```

- Objects (arrays, functions, etc.)

Variables in JavaScript

```
var x;           // undefined  
var y = "Foo";   // String  
var z = 5;        // Number
```

Declaring and Initializing Variables

- Declare variables to make them local:

```
var x;
```

- You can initialize them at the same time:

```
var n = 1;
```

```
var x, y=1, z;
```

- If you don't declare a variable with `var`, the first time you assign to an undefined identifier it will become a global variable.
- If you don't assign a value to a new variable it will be `undefined`

Variable Naming Conventions

- Use camelCase: `userName`, `partsPerMillion`
- Allowed: letters, numbers, underscore, and `$`
- Don't use JavaScript keywords as variable names
- Always start with a lowercase letter

(All identifiers can be made up of valid Unicode characters. Don't go crazy, not all browsers support this. Stick to UTF-8 identifiers.)

undefined and null

- There are two special values: `null` and `undefined`
- Variables declared *without* a value will start with `undefined`
- Setting a variable to `null` usually indicates “no appropriate value”

Numbers

- All numbers are 64bit floating point
- Integer and decimal (9 and 9.8 use the same type)
- Keep an eye on number precision:

```
0.1 + 0.2 == 0.3; // false
```

- Special numbers: NaN and Infinity

```
NaN == NaN; // false
```

```
1 / 0; // Infinity
```

How Do You Deal with Numeric Accuracy?

- Use a special data type like Big Decimal.
- Round to a fixed decimal place with `num.toFixed(2);`
- Only use integers (e.g., for money, represent as cents)

Strings

- Use double or single quotes (no difference between them):

```
"Hello" // Same as...  
'Hello'
```

- Typical backslash characters works (e.g., `\n` and `\t`) in both types of strings.
- Operators:

```
"Hello" + " World"; // "Hello World"  
"Lucky " + 21;      // "Lucky 21"  
"Lucky " - 21;      // NaN  
"1" - 1             // 0
```

Value Coercion

- JavaScript is loosely typed (uni-typed)
- Implicit conversion between “types” as needed
- Usually in unexpected ways:

```
8 * null; // 0
```

```
null > 0; // false
```

```
null == 0; // false
```

```
null >= 0; // true
```

JavaScript Comments

- Single-line comments:

// Starts with two slashes, runs to end of line.

- Multiple-line comments:

/ Begins with a slash and asterisk.*

Also a comment.

*Ends with a asterisk slash. */*

Exercise: Using Primitive Types

- 1 Open the following file:

`src/www/js/primitives/primitives.js`

- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

JavaScript Operators

Arithmetic	+	-	*	/	%	**		
Shortcut	+=	-=	*=	/=	%=	**=		
Inc/Dec	++n	n++	--n	n--				
Bitwise	~	&		^	>>	<<	>>>	
Comparison	>	>=	<	<=				
Equality	==	!=	===	!==				
Logic	!	&&						
Object	.	[]						
String	+							

(Most operators have assignment shortcut versions.)

Sloppy Equality

- The traditional equality operators in JS are sloppy
- That is, they do implicit type conversion

```
"1" == 1;    // true
```

```
[3] == "3";  // true
```

```
0 != "0";    // false
```

```
0 != "";     // false
```


Strict Equality

More traditional equality checking can be done with the `===` operator:

```
"1" === 1;    // false
```

```
0 === "";    // false
```

```
"1" !== 1;    // true
```

```
[0] !== "";   // true
```

(This operator first appeared in ECMAScript Edition 3, circa 1999.)

Same-Value Equality

Similar to “===” with a few small changes:

```
Object.is(NaN, NaN); // true
```

```
Object.is(+0, -0); // false
```

(This function first appeared in ECMAScript Edition 6, 2015.)

What Is true and What Is false?

- Things that are false:

```
false;  
null;  
undefined;  
""; // The empty string  
0;  
NaN;
```

- Everything else is true, including:

```
"0";      // String  
"false";  // String  
[];       // Empty array  
{};      // Empty object  
Infinity; // Yep, it's true
```

Boolean Operators: && (Conjunction)

`a && b` returns either `a` or `b` and short circuits:

```
if (a) {  
    return b;  
} else {  
    return a;  
}
```

Boolean Operators: || (Disjunction)

`a || b` returns either `a` or `b` and short circuits:

```
if (a) {  
    return a;  
} else {  
    return b;  
}
```

Boolean Operators: !

Boolean negation: !:

```
var x = false;  
var y = !x; // y is true
```

Double negation: !!:

```
var n = 1;  
var y = !!n; // y is true
```

Exercise: Boolean Operators

- Experiment with `&&`:

```
0 && console.log("Yep");  
1 && console.log("Yep");
```

- Experiment with `||`:

```
0 || console.log("Yep");  
1 || console.log("Yep");
```

Conditional Statements

```
if (expression) { then_part; }
```

```
if (expression) {  
    then_part;  
} else {  
    else_part;  
}
```


Chaining Conditionals

Shorthand:

```
if (expression) {  
    then_part;  
} else if (expression2) {  
    second_then_part;  
} else {  
    else_part;  
}
```

Long form:

```
if (expression) {  
    then_part;  
} else {  
    if (expression2) {  
        second_then_part;  
    } else {  
        else_part;  
    }  
}
```

Switch Statements

Cleaner conditional (using strict equality checking):

```
switch (expression) {  
  case val1:  
    then_part;  
    break;  
  
  case val2:  
    then_part;  
    break;  
  
  default:  
    else_part;  
    break;  
}
```

Don't forget that `break;` statement!

The Major Looping Statements

- Traditional for:

```
for (var i=0; i<n; ++i) { /* body */ }
```

- Traditional while:

```
while (condition) { /* body */ }
```

- Traditional do ... while:

```
do { /* block */ } while (condition)
```

- Object Property Version of for:

```
for (var prop in object) { /* body */ }
```

Traditional for Loops

- Just like in C:

```
for (var i=0; i<10; ++i) {  
    // executes 10 times.  
}
```

- Loops can be labeled and exited with `break`.
- Use `continue` to skip to the next iteration of the loop.

Traditional while Loops

```
var i=0;

while (i<10) {
    ++i;
}
```

Flipped while Loops

```
var i=0;
```

```
do {  
    ++i;  
} while (i<10);
```

Controlling a Loop

- Loops can be labeled and exited with `break`.

```
for (var i=1; i<100; ++i) {  
    if (i % 2 === 0) break;  
    console.log(i);  
}  
// prints 1
```

- Use `continue` to skip to the next iteration of the loop.

```
for (var i=1; i<100; ++i) {  
    if (i % 2 === 0) continue;  
    console.log(i);  
}  
// prints 1, 3, 5, 7, etc.
```

The Ternary Conditional Operator

- JavaScript supports a ternary conditional operator:

`condition ? then : else;`

- Example:

```
var isWarm; // Is set to something unknown.  
var shirt = isWarm ? "t-shirt" : "sweater";
```


Exercise: Experiment with Control Flow

- 1 Open the following file:
`src/www/js/control/control.js`
- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

A Collection of Key/Value Pairs

- Built up from the core types
- A dynamic collection of **properties**:

```
var box = {  
  color: "tan",  
  height: 12  
};
```

```
box.color;           // Getter method  
box.color = "red";   // Setter method
```

```
var x = "color";  
box[x];              // "red"  
box[x] = "blue";    // Alternative syntax
```

Object Basics

- Everything is an object (almost)
- Primitive types have object wrappers (except `null` and `undefined`)
- They remain primitive until used as objects, for performance reasons
- An object is a dynamic collection of properties
- Properties can be functions

Object Properties

There are four primary ways to work with object properties:

- 1 Dot notation:

```
object.property = "foo";  
var x = object.property;
```

- 2 Square bracket notation:

```
object["property"] = "foo";  
var x = object["property"];
```

- 3 Through the `Object.defineProperty` function

- 4 Using the `delete` function

Property Descriptors

- Object properties have descriptors that affect their behavior
- For example, you can control whether or not a property can be deleted or enumerated
- Typically, descriptors are hidden, use `defineProperty` to change them:

```
var obj = {};
```

```
Object.defineProperty(obj, "someName", {  
  configurable: false, // someName can't be deleted  
  enumerable:   false, // someName is hidden  
  writable:     false, // No setter for someName  
  // ...  
});
```

Object Reflection

Objects can be inspected with...

- the `typeof` operator:

```
typeof obj;
```

- the `in` operator:

```
"foo" in obj;
```

- the `hasOwnProperty` function:

```
obj.hasOwnProperty("foo");
```

Keep in mind that objects “inherit” properties. Use the `hasOwnProperty` to see if an object actually has its own copy of a property.

The typeof Operator

Sometimes useful for determining the type of a variable:

```
typeof 42;           // "number"  
typeof NaN;         // "number"  
typeof Math.abs;    // "function"  
typeof [1, 2, 3];   // "object"  
typeof null;        // "object"  
typeof undefined;   // "undefined"
```

(But not all that useful in reality.)

Property Enumeration

- The `for...in` loop iterates over an object's properties in an **unspecified** order.
- Use `object.hasOwnProperty(propertyName)` to test if a property is inherited or local.

```
for (var propertyName in object) {  
    /*  
        propertyName is a string.  
  
        Must use this syntax:  
        object[propertyName]  
  
        Does not work:  
        object.propertyName  
    */  
}
```


Object Keys

- Get an array of all “own”, enumerable properties:

```
Object.keys(obj);
```

- Get even non-enumerable properties:

```
Object.getOwnPropertyNames(obj);
```

Object References and Passing Style

- Objects can be passed to and from functions
- JavaScript is **call-by-sharing** (very similar to call-by-reference)
- Watch out for functions that modify your objects!
- Remember that `===` compares references
- Since `===` only compares references, it only returns `true` if the two operands are the same object in memory
- There's no built in way in JS to compare objects for similar contents

JavaScript and Mutability

- All primitives in JavaScript are immutable
- Using an assignment operator just creates a new instance of the primitive
- You can think of primitives as using **call-by-value**
- Unless you used an object constructor for a primitive!
- Objects are mutable (and use **call-by-sharing**)
- Their values (properties) can change

Exercise: Create a copy Function

- 1 Open the following file:
`src/www/js/copy/copy.js`
- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

Hints:

- `for (var prop in someobj) { /* ... */ }`
- `someobj.hasOwnProperty(prop)`

The Object.assign Function

Copies properties from one object to another:

```
var o1 = {a: 1, b: 2, c: 3};  
var o2 = { };
```

```
Object.assign(o2, o1);  
console.log(o2);
```

Produces this output:

```
{ a: 1, b: 2, c: 3 }
```

(This function first appeared in ECMAScript Edition 6, 2015.)

The String Object

- 16 bit unicode characters (UCS-2, not quite UTF-16)
- Single or double quotes (no difference)
- Similar strings are `===` equal (checks contents)
- `>=` ES5 supports multiple line literals using a backslash

String Properties and Instance (Prototype) Methods

- `str.length`
- `str.charAt(i);`
- `str.concat();`
- `str.indexOf(needle);`
- `str.slice(iStart, iEnd);`
- `str.substr(iStart, length);`
- `str.replace(regex|substr, newSubStr|function);`
- `str.toLowerCase();`
- `str.trim();`

The Number Object

- Constants:

- ▶ `Number.MAX_VALUE`
- ▶ `Number.NaN`
- ▶ `Number.POSITIVE_INFINITY`
- ▶ etc.

- Generic Methods:

- ▶ `Number.isInteger(n);`
- ▶ `Number.isFinite(n);`
- ▶ `Number.parseFloat(s);`
- ▶ `Number.parseInt(s);`

- Prototype Methods:

- ▶ `num.toString();`
- ▶ `num.toFixed();`
- ▶ `num.toExponential();`

The Math Object

- Constants:

- ▶ `Math.E`
- ▶ `Math.LOG2E`
- ▶ `Math.PI`
- ▶ etc.

- Generic Functions:

- ▶ `Math.abs(n)`;
- ▶ `Math.pow(n, e)`;
- ▶ `Math.sqrt(n)`;
- ▶ etc.

The Date Object

- An instance of the Date object is used to represent a point in time
- Must be constructed:

```
var d = new Date(); // current date  
var d = new Date("Wed, 28 Jan 2015 13:30:00 MST");
```

- Months start at 0, days start at 1
- Timestamps are unix time:

```
d.getTime(); // 1422477000000
```

The Date Object (functions)

- Generic Methods:

- ▶ `Date.now();`
- ▶ `Date.UTC();`
- ▶ `Date.parse("March 7, 2014");`

- Prototype Methods:

```
var d = new Date();
```

```
d.getMonth();
```

```
d.getHours();
```

```
d.getMinutes();
```

```
d.getFullYear(); // Don't use d.getYear();
```

```
d.setYear(1990);
```

The Array Object

- Arrays are objects that behave like traditional arrays
- Use arrays when order of the data should be sequential

The Array Object (Examples)

- Creating Arrays:

// Array literal:

```
var myArray = [1, 2, 3];
```

// Using the constructor function:

```
var myArray = new Array(1, 2, 3);
```

- Functions/Methods:

```
var a = [1, 2, 3];
```

```
a.length; // 3
```

```
Array.isArray(a); // true (>= ES5)
```

```
typeof a; // "object" :(
```

Array Cheat Sheet

- Insert: `a.unshift(x)`; **or** `a.push(x)`;
- Remove: `a.shift()`; **or** `a.pop()`;
- Combine: `var b = a.concat([4, 5])`;
- Extract: `a.slice(...)`; **or** `a.splice(...)`;
- Search: `a.indexOf(x)`;
- Sort: `a.sort()`;

Array Enumeration

WARNING: Use `for`, not `for...in`. The latter doesn't keep array keys in order!

```
for (var i=0; i < myArray.length; ++i) {  
    // myArray[i]  
}
```

Introduction to Functions

- “The best part of JavaScript”
- Functions are used to implement **many** features in JS:
 - ▶ Classes, constructors, and methods
 - ▶ Modules, namespaces, and closures
 - ▶ And a whole bunch of other stuff

Defining a Function

There are several ways of defining functions:

- Function statements (named functions)
- Function expression (anonymous functions)
- Arrow functions (new in ES2015)

Function Definition (Statement)

```
function add(a, b) {  
  return a + b;  
}
```

```
var result = add(1, 2); // 3
```

- This syntax is known as a **function definition statement**. It is only allowed where statements are allowed. This is when the distinction between statements and expressions becomes important.
- Most of the time you should use the expression form of function definition.

Function Definition (Expression)

```
var add = function(a, b) {  
  return a + b;  
};
```

```
var result = add(1, 2); // 3
```

- Function is callable through a variable
- Name after function is optional
- We'll see it used later

Function Invocation

- Parentheses are mandatory in JavaScript for function invocation
- Any number of arguments can be passed, regardless of the number defined
- Extra arguments won't be bound to a name
- Missing arguments will be `undefined`

Function Invocation (Example)

```
var add = function(a, b) {  
  return a + b;  
};
```

```
add(1)           // a is 1, b is undefined
```

```
add(1, 2)        // a is 1, b is 2
```

```
add(1, 2, 3)     // No name for 3.
```

Function Invocation and Parentheses

```
var add = function(a, b) {return a + b;};
```

```
var x = add;           // x is now a function object
```

```
x(1, 2);               // Same as add(1, 2);
```

```
var y = add(1, 2);     // y is 3
```

Functions that Return a Value

In order for a function to return a value to its caller, it must use the `return` keyword.

```
var add = function(a, b) {  
    // WRONG! Computes a sum then throws it away.  
    a + b;  
};
```

vs.

```
var add = function(a, b) {  
    return a + b; // CORRECT!  
};
```

Be Careful with Your Line Breaks

This:

```
var f = function(a, b) {  
    return  
        a + b;  
};
```

Instead, write:

```
var f = function(a, b) {  
    return a +  
        b;  
};
```

Turns into:

```
var f = function(a, b) {  
    return;  
    a + b;  
};
```


Special Function Variables

Functions have access to two special variables:

- `arguments`: An object that encapsulates all function arguments
- `this`: The object the function was called through

Rules for Using the arguments Variable

- Access all arguments, even unnamed ones
- Array-like, but not an actual array
- Only has length property
- Should be treated as read-only (never modify!)
- To treat like an array, convert it to one

```
var arr = Array.prototype.slice.call(arguments);
```

or, slightly more popular (but wasteful):

```
var arr = [].slice.call(arguments);
```

or, with ES6:

```
var args = Array.from(arguments);
```

Built-in Functions (Types and Conversions)

`isNaN(num)`: Safely test if num is NaN

`isFinite(num)`: Test if num is **not** NaN or Infinity

`parseInt(str)`: Convert a string to a number (integer)

`parseFloat(str)`: Convert a string to a number (float)

Exercise: Function Arguments and Parsing

- 1 Open the following file:

`src/www/js/parse/parse.js`

- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

Variable Scope

- **Scope** refers to how long a variable is alive and what code can see it
- There are basically two types of scope: **global** and **local**
- Functions are the only way to create a new local scope (with a few exceptions)
- If you don't use `var` then variables are **global**

Example: Identify the Scope For Each Variable

```
var a = 5;
```

```
function foo(b) {
```

```
  var c = 10;
```

```
  d = 15;
```

```
  if (d === c) {
```

```
    var e = "error: wrong number";
```

```
    console.log(e);
```

```
  }
```

```
  var bar = function(f) {
```

```
    var c = 2;
```

```
    a = 12;
```

```
    return a + c + b;
```

```
  };
```

```
}
```

Scope Tips

- Avoid using (and polluting) the global scope
- Use scoping to create namespaces (modules) your code
- You can “hide” things by wrapping them in a function
- Closures are born out of using lexical scope
- We'll see more of this later. . .
- No block scope

Exercise: Hoisting (Part 1 of 2)

What will the output be?

```
function foo() {  
  x = 42;  
  var x;  
  
  console.log(x); // ?  
  return x;  
}
```


Answer: Hoisting (Part 1 of 2)

This:

```
function foo() {  
  x = 42;  
  var x;  
  
  console.log(x); // ?  
  return x;  
}
```

Turns into:

```
function foo() {  
  var x;  
  x = 42;  
  
  console.log(x);  
  return x;  
}
```

Exercise: Hoisting (Part 2 of 2)

And this one?

```
function foo() {  
  console.log(x); // ?  
  var x = 42;  
}
```

Answer: Hoisting (Part 2 of 2)

This:

```
function foo() {  
  console.log(x); // ?  
  var x = 42;  
}
```

Turns into:

```
function foo() {  
  var x;  
  console.log(x);  
  x = 42;  
}
```

Explanation of Hoisting

- Hoisting refers to when a variable declaration is lifted and moved to the top of its scope (only the declaration, not the assignment)
- Function statements are hoisted too, so you can use them before actual declaration
- JavaScript essentially breaks a variable declaration into two statements:

```
var x=0, y;
```

// Is interpreted as:

```
var x=undefined, y=undefined;
```

```
x=0;
```

Introducing Higher-order Functions

The `forEach` function is a good example of a *higher-order* function:

```
var a = [1, 2, 3];  
  
a.forEach(function(val, index, array) {  
    // Do something...  
});
```

Or, less idiomatic:

```
var f = function(val) { /* ... */ };  
a.forEach(f);
```

Array Testing

- Test if a function returns true on all elements:

```
var a = [1, 2, 3];
```

```
a.every(function(val) {  
    return val > 0;  
});
```


- Test if a function returns true at least once:

```
a.some(function(val) {  
    return val > 2;  
});
```


Higher-order Array Functions

- `a.filter(f)` :: New array filtered with a predicate `f`
- `a.map(f)` :: New array after transforming with `f`
- `a.reduce(f)` :: **Fold** an array into something else using `f`

Filtering an Array with a Predicate Function



Mapping a Function Over an Array



Example: Folding an Array with reduce

```
var a = [1, 2, 3];  
  
// Sum numbers in `a`.  
var sum = a.reduce(function(acc, elm) {  
    // 1. `acc` is the accumulator  
    // 2. `elm` is the current element  
    // 3. You must return a new accumulator  
    return acc + elm;  
}, 0);
```

Exercise: Arrays and Functional Programming

- 1 Open the following file:

`src/www/js/array/array.js`

- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

Hint: Use <https://developer.mozilla.org/> for documentation.

Anonymous Functions

- A function expression without a name:

```
var anon = function() {};
```

- Pros:

- ▶ Powerful
- ▶ Functions can be passed as arguments
- ▶ Defined inline

- Cons:

- ▶ Difficult to test in isolation
- ▶ Discourages code re-use

Anonymous Functions (Tips)

- Name your anonymous functions for debugging

```
numbers.forEach(function foo(e) {  
    console.log(e);  
});
```

- Name is scoped to the inside of the anonymous function so it can refer to itself, easier to debug; errors reference the function name

Functions as Callbacks

- When a function is provided as an argument as something to be invoked inline, or under specific circumstances (like an event):

```
function runCallback(callback) {  
    // does things  
    return callback();  
}
```

- Functions that take functions as arguments are called *higher-order* functions.

Functions as Timers

- Establish delay for function invocation:

```
// setTimeout(func, delayInMs[, arg1, argn]);  
var timer = setTimeout(func, 500);
```

- Use `clearTimeout(timer)` to cancel
- Establish an interval for periodic invocation

```
setInterval(func, ms);  
clearInterval(timer);
```

Closures: Basics

- One of the most important features of JavaScript
- And often one of the most misunderstood & feared features
- But, they are all around you in JavaScript
- Happens automatically when you use function expressions

Closures: Definitions

- Bound variable: local variables created with `var` or `let` are said to be *bound*.
- Free variable: Any variable that isn't bound and isn't a global variable is called a *free* variable.
- A function that uses free variables *closes around* them, capturing them in a *closure*.
- A closure is a new scope for free variables.

Closures: Example

```
function outer() {  
    var name = "Grim";  
  
    var inner = function() {  
        console.log(name);  
    };  
  
    return inner;  
}
```

// Invoke 'outer' and get a function back:

```
var f = outer();
```

// Sometime in the future...

```
f();
```

See: <src/examples/js/closure.html>

Closures: Practical Example

```
var Foo = function() {  
  
    var privateVar = 42;  
  
    var getter = function() {  
        return privateVar;  
    };  
  
    return {  
        getPrivateVar: getter,  
    };  
};  
  
var x = Foo();  
x.getPrivateVar(); // 42
```

Exercise: Sharing Scope

- 1 Open the following file:
`src/www/js/closure/closure.js`
- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

Loops and Closures

```
// What will this output?  
for (var i=0; i<3; i++) {  
    setTimeout(function(){  
        console.log(i);  
    }, 1000*i);  
}  
console.log("Howdy!");
```

Adding Context to a Scope

- We already discussed **scope**
 - ▶ Determines visibility of variables
 - ▶ Lexical scope (location in source code)
- There is also **context**
 - ▶ Refers to the location a function was invoked
 - ▶ Dynamic, defined at runtime
 - ▶ Context is accessible as the `this` variable

Context Example

```
var apple  = {name: "Apple",  color: "red"   };  
var orange = {name: "Orange", color: "orange"};  
  
var logColor = function() {  
    console.log(this.color);  
};  
  
apple.logColor  = logColor;  
orange.logColor = logColor;  
  
apple.logColor();  
orange.logColor();
```

Context and the `this` Keyword

- The `this` keyword is a reference to “the object of invocation”
- Bound at invocation (depends on the call site)
- Allows a method to reference the “current” object
- A single function can then service multiple objects
- Central to prototypical inheritance in JavaScript

How JavaScript Sets the `this` Variable

- Resides in the global binding
- Inner functions do not capture parent's `this` (there are several workarounds such as `var self = this;`, `bind`, and ES6 arrow functions)
- The `this` object can be set manually! (Take a look at the `call`, `apply`, and `bind` functions.)

Constructor Functions and the new Operator

What's going on when you use new?

```
var m = new Message("pjones@devalot.com", "Hello");  
m.send(); // calls `Message.prototype.send`  
           // with `this` set to `m`
```

Writing a Constructor Function

```
var Message = function(sender, content) {  
    this.sender = sender;  
    this.content = content;  
};  
  
Message.prototype.send = function() {  
    if (this.content.length !== 0) {  
        console.log(this.sender, this.content);  
    }  
};
```

The new Keyword

```
var m = new Message("pjones@devalot.com", "Hello");  
m.send(); // calls `Message.prototype.send`  
           // with `this` set to `m`
```

The new operator does the following:

- ❶ Creates a new, empty object
- ❷ Sets up inheritance for the object and records which function constructed the object.
- ❸ Calls the function given as its operand, setting `this` to the newly created object

Implementing a Fake new Operator

```
var fakeNew = function(func) {  
  // Step 1. Create an object with proper inheritance:  
  var newObject = Object.create(func.prototype);  
  
  // Step 2. Invoke the constructor:  
  func.call(newObject);  
  
  // Step 3. Return the new object:  
  return newObject;  
};
```

Exercise: Constructor Functions

- 1 Open the following file:
`src/www/js/constructors/constructors.js`
- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

Introduction to Debugging

- All modern browsers have built-in JavaScript debuggers
- We've been using the debugging console the entire time!

Browser Debugging with the Console

- The console object:
 - ▶ Typically on window (doesn't always exist)
 - ▶ Methods
 - ★ `log`, `info`, `warn`, and `error`
 - ★ `table(object)`
 - ★ `group(name)` and `groupEnd()`
 - ★ `assert(boolean, message)`

Accessing the Debugger

- In the browser's debugging window, choose **Sources**
- You should be able to see JavaScript files used for the current site

Setting Breakpoints

There are a few ways to create breakpoints:

- Open the source file in the browser and click a line number
- Right-click the line number to create conditional breakpoints
- Use the `debugger;` statement in your code

Stepping Through Code

- After setting breakpoints, you can reload the page (or trigger a function)
- Once the debugger stops on a breakpoint you can step through the code using the buttons in the debugger
 - ▶ Step In: Jump into the current function call and debug it
 - ▶ Step Over: Jump over the current function call
 - ▶ Step Out: Jump out of the current function

Console Tricks

- `$_` the value of the last evaluation
- `$0—$4` last inspected elements in historical order
- `$("selector")` returns first matching node (CSS selector)
- `$$("selector")` returns all matching nodes
- `debug(function)` sets a breakpoint in function
- `monitor(function)` trace calls to function

Exception Basics

- Errors in JavaScript propagate as exceptions
- Dealing with errors therefore requires an exception handler
- Keywords for exception handling:
 - ▶ `try`: Run code that might throw exceptions
 - ▶ `catch`: Capture a propagating exception
 - ▶ `throw`: Start exception processing
 - ▶ `finally`: Resource clean-up handler

Example: Throwing an Exception

When a major error occurs, use the `throw` keyword:

```
if (someBadCondition) {  
    throw "Well, this is unexpected!";  
}
```

Built-in Exception Objects

- `Error`: Generic run-time exception
- `EvalError`: Errors coming from the `eval` function
- `RangeError`: Number outside expected range
- `ReferenceError`: Variable used without being declared
- `SyntaxError`: Error while parsing code
- `TypeError`: Variable not the expected type
- `URIError`: Errors from `encodeURIComponent` and `decodeURIComponent`

Creating Your Own Exception Object

This looks more traditional, but it's missing valuable information.

```
function ShoppingCartError(message) {  
  this.message = message;  
  this.name     = "ShoppingCartError";  
}  
  
// Steal from the `Error` object.  
ShoppingCartError.prototype = Error.prototype;  
  
// To throw the exception:  
throw new ShoppingCartError("WTF!");
```


Custom Exceptions: The Better Way

If you start with an `Error` object, you retain a stack trace and error source information (e.g., file name and line number).

```
var error = new Error("WTF!");  
error.name = "ShoppingCartError";  
error.extraInfo = 42;  
throw error;
```

Example: Catching Errors

```
var beSafe = function() {  
  try {  
    // Some code that might fail.  
  }  
  catch (e) {  
    // Errors show up here. All of them.  
  }  
};
```

Example: Catching Exceptions by Type

Most of the time you only want to deal with specific exceptions:

```
var beSafe = function() {  
  try { /* Code that might fail. */ }  
  catch (e) {  
    if (e instanceof TypeError) {  
  
      // If you're here then the error  
      // is a TypeError.  
  
    } else {  
      throw e; // Re-throw the exception.  
    }  
  }  
};
```

Exercise: Exceptions

- 1 Open the following file:

`src/www/js/exceptions/exceptions.js`

- 2 Complete the exercise.
- 3 Run the tests by opening the `index.html` file in your browser.

JavaScript Language Best Practices

- 1 Use a linting tool such as `[JSHint]` or `[ESLint]`
- 2 Avoid polluting the global namespace
- 3 Always use semicolons `(;)`
- 4 Prefer `===` and `!==` (strict comparison)
- 5 CamelCase the names of constructor functions
- 6 Don't use the `eval` function
- 7 Never modify the `arguments` object
- 8 Don't use `for...in` loops with arrays
- 9 Avoid monkey-patching standard objects