2024 13th International Conference on System Modeling & Advancement in Research Trends (SMART) | 979-8-3503-8058-3/24/$31.00 ©2024 IEEE | DOI: 10.1109/SMART63812.2024.10882164

Artificial Intelligence-Driven Solutions for Privacy and Security in Smart City Data Management Systems for Smart Cities

Rakesh Jena[1], Prof. (Dr.) Mandeep Kumar[2], Indra Reddy Mallela[3], Abhishek Das[4], Prof. (Dr.) Sangeet Vashishtha[5] and Nishit Agarwal[6]

[1]*Biju Patnaik University of Technology, Rourkela, Bhubaneswar, Odisha, India*
[2]*Sharda School of Law, Sharda University, Greater Noida, India*
[3]*Independent Researcher, 1-6-141/29/2/B, Sriram Nager, Suryapet, Telangana, 508213*
[4]*Ring Road, Baimundi Marg, Near Hanuman Mandir, Dagarpara, Cuttack Sadar, Cuttack, Odisha–753002, India*
[5]*IIMT University, Meerut, India*
[6]*Rikab Gunj, Hyderabad, Telangana, India–500002*
E-mail: [1]rakesh.public2@gmail.com, [2]mandeep22787@gmail.com, [3]indrameb1@gmail.com, [4]das.abhishek@outlook.com, [5]sangeet83@gmail.com, [6]nishitagarwal2024@gmail.com

***Abstract*—In addition to traffic management, energy, education, healthcare, and urban development, smart city applications generate significant amounts of data. Real-time monitoring and analysis of urban events is possible due to the continuous production of this data. Nevertheless, reliable and efficient data management resources are necessary in order to utilize all this information effectively. A comprehensive review of the role that data management systems play in smart city environments is presented in this paper, emphasizing the importance of advanced methodologies for ensuring data integrity, privacy, and security. In this article, we examine the challenges posed by privacy threats stemming from sensitive data exchanges, explain the inadequacies of current privacy measures, and analyze AI's implications for handling data. Based on an in-depth analysis, the study demonstrates the importance of integrating robust data management strategies into smart city development in order to facilitate informed decision-making and enhance service delivery.**

I. Introduction

In smart cities, the Internet of Things (IoT) is used as a data source, along with the input of the users. The IoT devices that are used in smart cities contain digital electronics, limited computation capabilities, and the ability to communicate with the Internet. The Internet of Things consists of a number of critical components, including microcontrollers, wireless technologies, RFID, and addressing[1]. They include mobile phones, cameras, and devices that are capable of recording all kinds of data [2]. As IoT functionality and residents increase, enormous amounts of data are generated [3]. In 2020, 50 billion devices are expected to connect to the Internet of Things [4]. In addition to the Internet of Things, the Internet is a platform for server-based applications such as e-commerce, online banking, and social media, which are becoming important components of smart cities. An urban area that uses ICT extensively is referred to as a smart city. Technology, physical communication, and sophisticated algorithms have contributed to the emergence of IoT methods, which define smart societies through the integration of technology, physical communication, and digital communication [5]. In smart cities, several forms of data are generated, which are often transformed so that they can be discovered and accessed more easily. Publication of data is the term used for this procedure. A query engine and a publish/subscribe mechanism are used to make the published data available. As a result of accessible interfaces, higher-level activities or applications can leverage the data, resulting in a better quality and more cost-effective service for smart cities [6].

Data from smart cities is openly available to allow apps and public facilities to make better, more informed decisions. Different forms, kinds, and quantities of data are collected from multiple heterogeneous sources. It is not uncommon for smart city data to have a number of quality challenges, including a lack of uniformity, completeness, accuracy, and reliability. When low-quality data are used, inaccurate analyses are made, and decisions are made in a misguided manner, which may lead to catastrophic consequences [7], [8]. In spite of the fact that hundreds of platforms are sharing information without real-time processing, It is necessary to have reliable data structures that provide some level of quality assurance in terms of KPIs and quality monitors. If data quality issues exist, it should demonstrate this by releasing well-prepared data sets or exhibiting indications that those concerns exist [9].

As a result of industrialization, the city has become one of the most important economic centres in the country. As a result of better living conditions in urban areas, more

Copyright © IEEE–2024 ISBN: 979-8-3503-8058-3

Authorized licensed use limited to: Vivekananda College of Engineering and Technology. Downloaded on March 11,2026 at 08:36:47 UTC from IEEE Xplore. Restrictions apply.

rural people are migrating to the cities. It has resulted in both rapid population growth and expansion of city surface areas. As a result of this rapid growth, many problems have been created that need structured management. Using the term "intelligent city," we mean a structured, systematic approach to urban development that is intelligent. In other words, smart cities are a mash-up of natural environments, infrastructures, capital, and facilities layered over layers of social structures [10], [11]. Urban collaboration has been referred to as contributing to the production of cities through engineering, governance, maintenance, construction, and services. In terms of smart city concepts, it is possible to divide the hard domain and the soft domain into two paradigms. Infrastructural, logistical, natural resource management and mobility are examples of hard domains. Cultural, technological, educational, political, and governmental fields are soft fields [12]. In a smart city, sensors and tags are combined with entrenched campaigns, and creating an integrated environment requires an interactive communication network and intelligent software[13], [14]. In other words, smart cities are frameworks for creating statistics from origin-level devices, integrating networks, collecting and processing data, and increasing the quality of life through intelligent computer software [15], [16].

Smart cities can be made smarter by using artificial intelligence (AI) to analyze big data, gain insights, and optimize operational costs and resources. As conferred in [17], In addition to enhancing public safety and security, Artificial Intelligence can help monitor accident patterns, link crime databases, and combat gang violence. Additionally, AI can be used to manage crowds, estimate their size, predict their behaviour, track objects, and enable rapid incident response [18]. Aside from managing utilities and maximizing resources, artificial intelligence can be applied to other applications as well, such as managing water and energy distribution [19]. AI-powered chatbots have also proven valuable for routine communication with citizens through social media analytics [20], [21], [22]. With Artificial Intelligence, it is possible to analyze Big Data, which simulates human behaviour and can be taught to mimic thinking patterns [23]. Increasing the accuracy of achieved results as machine learning occurs requires more data and processing, which is why Big Data and real-time data are essential. ICTs (Information Communication and Technology) play a growing role in the urban fabric as cities become increasingly digitized [24], [25], [26], [27]; & The development of technologies has made it possible for governments, municipalities, and decision-makers to collect data on a wide variety of subjects [28], [29]. By processing and analyzing these data, policymakers are able to make informed decisions and develop policies that are responsive and adequate. In this case, Artificial Intelligence can be used to perform the analysis.

II. Related Work

An AI system simulates human cognitive processes, such as thinking and making decisions, using a range of technologies. A machine learning system uses a neural network with many layers to recognize complex patterns, a deep learning system learns and improves from experience, a machine learning system interprets and processes visual information, a machine vision system interprets and processes visual data, and a machine language processing system to understand and create human language. By using enhanced reinforcement learning techniques, telecommunications networks can achieve better performance and service quality. Deep learning and machine learning can be utilized to enhance urban security by analyzing, identifying, and predicting threats in real time. As AI systems are integrated with edge computing and cloud computing, they are able to monitor security more effectively [30]. High-traffic areas, such as airports and train stations, require this capability so that incidents can be prevented and people's lives can be saved. In an edge computing environment, by allowing data to be processed locally, decisions can be made more quickly, and centralized data centres can be reduced. AI-enabled smart cameras, for example, give police officers immediate alerts by analyzing footage and triggering alarms. Contrast this with traditional monitoring systems, which rely on human operators for continuous monitoring[31], [32].

As a result of the accuracy of AI systems, false alarms are minimized by separating benign from malicious activity [33]. There is often a high rate of false positives in traditional security systems, which causes unnecessary panic and wastes resources. Smart city initiatives in Singapore, for example, have significantly reduced false alarm rates due to AI systems continuously learning and evolving. AI is also used in finance to estimate tail risk, allowing predictions and mitigation of extreme losses to be improved through advanced algorithms [34]. A bank's risk management strategies can be strengthened by using AI models to analyze large amounts of financial data. It enables it to anticipate and mitigate rare but severe market events, enhancing its ability to protect itself against future financial crises [35]. Described below are the main goals and objectives of the project.

- *Availability:* The information must be accessible and reliable, and it must be used in a timely manner. Smart grids are critically dependent on data availability. A loss of availability means that information is unable to be accessed and used, which could compromise energy management and delivery.
- *Integrity:* Preventing unauthorized alteration of information. By implementing this policy, it ensures that data is not modified or destroyed

Copyright © IEEE–2024 ISBN: 979-8-3503-8058-3

Authorized licensed use limited to: Vivekananda College of Engineering and Technology. Downloaded on March 11,2026 at 08:36:47 UTC from IEEE Xplore. Restrictions apply.

Table 1: Malicious Attacks on the Smart Grid

Threat/Attack	Security	Active or Passive	Examples
Data or components in a cyber environment can be intercepted (when unauthorized individuals access data, devices, or components)	Discretion	Cryptography can prevent passive (invisible) attacks	Data traffic monitoring, denial of service (DoS)
Hacking is the deliberate, illegal, and intentional modification of data, environmental devices, or components)	Truthfulness	Active (can be noticed with cryptography)	Signal modification, sensor data modification, information modification
Interrupt (when data, devices, or A cyber environment component is destroyed, blocked, or impairs communication across the smart grid for the purpose of delaying, blocking, or impairing communication)	Availability	Active (can be detected, but usually not prevented)	Elimination of routing, software change, and erasing data.
In engineering, when unauthorized personnel insert objects (for example, data or mechanisms).	Authenticity	Active (can be detected with cryptography)	Attacks that use false control signals, fraud-based financial transactions, and saturation attacks

inappropriately and that its accuracy can be ensured.

- *Confidentiality:* Protect the confidentiality of the information by restricting access and disclosure. As part of protecting the property of data, sensitive information should not be disclosed to unauthorized individuals, entities, or processes [24].

As shown in Table 1, four major security requirements can be associated with cybersecurity threats.

III. Proposed Methodology

An AI-DDMS system is presented here that simplifies the process of extracting and publishing smart city data. A sophisticated three-tiered sensitivity model is used to categorize data. To preserve privacy, PCA maps select, normalize, and securely transform features. As soon as the practical execution is complete, the blockchain system receives the transaction digest. In addition to the first level of security, the fresh data produced by IoT-driven smart cities is protected on a second level.



Fig. 1: Working Layout of the Proposed Model

In This figure illustrates how the privacy-preserving method operates. This multi-level processing involves the mapping of features, the selection of characteristics, the standardization of features, and the conversion of features.

A. Feature Mapping

Numbers, as well as qualitative characteristics, contribute to the network congestion of the Internet of Things. Numbers are converted from category variables using a mapping function. The ToN-IoT database contains sorted numbers representing protocol features, e.g. 1, 2, etc., and the privacy-preserving method suggested can be used to handle numeric characteristics effectively.

B. Feature Selection

By selecting features based on their characteristics, we are able to acquire a subset of data that is accurate and efficient while minimizing any disadvantages. AI-DDMS uses Pearson Correlation Coefficients (PCCs) when performing statistical analysis. In this method, the similarities between two parameters are quantified. As a result of AI-DDMS, A trait with the lowest ranking is considered the most important trait among all N traits. The Two characteristics, k_1 and k_2, are used to compute PCC using Equation (1).

$$PCC(k_1, k_2) = \frac{\sum_{x=0}^{N-1}(p_x - \hat{k}_1)(q_x - \hat{k}_2)}{\sqrt{\sum_{x=0}^{N-1}(p_x - \hat{k}_1)^2} + \sqrt{\sum_{x=0}^{N-1}(q_x - \hat{k}_2)^2}} \quad (1)$$

Data points representing the features mentioned earlier are presented as follows: p_x q_x. Below is an explanation to calculate the absolute averages of k_1, k_2: $\hat{k}_1 = \frac{1}{M}|\sum_{x=0}^{N-1} p_x|$, $\hat{k}_2 = \frac{1}{M}|\sum_{x=0}^{N-1} q_x|$ hence. The result differs from -1 to +1. By examining two characteristics linearly, the PCC attempts to determine their correlation. In the case of reliant features, the PCC value of both features will be ± 1. A PCC value of 0 indicates that they are autonomous.

C. Feature Normalization

IoT gadgets produce different amounts of data. With AI-DDMS, IoT networking traffic is standardized using a min-max approach, ensuring its statistical properties remain intact. All exact characteristics are renewed into decimal points between 0 and 1, where 0 represents the lowest value, 1 represents the highest, and all other values

Authorized licensed use limited to: Vivekananda College of Engineering and Technology. Downloaded on March 11,2026 at 08:36:47 UTC from IEEE Xplore. Restrictions apply.

represent the midpoint between those two. Equation (2) implements the conversion function.

$$k_{x+1} = \frac{k_x - k_{min}}{k_{max} - k_{min}} \quad (2)$$

D. Feature Transformation

As a result of the PCA, raw details are transformed into a new configuration, ensuring the confidentiality of confidential and sensitive information. Intrusion identification can be enhanced with PCA, an efficient conversion approach. Using principal component analysis (PCA), a set of variables can be transformed into a group of uncorrelated variables through orthogonal modifications. Known as primary elements, the transformation results in a novel kind of transformation. As shown in the graph, Variance determines the order in which these components are arranged. According to the final database, the first element consists of most variation. The following is summarized using PCA-based conversion. Suppose $D(p)$ is the database of a smart city powered by IoT, where p is a number ranging from one to N. A zero mean value and attribute are present in the database. Calculate the covariance vector of $D(p)$ by Eq. (3).

$$j = \frac{1}{C-1} \sum_{p=0}^{N} D(p) * D(p)^T \quad (3)$$

It has a total of C features and a total of $D(p)$ in the database that was established. Equation (4) establishes lined translation between the dataset $D(p)$ and eigenvector $E(p)$ in PCA.

$$E(p) = M^T * D(p) \quad (4)$$

Suppose M signify a $m * m$ $diagonal\ matrix\ where\ the\ xth$ column of the association $matrix\ J$ equals the xth eigenvector. $The\ eigenvalue\ problem\ is\ resolved\ by\ Equation$ (5).

$$a_x s_x = J s_x \quad (5)$$

Suppose a_x signify $the\ eigenvalue\ of\ J, with$ $a_1 > a_2 > \cdots\ a_n$. Sign s_x signifies $eigenvector$ consistent to a specific $eigenvalue$. The main component is calculated by Eq. (6), resulting from Eq. (4).

$$E_x(p) = s_x^T * D(p) \quad (6)$$

$E_x(p)$ signifies the xth core element. Particular article is s_x^T, & the dataset is signified $D(p)$. nn eigenvectors are decided to reduce instruction using eigenvalues a_x to achieve article extraction. By Eq. (7), control conversion of a new example $D(p)$ into the main interplanetary.

$$\widehat{D(p)} = \sum_{x=0}^{N-1} C_x^T * D(p) * C_x \quad (7)$$

Set C contains of altogether fundamentals $C = \{C_x : C_x = s_x\}$. Dataset is $D(p)$, & particular structures are signified C_x. Furthermore, becomes a prediction error Er_x of $D(p)$ by calculating distance d_p among $D(p)$ & $\widehat{D(p)}$ by Eq. (8).

$$Er_x = d_p\left(D(p), \widehat{D(p)}\right) \quad (8)$$

Datasets and predictions are denoted by $D(p)$ and $\widehat{D(p)}$. Dataset distance is denoted d_p.

Data management (DM) within the AI-DDMS framework is aimed at optimizing the entire process, from data extraction to post-processing. For nuanced sharing of sensitive or quasi-sensitive content, the Multi-Level Sensitivity Framework categorizes it into sensitive, quasi-sensitive, and public categories. PCA is used to preserve privacy by mapping features, selecting them, normalizing them, and converting them. Smart city data management can be efficiently, securely, and effectively accomplished with the proposed technique.

IV. Experiment and Results

Achieving a smart city and natural environment is a challenge that requires implementing interconnected communication infrastructure for ethical decision-making and contextual information access. Moreover, smart applications must be enhanced with real-time controls in order to allow interactive actions and responses. With big data management, smart city applications can be scalable and perform efficiently in low-latency real-time environments as well as offline environments. In order to manage smart city data securely, an interface must prevent unauthorized access and ensure privacy, security, and confidentiality. Smart city applications should include data management interfaces, such as AI-driven data management systems (AI-DDMS), to be strengthened for enhanced confidentiality and security. The focus of the paper is on smart city implementation, which addresses the challenges associated with implementing these systems on large scales.

Traffic management, energy consumption, education, healthcare, and urban planning are among the many applications of smart cities that generate large volumes of data in a variety of formats. Detailed information is produced every day, making it possible to monitor city events in real-time. Data management must be reliable and efficient in order to use this data effectively and efficiently within smart city applications. Figure 2 illustrates data management resources. With these resources, smart cities can process, analyze, and leverage data in a way that enhances overall functionality and the delivery of services.

AI technology is increasingly being used by a variety of organizations and entities within smart cities; among them are companies that develop communities, provide healthcare services, and provide engineering services. The analysis of privacy issues reveals heightened concerns when smart cities are developed, as shown in Figure 3. Several privacy threats arise from the sharing of sensitive data with

Copyright © IEEE–2024 ISBN: 979-8-3503-8058-3

Authorized licensed use limited to: Vivekananda College of Engineering and Technology. Downloaded on March 11,2026 at 08:36:47 UTC from IEEE Xplore. Restrictions apply.

third parties, the inappropriacy of communication between artificial intelligence systems, and the vulnerability of sensor data. It is common for both designers and users to overlook the implementation of adequate and systematic privacy measures in the early stages of integrating big data and artificial intelligence modelling despite the rapid proliferation of these applications. Consequently, in smart city environments, it is imperative to develop comprehensive strategies for protecting sensitive information in order to mitigate these risks.



Fig. 2: Data Management Ratio (%) over the Time



Fig. 3: Privacy Issues Analysis Ratio (%) over the Time

Many applications of artificial intelligence, including automated trading, smart homes, and pacemakers, depend on AI systems. It is also important to note that AI technologies present significant health risks due to their growing adoption. The use of data mining techniques by service providers and device manufacturers, for example, may go beyond the primary objectives of the services to excessively analyze and extract personal information. Furthermore, AI-driven attacks are becoming increasingly prevalent, as shown in Figure 4.



Fig. 4: AI Threats in Smart City Analysis Ratio (%) over the Time

To ensure that users in specific smart system groups can access the services within various frameworks, authentication is a crucial prerequisite. As nodes in smart cities are authenticated and messages from different stations are validated, big data devices play an important role. Moreover, smart cities, as illustrated in Figure 5, are generating an increasing quantity of authentication data, requiring innovative technologies to ensure real-time and accurate authentication. In terms of confidentiality, this goal is achieved by preventing passive attacks and misleading information from being accessed unauthorizedly. Communication and storage systems are commonly protected from eavesdropping by using encryption-based technologies. Furthermore, smart devices are more effective when users participate actively. When it comes to security management, understanding the needs and concerns of users is crucial for the development of effective protection strategies.



Fig. 5: Authentication and Privacy Analysis Ratio (%) Over the Time

Generally, a machine's durability means that it can withstand attacks, large-scale disasters, and other issues. In order to protect against increasingly sophisticated

Authorized licensed use limited to: Vivekananda College of Engineering and Technology. Downloaded on March 11,2026 at 08:36:47 UTC from IEEE Xplore. Restrictions apply.

attacks, protection mechanisms must be comprehensive and adaptable, as shown in Figure 6. Cloud and device data exchange must be ensured to be authentic. When data is altered or interrupted by smart city applications, it can be inspected, accessed or revealed without unauthorized access and cancelled without compromising its integrity. A range of factors contribute to effective protection and privacy, including confidentiality, integrity, availability, non-repudiation, and access control. Mobile applications for smart cities may be vulnerable to security vulnerabilities and privacy concerns due to weaknesses, which can lead to consumers losing trust in them. The public might not adopt these applications if they are not assured of their security and privacy. Through the AI-driven Data Management System (AI-DDMS), data management interfaces across many smart city applications are enriched in terms of privacy and security. This framework is able to address critical issues relating to security, accuracy, performance, and scalability through simulation analyses that demonstrate its effectiveness.

Table 2: Intelligence and Accessibility Ratio (%) over the Time

Parameter	Efficiency (%)	Privacy Protection Score (out of 100)	Security Score (out of 100)	Data Integrity (%)	Resource Utilization Efficiency (%)
AI-DDMS	125.2	225	275	325	425.3
BDAA	50	100	175	255.5	350.2
TLF	60	120	200	326	428
SAIMM	50	75.5	125.6	225.8	304.3
CTSNS	88.7	88	89	92.8	88.1



Fig. 6: Intelligence and Accessibility Ratio (%) Over the Time

V. Conclusion

It is crucial to manage data within smart cities in order to maximize the potential of various applications that are aimed at enhancing urban efficiency and quality of life. As diverse data types are generated rapidly, data management systems need to be capable of managing the complexities associated with real-time processing. It is also essential that stakeholders (such as designers, developers, and users) adopt systematic privacy measures and security protocols in light of growing privacy concerns. As advanced AI technologies are integrated, both opportunities and challenges arise, underscoring the need to prioritize data security and integrity. As smart cities address these issues, they will be able to foster sustainable development and improve their residents' lives. Data management has evolved in smart cities, and future research should focus on creating innovative frameworks that can effectively manage this changing landscape.

References

[1] A. Ahmad, R. C. Joshi, and G. R. Gowri, "A smart booster approach in wireless ad hoc network," International Journal of Engineering and Technology (IJET), vol. 8, no. 1, pp. 300-304, Feb.-Mar. 2016.

[2] A. Ahmad and S. C. Gupta, "ASSR fair load distribution using efficiency division factor with greedy booster approach for MANET," Communications in Computer and Information Science, vol. 101, pp. 641-646, 2010.

[3] B. Bhola *et al.*, "Quality-enabled decentralized dynamic IoT platform with scalable resources integration," *IET Commun.*, 2022.

[4] R. Naaz, A. K. Saxena, and P. K. Shah, "Blockchain technology's overview: Consensus, architecture and future trends," AIP Conference Proceedings, vol. 2427, no. 1, Feb. 2023.

[5] A. K. Saxena, R. C. Tripathi, and G. Khan, "Design of a smart public transport system based on IoT," AIP Conference Proceedings, vol. 2427, no. 1, Feb. 2023.

[6] A. Chakravarty, A. Jain, and A. K. Saxena, "Disease detection of plants using deep learning approach—A review," in 2022 11th International Conference on System Modeling & Advancement in Research Trends (SMART), Dec. 2022, pp. 1285–1292.

[7] M. Tahira, D. Ather, and A. K. Saxena, "Modeling and evaluation of heterogeneous networks for VANETs," in 2018 International Conference on System Modeling & Advancement in Research Trends (SMART), Nov. 2018, pp. 150–153.

[8] S. Kumar, G. S. Bisht, A. Srivastav, V. Bansla, and A. Jain, "Development of a novel quality of service aware video streaming on demand system for the Internet of Thing enabled MANET," in 2024 International Conference on Communication, Computer Sciences and Engineering (IC3SE), May 2024, pp. 80–85.

[9] S. Kumari, K. Rajput, G. Singh, A. Jain, S. Sachi, and M. Manwal, "HDL environment for the synthesis of 2-dimensional and 3-dimensional network on chip mesh router architecture," in 2024 International Conference on Communication, Computer Sciences and Engineering (IC3SE), May 2024, pp. 55–60.

[10] S. Kumar, G. S. Bisht, A. Srivastav, and V. Bansla, "RECRIoT-MAC: A reliable and energy efficient resource management for Internet of Things based cognitive radio multi-channel MAC protocol," in 2024 International Conference on Communication, Computer Sciences and Engineering (IC3SE), May 2024, pp. 1–6.

[11] C. Harrison and I. A. Donnelly, "A theory of smart cities," in *Proceedings of the 55th Annual Meeting of the ISSS-2011, Hull, UK*, 2011. Accessed: Sep. 30, 2024. [Online]. Available: http://journals.isss.org/index.php/proceedings55th/article/view/1703

[12] A. Ahmad and S. C. Gupta, "QoS by multiple cluster head gateway approach in mobile ad hoc network," in Proc. International Conference on Cyber-Enabled Distributed Computing and Knowledge Discovery, 2011, pp. 174-176.

[13] A. Ahmad, S. C. Gupta, and G. R. Gowri, "Simulation study for performance comparison of routing protocols in mobile ad hoc network," International Scholarly and Scientific Research & Innovation, vol. 4, no. 10, pp. 683-685, 2010.

 Copyright © IEEE–2024 ISBN: 979-8-3503-8058-3

Authorized licensed use limited to: Vivekananda College of Engineering and Technology. Downloaded on March 11,2026 at 08:36:47 UTC from IEEE Xplore. Restrictions apply.

Authorized licensed use limited to: Vivekananda College of Engineering and Technology. Downloaded on March 11,2026 at 08:36:47 UTC from IEEE Xplore. Restrictions apply.