Status	Finished
Started	Wednesday, 21 October 2026, 11:52 AM
Completed	Wednesday, 21 October 2026, 12:05 PM
Duration	12 mins 46 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. We can change the tuple once created

b. A tuple maintains the order of items ✓

c. A tuple is unordered

d. None of these

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

a. (1,2,3)(4,5,6)

b. (1,2,3,3,2,1)

c. Error

d. (1,2,3,4,5,6) ✓

Question **3**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

- a. Error ✓
- b. 5
- c. 2
- d. 1

Question **4**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t1 = (55, 44, 33, 22, 11)

x = [t1[i] for i in range(0, len(t1), 2)]

print(x)

- a. [(55,33,11)]
- b. ([55,33,11])
- c. [55, 33, 11] ✓
- d. (55,33,11)

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

- a. TypeError: update() doesn't allow list as a argument.
- b. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}
- c. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓
- d. Name Error

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True ✓
True

b. False
False

c. True
False

d. False
True

Question **7**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

a. 2

b. Error

c. 100

d. 117 ✓

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40)

b. (30, 40, 50)(40, 50, 60, 70, 80)

c. (10, 20, 30, 40) (40, 50, 60, 70, 80)

d. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

a. <class 'int'>

b. <class 'tuple'>

c. <class 'str'> ✓

d. str

Question **10**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

a. True

b. Error

c. Error

d. False ✓

Question **11**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

- a. (3,14,25)
- b. Error
- c. (58,47,36,25)
- d. (36, 25, 14) ✓

Question **12**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

t = (11, 3)

x = 3 * t

print(x)

- a. (11, 3, 11, 3, 11, 3) ✓
- b. [11,11,11,3,3,3]
- c. (11,3,11,11,3,11,11,11,3)
- d. (11,3)(11,3)(11,3)

Question **13**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

- a. It will throw an error as there are two 0 while creating the set.
- b. {0,0,9}
- c. {9}
- d. {0,9} ✓

Question **14**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True ✓

True

b. True

False

c. False

True

d. False

False

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, '10', 50, 20, 60, 30} ✓

b. SynatxError: Different types cannot be used with sets

c. {40, '10', 50, 20, 60, 30}

d. {40, 10, 50, 20, 60, 30}