

Structured Schemas for LLM-Modeler Collaboration in Quantitative Systems Pharmacology Model Calibration

Joel Eliason^{1,*} and Aleksander S. Popel¹

¹Department of Biomedical Engineering, Johns Hopkins University, Baltimore, MD, USA

*Corresponding author: jeliaso2@jh.edu

ORCID: J.E. 0000-0003-2227-8727; A.S.P. 0000-0002-6706-9235

Keywords: quantitative systems pharmacology, model calibration, large language models, parameter extraction, structured validation

Conflict of Interest: A.S.P. receives research funding from Merck and Pfizer in the area of QSP modeling; he is also a founder and holds equity in OptaNova Pharma and Terebra Therapeutics outside the work described therein. The terms of these arrangements are being managed by the Johns Hopkins University in accordance with its conflict-of-interest policies. J.E. declares that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

Funding: This work was supported in part by NIH grants R01CA138264 and U01CA212007 and the Lustgarten Foundation: Pancreatic Cancer Research.

Abstract

Quantitative systems pharmacology (QSP) models require calibration data from published literature, yet manual curation produces inconsistent documentation while large language model (LLM) extraction exhibits hallucination and fabrication errors unacceptable for quantitative modeling. We present MAPLE (Model-Aware Parameterization from Literature Evidence), a framework that uses structured validation schemas as a collaboration interface between LLMs and modelers. Two complementary schemas capture calibration data at different scales: one for isolated experiments that constrain individual parameters through simplified forward models,

and one for clinical and in vivo endpoints that constrain the full model through species-level observables. Both schemas separate data extraction from modeling decisions, capturing literature values with full provenance in a machine-verifiable form. Targeted validators catch characteristic LLM errors: value-in-snippet matching detects hallucinated values, DOI resolution flags fabricated citations, and code execution catches malformed forward models. We evaluate MAPLE on 37 SubmodelTargets and 54 CalibrationTargets for a pancreatic ductal adenocarcinoma (PDAC) QSP model, using two collaboration modes: batch LLM extraction followed by interactive curation, and interactive extraction where modeler and LLM collaborate in real time. Both modes required substantial modeler input: the modeler changed forward model types in 65% of SubmodelTargets, adjusted prior parameters in 46%, and revised source relevance assessments in all files. The LLM produces competent forward-model choices and observable code given sufficient context, and can independently miss or lose track of inputs across long records; the modeler supplies context the LLM cannot infer from a static prompt and reviews each record to catch lapses the validators do not detect, with the schema recording both contributions with full provenance.

Interactively extracted targets embedded modeler effort in the extraction process, producing near-final output. The schemas ensure completeness and enable reproducible, provenance-rich calibration regardless of workflow. This evaluation characterizes the framework on a single QSP model in one disease area, developed by one modeling group, and does not establish performance bounds across therapeutic areas or modeling teams.

1 Introduction

Quantitative systems pharmacology models translate mechanistic understanding of disease biology into predictions of drug response¹. QSP models can comprise tens to hundreds of ordinary differential equations, and calibration requires data from diverse sources including targeted experimental studies and clinical endpoints^{2,3}. Because virtual population generation and virtual clinical trials depend on parameter distributions rather than point estimates^{4,5}, calibration must quantify uncertainty. As QSP increasingly integrates with machine learning^{6,7,8,9,10}, the bottleneck of manual parameter extraction becomes more acute.

Extracting calibration data from literature requires judgment about applicability, uncertainty, and potential biases, with full provenance for reproducibility. A structured representation of such data captures what was measured, under what conditions, with what uncertainty, and how that

measurement relates to model parameters or observables. Some studies isolate specific mechanisms (e.g., in vitro proliferation assays, ex vivo cytotoxicity studies) and directly constrain individual parameters, while clinical and in vivo endpoints constrain the integrated model through observables computed over the full system state.

Manual curation remains the standard approach but is labor-intensive, with inconsistent documentation across individuals and projects. When personnel change, the reasoning behind parameter choices may be lost. Without structured representations, combining constraints from multiple experiments requires ad-hoc scripting with no standard path from extracted data to inference code. Traditional NLP pipelines for automated extraction require task-specific training data^{11,12,13} and do not generalize to the diverse parameter types in QSP modeling.

Large language models offer a more flexible approach. LLMs can identify relevant literature given mechanistic context, read scientific text, and extract information into structured templates^{14,15,16,17,18}. However, LLMs exhibit hallucination and fabrication errors that are unacceptable for quantitative modeling^{19,20,21}. Many of these failure modes, however, are amenable to systematic detection: hallucinated values can be caught by requiring verbatim source text, fabricated citations through DOI resolution, and internal inconsistencies through schema validation. This suggests a workflow where LLMs handle extraction while automated validators catch characteristic errors, with Pydantic²², a Python data validation library, enabling a self-correcting retry loop.

We present MAPLE (Model-Aware Parameterization from Literature Evidence), a framework for LLM-assisted QSP model calibration with four components: (1) model-aware literature search using mechanistic context to guide LLM web search; (2) validated YAML schemas for two calibration regimes (isolated experiments constraining individual parameters, and clinical/in vivo endpoints constraining the full model), separating data extraction from model specification while preserving traceability; (3) targeted validators for hallucination detection (value-in-snippet matching), citation verification (DOI resolution), and code correctness; and (4) code generation for Bayesian inference. We evaluate MAPLE on [SubmodelTargets](#) and [CalibrationTargets](#) for a PDAC QSP model and report metrics on validation performance and extraction reliability. [The LLM is reliable for forward-model choices and observable code when given sufficient context, but cannot judge when context is missing, and can independently miss inputs or lose track of constraints across long](#)

records. The schema and validators make the modeler’s context supply (unit conventions, source-applicability decisions) explicit, and the modeler’s review of every record catches the LLM lapses the validators do not detect, so the calibration record shows both what the LLM produced and what the modeler supplied or corrected.

2 Methods




Figure 1: MAPLE workflow. An LLM searches the literature for a parameter target and extracts a structured YAML target carrying values, provenance, and a forward model. Automated validators gate the YAML, while failures trigger LLM retry. Validated targets are reviewed by the modeler, who may also revise the source or re-extract. Curated targets feed a joint Bayesian inference yielding posteriors with full provenance.

2.1 Model-Aware Literature Search

Figure 1 summarizes the full MAPLE pipeline. The user specifies which model parameters or observables need calibration, and the system builds a prompt that guides an LLM with web search

capability to find relevant experimental literature. The framework supports multiple LLM providers (OpenAI, Anthropic, Google) through a common interface. In this study, we used GPT-5.1 for batch extraction and Claude Opus 4.6 for interactive extraction.

The prompt injects mechanistic context from the model structure: for each target, the system retrieves its name, units, and description. For parameters, it also retrieves the reactions where the parameter appears with rate laws, the species involved, and the broader reaction network. For observables, it retrieves the species and compartments that define the observable. This context guides the LLM toward experiments that constrain the targets. Source exclusion prevents reuse of papers across extractions to promote literature diversity. The prompt also includes the complete schema structure and guidance on common pitfalls (SEM vs. SD conversion, hardcoded constants, source relevance documentation), reducing the retry loop by preventing predictable errors.

2.2 Schema Design

The framework defines two complementary schemas for two calibration regimes. The *SubmodelTarget* schema captures isolated experiments (in vitro assays, single-mechanism studies) that constrain individual model parameters through simplified forward models. The *CalibrationTarget* schema captures clinical and in vivo endpoints that constrain the full model through observables computed over the complete species state. Both schemas share a common design philosophy but differ in how they connect literature data to model parameters and outputs. For clarity, the manuscript refers to these two schemas by name (*SubmodelTarget* and *CalibrationTarget*) rather than using “calibration target” as a general term.

2.2.1 Shared Design Principles

Both schemas enforce a data-first architecture: extraction of what the paper reports is separated from specification of how to use it for calibration. Every extracted numeric value must appear verbatim in a quoted text snippet from the source, creating an auditable trail and enabling automated hallucination detection. Both schemas require structured source documentation (DOI, title, authors), source relevance assessment (indication match, species translation, TME compatibility), and experimental context metadata (species, system type, disease stage). When YAML is parsed, the framework validates all constraints automatically, with structured error messages providing

actionable feedback for the LLM retry loop.

2.2.2 SubmodelTarget: Parameter Priors from Isolated Experiments

The SubmodelTarget schema structures each record into two layers: an *inputs* layer that captures data exactly as reported in the literature (value, units, uncertainty, sample size, source reference, and quoted snippet), and a *calibration* layer that specifies how that data constrains model parameters through a simplified forward model. For time-course data, this is typically a simplified ODE (e.g., exponential growth $dy/dt = k \cdot y$); for derived measurements, an algebraic model may suffice (e.g., $t_{1/2} = \ln(2)/k$). In both cases, the submodel derives from the full QSP model by isolating relevant species. Shared parameter names establish the connection: a proliferation rate named `k_apsc_prolif` in a submodel refers to the same parameter in the full model, allowing posteriors to serve directly as priors for full-model calibration. Each parameter includes a prior distribution with documented rationale, and an error model specifies the likelihood function connecting predictions to data. Supplementary Section 6 provides detailed field descriptions with YAML examples.

Forward model type system. The schema provides 15 built-in forward model types organized in four categories: ODE templates (exponential growth, first-order decay, two-state transitions, logistic growth, saturation, Michaelis-Menten), structured steady-state types for equilibrium measurements, a batch accumulation type for secretion assays, and generic fallbacks (algebraic, direct fit, custom). The complete type system is described in Supplementary Table 1. Each structured model declares its fields as typed roles (calibration parameter, extracted input, reference value, or literal) rather than raw values, allowing the same template to serve different estimation scenarios depending on which field is treated as the unknown.

A complete SubmodelTarget example is provided in Supplementary Section 1; [Figure 2 shows a compact version illustrating the two-layer structure.](#)

2.2.3 CalibrationTarget: Clinical and In Vivo Endpoints

Many calibration constraints come from clinical or in vivo studies where the measurement reflects integrated model behavior. For example, intratumoral CD8+ T cell density reflects the net effect of recruitment, proliferation, exhaustion, and death. The CalibrationTarget schema represents

```

# SubmodelTarget: activated PSC proliferation rate
target_id: psc_proliferation_PDAC_deriv001

# INPUTS layer: literature values with provenance
inputs:
  - name: pdgf_fold_mean
    value: 4.37
    units: dimensionless
    role: target
    source_ref: Schneider2001_PSC_PDGF
    value_snippet: "Cell proliferation (4.37 +/- 0.49- and
                    2.96 +/- 0.39-fold of control)."
```

```

# CALIBRATION layer: how the value constrains the model
calibration:
  parameters:
    - name: k_apsc_prolif
      units: 1/day
      prior:
        distribution: lognormal
        mu: 0.0
        sigma: 1.0
  model:
    type: exponential_growth
    rate_constant: k_apsc_prolif
  independent_variable:
    name: time
    units: day
    span: [0.0, 1.0]
```

Figure 2: Compact SubmodelTarget example. The `inputs` layer records the literature value with the verbatim source snippet that anchors it; the `calibration` layer specifies how that value constrains the model parameter `k_apsc_prolif` through a simplified forward model. Rationale fields and the auxiliary standard-deviation input are omitted for brevity; Supplementary Section 1 gives the complete record.

these full-model endpoints through three components. The *observable* specifies how to compute the measurement from model species as a Python function that receives the solved state and returns a quantity with units; named constants carry provenance traced to a curated reference database or literature source. The *empirical data* block derives summary statistics (median and 95% CI) from literature inputs via Monte Carlo simulation, handling complications like subgroup mixing, SEM-to-SD conversion, and non-Gaussian uncertainty. For intervention studies, a *scenario* block captures treatment context (agents, doses, schedules). Complete examples and schema definitions are provided in Supplementary Sections 7 and 5.

2.2.4 Source Relevance Assessment

Experimental data rarely matches the target model perfectly. The `source_relevance` block documents the translation from source context to model context across several dimensions: indication match (exact, related, proxy, or unrelated), species translation (e.g., mouse to human), evidence type (clinical, in vitro, animal, review), and tumor microenvironment compatibility. Each dimension requires justification when the source deviates from the target model. An `estimated_translation_uncertainty` field quantifies the combined expected uncertainty from all translation factors, which propagates to prior width during inference (e.g., cross-species extraction from a proxy indication might warrant 10-fold uncertainty). Supplementary Section 13 provides detailed field descriptions.

2.2.5 Schema Implementation

Both schemas are implemented using Pydantic²² with typed fields and constraints validated automatically during YAML parsing. Validation error messages are detailed and structured (e.g., reporting field path, expected type, and actual value), providing actionable feedback for the LLM retry loop. SubmodelTarget uses discriminated unions for its 15 forward model types; CalibrationTarget uses a class hierarchy with shared base models. Supplementary Section 5 provides the complete schema definitions and Supplementary Section 12 provides implementation details.

2.3 Validation Framework

Both schemas share a common validation core (DOI resolution, value-in-snippet matching, unit parsing, source relevance checks) with schema-specific extensions. Each validator runs indepen-

dently, and a target must pass all validators before proceeding to downstream use.

2.3.1 Reference Validation

LLMs sometimes generate references to entities that do not exist elsewhere in the document. Reference validators check that every `uses_inputs` reference matches a defined input name, every `source_ref` matches a defined source, parameters referenced in the model exist in the parameter list, and observable definitions reference valid state variables.

2.3.2 Content Validation

Content validators address fabrication of values, citations, and other factual claims. *DOI validation* queries CrossRef for every DOI; title validation further checks that the extracted paper title fuzzy-matches the CrossRef metadata (75% similarity threshold), catching cases where a valid DOI is paired with fabricated bibliographic details. *Value-in-snippet validation* compares each extracted numeric value against its associated source text, providing the primary anti-hallucination defense: when an LLM hallucinates a number, it rarely fabricates a consistent snippet, and the mismatch provides a reliable detection signal. A separate external validator (Section 2.3.3) further verifies that snippets appear in the cited papers. *Unit validation* parses all unit strings using Pint²³ to verify dimensional validity. *Code validation* executes observation and observable code with mock data to verify correct behavior, catching logic errors and signature mismatches before inference. *Hardcoded constant detection* scans code blocks for undocumented numeric literals that should be traced to inputs or reference values. *Scale consistency validation* checks that observable outputs respond appropriately to varying inputs and have expected magnitudes. *Source relevance validators* enforce minimum uncertainty thresholds for cross-species (2-fold), cross-indication (3-fold), and low TME compatibility (10-fold) extractions, ensuring translation uncertainty propagates to prior widths. The fuzzy-match thresholds (75% for titles, 80% for snippets) were set to tolerate minor formatting, punctuation, and OCR differences between extracted and source text while still rejecting genuinely different strings; the cross-species, cross-indication, and low-TME multipliers are conservative minimum uncertainty defaults, applied as floors that the modeler may widen further when source applicability is weaker.

Each validator raises a specific exception class with a `category` attribute (hallucination, fabri-

cation, code, units, reference, structural, prior) that enables aggregation across extraction runs and feeds into the metrics reported in Section 3. Exception messages are designed for the LLM retry loop, including both the specific failure and guidance for correction. Optional Logfire instrumentation²⁴ provides OpenTelemetry-based tracing for debugging extraction failures. Supplementary Section 3 provides implementation details for each validator.

2.3.3 External Validation

An additional external validator verifies that value snippets actually appear in the cited source papers by fetching paper text from Europe PMC and Unpaywall using the DOI, then using fuzzy matching (80% similarity threshold) to locate each snippet. This catches a subtle failure mode where the LLM fabricates plausible-looking snippets that contain the correct value but do not actually appear in the cited paper. Because this requires network access to external APIs, it runs as a separate manual step. [It is provided in the repository as an on-demand verification tool and was applied selectively during curation rather than as part of the automated per-target validation gate, since external full-text availability is uneven across sources; the value-in-snippet check described above is the systematically applied internal anti-hallucination defense.](#)

2.3.4 Structural and CalibrationTarget-Specific Validation

Structural validators check schema-level constraints (time span ordering, required fields per model type, array dimension consistency). CalibrationTarget adds validators for full-model observables: observable code execution against mock species data, a denominator audit for density/fraction observables (catching a common source of order-of-magnitude errors), species existence checks, and distribution code verification that computed summary statistics match reported empirical data within tolerance (1% for median, 10% for CI bounds). Supplementary Section 3 provides implementation details for all validators.

2.4 Code Generation

Validated SubmodelTarget specifications can be automatically translated into Julia scripts for Bayesian inference using Turing.jl²⁵. The translator generates self-contained scripts with observed data constants, forward model functions, prior distributions, and likelihood terms. When multiple

227 targets share parameters (identified by matching parameter names), the translator generates a joint
228 model that declares each shared parameter once and constrains it from all relevant data sources
229 simultaneously, yielding tighter posteriors than independent calibration. We chose to generate com-
230 plete, readable scripts rather than provide a library abstraction, so that users can inspect, modify,
231 and debug the inference model directly. Supplementary Section 4 provides details on the generated
232 code structure, forward model handling, and inference diagnostics.

233 The two schemas connect through a natural calibration pipeline: SubmodelTarget posteriors
234 from isolated experiments become informative priors for full-model calibration against Calibra-
235 tionTarget endpoints. Because SubmodelTarget parameter names match the full model, the poste-
236 rior distributions transfer directly without post-hoc mapping.

237 2.5 Application: PDAC QSP Model

238 The PDAC QSP model used in this study is adapted from a spatial QSP model of hepatocellular
239 carcinoma²⁶ that first incorporated fibroblast dynamics into the tumor microenvironment. We
240 evaluate MAPLE on this model using both schemas: 37 curated SubmodelTargets for individ-
241 ual parameter calibration from isolated experiments (spanning tumor growth, stromal dynamics,
242 immune recruitment, and cytokine signaling), and 54 CalibrationTargets for full-model endpoints
243 (baseline tumor microenvironment composition, neoadjuvant immunotherapy response, and clinical
244 progression). Batch extraction used OpenAI gpt-5.1 at high reasoning effort, both for Submod-
245 elTargets and for the batch-pipeline portion of CalibrationTargets; interactive CalibrationTarget
246 extraction and all curation used Anthropic claude-opus-4-6 through Claude Code. All extraction
247 and curation runs were performed between 2026-02-20 and 2026-02-27.

248 2.5.1 Evaluation Metrics

249 We report metrics across four workflow stages: extraction performance (pass rate, retries, time,
250 tokens), error analysis (failures by category and tool usage), source characteristics (source types,
251 species translation, indication match), and curation analysis (revision rates for batch vs. interactive
252 modes, edit classification by content type).

3 Results

3.1 SubmodelTarget Extraction and Validation

We applied MAPLE to extract SubmodelTargets for a PDAC QSP model, covering tumor growth, stromal dynamics, immune recruitment, and cytokine signaling. An initial batch of 18 targets (one derivation per parameter) was extracted through the automated retry loop and traced with Logfire (Table 1); additional derivations were extracted by the same batch pipeline for parameters where multiple complementary sources were available, yielding a final curated set of 37 SubmodelTargets used for joint inference. Per-target Logfire metrics in Table 1 cover the initial 18-target subset; the schema-validation and curation results in Section 3.2 cover all 37.

Table 1: Extraction metrics per SubmodelTarget.

Target	Retries	Duration (min)	Tokens
N_IL2_CD4	3	6.5	198,267
N_IL2_CD8	1	3.4	98,233
initial_tumour_diameter	1	3.0	70,219
k_C1_growth	1	4.1	81,606
k_CCL2_sec	5	9.2	367,754
k_ECM_apsc_sec	5	10.8	285,309
k_ECM_deg	1	5.8	135,317
k_ECM_qpsc_sec	5	12.0	406,891
k_M1_pol	1	7.1	190,149
k_MDSC_rec	3	8.4	221,048
k_Mac_rec	3	10.0	239,265
k_apsc_death	2	5.4	134,626
k_psc_activation	7	9.9	354,840
k_psc_const	2	7.7	209,064
k_qpsc_death	1	3.8	91,974
n_CD8_clones	1	5.3	114,839
n_Treg_clones	2	5.7	133,558
q_Treg_T_in	6	23.9	586,283
Average	2.8	7.9	217,735

None of the extractions passed validation on the first attempt; all required at least one automated retry. Seven targets succeeded after a single retry, three each after two, three, and five retries, and one each after six and seven retries; parameters like CCL2 secretion and PSC activation required up to 7 iterations to resolve unit ambiguities or conflicting literature. Each extraction took 7.9 minutes on average, consuming 217,735 tokens per target (3.9M total). The validators

267 caught 24 errors during extraction (Table 2), with unit errors most common, followed by fabrication
 268 (invalid DOIs), prior specification, and code errors. The LLM used 210 web searches and 22 code
 269 executions.

Table 2: Error categories caught by validators during batch extraction. Units: incorrect or inconsistent unit conversions. Prior: proposed uncertainty range incompatible with stated translation context. Fabrication: LLM-generated DOIs or citations that do not resolve to real publications. Code: observation function fails unit checks or execution. Hallucination: extracted values not found in the cited source text. Each target may trigger multiple errors.

Error Category	Count	%
units	9	38%
prior	5	21%
fabrication	4	17%
code	4	17%
other	1	4%
hallucination	1	4%
Total	24	

270 3.1.1 Source Characteristics

271 The 37 curated targets drew from diverse sources (Supplementary Section 8): 45% human clin-
 272 ical, with the remainder from animal studies. About 56% used human data directly; the rest
 273 required cross-species scaling from mouse (35%) or rat (8%). Only 45% came from PDAC-specific
 274 experiments; most (43%) relied on proxy indications.

275 3.2 Human Curation

276 To quantify human curation, we compared raw LLM output against final curated versions. All cu-
 277 ration was performed interactively with Claude Code (claude-opus-4-6), with the modeler directing
 278 edits and modeling decisions while the LLM handled text generation, code writing, and literature
 279 comprehension. No batch extraction was used without modification; in a documented review of
 280 one batch (12 CalibrationTarget files), 58% were rejected outright. [This rate comes from a single](#)
 281 [small batch and should be read as indicative rather than a precise rejection rate.](#)

282 For the 37 batch-extracted SubmodelTarget files, the modeler changed the forward model type
 283 in 65% of files (24/37), adjusted prior distribution parameters in 46%, changed input data values

in 46%, and revised source relevance assessments in every file. For CalibrationTargets, the batch pipeline produced 22 drafts; 4 were retired during curation (18%), leaving 18 surviving batch-extracted targets in the active cohort. Among the survivors the modeler revised observable code in 39% of files, changed species lists in 28%, adjusted empirical data in 17%, and revised source relevance assessments in 28% of files (a lower rate than for SubmodelTargets, since the batch-extracted CalibrationTargets were sourced from a smaller, more curated input pool).

A further 27 CalibrationTargets in the final cohort were extracted interactively with Claude Code using source PDFs loaded directly into the session. The modeler provided domain guidance (species mapping, denominator definitions, distribution choices) while the LLM handled literature comprehension and code generation. These files required minimal subsequent revision (a single shared reference value correction across 7,619 total lines); modeler judgment was embedded in the extraction process rather than applied post-hoc.

3.2.1 Categories of modeler-supplied context

The field-level curation rates above aggregate changes of several different kinds. Across the SubmodelTarget and CalibrationTarget revisions, modeler-supplied context fell into the following recurring categories:

1. *Unit conventions and dimensional bridges.* Conversion factors that the LLM cannot infer from `model.structure.json` alone, such as a missing 10^{-6} tissue protein density conversion in cDC and Treg density formulas, or the Abercrombie 3D-to-2D correction used to convert section-level cell counts to volumetric densities.
2. *Source selection and retirement.* Excluding a study after recognizing a mismatch between assay or marker definitions and model categorization (e.g., a study reporting CD86+ as an M1 marker, where the simulation does not enforce that definition), or substituting a better source when one becomes available.
3. *Cross-source aggregation.* Decisions to pool measurements from multiple studies (e.g., `cd8_density` aggregated across Golesworthy 2022 and Liu 2015) rather than treat them as separate targets.
4. *Measurement-to-state translation logic.* Code inside the observable function that converts a

paper’s measurement into a model-relevant quantity, such as serum-to-tissue bridging factors that translate plasma cytokine concentrations to tissue-level model species, or active-fraction adjustments where immunoassays detect total cytokine although only a signalling-active fraction is biologically meaningful.

5. *Denominator and normalization choices.* What a percentage is taken of (CD8 of CD3 versus of nucleated cells), and which compartment volume normalizes a per-tissue measurement.
6. *Scenario-specific forward-model structure.* Constraints particular to a calibration scenario rather than to the underlying biology: peak-ordering constraints (e.g., a tumor-volume minimum that must follow a CD8 peak in the GVAX-only arm), or reparameterization of a kinetic in its linear sub-saturating regime when the data do not span saturation.
7. *Uncertainty widening from source quality.* Adjusting prior or likelihood widths upward when a source is cross-species or cross-indication; the schema’s `source_relevance` block records the rationale alongside the widening.

These categories did not contribute equally to curation effort. Unit conventions and source selection accounted for the largest share of edits. Auxiliary-parameter additions and denominator decisions occurred less often but represented modeling decisions about how a measurement maps to a model state, and typically took longer per edit than the unit corrections. Forward-model restructuring and uncertainty widening were applied selectively to a smaller number of targets.

The reduced revision rate for interactively extracted CalibrationTargets is observational rather than controlled. The batch pipeline used GPT-5.1 and the interactive pipeline used Claude Opus 4.6; these models differ in context handling and characteristic error profiles, so any per-mode difference may partly reflect model capability rather than collaboration mode. The interactive work also followed curation of the batch outputs, meaning the modeler entered interactive extraction with working knowledge of where the LLM tended to fail on this corpus. The data are consistent with interactive curation reducing post-hoc revision, but a controlled comparison would require the same underlying model in both modes and randomized assignment of targets.

3.3 CalibrationTarget Extraction

We applied the CalibrationTarget schema to 54 full-model endpoints for the same PDAC QSP model, organized into three scenario groups: 35 baseline (no treatment) targets capturing the untreated tumor microenvironment, 18 neoadjuvant immunotherapy targets (GVAX $\pm$ nivolumab), and 1 clinical progression target (Table 3). All 54 targets pass schema validation including observable code execution, distribution code verification, and unit consistency checks.

Table 3: CalibrationTarget summary by scenario group.

Scenario Group	Targets
Baseline (no treatment)	35
Neoadjuvant immunotherapy (GVAX $\pm$ nivolumab)	18
Clinical progression	1
Total	54

Of the 54 targets, 18 were extracted by GPT-5.1 through the batch pipeline, 27 interactively with Claude Opus 4.6 using source PDFs, and 9 manually. The 18 batch-extracted figure is the surviving subset of the 22 drafts produced by the batch pipeline; 4 drafts were curated and then retired (Section 3.2). The 9 manual targets did not pass through the LLM-extraction pipeline and so do not enter the field-level curation diffs. The 18 neoadjuvant immunotherapy targets include per-patient data digitized from scatter plots (27% of all CalibrationTargets). Curation metrics for both extraction modes are reported in Section 3.2.

The observables span 25 unique model species, with complexity ranging from 1 to 19 species per target (mean 7.4). The targets drew from 23 unique primary sources (from years 2000–2026). Supplementary Section 9 provides detailed per-target metrics.

Per-target extraction metrics (retry counts, token usage, and validator-error categories) were collected through Logfire instrumentation that was active only for the SubmodelTarget batch run. The CalibrationTarget extraction runs predate that instrumentation, so equivalent per-target metrics are not available for this cohort; the SubmodelTarget metrics in Table 1 are reported as representative of the automated retry loop, and the schema-validation and curation results above are the performance evidence specific to CalibrationTargets.

3.4 Code Generation and Inference

All 37 SubmodelTargets were translated to a joint Julia inference script targeting Turing.jl²⁵. The translator identified 19 unique parameters and generated corresponding priors and likelihood terms. All parameters converged ($\hat{R} < 1.01$), with bulk-ESS > 2600 and tail-ESS > 1300 throughout (Table 9). Posterior estimates yielded biologically plausible values, with an inferred tumor doubling time of ~ 130 days consistent with clinical PDAC volume-doubling-time measurements^{27,28}. Full inference results including convergence diagnostics, posterior distributions, and model type breakdown are reported in Supplementary Section 10.

4 Discussion

MAPLE demonstrates that structured schemas can serve as a productive collaboration interface between LLMs and modelers for QSP model calibration. The curation analysis shows that LLM-generated drafts are competent at the bibliographic, transcription, and unit-handling tasks the schema encodes, while a substantive minority of fields, concentrated in source selection, prior specification, and forward- or observable-model choice, were revised by the modeler. Rather than automating away the modeler, the framework restructures the collaboration: the schema defines what must be captured, validators catch errors from both LLM and human sources, and the separation of data extraction from modeling decisions clarifies where different types of expertise are needed.

4.1 Validation as the Core Mechanism

None of the 18 SubmodelTarget extractions passed validation on the first attempt, and the same automated retry pipeline was used for batch-extracted CalibrationTargets (detailed retry metrics are reported for SubmodelTargets, where the Logfire-instrumented pipeline provided per-target tracing). This is expected behavior: the validators serve as an automated first-pass review, and the retry loop resolves most issues without human intervention. Extractions requiring multiple retries (up to 7) typically involved ambiguous unit conventions or conflicting literature values.

The value-in-snippet requirement proved particularly effective, catching a common LLM behavior: paraphrasing source text rather than quoting it exactly. The validator flags these cases,

and the retry loop produces verbatim snippets. A separate external validator checks that snippets actually appear in the cited papers, catching cases where the LLM generates plausible text that does not exist in the source. Together, these validators support human review: a reviewer can verify each extraction by checking the snippet against the source paper, without re-reading entire methods sections.

A target that passes all validators is structurally complete, internally consistent, traceable to a resolvable source, dimensionally valid, and executable, but passing validation does not certify the scientific judgment encoded in the calibration layer. No final SubmodelTarget or CalibrationTarget in this study retains an unresolved validator failure; every record passes the full validator suite, verified by re-running the complete Pydantic validator pipeline at MAPLE v0.1.0 against all final YAMLS. The errors that survive automated validation are therefore not validator failures but judgment errors: a forward-model type that is well-formed yet inappropriate for the experiment, a prior that is valid yet mis-centered, or a source that resolves yet is only weakly applicable to the target indication. The curation revision rates in Section 3.2 are the measure of this residual category, which is why curation remains necessary even though automated validation has a perfect final pass rate.

4.2 Schema Design Choices

The separation of data extraction from model specification clarifies where human judgment is required (the inputs should be objective; the calibration layer involves modeling choices), enables reuse (if a modeling assumption changes, the inputs remain valid), and supports independent review of data versus modeling decisions.

The dual-schema architecture applies the same data-first principles at two scales of calibration. SubmodelTarget operates on isolated experiments that constrain individual parameters through simplified forward models; CalibrationTarget operates on clinical and in vivo endpoints that constrain the integrated model through full-species observables. Shared design elements (source provenance, relevance assessment, experimental context, value-snippet validation) ensure consistent rigor across both scales, while schema-specific components (forward model types vs. observable code, error models vs. distribution code) capture the distinct requirements of each calibration regime.

4.3 Modeler Contribution and Limitations of Extracted Data

The curation results show where modeler input enters the workflow. The LLM produces competent forward-model choices and observable code when it has enough context, but cannot recognize when context is missing, and can also miss inputs or lose track of constraints across long records. Modeler curation closes the resulting gaps: for batch-extracted SubmodelTargets, forward-model type changed in 65% of files, prior distributions in 46%, input data values in 46%, and source-relevance assessments in every file; for CalibrationTargets, observable code in 39% of batch-extracted files, species lists in 28%, and empirical data in 17%. Missing context typically involves unit conventions the LLM cannot infer from the model definition (for example, the Abercrombie 3D-to-2D correction used to convert section-level cell counts to volumetric densities) and source-applicability decisions that require recognizing marker-definition mismatches (e.g., a study reporting CD86+ as an M1 marker mismatched to the simulation’s M1/M2 categorization). Section 3.2.1 describes the full taxonomy. Interactive extraction reduces these revisions by letting the modeler supply context as gaps surface. The modeler’s review of every record also catches the LLM lapses the validators do not detect, which is why paired human review remains part of the workflow even with full validator coverage. The framework makes the context dependency auditable: every claim in the YAML carries both a source reference and a verbatim snippet, with cross-species or cross-indication uses additionally requiring a documented justification (Supplementary Section 14).

The source characteristics reveal a fundamental challenge in QSP calibration: only 45% of SubmodelTargets came from PDAC-specific experiments, and 35% required cross-species translation from mouse data. The schema addresses this through the `source_relevance` block, which requires that translation uncertainty propagate to prior widths. A parameter calibrated from mouse fibrosis data with 5-fold translation uncertainty will have a correspondingly wide posterior, appropriately reflecting the limited applicability of available evidence.

The token cost reported above (217,735 tokens per SubmodelTarget, averaging roughly \$0.37 per target and \$6.72 for the full SubmodelTarget cohort at the API pricing in effect during these runs) is modest in absolute terms, so the dominant cost of the workflow is modeler time rather than compute. That time differs by collaboration mode: batch curation requires the modeler to review, and often reject or repair, drafts that may carry unit, source-selection, or denominator errors,

whereas interactive extraction front-loads modeler effort during extraction but yields near-final output. We do not report a controlled time comparison against fully manual extraction, since the two were not run on the same targets under matched conditions, and net time efficiency will depend on the model, the literature base, and modeler familiarity with the framework. The contribution of MAPLE is not that it reduces modeler effort to zero but that it makes that effort structured, auditable, and reproducible: the schema records which decisions the modeler made and why, which a free-text extraction does not.

4.4 Relationship to Existing Approaches

MAPLE addresses a gap between general-purpose biomedical extraction frameworks^{17,18}, which do not address QSP-specific downstream requirements (uncertainty quantification, forward model specification, code generation), and QSP-focused tools like QSP-Copilot¹⁶, which include literature extraction components but emphasize model structure discovery rather than quantitative parameter calibration with documented provenance and uncertainty propagation. The validation approach combines grounding strategies from retrieval-augmented generation²⁹ and constrained decoding³⁰ with domain-specific validators (DOI resolution, unit parsing, code execution) tailored to quantitative scientific extraction.

Unlike knowledge graph approaches that prioritize coverage across thousands of abstracts^{14,31} and can tolerate some extraction errors, parameter calibration requires higher per-target stringency because each value directly influences model predictions. MAPLE aligns with IQ Consortium best practices for AI/ML in quantitative modeling⁷, emphasizing explainability, human-in-the-loop oversight, and documented provenance. While evaluated on a QSP model, the approach applies to any parameter-rich mechanistic model that draws calibration data from literature. A more detailed comparison of individual tools and approaches is provided in Supplementary Section 15.

4.5 Limitations and Future Work

Several limitations merit discussion. First, the framework relies on the LLM’s built-in web search for source discovery, so extraction quality is bounded by the LLM’s ability to locate and access papers. Closed-access publications may be only partially available (e.g., abstract only), limiting extraction depth. Emerging agentic capabilities (LLM-controlled browsers with institutional authentication)

may address this. Work in progress extends the framework to a staged extraction pipeline that retrieves full-text papers in advance and batches extraction over them systematically, which would make the external snippet-in-paper check part of the automated gate rather than an on-demand step. The framework also depends on evolving LLM capabilities: extraction is stochastic, and performance characteristics vary across providers and model versions.

Second, modeler intervention is pervasive. For SubmodelTargets, the modeler changed the forward model type in 65% of files and adjusted prior parameters in 46%. Prompt improvements could reduce some recurring errors, but core scientific decisions will remain modeler responsibilities regardless of LLM capability. CalibrationTargets required different curation: observable code (changed in 39% of batch-extracted files), Monte Carlo distribution derivation, and denominator audit fields demand modeling expertise that current LLMs provide as a starting point. The schema and validators can also be used without LLMs, providing structure for purely manual curation.

Third, extracting structured quantitative data from figures remains challenging; the neoadjuvant immunotherapy targets required manual digitization of scatter plots. Integrating multimodal LLM vision capabilities is a natural direction for future work. Fourth, per-target extraction metrics are available only for the SubmodelTarget cohort, as discussed in Section 3.3.

Generalization requirements. This evaluation covers one QSP model in one disease area, extracted and curated by one modeling group, so it characterizes the framework rather than bounding its performance. Several components are domain-independent: the separation of an inputs layer from a calibration layer, the typed-role fields, the value-in-snippet, DOI-resolution, and code-execution validators, and the provenance requirements all apply to any literature-derived parameter. The forward-model type library is the main domain-specific surface. 48% of SubmodelTargets used the generic algebraic type, which indicates that the 15 built-in templates covered roughly half of the use cases even within this model; a portion of those algebraic uses are genuinely simple derived relations (half-lives, ratios) for which no structured template is needed, but the fraction also shows the template library is not exhaustive. A non-oncology application, for instance a PK/PD model, would likely require additional templates for compartmental pharmacokinetics, receptor occupancy, or indirect-response dynamics; the generic algebraic, direct-fit, and custom fallbacks accept such cases today but without the structured role typing that the built-in templates provide. The model-

aware search and shared-parameter-name binding assume a structured QSP model is already in hand, which holds in any domain but means the framework supports calibration of an existing model rather than model construction.

Study Highlights

What is the current knowledge on the topic?

QSP model calibration requires data from published literature, spanning experimental studies and clinical endpoints. Manual curation is labor-intensive with inconsistent documentation, while LLM extraction exhibits hallucination and fabrication errors unacceptable for quantitative modeling.

What question did this study address?

Can structured schemas serve as a collaboration interface between LLMs and modelers for QSP model calibration, and what is the relative contribution of each?

What does this study add to our knowledge?

Structured validation schemas enable LLM-modeler collaboration through batch or interactive extraction. Both modes required substantial modeler input, with forward model types changed in 65% of SubmodelTargets and observable code revised in 39% of CalibrationTargets. Targeted validators catch characteristic LLM errors, and code generation enables joint Bayesian inference.

How might this change drug discovery, development, and/or therapeutics?

The framework produces reproducible, provenance-rich calibration data that improve documentation consistency across modeling teams while making modeler contributions explicit and auditable.

Acknowledgments

Claude Opus 4.6 (Anthropic, model identifier `claude-opus-4-6`) and GPT-5.1 (OpenAI, model identifier `gpt-5.1`) were used for literature search, data extraction, and code generation as described in the Methods, and Claude Code (`claude-opus-4-6`) assisted with manuscript preparation and interactive curation. All AI-generated content was reviewed and verified by the authors.

Author Contributions

J.E. designed research, performed research, analyzed data, and wrote the manuscript. A.S.P. designed research and wrote the manuscript.

Data Availability Statement

MAPLE (the SubmodelTarget and CalibrationTarget schemas, validation framework, and inference code generator) is available at <https://github.com/popellab/maple>. The results reported here were generated with MAPLE v0.1.0 (commit 7f1faa4), and the repository includes the representative extraction prompts used for both schemas. Extraction inputs, curated YAML targets, and scripts to reproduce all paper statistics are available at <https://github.com/popellab/maple-paper>. The 37 SubmodelTargets and 54 CalibrationTargets used in this study are provided as supplementary YAML files. Generated Julia inference scripts are included in the supplementary materials. The underlying PDAC QSP model is part of separate work that has not yet been published; the structural representation that MAPLE consumes (model structure, species and parameter definitions, and unit mappings) is included in the maple-paper repository, so the extraction inputs and reported evaluation are fully reproducible. The complete PDAC model will be released with its own publication.

References

- [1] Gadkar K, Kirouac DC, Mager DE, van der Graaf PH, Ramanujan S. A Six-Stage Workflow for Robust Application of Systems Pharmacology. CPT: Pharmacometrics & Systems Pharmacology. 2016 May;5(5):235-49. doi:10.1002/psp4.12071.
- [2] Wang H, Arulraj T, Ippolito A, Popel AS. Quantitative Systems Pharmacology Modeling in Immuno-Oncology: Hypothesis Testing, Dose Optimization, and Efficacy Prediction. Handbook of Experimental Pharmacology. 2025;289:261-84. doi:10.1007/164_2024_735.
- [3] Wang H, Arulraj T, Ippolito A, Popel AS. From Virtual Patients to Digital Twins in Immuno-

Oncology: Lessons Learned from Mechanistic Quantitative Systems Pharmacology Modeling.
npj Digital Medicine. 2024 Jul;7(1):189. doi:10.1038/s41746-024-01188-4.

[4] Rieger TR, Allen RJ, Bystricky L, Chen Y, Colopy GW, Cui Y, et al. Improving the Generation and Selection of Virtual Populations in Quantitative Systems Pharmacology Models. Progress in Biophysics and Molecular Biology. 2018 Nov;139:15-22. doi:10.1016/j.pbiomolbio.2018.06.002.

[5] Craig M, Gevertz JL, Kareva I, Wilkie KP. A Practical Guide for the Generation of Model-Based Virtual Clinical Trials. Frontiers in Systems Biology. 2023 Jun;3. doi:10.3389/fsysb.2023.1174647.

[6] Folguera-Blasco N, Boshier FAT, Uatay A, Pichardo-Almarza C, Lai M, Biasetti J, et al. Coupling Quantitative Systems Pharmacology Modelling to Machine Learning and Artificial Intelligence for Drug Development: Its pAIns and gAIns. Frontiers in Systems Biology. 2024 Jul;4. doi:10.3389/fsysb.2024.1380685.

[7] Terranova N, Renard D, Shahin MH, Menon S, Cao Y, Hop CECA, et al. Artificial Intelligence for Quantitative Modeling in Drug Discovery and Development: An Innovation and Quality Consortium Perspective on Use Cases and Best Practices. Clinical Pharmacology & Therapeutics. 2024;115(4):658-72. doi:10.1002/cpt.3053.

[8] Goryanin I, Goryanin I, Demin O. Revolutionizing Drug Discovery: Integrating Artificial Intelligence with Quantitative Systems Pharmacology. Drug Discovery Today. 2025 Sep;30(9):104448. doi:10.1016/j.drudis.2025.104448.

[9] Androulakis IP, Cucurull-Sanchez L, Kondic A, Mehta K, Pichardo C, Pryor M, et al. The Dawn of a New Era: Can Machine Learning and Large Language Models Reshape QSP Modeling? Journal of Pharmacokinetics and Pharmacodynamics. 2025 Jun;52(4):36. doi:10.1007/s10928-025-09984-5.

[10] Androulakis IP, Cheng L, Cho CR, Zhang T. Leveraging Large Language Models to Compare Perspectives on Integrating QSP and AI/ML. Journal of Pharmacokinetics and Pharmacodynamics. 2025 May;52(3):29. doi:10.1007/s10928-025-09976-5.

- [11] Zhao S, Su C, Lu Z, Wang F. Recent Advances in Biomedical Literature Mining. *Briefings in Bioinformatics*. 2021 May;22(3):bbaa057. doi:10.1093/bib/bbaa057.
- [12] Hu J, Bao R, Lin Y, Zhang H, Xiang Y. Accurate Medical Named Entity Recognition Through Specialized NLP Models. *arXiv preprint arXiv:241208255*. 2024 Dec. doi:10.48550/arXiv.2412.08255.
- [13] Gonzalez Hernandez F, Nguyen Q, Smith VC, Cordero JA, Ballester MR, Duran M, et al. Named Entity Recognition of Pharmacokinetic Parameters in the Scientific Literature. *Scientific Reports*. 2024 Oct;14(1):23485. doi:10.1038/s41598-024-73338-3.
- [14] He S, Tan Y, Ye Q, M Gubin M, Dede M, Rafei H, et al. AI-powered Immune Cell Knowledge Graph (ICKG) with Granular Immune Contexts Enables Immune Program Interpretation. *npj Artificial Intelligence*. 2026 Jan;2(1):13. doi:10.1038/s44387-025-00060-4.
- [15] Khan MA, Ayub U, Naqvi SAA, Khakwani KZR, Sipra ZBR, Raina A, et al. Collaborative Large Language Models for Automated Data Extraction in Living Systematic Reviews. *medRxiv: The Preprint Server for Health Sciences*. 2024 Sep;2024.09.20.24314108. doi:10.1101/2024.09.20.24314108.
- [16] Saini A, Farnoud A. QSP-Copilot: An AI-Augmented Platform for Accelerating Quantitative Systems Pharmacology Model Development. *CPT: Pharmacometrics & Systems Pharmacology*. 2025;14(11):1775-86. doi:10.1002/psp4.70127.
- [17] Hsu E, Roberts K. LLM-IE: A Python Package for Biomedical Generative Information Extraction with Large Language Models. *JAMIA Open*. 2025 Apr;8(2):ooaf012. doi:10.1093/jamiaopen/ooaf012.
- [18] Wang X, Huey SL, Sheng R, Mehta S, Wang F. SciDaSynth: Interactive Structured Data Extraction From Scientific Literature With Large Language Model. *Campbell Systematic Reviews*. 2025;21(4):e70073. doi:10.1002/cl2.70073.
- [19] Farquhar S, Kossen J, Kuhn L, Gal Y. Detecting Hallucinations in Large Language Models Using Semantic Entropy. *Nature*. 2024 Jun;630(8017):625-30. doi:10.1038/s41586-024-07421-0.

- [20] Huang L, Yu W, Ma W, Zhong W, Feng Z, Wang H, et al. A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions. *ACM Transactions on Information Systems*. 2025 Mar;43(2):1-55. doi:10.1145/3703155.
- [21] Pandit S, Xu J, Hong J, Wang Z, Chen T, Xu K, et al.. MedHallu: A Comprehensive Benchmark for Detecting Medical Hallucinations in Large Language Models. *arXiv*; 2025. doi:10.48550/arXiv.2502.14302.
- [22] Colvin S, Jolibois E, Ramezani H, Garcia Badaracco A, Dorsey T, Montague D, et al.. Pydantic Validation; 2025. Available from: <https://github.com/pydantic/pydantic>.
- [23] Grecco HE. Pint: Operate and manipulate physical quantities in Python; 2025. Available from: <https://github.com/hgrecco/pint>.
- [24] Pydantic. Logfire: Observability platform for Python applications; 2025. Available from: <https://pydantic.dev/logfire>.
- [25] Ge H, Xu K, Ghahramani Z. Turing: A Language for Flexible Probabilistic Inference. In: *Proceedings of the Twenty-First International Conference on Artificial Intelligence and Statistics*. PMLR; 2018. p. 1682-90. Available from: <https://proceedings.mlr.press/v84/ge18b.html>.
- [26] Zhang S, Wang H, Cho Y, Wong W, Yarchoan M, Jaffee EM, et al. Quantitative Calibration of a Spatial QSP Model Identifies Fibroblast Impact on HCC Immunotherapy. *bioRxiv*. 2025 Nov;2025.10.31.685939. doi:10.1101/2025.10.31.685939.
- [27] Ahn SJ, Choi SJ, Kim HS. Time to Progression of Pancreatic Cancer: Evaluation with Multi-Detector Computed Tomography. *Journal of Gastrointestinal Cancer*. 2017;48(2):164-9. doi:10.1007/s12029-016-9876-7.
- [28] Jang KM, Kim SH, Kim YK, Song KD, Lee SJ, Choi D. Missed Pancreatic Ductal Adenocarcinoma: Assessment of Early Imaging Findings on Prediagnostic Magnetic Resonance Imaging. *European Journal of Radiology*. 2015;84(8):1473-9. doi:10.1016/j.ejrad.2015.05.012.

- 628 [29] Li Y, Fu X, Verma G, Buitelaar P, Liu M. Mitigating Hallucination in Large Language Models
629 (LLMs): An Application-Oriented Survey on RAG, Reasoning, and Agentic Systems. arXiv;
630 2025. doi:10.48550/arXiv.2510.24476.
- 631 [30] Geng S, Cooper H, Moskal M, Jenkins S, Berman J, Ranchin N, et al. JSONSchemaBench:
632 A Rigorous Benchmark of Structured Outputs for Language Models. arXiv preprint
633 arXiv:250110868. 2025 Feb. doi:10.48550/arXiv.2501.10868.
- 634 [31] Gao T, Zhai X, Yang C, Lv L, Wang H. Joint Extraction of Entity and Relation Based
635 on Fine-Tuning BERT for Long Biomedical Literatures. Bioinformatics Advances. 2024
636 Jan;4(1):vbae194. doi:10.1093/bioadv/vbae194.