

untangle::actuator

Generated by Doxygen 1.18.0

1 actuator	1
2 Topic Index	5
2.1 Topics	5
3 Namespace Index	7
3.1 Namespace List	7
4 Concept Index	9
4.1 Concepts	9
5 Class Index	11
5.1 Class List	11
6 File Index	13
6.1 File List	13
7 Topic Documentation	15
7.1 namespace untangle: functions	15
7.1.1 Detailed Description	15
7.1.2 Function Documentation	15
7.1.2.1 connect() [1/4]	15
7.1.2.2 connect() [2/4]	17
7.1.2.3 connect() [3/4]	17
7.1.2.4 connect() [4/4]	18
7.1.2.5 bind() [1/2]	19
7.1.2.6 bind() [2/2]	19
8 Namespace Documentation	21
8.1 untangle Namespace Reference	21
8.1.1 Detailed Description	22
8.1.2 Typedef Documentation	22
8.1.2.1 task_t	22
8.1.3 Function Documentation	23
8.1.3.1 last_arg()	23
8.1.3.2 connect_one()	23
8.1.3.3 connect_named_one()	24
8.1.3.4 bind_task()	25
9 Concept Documentation	27
9.1 untangle::task_callback_for Concept Reference	27
9.1.1 Concept definition	27
9.1.2 Detailed Description	27
9.2 untangle::testable_for_emptiness Concept Reference	28
9.2.1 Concept definition	28
9.2.2 Detailed Description	28

10 Class Documentation	29
10.1 untangle::actuator< action_t > Struct Template Reference	29
10.1.1 Detailed Description	31
10.1.2 Member Typedef Documentation	32
10.1.2.1 actions_t	32
10.1.2.2 tasks_t	32
10.1.2.3 results_t	32
10.1.2.4 errors_t	32
10.1.3 Constructor & Destructor Documentation	33
10.1.3.1 actuator()	33
10.1.4 Member Function Documentation	33
10.1.4.1 operator=()	33
10.1.4.2 type()	33
10.1.4.3 reset()	34
10.1.4.4 copy_from()	34
10.1.4.5 release_owned()	34
10.1.4.6 invoke_callback()	35
10.1.4.7 operator()()	36
10.1.4.8 invoke_action()	36
10.1.4.9 call_tasks()	37
10.1.4.10 add() [1/4]	37
10.1.4.11 add() [2/4]	38
10.1.4.12 add() [3/4]	38
10.1.4.13 add() [4/4]	38
10.1.4.14 add_task()	39
10.1.4.15 remove() [1/2]	39
10.1.4.16 remove() [2/2]	40
10.1.4.17 is_connected()	40
10.1.4.18 has_tasks()	41
10.1.4.19 has_action()	41
10.1.5 Member Data Documentation	41
10.1.5.1 tasks	41
10.1.5.2 owned	42
10.2 untangle::invalid_action Struct Reference	42
10.2.1 Detailed Description	42
10.2.2 Constructor & Destructor Documentation	42
10.2.2.1 invalid_action()	42
10.2.3 Member Function Documentation	43
10.2.3.1 what()	43
11 File Documentation	45
11.1 actuator.hpp	45
Index	51

Chapter 1

actuator

An actuator is a generic callable that may invoke a list of actions(callables of type `std::function<...>`).

Its goal is to provide a light and simple mechanism to connect components that want to communicate with each other. It works similar as the "signal and slots" mechanisms from other frameworks, but much simplified.

Modern programming languages do not offer class intrinsic interfaces that would improve significantly how objects are connected and how they communicate. Instead, languages, like C++, are using external interfaces, that are not only cluttering the code, but they don't feel "natural" as they are opposed to what an interface is in reality. Basically the objects and interfaces are not separated, and the interface is intrinsic to the object(think on the cogs in a mechanism). A generic callable is an attempt to mitigate this problem. `async` implementation is such use case.

An actuator provides the results of all actions in a vector, in the same order as the actions were added.

Example: how to use actuator instead of polymorphism

```
void rotate_shapes(const std::vector<shape*>& shapes, int angle)
{
    for (const auto& s : shapes)
    {
        s->rotate(angle);
    }
}

std::shared_ptr<triangle> t(new triangle);
std::shared_ptr<circle> c(new circle);
std::shared_ptr<square> s(new square);

// using polymorphism
std::vector<shape*> shapes;
shapes.push_back(t.get());
shapes.push_back(c.get());
shapes.push_back(s.get());

rotate_shapes(shapes, 10);

// using actuator
auto action1 = untangle::bind(t, &triangle::rotate);
auto action2 = untangle::bind(c, &circle::rotate);
auto action3 = untangle::bind(s, &square::rotate);
auto actuator_rotate = untangle::connect(action1, action2, action3);
actuator_rotate(20);
```

Anonymous lambdas as actions

An actuator normally does not own its actions: it stores pointers to `std::function` objects the caller keeps alive. `add()` also has an overload that takes an action by value, so an anonymous lambda can be an action with no named variable to keep around, and returns a handle to pass to `remove()`:

```
untangle::actuator<std::function<int(int)>> actuator_scale;
auto* handle = actuator_scale.add([](int v) { return v * 2; });
actuator_scale.add("triple", [](int v) { return v * 3; });
```

`connect()` accepts them too, but it deduces the action type from its arguments, and a lambda has its own closure type – it is not a `std::function` until something converts it. A call made only of anonymous lambdas therefore has nothing to deduce from, and the signature has to be named on `connect()` itself:

```
auto actuator_rotate = untangle::connect<std::function<void(int)>>(
    [](int angle) { /* ... */ }, [](int angle) { /* ... */ });
```

Naming the type of the variable the result is assigned to does not supply it – template arguments are deduced from the call arguments alone, never from what the returned value is assigned to:

```
// ill formed: "no matching function for call to connect"
untangle::actuator<std::function<void(int)>> actuator_rotate =
    untangle::connect([](int angle) { /* ... */ });
```

One named action anywhere in the call deduces the type for the whole of it, and the anonymous lambdas beside it then need nothing:

```
auto actuator_rotate = untangle::connect(action1, [](int angle) { /* ... */ });
```

The named form of `connect()` works the same way: a pair holding a pointer names an action the caller owns, a pair holding the action by value hands it over to the actuator, and the two can be mixed. The action type is deduced from the pointer, so a call whose first pair holds a lambda has to name the signature:

```
auto actuator_rotate = untangle::connect<std::function<void(int)>>(
    std::make_pair("triangle", [](int angle) { /* ... */ }),
    std::make_pair("circle", [](int angle) { /* ... */ }));

// deduced from the leading pointer, so the lambda beside it needs nothing
auto actuator_mixed = untangle::connect(std::make_pair("triangle", &action1),
    std::make_pair("circle", [](int angle) { /* ... */ }));
```

Tasks: an action bound to its arguments and to the callback it must notify

An action is a subscription: it lives across invocations, and it is fired with a pack the caller supplies each time. A task is a one-shot. It carries its own arguments, is fired once, and reports what it produced to a callback it was built with. The two live side by side in one actuator and share nothing else – `operator()` fires the actions and leaves the tasks alone, `call_tasks()` fires the tasks and leaves the actions alone.

A task exists so that work which runs later than it was described can still say what became of it. That is what a queue needs, and an actuator holding only actions cannot give: the callback convention on `operator()` reads the trailing argument of the invocation, and a queued call has no invocation left to read from.

```
untangle::actuator<std::function<int(int)>> actuator_scale;

// the callback comes last, after the arguments the action is bound to
actuator_scale.add_task(untangle::bind_task(action, 21, [](int result) { /* result == 42 */ }));

actuator_scale.call_tasks(); // runs it, notifies it, and empties the list
```

A task without a callback does not exist. That is the whole difference from an action's callback, which is optional and is recognised by its type – a trailing argument that does not look like a callback is simply an argument, and nothing fires. A task's callback is the last argument of `bind_task()`, taken by position, and `task_callback_for` only checks that it can serve. There is no answer "no" to fall through to, so a missing or unusable callback is a `static_assert` rather than silence.

It is not forwarded to the action either, so an action needs no callback parameter of its own – and a task whose action returns void is a task like any other. It reports with a void() callback, because finished is the message and the result is optional:

```
untangle::actuator<std::function<void(int)>> actuator_notify;
actuator_notify.add_task(untangle::bind_task(action, 5, [] { /* finished */ }));
```

The arguments are copied when the task is built, while the caller still holds them, and handed to the action as the task's own lvalues when it runs. A task outlives the call that described it and cannot borrow what may already be gone; a move-only argument therefore does not compile.

add_task() answers bool. It refuses a task that has nothing to run or no callback to notify, and the refusal is the whole report – nothing is thrown and nothing is stored. Both are the caller's own mistake, and both are caught while the caller is still on the stack rather than surfacing later from call_tasks() as a std::bad_function_call recorded against a task whose action had in fact succeeded.

Finished does not mean failed. A task whose action throws is not notified: there is no result to hand over, and for a void task no completion to report either. What it threw goes to actuator::errors, the tasks behind it still run, and a caller relying on the callback alone will never hear about it. A callback runs inside the same try as the task that owns it, so what it throws travels the same path – errors can hold a failure for a task that succeeded.

A task's result goes to its callback and nowhere else: actuator::results is how an action hands back what it returned, and a task was built with something better. call_tasks() appends to errors rather than clearing it, while operator() clears both as it starts – so an actuator fired as one(); one.call_tasks(); reports both kinds together, and the actions go first.

Ask has_tasks() whether a task is waiting. is_connected() answers for the actions and for nothing else: an actuator holding only tasks is not connected, and a queue reading the wrong one would report a batch of tasks as nothing to do.

For convenience there are provided helpers methods to "connect" to an initial list of "actions", or to create bindings to class methods.

Please check the manual in doc/refman.pdf for further references.

Chapter 2

Topic Index

2.1 Topics

Here is a list of all topics with brief descriptions:

namespace untangle: functions [15](#)

Chapter 3

Namespace Index

3.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

untangle	Interface to untangle::actuator functor	21
--------------------------	---	--------------------

Chapter 4

Concept Index

4.1 Concepts

Here is a list of all documented concepts with brief descriptions:

untangle::task_callback_for	
Can callback_t serve as the completion callback of a task returning result_t?	27
untangle::testable_for_emptyiness	
Can callable_t say whether it is empty?	28

Chapter 5

Class Index

5.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

untangle::actuator< action_t >	
An actuator is a functor that can trigger a dynamic list of actions (of type std::↵ function<...>)	29
untangle::invalid_action	
Invalid action exception	42

Chapter 6

File Index

6.1 File List

Here is a list of all documented files with brief descriptions:

actuator.hpp		45
------------------------------	-------	----

Chapter 7

Topic Documentation

7.1 namespace untangle: functions

Functions

- `template<typename action_t, typename... Actions>`
`actuator< action_t > untangle::connect (action_t &A1, Actions &&... An)`
Creates an actuator holding an initial list of actions.
- `template<typename action_t, typename... Actions>`
`actuator< action_t > untangle::connect (std::type_identity_t< action_t > &&A1, Actions &&... An)`
Creates an actuator owning an initial list of actions.
- `template<typename action_t, typename key_t, typename... Actions>`
`actuator< action_t > untangle::connect (std::pair< key_t, action_t * > A1, Actions &&... An)`
Creates an actuator holding an initial map of named actions.
- `template<typename action_t, typename key_t, typename value_t, typename... Actions>`
requires (!std::is_same_v<value_t, action_t*>)
`actuator< action_t > untangle::connect (std::pair< key_t, value_t > A1, Actions &&... An)`
Creates an actuator owning an initial map of named actions.
- `template<typename class_t, typename T, typename action_t = std::function<typename function_remove_const<↵ T>::type>>`
`action_t untangle::bind (const std::shared_ptr< class_t > &obj, T class_t::*method)`
Binding to a class function member.
- `template<typename class_t, typename T, typename action_t = std::function<typename function_remove_const<↵ T>::type>>`
`action_t untangle::bind (class_t *obj, T class_t::*method)`
Binding to a class method.

7.1.1 Detailed Description

7.1.2 Function Documentation

7.1.2.1 connect() [1/4]

```
template<typename action_t, typename... Actions>
actuator< action_t > untangle::connect (
    action_t & A1,
    Actions &&... An)
```

Creates an actuator holding an initial list of actions.

Remarks

Ownership: an action passed as an lvalue is one the caller owns, and the actuator only points at it – it must outlive the actuator. An action passed as an rvalue, an anonymous lambda above all, is moved into the actuator instead and needs no named variable at all. The two can be mixed in one call. See the ownership convention on [actuator](#).

Warning

A call made only of anonymous lambdas can not deduce `action_t`. A lambda has its own closure type and is not a `std::function` until something converts it, so there is nothing in such a call to deduce the action signature from, and it has to be named:

```
auto actuator_rotate = untangle::connect<std::function<void(int)>>(
    [](int angle) { ... }, [](int angle) { ... });
```

Warning

Naming the type of the variable the result is assigned to does not supply it:

```
// still ill formed -- "no matching function for call to connect"
untangle::actuator<std::function<void(int)>> actuator_rotate =
    untangle::connect([](int angle) { ... });
```

Template arguments are deduced from the call arguments alone, never from what the returned value is assigned to, so the explicit argument belongs on [connect\(\)](#) itself. One named action anywhere in the call deduces `action_t` for the whole of it, and the anonymous lambdas beside it then need nothing.

Parameters

A1	- The first action. It is specified as <code>std::function<...></code> .
An	- Any number of further actions, each convertible to the type of A1.

Returns

An [actuator](#).

Example:

```
void rotate_shapes(const std::vector<shape*>& shapes, int angle) {
    for (const auto& s : shapes) {
        s->rotate(angle);
    }
}

auto action1 = untangle::bind(t, &triangle_mock::rotate);
auto action2 = untangle::bind(c, &circle_mock::rotate);
auto action3 = untangle::bind(s, &square_mock::rotate);

auto actuator_rotate = untangle::connect(action1, action2, action3);
actuator_rotate(20);

// connect() deduces the action type from its arguments. A lambda has its own closure type
// and is not a std::function until something converts it, so a call made only of anonymous
// lambdas has nothing to deduce from and the signature has to be named on connect()
// itself. Naming the type of the variable assigned to would not supply it: template
// arguments are never deduced from what the returned value is assigned to.
auto actuator_scale = untangle::connect<std::function<int(int)>>([](int v) { return v * 2; },
    [](int v) { return v * 3; });

actuator_scale(10);
ASSERT_THAT(actuator_scale.results, ::testing::ElementsAre(20, 30));
```

7.1.2.2 connect() [2/4]

```
template<typename action_t, typename... Actions>
actuator< action_t > untangle::connect (
    std::type_identity_t< action_t > && A1,
    Actions &&... An)
```

Creates an actuator owning an initial list of actions.

This overload takes the first action by rvalue, so it is the one that accepts a leading anonymous lambda. `std::type_identity_t` makes `action_t` a non-deduced context here, which is what both keeps this overload out of the way of the lvalue one – it is not a candidate at all unless `action_t` is named – and states the requirement described by the warning on the overload taking the first action by lvalue.

Parameters

A1	- The first action, as an rvalue.
An	- Any number of further actions, owned or pointed at by value category.

Returns

An **actuator**.

7.1.2.3 connect() [3/4]

```
template<typename action_t, typename key_t, typename... Actions>
actuator< action_t > untangle::connect (
    std::pair< key_t, action_t * > A1,
    Actions &&... An)
```

Creates an actuator holding an initial map of named actions.

Remarks

Ownership works as it does for the unnamed **connect()** overloads: a pair holding a pointer names an action the caller owns, and a pair holding an action by value – an anonymous lambda above all – hands it to the actuator to own. The two can be mixed in one call.

Warning

The action type is deduced from the pointer in the first pair, so a call whose first pair holds an anonymous lambda has nothing to deduce it from and has to name the signature on **connect()** itself, exactly as the unnamed overload does:

```
auto actuator_rotate = untangle::connect<std::function<void(int)>>(
    std::make_pair("triangle", [](int angle) { ... })),
    std::make_pair("circle", [](int angle) { ... }));
```

Remarks

`action_t` leads the template parameter list, ahead of `key_t`, so that naming it – **connect**<std::function<...>>(...) – means the same thing on every **connect()** overload. Both parameters are deduced from the first pair whenever it holds a pointer, so nothing has to be named here in the first place.

Parameters

A1	- The first name/action pair. Its second element is a pointer to an action.
An	- Any number of further name/action pairs, owned or pointed at according to whether they hold the action itself or a pointer to it.

Returns

An [actuator](#).

Example:

```
// A pair holding the action itself hands it to the actuator to own. The action type is
// deduced from a pointer, and there is no pointer here, so the signature has to be named
// on connect() -- as it does for the unnamed overload.
auto actuator_scale = untangle::connect<std::function<int(int)>>(
    std::make_pair("double", [](int v) { return v * 2; }),
    std::make_pair("triple", [](int v) { return v * 3; }));

actuator_scale.invoke_action("double", 10);
ASSERT_THAT(actuator_scale.results, ::testing::ElementsAre(20));
actuator_scale.invoke_action("triple", 10);
ASSERT_THAT(actuator_scale.results, ::testing::ElementsAre(30));
```

7.1.2.4 connect() [4/4]

```
template<typename action_t, typename key_t, typename value_t, typename... Actions>
requires (!std::is_same_v<value_t, action_t*>)
actuator< action_t > untangle::connect (
    std::pair< key_t, value_t > A1,
    Actions &&... An)
```

Creates an actuator owning an initial map of named actions.

This overload takes a first pair holding the action itself rather than a pointer to it, so it is the one that accepts a leading anonymous lambda. `action_t` is never deduced here – the `requires` clause is what keeps it from competing with the overload taking a pointer in the first pair over a leading pointer pair, which both would otherwise accept once `action_t` is named.

Parameters

A1	- The first name/action pair, holding the action itself.
An	- Any number of further name/action pairs.

Returns

An [actuator](#).

7.1.2.5 bind() [1/2]

```
template<typename class__t, typename T, typename action__t = std::function<typename function_remove_const<T>::<
type>>>
action__t untangle::bind (
    const std::shared_ptr< class__t > & obj,
    T class__t::* method)
```

Binding to a class function member.

It returns a `std::function(lambda)` that wraps the function member. It may be used to provide an action for [connect\(\)](#) or [actuator::add\(\)](#).

Remarks

It requires a shared pointer to the class type. A `std::weak_ptr` to it is captured internally in a lambda, so the binding can always check whether the shared object is still alive without keeping it alive itself. Therefore, it is safe to use actions provided by this binding inside an [actuator](#), and safe for the action to outlive the caller's shared pointer.

Parameters

obj	- Class object.
method	- Pointer to function member. It is specified as <code>&<class type>::<function member></code>

Returns

action__t - A `std::function` that wraps the pointer to function member.

Remarks

If the class object gets invalid, invoking this binding will throw an exception of type [invalid_action](#).

7.1.2.6 bind() [2/2]

```
template<typename class__t, typename T, typename action__t = std::function<typename function_remove_const<T>::<
type>>>
action__t untangle::bind (
    class__t * obj,
    T class__t::* method)
```

Binding to a class method.

Attention

It is not safe to use this binding when the pointed-to object may be destroyed. A null pointer is detected and reported as a dead action, but a pointer to an already destroyed object can not be distinguished from a valid one. Prefer the overload taking a `std::shared_ptr`.

Remarks

It is provided for convenience of use: within a class it is safe to create bindings through this pointer.

Binding a null pointer produces an action that is always dead: invoking it throws [invalid_action](#).

Parameters

obj	- Pointer to class.
method	- Pointer to function member. It is specified as <code>&<class type>::<function member></code>

Returns

action_t - A `std::function` that wraps the pointer to function member.

Chapter 8

Namespace Documentation

8.1 untangle Namespace Reference

Interface to [untangle::actuator](#) functor.

Classes

- struct [invalid_action](#)
Invalid action exception.
- struct [actuator](#)
An actuator is a functor that can trigger a dynamic list of actions (of type `std::function<...>`).

Concepts

- concept [task_callback_for](#)
Can `callback_t` serve as the completion callback of a task returning `result_t`?
- concept [testable_for_emptyiness](#)
Can `callable_t` say whether it is empty?

Typedefs

- using [task_t](#) = `std::function<void()>`
An action, its arguments and the callback it notifies, sealed into one nullary callable.

Functions

- `template<typename... Args>`
`auto last_arg (Args &&... args)`
 Get last argument of params pack;.
- `template<typename action_t, typename arg_t>`
`void connect_one (actuator< action_t > &target, arg_t &&arg)`
 Add one `connect()` argument to the actuator being built.
- `template<typename action_t, typename... Actions>`
`actuator< action_t > connect (action_t &A1, Actions &&... An)`
 Creates an actuator holding an initial list of actions.
- `template<typename action_t, typename... Actions>`
`actuator< action_t > connect (std::type_identity_t< action_t > &&A1, Actions &&... An)`
 Creates an actuator owning an initial list of actions.
- `template<typename action_t, typename entry_t>`
`void connect_named_one (actuator< action_t > &target, entry_t &&entry)`
 Add one named `connect()` argument to the actuator being built.
- `template<typename action_t, typename key_t, typename... Actions>`
`actuator< action_t > connect (std::pair< key_t, action_t * > A1, Actions &&... An)`
 Creates an actuator holding an initial map of named actions.
- `template<typename action_t, typename key_t, typename value_t, typename... Actions>`
`requires (!std::is_same_v<value_t, action_t*>)`
`actuator< action_t > connect (std::pair< key_t, value_t > A1, Actions &&... An)`
 Creates an actuator owning an initial map of named actions.
- `template<typename class_t, typename T, typename action_t = std::function<typename function_remove_const<↵`
`T>::type>>`
`action_t bind (const std::shared_ptr< class_t > &obj, T class_t::*method)`
 Binding to a class function member.
- `template<typename class_t, typename T, typename action_t = std::function<typename function_remove_const<↵`
`T>::type>>`
`action_t bind (class_t *obj, T class_t::*method)`
 Binding to a class method.
- `template<typename action_t, typename... Args>`
`task_t bind_task (action_t action, Args &&... args)`
 Binds an action to its arguments and to the callback it must notify, which comes last.

8.1.1 Detailed Description

Interface to `untangle::actuator` functor.

8.1.2 Typedef Documentation

8.1.2.1 task_t

using `untangle::task_t = std::function<void()>`

An action, its arguments and the callback it notifies, sealed into one nullary callable.

What `bind_task()` builds, `actuator::add_task()` holds and `actuator::call_tasks()` fires.

Remarks

An action is a subscription; a task is a one-shot: it carries its own arguments, is fired once and reports to its own callback – so it is held by value, and `call_tasks()` consumes it.

Running it is what reports, and it returns nothing: the result goes to the callback and nowhere else, so there is nothing to read back and no part of it to reach from outside.

It names neither the argument types nor the result type, so one container holds tasks built from completely different actions. Anything that can be a `std::function<void()>` is a task.

8.1.3 Function Documentation

8.1.3.1 `last_arg()`

```
template<typename... Args>
auto untangle::last_arg (
    Args &&... args)
```

Get last argument of params pack;.

Template Parameters

Args	params template types
------	-----------------------

Parameters

args	params
------	--------

Returns

last param value in case it exist, otherwise 0.

8.1.3.2 `connect_one()`

```
template<typename action__t, typename arg__t>
void untangle::connect_one (
    actuator< action__t > &target,
    arg__t && arg)
```

Add one **connect()** argument to the actuator being built.

An argument that is an lvalue of the action type is one the caller owns: only its address is stored, and it has to outlive the actuator. Anything else – an anonymous lambda, a temporary `std::function`, a named lambda that is not an `action__t` yet – has no owner to outlive the actuator, so it is converted to an action and moved into it.

Remarks by Doxygen

Empty actions are dropped rather than stored, which is what **connect()** has always done with them. Dropping an empty owned action before it is stored is what keeps **actuator::owned** free of entries nothing points at.

Template Parameters

<code>action_↔ _t</code>	Action type of the actuator being built.
<code>arg_t</code>	Deduced type of the argument, carrying its value category.

Parameters

<code>target</code>	- The actuator being built.
<code>arg</code>	- One connect() argument.

8.1.3.3 `connect_named_one()`

```
template<typename action_t, typename entry_t>
void untangle::connect_named_one (
    actuator< action_t > & target,
    entry_t && entry)
```

Add one named [connect\(\)](#) argument to the actuator being built.

It is [connect_one\(\)](#) for the named overloads: the second element of the pair decides ownership. A pointer to an action is one the caller owns and is only stored; anything else – an anonymous lambda, a temporary `std::function` – is converted to an action and moved into the actuator.

Remarks

A null pointer is dropped rather than stored, which is what the named [connect\(\)](#) has always done with one. An owned action that is empty is dropped for the same reason the unnamed [connect_one\(\)](#) drops one: nothing would ever point at it.

Template Parameters

<code>action_↔ _t</code>	Action type of the actuator being built.
<code>entry_t</code>	Deduced type of the pair, carrying its value category.

Parameters

<code>target</code>	- The actuator being built.
<code>entry</code>	- One name/action pair.

8.1.3.4 `bind_task()`

```
template<typename action_t, typename... Args>
task_t untangle::bind_task (
    action_t action,
    Args &&... args)
```

Binds an action to its arguments and to the callback it must notify, which comes last.

Running the `task_t` it returns invokes the action and then hands the callback what it returned. The arguments are copied here, while the caller still holds them, and handed to the action as the task's own lvalues – a task runs later than it was built.

Remarks

The callback is the last argument, by position, not recognised by its type as an action's is: a pack cannot be followed by a deducible parameter, so it is split off here and callers above just forward (action, args...). `task_callback_for` only asks whether it can serve, which is what lets it be required. It is not forwarded to the action, which therefore needs no callback parameter of its own – and a void action is a task like any other.

Attention

Each argument is copied, so a move-only one does not compile.

An empty callback or an empty action builds an empty task, which `actuator::add_task()` refuses. Only a callable that can be tested for emptiness is tested, so a bare lambda is never refused.

Template Parameters

<code>action_t</code>	Type of the action; any callable naming a <code>result_type</code> will do.
<code>Args</code>	Types of the arguments to bind, of which the last is the callback.

Parameters

<code>action</code>	- The action to bind.
<code>args</code>	- The arguments to bind to action, followed by the callback to notify.

Returns

The task, or an empty one – see above.

Chapter 9

Concept Documentation

9.1 `untangle::task_callback_for` Concept Reference

Can `callback_t` serve as the completion callback of a task returning `result_t`?

```
#include <actuator.hpp>
```

9.1.1 Concept definition

```
template<typename callback_t, typename result_t>
concept task_callback_for =
    requires(callback_t& c, result_t& r) { requires std::is_void_v<decltype(c(r))>; } ||
    (std::is_void_v<result_t> &&
     requires(callback_t& c) { requires std::is_void_v<decltype(c())>; })
```

9.1.2 Detailed Description

Can `callback_t` serve as the completion callback of a task returning `result_t`?

It asks only whether it can serve, never whether it was meant as one: `bind_task()` takes the callback by position. A void result reports finished, so its callback takes no argument.

Attention

Both disjuncts are load-bearing: the first yields false for a void result rather than failing hard (void& in a requires-parameter list is a substitution failure in the immediate context), and the second's `std::is_void_v` guard keeps a `std::function<void()>` from satisfying this for any result type.

Template Parameters

<code>callback_</code> <code>_t</code>	Type of the callback.
<code>result_t</code>	Result type of the task it reports on.

9.2 untangle::testable_for__emptiness Concept Reference

Can callable_t say whether it is empty?

```
#include <actuator.hpp>
```

9.2.1 Concept definition

```
template<typename callable_t>
concept testable_for__emptiness =
    std::is_pointer_v<callable_t> || requires(const callable_t& c) { c.operator bool(); }
```

9.2.2 Detailed Description

Can callable_t say whether it is empty?

bind_task() refuses an empty action or an empty callback, and has to decide first whether that question can be put at all. A std::function answers it with operator bool, and a pointer with its own value.

Attention

A lambda is not asked, and asking anyway is worse than not asking. A captureless one converts implicitly to a function pointer, so a plain static_cast<bool> test compiles and answers on its behalf – always true, because that conversion never yields null. The test is dead for every lambda that reaches it, and MSVC reports the conversion it rests on as a truncation (C4305). Asking for operator bool by name is what leaves a lambda out.

Template Parameters

callable_t	Type of the action or the callback.
------------	-------------------------------------

Chapter 10

Class Documentation

10.1 untangle::actuator< action_t > Struct Template Reference

An actuator is a functor that can trigger a dynamic list of actions (of type `std::function<...>`).

```
#include <actuator.hpp>
```

Public Types

- using `actions_t` = `std::list<action_t*>`
Actions container type.
- using `tasks_t` = `std::list<task_t>`
Tasks container type.
- using `results_t` = `std::vector<typename result_t::type>`
Results container type.
- using `errors_t` = `std::vector<std::exception_ptr>`
Errors container type.

Public Member Functions

- `actuator` (const actuator &other)
Copy constructor.
- actuator & `operator=` (const actuator &other)
Assignment operator.
- action_t `type` () const
Helper method to access the action type of this object.
- void `reset` ()
Remove all actions, and any stored results and errors.
- void `copy_from` (const actuator &other)
Copy another actuator, re-pointing the copied actions at this object's storage.
- void `release_owned` (const action_t *action)
Destroy an owned action that nothing points at any more.
- template<typename last_t>
void `invoke_callback` (last_t &last)
Invoke the trailing callback argument, if the invocation has one.

- `template<typename... Args>`
`void operator()` (`Args &&... args`)
The call operator.
- `template<typename... Args>`
`void invoke_action` (`const std::string &name, Args &&... args`)
Invokes one single action associated with a key.
- `void call_tasks` ()
Fires every task held, in the order `add_task()` took them, and empties the list.
- `void add` (`action_t *action`)
Add an action to the actions list.
- `action_t * add` (`action_t &&action`)
Add an action the actuator owns.
- `void add` (`const std::string &name, action_t *action`)
Add action to the actions map associated with a name.
- `action_t * add` (`const std::string &name, action_t &&action`)
Add an action the actuator owns, associated with a name.
- `bool add_task` (`task_t &&task`)
Adds a task, to be fired by `call_tasks()`.
- `void remove` (`const action_t *action`)
Remove an action from the actions list.
- `void remove` (`const std::string &name`)
Remove an action from actions map.
- `bool is_connected` () `const`
Check if this actuator is "connected" with other actions.
- `bool has_tasks` () `const`
Is there a task waiting to be fired?
- `bool has_action` (`const std::string &name`) `const`
Check if there is certain named action.

Public Attributes

- `actions_t` actions
Actions list.
- `actions_map_t` actions_map
Named actions map.
- `results_t` results
Actions return values list.
- `errors_t` errors
What the actions threw. See `errors_t`.
- `tasks_t` tasks
Tasks waiting to be fired, in the order `add_task()` took them.
- `std::list< action_t > owned`
Actions this actuator owns, as added by `add(action_t&&)`.

10.1.1 Detailed Description

```
template<typename action_t>
struct untangle::actuator< action_t >
```

An actuator is a functor that can trigger a dynamic list of actions (of type `std::function<...>`).

Remarks

An actuator object can be constructed with an initial list of actions by [connect\(\)](#).

Callback convention: when the last argument of an invocation can be called with the action return type `R` and returns nothing, it is not passed on as a plain argument alone – it is also treated as a completion callback. The action is invoked with the full argument list as usual, and the callback is then invoked with the action return value. Any void returning callable qualifies: a `std::function<void(R)>`, a lambda taking `R`, a function pointer. It applies to [operator\(\)](#) and to [invoke_action\(\)](#) alike. Actions returning void have no result to report, so no callback is invoked for them.

Warning

The return type is what separates a callback from an argument the action means to consume itself. A trailing callable that returns a value – a transform, a comparator – is left alone, and by the same rule a callback written to return something is silently not invoked. A callback returns nothing.

Remarks

Argument convention: an action must not take ownership of the arguments it is invoked with. [operator\(\)](#) forwards one argument pack to every action in the list, and an rvalue can be moved from only once, so an action that consumes an argument leaves the actions after it holding a moved-from object – an empty `std::function` for a callback a later action means to call itself. The arguments are forwarded rather than copied so that a single action pays nothing for the broadcast; what that buys has to be respected by the actions.

Warning

An action does not have to move an argument in its body to consume it: a parameter taken by value is move constructed from an rvalue by the call itself. Take arguments by reference or const reference, or invoke with lvalues, whenever more than one action is connected. The behaviour is otherwise unpredictable, and it is the caller and the action signatures together that decide it – an actuator cannot detect the violation.

Remarks

[invoke_action\(\)](#) invokes one single action, so nothing follows it and the convention does not constrain it.

Failure convention: an action that throws does not stop the invocation. What it threw is stored in [actuator::errors](#), one `std::exception_ptr` per failure, and the actions after it still run. An [untangle::invalid_action](#) means a dead binding, so that action is dropped as well; anything else leaves the action in place. Nothing is printed and nothing escapes the call - the caller reads [actuator::errors](#) and decides.

Ownership convention: an actuator normally does not own its actions. It stores pointers to `std::function` objects the caller keeps alive, and those have to outlive it. [add\(action_t&&\)](#) is the exception – it moves the action into [actuator::owned](#) and points at the stored copy – which is what lets [add_anonymous_lambda](#) be an action, with no named variable to keep around. The handle it returns is the only way to [remove\(\)](#) such an action afterwards.

Template Parameters

<code>action_↔ _t</code>	Action type. It is specified as <code>std::function<...></code> .
------------------------------	---

10.1.2 Member Typedef Documentation

10.1.2.1 `actions_t`

```
template<typename action_t>
using untangle::actuator< action_t >::actions_t = std::list<action_t*>
```

Actions container type.

Remarks

The elements stored are of pointer type, that is required to implement the [remove\(\)](#) operation. `std::function` supports only equality operator for `nullptr` (two `std::function(s)` can not compare).

10.1.2.2 `tasks_t`

```
template<typename action_t>
using untangle::actuator< action_t >::tasks_t = std::list<task\_t>
```

Tasks container type.

Remarks

The elements are values, not pointers: identity is what [remove\(\)](#) needs of an action, and no one removes a single task – [call_tasks\(\)](#) consumes the whole list.

A `std::list`, as [owned](#) is – adding never invalidates the address of an element already in it, so a reference taken into the list stays good. It names no result type, because [untangle::task_t](#) does not.

10.1.2.3 `results_t`

```
template<typename action_t>
using untangle::actuator< action_t >::results_t = std::vector<typename result_t::type>
```

Results container type.

It holds the return values of the actions that have a non-void return type. Upon the actuator invocation, the returns can be extracted from [results](#).

10.1.2.4 `errors_t`

```
template<typename action_t>
using untangle::actuator< action_t >::errors_t = std::vector<std::exception_ptr>
```

Errors container type.

It holds what the actions threw, as `std::exception_ptr`, in the order they were invoked.

10.1.3 Constructor & Destructor Documentation

10.1.3.1 actuator()

```
template<typename action_t>
untangle::actuator< action_t >::actuator (
    const actuator< action_t > & other) [inline]
```

Copy constructor.

Remarks

It can not be defaulted, see [copy_from\(\)](#).

10.1.4 Member Function Documentation

10.1.4.1 operator=()

```
template<typename action_t>
actuator & untangle::actuator< action_t >::operator= (
    const actuator< action_t > & other) [inline]
```

Assignment operator.

Example:

```
const auto t = std::make_shared<triangle_mock>();
const auto c = std::make_shared<circle_mock>();
const auto s = std::make_shared<square_mock>();

EXPECT_CALL(*t, rotate(testing::_)).WillOnce(testing::Return());
EXPECT_CALL(*c, rotate(testing::_)).WillOnce(testing::Return());
EXPECT_CALL(*s, rotate(testing::_)).WillOnce(testing::Return());
auto action1 = untangle::bind(t, &triangle_mock::rotate);
auto action2 = untangle::bind(c, &circle_mock::rotate);
auto action3 = untangle::bind(s, &square_mock::rotate);

auto actuator_rotate = untangle::connect(action1, action2, action3);
untangle::actuator<decltype(actuator_rotate.type())> actuator_rotate_1 = actuator_rotate;
actuator_rotate_1(20);

testing::Mock::VerifyAndClearExpectations(t.get());
testing::Mock::VerifyAndClearExpectations(c.get());
testing::Mock::VerifyAndClearExpectations(s.get());
```

10.1.4.2 type()

```
template<typename action_t>
action_t untangle::actuator< action_t >::type () const [inline]
```

Helper method to access the action type of this object.

Note

Intended to be used in expressions by `decltype(<actuator instance>.type())`

Returns

`action_t`

10.1.4.3 reset()

```
template<typename action_t>
void untangle::actuator< action_t >::reset () [inline]
```

Remove all actions, and any stored results and errors.

After this call the actuator is empty: `actuator::is_connected()` returns false. The actions it owns are destroyed, so every handle returned by `add(action_t&&)` is dangling afterwards; the actions it merely points at are left untouched.

10.1.4.4 copy_from()

```
template<typename action_t>
void untangle::actuator< action_t >::copy_from (
    const actuator< action_t > & other) [inline]
```

Copy another actuator, re-pointing the copied actions at this object's storage.

Remarks

A defaulted copy is wrong as soon as an actuator owns anything: it duplicates `actuator::owned` but leaves `actuator::actions` pointing into other's copy of it, so the new object dangles the moment other is destroyed. The owned actions are copied first, then each pointer into `other::owned` is translated to the matching element here.

A pointer to an action the caller owns is external to both actuators and is copied unchanged: it is not in either `actuator::owned`, so it is not in the translation table and is left as it is.

Parameters

other	- The actuator to copy. Self copy is the caller's to exclude.
-------	---

10.1.4.5 release_owned()

```
template<typename action_t>
void untangle::actuator< action_t >::release_owned (
    const action_t * action) [inline]
```

Destroy an owned action that nothing points at any more.

Remarks

Removing an action only drops a pointer to it. When the actuator owns that action the `std::function` itself lives in `actuator::owned` and has to go too, or a loop of `add(action_t&&)` and `remove()` grows `actuator::owned` without bound.

The action is kept while anything still refers to it: one handle can be added to both the list and the map, and removing it from one must not leave the other pointing at a destroyed object. An action the actuator does not own is not in `actuator::owned`, so nothing is found to erase and the caller's object is left alone.

Parameters

action	- The action just removed. A null pointer is accepted and matches nothing.
--------	--

10.1.4.6 invoke_callback()

```
template<typename action_t>
template<typename last_t>
void untangle::actuator< action_t >::invoke_callback (
    last_t & last) [inline]
```

Invoke the trailing callback argument, if the invocation has one.

Does nothing unless last_t can be called with the action return type and returns nothing, so any other trailing argument is left alone. The test is on what the type can do, not on what it is, so a plain lambda qualifies as well as a std::function. See the callback convention on [actuator](#).

Remarks

The single condition does the work of two tests: (1) whether last can be called with the action return type at all, and (2) whether that call returns nothing. Spelled out as traits they need two nested if constexpr:

```
// (1)
if constexpr (std::is_invocable_v<last_t&, typename result_t::type>) {
// (2)
    if constexpr (std::is_void_v<std::invoke_result_t<last_t&, typename result_t::type>») {
        last(results.back());
    }
}
```

Both are folded into the one expression instead, each in a different part of it:

```
requires { requires std::is_void_v<decltype( last(results.back()) )>; }
//      \_____ (2) _____/      \_____ (1) _____/
```

Remarks

(1) Invocability comes for free. To form decltype(last(results.back())) the compiler must first form the call last(...). If last is an int, that expression does not exist – and inside a requires-expression a substitution failure yields false instead of being ill formed, the same property concepts are built on. So invocability is never tested separately: it is a precondition of the return type question, and failing it is what makes the whole condition false.

(2) The return type test is the inner requires, and the doubled keyword is not a typo. requires { expr; } asks only whether expr is well formed, and std::is_void_v<...> is well formed when it is false too – that spelling would let a value returning callable through. The second keyword makes it a nested requirement: a condition that has to hold, not merely compile.

The trait spelling has to nest, which is part of why it is not the one used here: the two if constexpr cannot be joined with &&. && short circuits evaluation, not instantiation, so std::invoke_result_t is formed whatever the first trait says, and for a type that is not invocable at all it has no ::type – a hard error rather than a false result.

The caller must copy the callback out of the argument pack before invoking the action: an action taking it by value moves from the caller's std::function, which would leave this an empty function to call.

Template Parameters

<code>last_↔ _t</code>	Type of the last argument, as returned by <code>last_arg()</code> .
----------------------------	---

Parameters

<code>last</code>	- Last argument value, copied before the action was invoked.
-------------------	--

10.1.4.7 `operator>()()`

```
template<typename action_t>
template<typename... Args>
void untangle::actuator< action_t >::operator() (
    Args &&... args) [inline]
```

The call operator.

Actions in the `actuator::actions` list are triggered by invoking the call operator.

Parameters

<code>args</code>	- Arguments list must match the action arity. A trailing callback is invoked once per action, with that action's return value; see the convention on <code>actuator</code> .
-------------------	--

Warning

The same argument pack is forwarded to every action in the list, so the argument convention on `actuator` applies here in full: an action that consumes an argument leaves the actions after it with a moved-from object.

Remarks

Nothing escapes this call: what an action throws goes to `actuator::errors`, and the actions after it still run. See the failure convention on `actuator`.

10.1.4.8 `invoke_action()`

```
template<typename action_t>
template<typename... Args>
void untangle::actuator< action_t >::invoke_action (
    const std::string & name,
    Args &&... args) [inline]
```

Invokes one single action associated with a key.

Generated by Doxygen

An action that can not be invoked – a null pointer, an empty `std::function`, a binding whose object is gone – is dropped from `actuator::actions_map` instead, exactly as `operator>()()` drops one from `actuator::actions`.

Parameters

name	- Key associated with the action. Invoking a key that is not in the map does nothing.
args	- Arguments list must match the action arity. A trailing callback is invoked with the action's return value; see the convention on actuator .

10.1.4.9 call_tasks()

```
template<typename action_t>
void untangle::actuator< action_t >::call_tasks () [inline]
```

Fires every task held, in the order [add_task\(\)](#) took them, and empties the list.

Each task notifies its own callback as it runs, and its result goes there alone – never to [actuator::results](#). It does not fire the actions, as [operator>\(\)](#) does not fire the tasks.

Remarks

Errors are appended to [actuator::errors](#), which [operator>\(\)](#) clears instead – so `one(); one.call_tasks();` reports both kinds together, and the actions go first.

Attention

Finished does not mean failed. A task that throws does not stop the pass and is not notified; a callback that throws lands in [actuator::errors](#) the same way. The task is consumed either way, so a caller waiting on the callback alone must read the errors.

10.1.4.10 add() [1/4]

```
template<typename action_t>
void untangle::actuator< action_t >::add (
    action_t * action) [inline]
```

Add an action to the actions list.

Parameters

action	- Action to be added.
--------	-----------------------

Example:

```
const auto t = std::make_shared<triangle_mock>();
const auto c = std::make_shared<circle_mock>();
const auto s = std::make_shared<square_mock>();

EXPECT_CALL(*t, rotate(testing::_)).Times(2).WillRepeatedly(testing::Return());
EXPECT_CALL(*c, rotate(testing::_)).WillOnce(testing::Return());
EXPECT_CALL(*s, rotate(testing::_)).WillOnce(testing::Return());
auto action1 = untangle::bind(t, &triangle_mock::rotate);
auto action2 = untangle::bind(c, &circle_mock::rotate);
auto action3 = untangle::bind(s, &square_mock::rotate);

auto actuator_rotate = untangle::connect(action1, action2, action3);
actuator_rotate.add(&action1);
actuator_rotate(20);

testing::Mock::VerifyAndClearExpectations(t.get());
testing::Mock::VerifyAndClearExpectations(c.get());
testing::Mock::VerifyAndClearExpectations(s.get());
```

10.1.4.11 add() [2/4]

```
template<typename action_t>
action_t * untangle::actuator< action_t >::add (
    action_t && action)    [inline]
```

Add an action the actuator owns.

The action is moved into `actuator::owned`, so it needs no named variable outliving the actuator: an anonymous lambda can be passed straight in, and the call converts it to `action_t`. See the ownership convention on `actuator`.

Parameters

action	- Action to be added. It is taken by value and moved from.
--------	--

Returns

`action_t*` - A handle to the stored action, to pass to `remove()`. It stays valid until that action is removed or the actuator is destroyed. A copy of the actuator owns its own copy of the action and has its own handle to it.

Example:

```
// An anonymous lambda has no named variable to outlive the actuator, so the actuator takes
// ownership of it: it is moved into actuator::owned and the list points at the stored copy.
untangle::actuator<std::function<int(int)>> actuator_scale;
actuator_scale.add([](int v) { return v * 2; });
actuator_scale.add([](int v) { return v * 3; });

actuator_scale(10);
ASSERT_THAT(actuator_scale.results, ::testing::ElementsAre(20, 30));
```

10.1.4.12 add() [3/4]

```
template<typename action_t>
void untangle::actuator< action_t >::add (
    const std::string & name,
    action_t * action)    [inline]
```

Add action to the actions map associated with a name.

Parameters

name	- Name of the action.
action	- Action to be added.

10.1.4.13 add() [4/4]

```
template<typename action_t>
action_t * untangle::actuator< action_t >::add (
    const std::string & name,
    action_t && action)    [inline]
```

Parameters

name	- Name of the action.
action	- Action to be added. It is taken by value and moved from.

Returns

action_t* - A handle to the stored action, as `add(action_t&&)` returns, or nullptr when name is already taken. The name already in the map keeps the action it has, as it does for `add(const std::string&, action_t*)`, and the action offered here is dropped rather than left ownerless in `actuator::owned`.

10.1.4.14 add_task()

```
template<typename action_t>
bool untangle::actuator< action_t >::add_task (
    task_t && task) [inline]
```

Adds a task, to be fired by `call_tasks()`.

It is stored by value: an actuator owns every task it holds, unlike the actions it merely points at. Anything that can be an `untangle::task_t` is taken, from `bind_task()` or not. There is no counterpart to `remove()` and no named form – `call_tasks()` consumes the list, and tasks fire as a batch, in the order they were added.

Attention

It refuses an empty task, and the refusal is the whole report: nothing is thrown and nothing is stored. It lands while the caller is still on the stack, rather than surfacing from `call_tasks()` as a `std::bad_function_call` read as the failure of a task that had in fact run.

Parameters

task	- The task to add. Taken by value and moved from; a refused one is dropped.
------	---

Returns

true - taken, and `call_tasks()` will fire it.
false - refused: it is empty, so it can neither run nor report.

10.1.4.15 remove() [1/2]

```
template<typename action_t>
void untangle::actuator< action_t >::remove (
    const action_t * action) [inline]
```

Remove an action from the actions list.

An invalid action (empty `std::function`) is implicitly removed when `operator>()()` is invoked.

An action the actuator owns is destroyed by this call, so the handle to it is dangling afterwards. See

Parameters

action	- Action to be removed. For an owned action this is the handle returned by add(action_t&&) .
--------	--

Example:

```

const auto t = std::make_shared<triangle_mock>();
const auto c = std::make_shared<circle_mock>();
const auto s = std::make_shared<square_mock>();

EXPECT_CALL(*t, rotate(testing::_)).Times(0);
EXPECT_CALL(*c, rotate(testing::_)).WillOnce(testing::Return());
EXPECT_CALL(*s, rotate(testing::_)).WillOnce(testing::Return());
auto action1 = untangle::bind(t, &triangle_mock::rotate);
auto action2 = untangle::bind(c, &circle_mock::rotate);
auto action3 = untangle::bind(s, &square_mock::rotate);

auto actuator_rotate = untangle::connect(action1, action2, action3);
actuator_rotate.remove(&action1);
actuator_rotate(50);

testing::Mock::VerifyAndClearExpectations(t.get());
testing::Mock::VerifyAndClearExpectations(c.get());
testing::Mock::VerifyAndClearExpectations(s.get());

```

10.1.4.16 remove() [2/2]

```

template<typename action_t>
void untangle::actuator< action_t >::remove (
    const std::string & name) [inline]

```

Remove an action from actions map.

An action the actuator owns is destroyed by this call, so the handle to it is dangling afterwards. See [release_owned\(\)](#).

Parameters

name	- Name of the action to remove.
------	---------------------------------

10.1.4.17 is_connected()

```

template<typename action_t>
bool untangle::actuator< action_t >::is_connected () const [inline]

```

Check if this actuator is "connected" with other actions.

Remarks

It answers for the actions and for nothing else. Tasks are not actions and do not make an actuator connected; ask [has_tasks\(\)](#) about those. Kept this way deliberately when tasks arrived, because a caller that will never hold a task – an attachment, a poll – reads this and must keep reading the answer it always read.

Returns

true - if the [actuator::actions](#) list is not empty.
false - if the [actuator::actions](#) list is empty.

10.1.4.18 has_tasks()

```
template<typename action_t>
bool untangle::actuator< action_t >::has_tasks () const [inline]
```

Is there a task waiting to be fired?

The counterpart to [is_connected\(\)](#), and the two answer different questions: this one is about [actuator::tasks](#), that one about [actuator::actions](#). An actuator can hold either, both, or neither.

Remarks

It is what a queue asks to decide whether its worker still has work. Reading [is_connected\(\)](#) for that would report a batch of tasks as nothing to do, and the work would sit unfired.

A refused task is not a waiting one: [add_task\(\)](#) answering false means the task was dropped, so this stays false.

Returns

true - a task is waiting; [call_tasks\(\)](#) has something to fire.

false - no task is waiting. True again after [call_tasks\(\)](#), which consumes them.

10.1.4.19 has_action()

```
template<typename action_t>
bool untangle::actuator< action_t >::has_action (
    const std::string & name) const [inline]
```

Check if there is certain named action.

Parameters

name	- Name associated with the action.
------	------------------------------------

Returns

true - if name can be found in [actuator::actions_map](#)

false - if name can not be found in [actuator::actions_map](#)

10.1.5 Member Data Documentation

10.1.5.1 tasks

```
template<typename action_t>
tasks_t untangle::actuator< action_t >::tasks
```

Tasks waiting to be fired, in the order [add_task\(\)](#) took them.

Remarks

Held beside [actions](#) and sharing nothing with them: [operator>\(\)\(\)](#) fires the actions and leaves these alone, [call_tasks\(\)](#) fires these and leaves the actions alone.

10.1.5.2 owned

```
template<typename action_t>
std::list<action_t> untangle::actuator< action_t >::owned
```

Actions this actuator owns, as added by [add\(action_t&&\)](#).

Remarks

It is a `std::list` because inserting into one never invalidates the address of an element already in it, so every handle already handed out stays valid as further actions are added. A `std::vector` would reallocate and dangle all of them at once.

The documentation for this struct was generated from the following file:

- `actuator.hpp`

10.2 [untangle::invalid_action](#) Struct Reference

Invalid action exception.

```
#include <actuator.hpp>
```

Public Member Functions

- [invalid_action](#) (`std::string text`)
Construct a new invalid action object.
- `const char * what ()` `const` noexcept override
The message text describing the reason of this exception.

10.2.1 Detailed Description

Invalid action exception.

Remarks

An action may be provided as a binding to a class function member, by using [untangle::bind\(\)](#). When the class object gets invalid, invoking the action will raise an exception to this type.

10.2.2 Constructor & Destructor Documentation

10.2.2.1 `invalid_action()`

```
untangle::invalid\_action::invalid\_action (  
    std::string text) [inline], [explicit]
```

Construct a new invalid action object.

Parameters

text	- A message text, describing the reason of this exception.
------	--

10.2.3 Member Function Documentation

10.2.3.1 what()

const char * untangle::invalid_action::what () const [inline], [override], [noexcept]

The message text describing the reason of this exception.

Returns

const char* - The message text.

The documentation for this struct was generated from the following file:

- actuator.hpp

Chapter 11

File Documentation

11.1 actuator.hpp

```
00001 // Copyright (c) 2018 Nicolae Popescu. MIT License.
00002
00003 // Two doxygen gotchas this file has met, for whoever writes the next comment in it. Both cost a
00004 // session before they were understood; tools/make_doc.sh fails on either, so neither reaches the
00005 // PDF. Recorded in todo/FEATURE_PLAN.md as well.
00006 // - A \ref from inside a concept's documentation block never resolves. It resolves from an
00007 //   ordinary block -- a using, a function, a member -- which is what makes the failure read as a
00008 //   missing symbol. Name symbols in code font inside a concept.
00009 // - A colon run onto a \ref is swallowed into the symbol name: '\ref owned:' is read as a
00010 //   reference to a symbol called `owned:`. End the sentence, or reword, rather than punctuating
00011 //   straight after a reference.
00012
00016 #pragma once
00017
00018 #include <cstdint>
00019 #include <exception>
00020 #include <functional>
00021 #include <list>
00022 #include <map>
00023 #include <memory>
00024 #include <string>
00025 #include <tuple>
00026 #include <type_traits>
00027 #include <utility>
00028 #include <vector>
00029
00030 namespace untangle {
00031 // exception
00040 struct invalid_action : std::exception {
00046     explicit invalid_action(std::string text) : message(std::move(text)) {}
00047
00053     const char* what() const noexcept override { return message.c_str(); }
00054
00055 private:
00056     std::string message;
00057 };
00058
00066 template <typename... Args>
00067 auto last_arg(Args&&... args) {
00068     if constexpr (sizeof...(Args) <= 0) {
00069         return 0;
00070     } else {
00071         return std::get<sizeof...(Args) - 1>(std::forward_as_tuple(args...));
00072     }
00073 }
00074
00089 template <typename callback_t, typename result_t>
00090 concept task_callback_for =
00091     requires(callback_t& c, result_t& r) { requires std::is_void_v<decltype(c(r))>; } ||
00092     (std::is_void_v<result_t> &&
00093      requires(callback_t& c) { requires std::is_void_v<decltype(c())>; });
00094
00110 template <typename callable_t>
00111 concept testable_for_emptyiness =
00112     std::is_pointer_v<callable_t> || requires(const callable_t& c) { c.operator bool(); };
00113
00129 using task_t = std::function<void()>;
```

```

00130
00182 template <typename action_t>
00183 struct actuator final {
00191     using actions_t = std::list<action_t*>;
00192     using actions_map_t = std::map<std::string, action_t*>;
00203     using tasks_t = std::list<task_t>;
00204     using result_t = std::conditional<std::is_void<typename action_t::result_type>::value, int,
00205                                     typename action_t::result_type>;
00212     using results_t = std::vector<typename result_t::type>;
00218     using errors_t = std::vector<std::exception_ptr>;
00219
00220     actions_t actions;
00221     actions_map_t actions_map;
00222     results_t results;
00223     errors_t errors;
00224
00231     tasks_t tasks;
00232
00240     std::list<action_t> owned;
00241
00242     actuator() = default;
00248     actuator(const actuator& other) { copy_from(other); }
00249     actuator(actuator&&) noexcept = default;
00250     ~actuator() = default;
00257     actuator& operator=(const actuator& other) {
00258         if (this != &other) {
00259             copy_from(other);
00260         }
00261         return *this;
00262     }
00263     actuator& operator=(actuator&&) noexcept = default;
00264
00272     action_t type() const { return nullptr; }
00273
00281     void reset() {
00282         actions.clear();
00283         actions_map.clear();
00284         results.clear();
00285         errors.clear();
00286         owned.clear();
00287     }
00288
00303     void copy_from(const actuator& other) {
00304         owned = other.owned;
00305
00306         // Old address -> new address, for the owned actions only.
00307         std::map<const action_t*, action_t*> remap;
00308         auto src = other.owned.begin();
00309         auto dst = owned.begin();
00310         for (; src != other.owned.end(); ++src, ++dst) {
00311             remap.emplace(&*src, &*dst);
00312         }
00313         const auto translate = [&remap](action_t* action) {
00314             const auto it = remap.find(action);
00315             return it != remap.end() ? it->second : action;
00316         };
00317
00318         actions.clear();
00319         for (const auto& action : other.actions) {
00320             actions.push_back(translate(action));
00321         }
00322         actions_map.clear();
00323         for (const auto& entry : other.actions_map) {
00324             actions_map.emplace(entry.first, translate(entry.second));
00325         }
00326         // Named explicitly, like every member here: this function does not default, so anything it
00327         // does not copy is silently lost by every copy of an actuator.
00328         tasks = other.tasks;
00329         results = other.results;
00330         errors = other.errors;
00331     }
00332
00347     void release_owned(const action_t* action) {
00348         for (const auto& a : actions) {
00349             if (a == action) {
00350                 return;
00351             }
00352         }
00353         for (const auto& entry : actions_map) {
00354             if (entry.second == action) {
00355                 return;
00356             }
00357         }
00358         owned.remove_if([action](const action_t& a) { return &a == action; });
00359     }
00360
00416     template <typename last_t>

```

```

00417 void invoke_callback(last_t& last) {
00418     if constexpr (requires { requires std::is_void_v<decltype(last(results.back()))>; }) {
00419         last(results.back());
00420     }
00421 }
00422
00438 template <typename... Args>
00439 void operator()(Args&&... args) {
00440     results.clear();
00441     errors.clear();
00442
00443     // Copied up front, before any action can move the callback out of the argument pack.
00444     auto last = last_arg(args...);
00445
00446     // Dead bindings are collected here and dropped after the loop.
00447     // The actuator does not own the actions it points at, so it must never
00448     // write through action_t* into a std::function belonging to the caller.
00449     std::vector<action_t*> dead_actions;
00450
00451     for (const auto& action : actions) {
00452         // A null pointer or an empty std::function can never be invoked. Calling an
00453         // empty one throws std::bad_function_call, which is not an invalid_action and
00454         // would escape this operator, so drop it instead of invoking it.
00455         if (action == nullptr || !*action) {
00456             dead_actions.push_back(action);
00457             continue;
00458         }
00459
00460         try {
00461             if constexpr (std::is_same_v<typename action_t::result_type, void>) {
00462                 (*action)(std::forward<Args>(args)...);
00463             } else {
00464                 results.push_back((*action)(std::forward<Args>(args)...));
00465                 invoke_callback(last);
00466             }
00467         } catch (const invalid_action&) {
00468             // A dead binding is not coming back: it is recorded and the action is dropped.
00469             errors.push_back(std::current_exception());
00470             dead_actions.push_back(action);
00471         } catch (...) {
00472             // Anything else is the action's own failure. It is recorded, the action is kept, and the
00473             // actions behind it still run.
00474             errors.push_back(std::current_exception());
00475         }
00476     }
00477
00478     for (const auto& dead_action : dead_actions) {
00479         actions.remove(dead_action);
00480         release_owned(dead_action);
00481     }
00482 }
00483
00500 template <typename... Args>
00501 void invoke_action(const std::string& name, Args&&... args) {
00502     results.clear();
00503     errors.clear();
00504
00505     // Copied up front, before the action can move the callback out of the argument pack.
00506     auto last = last_arg(args...);
00507     const auto it = actions_map.find(name);
00508     if (it == actions_map.end()) {
00509         return;
00510     }
00511
00512     // A null pointer or an empty std::function can never be invoked, and dereferencing a
00513     // null one to try is undefined behaviour before a call is even made. Calling an empty
00514     // one throws std::bad_function_call, which is not an invalid_action and would escape
00515     // this method. Drop it instead, as operator()() does for the actions list.
00516     if (it->second == nullptr || !*it->second) {
00517         const action_t* dead_action = it->second;
00518         actions_map.erase(it);
00519         release_owned(dead_action);
00520         return;
00521     }
00522
00523     try {
00524         if constexpr (std::is_same_v<typename action_t::result_type, void>) {
00525             (*it->second)(std::forward<Args>(args)...);
00526         } else {
00527             results.push_back((*it->second)(std::forward<Args>(args)...));
00528             invoke_callback(last);
00529         }
00530     } catch (const invalid_action&) {
00531         errors.push_back(std::current_exception());
00532         const action_t* dead_action = it->second;
00533         actions_map.erase(name);
00534         release_owned(dead_action);

```

```

00535     } catch (...) {
00536         errors.push_back(std::current_exception());
00537     }
00538 }
00539
00553 void call_tasks() {
00554     // Taken by swap, so a callback that adds a task adds it to the *next* pass. Iterating the
00555     // member instead would let a task that re-adds itself keep this loop from ever ending -- and
00556     // it is the same reason a queue built on this takes its batch by move.
00557     tasks_t firing;
00558     firing.swap(tasks);
00559
00560     for (auto& task : firing) {
00561         try {
00562             // The task notifies its own callback: bind_task() sealed the two together.
00563             task();
00564         } catch (...) {
00565             // The task's own failure, or its callback's -- the two are not told apart here, and the
00566             // attention above says why.
00567             errors.push_back(std::current_exception());
00568         }
00569     }
00570 }
00571
00580 void add(action_t* action) { actions.push_back(action); }
00581
00597 action_t* add(action_t&& action) {
00598     owned.push_back(std::move(action));
00599     actions.push_back(&owned.back());
00600     return &owned.back();
00601 }
00602
00609 void add(const std::string& name, action_t* action) { actions_map.emplace(name, action); }
00610
00621 action_t* add(const std::string& name, action_t&& action) {
00622     owned.push_back(std::move(action));
00623     const auto [it, inserted] = actions_map.emplace(name, &owned.back());
00624     if (!inserted) {
00625         owned.pop_back();
00626         return nullptr;
00627     }
00628     return &owned.back();
00629 }
00630
00649 bool add_task(task_t&& task) {
00650     if (!task) {
00651         return false;
00652     }
00653
00654     tasks.push_back(std::move(task));
00655     return true;
00656 }
00657
00672 void remove(const action_t* action) {
00673     actions.remove_if([&action](const auto& a) { return (action == a); });
00674     release_owned(action);
00675 }
00676
00685 void remove(const std::string& name) {
00686     const auto it = actions_map.find(name);
00687     if (it == actions_map.end()) {
00688         return;
00689     }
00690     const action_t* action = it->second;
00691     actions_map.erase(it);
00692     release_owned(action);
00693 }
00694
00706 bool is_connected() const { return !actions.empty() || !actions_map.empty(); }
00707
00725 bool has_tasks() const { return !tasks.empty(); }
00726
00734 bool has_action(const std::string& name) const {
00735     return actions_map.find(name) != actions_map.end();
00736 }
00737 };
00738
00756 template <typename action_t, typename arg_t>
00757 void connect_one(actuator<action_t>& target, arg_t&& arg) {
00758     if constexpr (std::is_lvalue_reference_v<arg_t&&> &&
00759                 std::is_same_v<std::decay_t<arg_t>, action_t>) {
00760         if (arg != nullptr) {
00761             target.add(&arg);
00762         }
00763     } else {
00764         action_t action(std::forward<arg_t>(arg));
00765         if (action != nullptr) {

```

```

00766     target.add(std::move(action));
00767 }
00768 }
00769 }
00770
00813 template <typename action_t, typename... Actions>
00814 actuator<action_t> connect(action_t& A1, Actions&&... An) {
00815     actuator<action_t> target;
00816     connect_one(target, A1);
00817     (connect_one(target, std::forward<Actions>(An)), ...);
00818     return target;
00819 }
00820
00837 template <typename action_t, typename... Actions>
00838 actuator<action_t> connect(std::type_identity_t<action_t>&& A1, Actions&&... An) {
00839     actuator<action_t> target;
00840     connect_one(target, std::move(A1));
00841     (connect_one(target, std::forward<Actions>(An)), ...);
00842     return target;
00843 }
00844
00845 template <typename actuator_t>
00846 void remove_empty_actions(actuator_t& actuator) {
00847     std::vector<typename actuator_t::actions_map_t::const_iterator> removable_iterators;
00848     for (auto it = actuator.actions_map.begin(); it != actuator.actions_map.end(); ++it) {
00849         if (it->second == nullptr) {
00850             removable_iterators.push_back(it);
00851         }
00852     }
00853     for (auto it : removable_iterators) {
00854         actuator.actions_map.erase(it);
00855     }
00856 }
00857
00875 template <typename action_t, typename entry_t>
00876 void connect_named_one(actuator<action_t>& target, entry_t&& entry) {
00877     if constexpr (std::is_same_v<std::remove_cvref_t<decltype(entry.second)>, action_t*>) {
00878         if (entry.second != nullptr) {
00879             target.add(entry.first, entry.second);
00880         }
00881     } else {
00882         action_t action(std::forward<entry_t>(entry).second);
00883         if (action != nullptr) {
00884             target.add(entry.first, std::move(action));
00885         }
00886     }
00887 }
00888
00923 template <typename action_t, typename key_t, typename... Actions>
00924 actuator<action_t> connect(std::pair<key_t, action_t*> A1, Actions&&... An) {
00925     actuator<action_t> target;
00926     connect_named_one(target, std::move(A1));
00927     (connect_named_one(target, std::forward<Actions>(An)), ...);
00928     return target;
00929 }
00930
00947 template <typename action_t, typename key_t, typename value_t, typename... Actions>
00948 requires (std::is_same_v<value_t, action_t*>)
00949 actuator<action_t> connect(std::pair<key_t, value_t> A1, Actions&&... An) {
00950     actuator<action_t> target;
00951     connect_named_one(target, std::move(A1));
00952     (connect_named_one(target, std::forward<Actions>(An)), ...);
00953     return target;
00954 }
00955
00956 // generic helpers to remove const qualifier from a function type,
00957 // for instance const member functions
00958 template <typename T>
00959 struct function_remove_const;
00960
00961 template <typename R, typename... Args>
00962 struct function_remove_const<R(Args...)> {
00963     using type = R(Args...);
00964 };
00965
00966 template <typename R, typename... Args>
00967 struct function_remove_const<R(Args...) const> {
00968     using type = R(Args...);
00969 };
00970
00974
00996 template <typename class_t, typename T,
00997     typename action_t = std::function<typename function_remove_const<T>::type>
00998 action_t bind(const std::shared_ptr<class_t>& obj, T class_t::* method) {
00999     return [wp = std::weak_ptr<class_t>(obj), method](auto&&... args) ->
01000         typename action_t::result_type {
01001         // lock() also keeps the object alive for the duration of the call

```

```

01002         const auto obj_ = wp.lock();
01003         if (!obj_) {
01004             // inform the actuator about dead binding
01005             throw invalid_action("bind: invalid object");
01006         }
01007         return ((*obj_).method)(std::forward<decltype(args)>(args)...);
01008     };
01009 }
01010
01031 template <typename class_t, typename T,
01032           typename action_t = std::function<typename function_remove_const<T>::type>
01033 action_t bind(class_t* obj, T class_t::* method) {
01034     return [obj, method](auto&&... args) -> typename action_t::result_type {
01035         if (!obj) {
01036             // inform the actuator about dead binding
01037             throw invalid_action("bind: invalid object");
01038         }
01039         return ((obj)->*method)(std::forward<decltype(args)>(args)...);
01040     };
01041 }
01042
01069 template <typename action_t, typename... Args>
01070 task_t bind_task(action_t action, Args&&... args) {
01071     using result_t = typename action_t::result_type;
01072
01073     static_assert(sizeof...(Args) > 0,
01074                 "bind_task: a task must be given a callback as its last argument");
01075
01076     constexpr std::size_t last = sizeof...(Args) - 1;
01077     using callback_t = std::tuple_element_t<last, std::tuple<std::decay_t<Args>...>>;
01078
01079     static_assert(task_callback_for<callback_t, result_t>,
01080                 "bind_task: the last argument must be a callback taking the task's result and "
01081                 "returning nothing (void()) for a task that returns nothing");
01082
01083     // References into the caller's arguments. What is copied out of it is the task's own, below.
01084     auto pack = std::forward_as_tuple(std::forward<Args>(args)...);
01085
01086     // A task that could not do its job is built empty, and add_task() refuses it on the caller's
01087     // own stack. Only a callable that can answer is asked -- see \ref testable_for_emptiness -- and
01088     // the answer is read contextually, so no explicit conversion is left to truncate.
01089     if constexpr (testable_for_emptiness<callback_t>) {
01090         if (!std::get<last>(pack)) {
01091             return {};
01092         }
01093     }
01094     if constexpr (testable_for_emptiness<action_t>) {
01095         if (!action) {
01096             return {};
01097         }
01098     }
01099
01100     // The pack is indexed rather than unpacked, because everything but its last element is bound and
01101     // a fold cannot say "all but the last". The bound arguments are copied into one tuple rather
01102     // than into a capture pack: an init-capture pack expanded in a dependent context crashes GCC 14
01103     // (an ICE in tsubst_pack_expansion), and a tuple says the same thing in an ordinary expression.
01104     return [&<std::size_t... i>(std::index_sequence<i...>) -> task_t {
01105         return [action = std::move(action), callback = callback_t(std::get<last>(pack)),
01106             bound = std::tuple<std::decay_t<decltype(std::get<i>(pack))>...>(
01107                 std::get<i>(pack)...)]() mutable -> void {
01108             if constexpr (std::is_void_v<result_t>) {
01109                 std::apply(action, bound);
01110                 callback();
01111             } else {
01112                 // One expression, so the result is handed over as an rvalue: a result type that cannot be
01113                 // copied is still a result a task can report.
01114                 callback(std::apply(action, bound));
01115             }
01116         };
01117     }(std::make_index_sequence<last>{}));
01118 }
01119
01120 } // namespace untangle

```

Index

actions_t
 untangle::actuator< action_t >, 32
actuator, 1
 untangle::actuator< action_t >, 33
add
 untangle::actuator< action_t >, 37, 38
add_task
 untangle::actuator< action_t >, 39

bind
 namespace untangle: functions, 18, 19
bind_task
 untangle, 24

call_tasks
 untangle::actuator< action_t >, 37
connect
 namespace untangle: functions, 15, 16, 17, 18
connect_named_one
 untangle, 24
connect_one
 untangle, 23
copy_from
 untangle::actuator< action_t >, 34

errors_t
 untangle::actuator< action_t >, 32

has_action
 untangle::actuator< action_t >, 41
has_tasks
 untangle::actuator< action_t >, 40

invalid_action
 untangle::invalid_action, 42
invoke_action
 untangle::actuator< action_t >, 36
invoke_callback
 untangle::actuator< action_t >, 35
is_connected
 untangle::actuator< action_t >, 40

last_arg
 untangle, 23

namespace untangle: functions, 15
 bind, 18, 19
 connect, 15, 16, 17, 18

operator()
 untangle::actuator< action_t >, 36

operator=
 untangle::actuator< action_t >, 33
owned
 untangle::actuator< action_t >, 41

release_owned
 untangle::actuator< action_t >, 34
remove
 untangle::actuator< action_t >, 39, 40
reset
 untangle::actuator< action_t >, 33
results_t
 untangle::actuator< action_t >, 32

task_t
 untangle, 22
tasks
 untangle::actuator< action_t >, 41
tasks_t
 untangle::actuator< action_t >, 32
type
 untangle::actuator< action_t >, 33

untangle, 21
 bind_task, 24
 connect_named_one, 24
 connect_one, 23
 last_arg, 23
 task_t, 22
untangle::actuator< action_t >, 29
 actions_t, 32
 actuator, 33
 add, 37, 38
 add_task, 39
 call_tasks, 37
 copy_from, 34
 errors_t, 32
 has_action, 41
 has_tasks, 40
 invoke_action, 36
 invoke_callback, 35
 is_connected, 40
 operator(), 36
 operator=, 33
 owned, 41
 release_owned, 34
 remove, 39, 40
 reset, 33
 results_t, 32
 tasks, 41

- tasks_t, [32](#)
- type, [33](#)
- untangle::invalid_action, [42](#)
 - invalid_action, [42](#)
 - what, [43](#)
- untangle::task_callback_for, [27](#)
- untangle::testable_for_emptiness, [28](#)
- what
 - untangle::invalid_action, [43](#)