

Virtual Cloud Generation Firewall

BLUEMAX

NGF 5000



BLUEMAX NGF 5000, a next-generation network security firewall that provides the stable high-performance, high-availability HW architecture and user ID interface control, application control and device control in the Enterprise (Data Center) environment.




Features of BLUEMAX NGF


Legacy and NGFW mode switch without an equipment replacement

Simultaneously providing both Legacy FW mode of excellence basic firewall performance and NGFW mode of precise security set up.

Legacy FW mode (5-tuple)



NGFW mode (8-tuple)



Always-on service with high-availability HW architecture



System SSD

Basic application of the high-performance SSD



Log SSD

Separating the space for storing the system SW and the security log

Key functions of BLUEMAX NGF



Virtual System

Complicated security configuration of On-Premise is effecienated by the Virtual System of the single HW equipment



SaaS App control

Reinforcing the global application control function in order to reinforce the security to deal with the proliferation of cloud-based SaaS applications



Application control

The function to analyze applications and respond provocatively to attacks that are difficult to handle with existing UTM



Device control

Controlling the access to important files and blocks malware by user terminal security set up, mandatory SW installation and security update checkup.



User ID interface control

Applying the same security policy by recognizing user ID no matter when and where the user connects to the network



Open API

Flexibly interfacing with the integrated security management system, vulnerability diagnostics system and security policy analysis system of both local and overseas vendors



Domain object

Periodically Collecting up to 2,048 domain IPs in real time according to the cloud environment (portal and webhard)



SSL Inspection

The function to detect SSL sessions automatically and decrypt SSL packets to apply them to various next-generation network security functions.

Software Specification

Virtual Cloud Gen Function				Client Security	
NGFW	User-based policy control	IPS	Signature exporting & applying fucuntion by auto-learning	SSL VPN Client(PC, Linux, Android, iOS)	
	Application/device-based policy control		PCRE (Regular expression)	Abnormal detection, isolation and deletion	
	AD setup wizard for AD SSO interface		Detection of multi-pattern (parallel detection)	Collection of abnormal traffic, files and URLs	
	QoS for each application and each user ID	Working with vulnerability checking tool, signature optimization	Provision of terminal security status information through compliance inspection		
	Own user authentication (Captive Portal) and SSO	Anti-DDoS	Application layer defense	Collection of terminal security information (update, security settings)	
SaaS application control	Behavior-based web attack defense and DrDoS (N:1)				
Allocation of resources by virtual system	Region-based blocking and blacklist (IPv4/IPv6)				
Virtual System	Intuitive configuration of the virtual network with the topology map	Blocking unknown attacks and GRE attacks		Management Function	
	Independent operating environment by administrator	IPSec VPN	IKE(v1/v2), PKI(X.509)	Firmware Upgrade and Downgrade(Rollback)	
APT (responding to threats)	GRE/IPIP, L2TP, PPTP Tunneling		Policy settings Multi R/W function		
	APT threat analysis function by interfacing with Sandbox equipment and a threat blocking function through Clients		3DES, AES, SEED, ARIA, CAST, Blowfish, etc.	CLI execution and Packet Capture on GUI	
SSL Inspection	Information sharing of detected threats information (attacker/IP and URL of the place of distribution, malicious file hash value etc.)	MD5, SHA-1, SHA-256, SHA-512, HAS160, etc.		Administrator access to LDAP/RADIUS/TACACS+/OTP, etc.	
	HTTPS, SMTPS, POP3S, IMAPS, FTPS	Contents Filtering Function		Administrator privilege profile	
Legacy Firewall	Hardware Acceleration	Anti-Virus & Anti-SPAM	Anti-Virus Engine(File-based or Stream-based)	Open API and other external solution interface	
	Application Control, IPS, DLP, WebFilter, Anti-X, etc.		Realtime Blackhole List(RBL)	SNMP (v1,2,3), Syslog transmission	
SSL VPN	UTM Function	Web Filter	Restriction on the number of recipients and bulk mail transmission	DB-based log management (supporting compression)	
	Active-Active HA with L2/L3/L4		URL Filtering (settings by category)	Warning alarm threshold settings	
Legacy Firewall	Domain poliai (URL object)	DLP(Data Loss Prevention)	URL extension check (URI query inspection)	Report (policy details, report browser)	
	Duplication policy & unued (non-referenced) policy inspection		Global Categorized URL (local/cloud DB)	Monitoring of Application,Traffic/Session by user	
SSL VPN	Policy-based NAT & Interface-based NAT		Blocking the Anonymizer server list	LACP, VLAN, dynamic asset control	
	Setting up the security policy group		Warning page setting and editing	IPv6 transition (settings tunneling, 6to4) & translation (NAT64/NAT46, DNS64)	
SSL VPN	Activation scheculing by securiy policy		HTTP/HTTPS, FTP/FTPS, SMTP/SMTPS, POP3/POP3S, IMAP/IMAPS	DHCP, DHCPv6 and RA server	
	Full Tunnel mode		Control of the information leakage through webmail	DNS, DDNS, Split DNS	
SSL VPN	Supporting Multi-Factor authentication (3rd authentication)		Registration/inspection and blockade of ID and credit card numbers	QoS (by IP, Application and interface)	
			39 or more general-purpose file formats	Routing Protocol (IPv4-OSPF/RIP/BGP, IPv6-OSPFv3/RIPng/BGP4+)	
			Compressed file (ZIP, TAR, GZIP, ALZIP, BZIP, RAR, 7ZIP)	GPRS Tunneling packet inspection support (GTP Inspection)	
			Filter and save (archive)		

Hardware Specification

Model Name		BLUEMAX NGF 5000
CPU		24 Core
Memory		64/128 GB
Storage	System	128/512 GB
	Log	1.92 TB/RAID
Interface	40G Fiber	max 8
	10G Fiber	10(max 26)
	1G Fiber	8(max 40)
	1G Copper	8(max 40)
	Mgmt	2
Throughput		120 Gbps
CC (Concurrent)		30,000,000
Power Supply		Redundant
Dimension (WxDxH)		2U(438x685x88)

SECUI (주)시큐아이

5-7F 48 Sogong-ro, Jung-gu, Seoul
tel 02 3783 6600 fax 02 3783 6499 www.secui.com

a representative telephone **080 331 6600**

Infringement Response Center **02 3783 6500**

Infringement Response Center **02 3783 6500**

Weekday : 8 a.m. ~ 5 p.m. (Excluding Saturdays, days, and holidays)

CERTIFICATIONS



Copyright © SECUI All Rights Reserved. Company name and product name posted in this catalog are our registered trademarks. Specifications and appearance may change without notice for upgrades.