


# Gradient-Based Optimization Wrap Up

## Lecture 21



ME EN 575  
Andrew Ning  
[aning@byu.edu](mailto:aning@byu.edu)

## Outline

---

Multiobjective Optimization

Other Techniques

# Multiobjective Optimization

## Multiobjective Optimization



---


First, ask if it should be multiobjective:

- Is there a higher-level objective that you are actually after?
- Are some of your objectives actually constraints?


Good reasons to pursue multiobjective:


- Explore tradeoffs between potential objectives
- You aren't making the decision and want to present options





Point C is **dominated** by Point A





The dashed line represents the **Pareto front** and points on the front are called **Pareto optimal**.


## Weighted Sum

---

Combine the two objectives as a weighted sum:

$$J(x) = J_1(x) + kJ_2(x)$$

vary  $k$  to define the Pareto front.



Pros: Simple


Cons: Difficult to determine appropriate weightings, nonuniform spacing, yields only the convex portion of the Pareto front.

## Constraint Epsilon

---

Set the other objectives as constraints, but vary their limits:

$$c(x) \leq c_{max}$$




Pros: Simple, constraint limits are more intuitive.

Cons: Nonuniform spacing.

## Normal Boundary Interface or Normal Constraint Method

---




Pros: Uniform spacing

Cons: Can waste time resolving portions of the

# Smart Pareto Method

---



Pros: Uniform spacing, avoids resolving unimportant regions.

Hancock and Mattson, 2014


## Gradient-free Approach

---

Use a multiobjective gradient-free method like an evolutionary algorithm.

Pros: Easy to use Cons: Very slow and inefficient





Nick Antoine, Aircraft Optimization for Minimal Environmental Impact, PhD Dissertation, 2004.

Some line search techniques use a filter method. This is a multiobjective problem with two objectives:

$$J_1(x) = f(x)$$





$$J_2(x) = \|c_{vio}(x)\|_1$$

# Other Techniques

## Scaling

---

Last time we discussed an example where scaling the design variables was important.



Scaling objectives and constraints is also important. Consider an infeasible point where  $\nabla f$  is very large and  $\nabla c$  is very small.

Rule of thumb:

Scale objectives, constraints, and design variables to all be of  $\mathcal{O}(1)$ .

Sometimes, intentionally skewed scaling is desirable.



$$0 \leq \phi \leq 120^\circ$$

$$0 \leq \frac{\phi}{1000} \leq \frac{120^\circ}{1000}$$


# Reformulation

---

- absolute value, max/min
- mathematically equivalent formulations
- example: distance to barrier
- example: delegates per vote


## Local Optima

---



# Gradients

---



## Parallelization

---

What opportunities have you noticed for parallelization?