

Date Submitted: November 12, 2019**Task 01 (ADC Gui):**Youtube Link: <https://youtu.be/0uyVUwZCRqo>**Modified Code:**

```

/* For usleep() */
#include <unistd.h>
#include <stdint.h>
#include <stddef.h>

/* Driver Header files */
#include <ti/drivers/GPIO.h>
#include <ti/drivers/ADC.h>
// #include <ti/drivers/I2C.h>
// #include <ti/drivers/SPI.h>
// #include <ti/drivers/UART.h>
// #include <ti/drivers/Watchdog.h>

/* Driver configuration */
#include "ti_drivers_config.h"

/* global variables FOR GUI COMPOSER */
uint16_t adcValue = 0;
uint16_t threshold = 100;
uint16_t alert = 0;

/*
 * ===== mainThread =====
 */

void *mainThread(void *arg0)
{
    /* ~10 loops/second */
    uint32_t time = 100000; // update ~10/second

    /* Call driver init functions */
    GPIO_init();
    ADC_init();
    // I2C_init();
    // SPI_init();
    // UART_init();
    // Watchdog_init();

    /* Open ADC Driver */
    ADC_Handle adc;
    ADC_Params params;
    ADC_Params_init(&params);
    adc = ADC_open(CONFIG_ADC_0, &params);
    if (adc == NULL) {

```

```

// Error initializing ADC channel 0
while (1);
}


while (1) {
    int_fast16_t res;


    res = ADC_convert(adc, &adcValue);
    if (res == ADC_STATUS_SUCCESS) {
        if(adcValue >= threshold) {
            GPIO_write(CONFIG_GPIO_LED_0, CONFIG_GPIO_LED_ON);
            alert = 1;
        } else{
            GPIO_write(CONFIG_GPIO_LED_0, CONFIG_GPIO_LED_OFF);
            alert = 0;
        }
    }

    usleep(time);
}
}

```

Screenshots of ROV view and SysCfg Modifications





Task 02 (RTOS Example):

Youtube Link: <https://youtu.be/dQ99x-8o9Iw>

Modified Code:

```
/*
 * ===== empty.c =====
 */

/* For usleep() */
#include <unistd.h>
#include <stdint.h>
#include <stddef.h>

/* Driver Header files */
#include <ti/drivers/GPIO.h>
#include <ti/drivers/ADC.h>
#include <ti/display/Display.h>
// #include <ti/drivers/I2C.h>
// #include <ti/drivers/SPI.h>
// #include <ti/drivers/UART.h>
// #include <ti/drivers/Watchdog.h>

/* Driver configuration */
#include "ti_drivers_config.h"

/* global variableS FOR GUI COMPOSER */
uint16_t adcValue = 0;
uint16_t threshold = 100;
uint16_t trigger = 0;

/*
 * ===== gpioButtonFxn0 =====
 */
```

```

* Callback function for the GPIO interrupt on Board_GPIO_BUTTON0.
*/
void gpioButtonFxn0(uint_least8_t index)
{
    /* Clear the GPIO interrupt and decrement threshold */
    if(threshold < 250){ // Ensure threshold doesn't go below zero
        threshold = 0;
    }
    else {
        threshold -= 250; // decrement by 250
    }
}

void gpioButtonFxn1(uint_least8_t index)
{
    /* Clear the GPIO interrupt and increment threshold */
    if(threshold > 4095){ // Ensure threshold doesn't go above max ADC range
        threshold = 4095;
    }
    else {
        threshold += 250; // increment by 250
    }
}

/*
* ===== gpioButtonFxn1 =====
* Callback function for the GPIO interrupt on Board_GPIO_BUTTON1.
* This may not be used for all boards.
*/

/*
* ===== mainThread =====
*/

void *mainThread(void *arg0)
{
    /* ~10 loops/second */
    uint32_t time = 100000; // update ~10/second

    /* Call driver init functions */
    GPIO_init();
    ADC_init();
    // I2C_init();
    // SDSPI_init();
    // SPI_init();
    // UART_init();
    // Watchdog_init();

    /* Open Display Driver */
    Display_Handle    displayHandle;
    Display_Params    displayParams;
    Display_Params_init(&displayParams);
    displayHandle = Display_open(Display_Type_UART, NULL);

```

```

/* Open ADC Driver */
ADC_Handle adc;
ADC_Params params;
ADC_Params_init(&params);
adc = ADC_open(CONFIG_ADC_0, &params);
if (adc == NULL) {
    // Error initializing ADC channel 0
    while (1);
}

/* install Button callback */


GPIO_setCallback(CONFIG_GPIO_BTN1, gpioButtonFxn0);
GPIO_setCallback(CONFIG_GPIO_BTN2, gpioButtonFxn1);


/* Enable interrupts */
GPIO_enableInt(CONFIG_GPIO_BTN1);
GPIO_enableInt(CONFIG_GPIO_BTN2);

while (1) {
    int_fast16_t res;
    res = ADC_convert(adc, &adcValue);
    if (res == ADC_STATUS_SUCCESS) {
        Display_printf(displayHandle, 1, 0, "ADC Reading %d", adcValue);
        if(adcValue >= threshold){
            GPIO_write(CONFIG_GPIO_LED_0, CONFIG_GPIO_LED_ON);
            trigger = 1;
        } else{
            GPIO_write(CONFIG_GPIO_LED_0, CONFIG_GPIO_LED_OFF);
            trigger = 0;
        }
    }
    usleep(time);
}
}

```

Screenshots of ROV view and SysCfg Modifications



COM6 - PuTTY

```
ADC Reading 1628
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1628
ADC Reading 1629
ADC Reading 1628
ADC Reading 1628
ADC Reading 1628
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1629
ADC Reading 1628
ADC Reading 1629
ADC Reading 1628
ADC Reading 1628
ADC Reading 1629
```
