The Minimal Retroreflective Microfacet Model

| Matthias Raab	Laurent Belcour	Frankie Liu	Jamie Portsmouth
NVIDIA	Intel	NVIDIA	Autodesk

Figure 1. Comparison of our retroreflector model (top) obtained by an almost trivial modification of the equivalent roughness GGX microfacet model (bottom). The lighting varies (left to right) from side-on, quarter-on, and straight-on, exhibiting the strong retro-reflective peak.

Abstract

We introduce the "Minimal Retroreflective Microfacet" (MRM) model, which provides a simple scheme for modifying a pre-existing microfacet BRDF implementation to produce a visually plausible, energy-conserving retroreflective result.

1. Introduction

Rendering of retro-reflective materials is useful in a variety of contexts. A number of CG models have been proposed. For practical purposes in visual effects, we are interested in a model which is a) visually plausible at least, b) provably energy-conserving, c) efficient and easy to implement, ideally a small modification to well-understood microfacet models. We present here a model based on a the previously published back-vector formulation [Belcour et al. 2014] which meets are these requirements. It is so simple a modification to a regular microfacet model, that we 'Minimal Retroreflective Microfacet" (MRM) model which achieves a plausible retro-reflective result.

In this document, we detail the correct usage and derivation of this retro-reflective BRDF model within the microfacet framework [Walter et al. 2007; Heitz 2014]. We first recall some basic principles from microfacets theory (Section 2) and show how to change it to account for retro-reflective microfacets (Section 3). We then detail how to implement this in practice (Section 5). Finally, we discuss how retro-reflection can

$\mathbf{v}$	normalized vector to viewer
$\mathbf{l}$	normalized vector to light
$\mathbf{n}$	surface normal
$\mathbf{t_1}, \mathbf{t_2}$	tangent and bitangent (forming an orthonormal coordinate frame with the normal)
$\mathbf{h}$	half vector, $\mathbf{h} = \mathbf{h}(\mathbf{v}, \mathbf{l}) = \frac{\mathbf{v}+\mathbf{l}}{\|\mathbf{v}+\mathbf{l}\|}$
$\langle \mathbf{x}, \mathbf{y} \rangle$	dot product of $\mathbf{x}$ and $\mathbf{y}$
$\text{reflect}(\mathbf{x}, \mathbf{m})$	reflection of vector $\mathbf{x}$ on surface with normal $\mathbf{m}$, i.e. $\text{reflect}(\mathbf{x}, \mathbf{m}) = -\mathbf{x} + 2\langle \mathbf{x}, \mathbf{m} \rangle \mathbf{m}$
Ω	hemisphere of directions around the normal

Figure 2. Notations used.

occur at the microfacet level (Section 4).

2. Microfacet BRDF Models

Using the notations from figure 2, a microfacet BRDF [Walter et al. 2007; Heitz 2014] takes the form (Walter et al. [2007] Equation (20))

$$f(\mathbf{v}, \mathbf{l}) = \frac{D(\mathbf{h})\,G_2(\mathbf{v}, \mathbf{l})\,F(\mathbf{h}, \mathbf{v})}{4\,\langle \mathbf{v}, \mathbf{n} \rangle\,\langle \mathbf{l}, \mathbf{n} \rangle} \tag{1}$$

where D is the distribution of microfacets, normalized to fulfill $\int_\Omega D(\mathbf{h})\,\langle \mathbf{n}, \mathbf{h} \rangle\,d\mathbf{h} = 1$, G_2 is the shadowing-masking function, and F is the Fresnel term. The half-vector $\mathbf{h}$ is used as the *selector* for microfacets reflecting light from incident direction $\mathbf{l}$ to outgoing direction $\mathbf{v}$ (*i.e.* only microfacet with normals aligned with the half-vector will reflect light). In Section 4.1 of their work, Walter et al. [Walter et al. 2007] detail the effect of using the half vector as the microfacet selector and obtain Equation 1.

In this work, we show that we can use the back vector [Belcour et al. 2014] used to model retro-reflection as a microfacet selector. Before detailing the impact of such a change, we review some properties of microfacet models.

Shadowing-Masking. The shadowing-masking function combines the visibility masking function $G_1(\mathbf{v}, \mathbf{l})$ for view direction and $G_1(\mathbf{l}, \mathbf{v})$ for light direction:

$$G_2(\mathbf{v}, \mathbf{l}) = G_2\left(G_1(\mathbf{v}, \mathbf{l}), G_1(\mathbf{l}, \mathbf{v})\right) \tag{2}$$

Mathematically, the BRDF is plausible if G_2 is symmetric w.r.t. to exchanging $\mathbf{v}$ and $\mathbf{l}$, fulfills $G_2(\mathbf{v}, \mathbf{l}) \leq G_1(\mathbf{v}, \mathbf{l})$, and if G_1 further establishes the correct projected area of visible micro-surfaces [Heitz 2014]

$$\langle \mathbf{v}, \mathbf{n} \rangle = \int_{\{\mathbf{h} \in \Omega:\langle \mathbf{v}, \mathbf{h} \rangle \geq 0\}} D(\mathbf{h})G_1(\mathbf{v}, \text{reflect}(\mathbf{v}, \mathbf{h}))\,\langle \mathbf{v}, \mathbf{h} \rangle\,d\mathbf{h}. \tag{3}$$

Choices for G_1 with this property are the Smith masking function

$$G_1(\mathbf{v}, \mathbf{l}) = G_{1,\text{Smith}}(\mathbf{v}) = \frac{\langle \mathbf{v}, \mathbf{n} \rangle}{\int_{\{\mathbf{h} \in \Omega : \langle \mathbf{v}, \mathbf{h} \rangle \geq 0\}} D(\mathbf{h}) \langle \mathbf{v}, \mathbf{h} \rangle \, d\mathbf{h}}, \tag{4}$$

where analytic expressions are available for Beckmann and GGX distributions, and the v-cavity masking function

$$G_1(\mathbf{v}, \mathbf{l}) = G_{1,\text{vc}}(\langle \mathbf{v}, \mathbf{n} \rangle, \langle \mathbf{n}, \mathbf{h} \rangle, \langle \mathbf{v}, \mathbf{h} \rangle) = \min \left\{ \frac{2 \langle \mathbf{v}, \mathbf{n} \rangle \langle \mathbf{n}, \mathbf{h} \rangle}{\langle \mathbf{v}, \mathbf{h} \rangle}, 1 \right\}, \tag{5}$$

which is generally applicable for distributions with symmetry around the normal.

3. Back-vector Modification

If instead of half-vector $\mathbf{h}$, we use the back-vector $\mathbf{b}$ [Belcour et al. 2014] defined as

$$\mathbf{b}(\mathbf{v}, \mathbf{l}) = \mathbf{h}(\mathbf{v}', \mathbf{l}) = \frac{\mathbf{v}' + \mathbf{l}}{\|\mathbf{v}' + \mathbf{l}\|}, \text{ with } \mathbf{v}' = \text{reflect}(\mathbf{v}, \mathbf{n}), \tag{6}$$

to select the reflecting microfacet, we are to re-derive the microfacet model.

Jacobian of Back-Vector. The first step is to write the Jacobian of the change of variable from the back-vector to the light vector $\mathbf{l}$ (Equation (11) and (14) of Walter et al. [2007]). Fortunately, this jacobian has the same form as the half-vector one:

$$\left\| \frac{\partial \omega_{\mathbf{b}}}{\partial \omega_{\mathbf{l}}} \right\| = \left\| \frac{\partial \omega_{\mathbf{h}(\mathbf{v}', \mathbf{l})}}{\partial \omega_{\mathbf{l}}} \right\| = \frac{1}{4 \left| \mathbf{l} \cdot \mathbf{h}(\mathbf{v}', \mathbf{l}) \right|} = \frac{1}{4 \left| \mathbf{l} \cdot \mathbf{b} \right|} \tag{7}$$

Microfacet reflection term. We do not know for sure how the retro-reflective microfacet interacts with incident light. However, we have experimental evidence [Belcour et al. 2014] that it behaves similarly to a Fresnel term. We opted to reuse the Fresnel as well in the $(\mathbf{v}', \mathbf{l})$ configuration. As such, we update the formulation of $\rho(\mathbf{v}, \mathbf{m})$ (Equation (11) of Walter et al. [2007]) to use the reflected view vector instead. It follows that the reflection microsurface BRDF (Equation (15) of Walter et al. [2007]) becomes

$$f_r^m(\mathbf{v}, \mathbf{l}, \mathbf{m}) = F(\mathbf{v}', \mathbf{m}) \frac{\delta(\mathbf{b}, \mathbf{m})}{4 \left| \mathbf{v}' \cdot \mathbf{b} \right|^2}. \tag{8}$$

We used the fact that $\left| \mathbf{l} \cdot \mathbf{b} \right| = \left| \mathbf{v}' \cdot \mathbf{b} \right|$.

Shadowing & Masking. **[TODO:** Laurent: I think we could extract the shadowing from Matthias derivation here. The other way to justify the derivation of the full model is to highlight that Smith's shadowing/masking does not depend on the microfacet (appart from the sideness). Hence, whatever the microfacet selector (as long as the sideness matches), the shadowing/masking is the same. Since $\mathbf{v}$ and $\mathbf{v}'$ share the same slope, we can exchange them in the equation.**]**

Final form.

$$f_R(\mathbf{v}, \mathbf{l}) = \frac{D(\mathbf{b})\, G_2(\mathbf{v}', \mathbf{l})\, F(\mathbf{b}, \mathbf{v}')}{4\, \langle \mathbf{v}', \mathbf{n} \rangle\, \langle \mathbf{l}, \mathbf{n} \rangle} \tag{9}$$

4. Plausibility of the Back-vector Modification

In analogy to $\mathbf{v}'$ we let $\mathbf{l}' := \text{reflect}(\mathbf{l}, \mathbf{n})$. First we observe

$$\langle \mathbf{v}', \mathbf{n} \rangle = \langle \mathbf{v}, \mathbf{n} \rangle \text{ and}$$
$$\langle \mathbf{l}, \mathbf{n} \rangle = \langle \mathbf{l}', \mathbf{n} \rangle. \tag{10}$$

For the back-vector we show $\mathbf{h}(\mathbf{v}', \mathbf{l}) = \text{reflect}\left(\mathbf{h}(\mathbf{l}', \mathbf{v}), \mathbf{n}\right)$, as

$$\begin{aligned}
\mathbf{v}' + \mathbf{l} &= (-\mathbf{v} + 2\,\langle \mathbf{v}, \mathbf{n} \rangle\,\mathbf{n}) + \mathbf{l} \\
&= (-\mathbf{v} + 2\,\langle \mathbf{v}, \mathbf{n} \rangle\,\mathbf{n}) + \left(-\mathbf{l}' + 2\,\langle \mathbf{l}', \mathbf{n} \rangle\,\mathbf{n}\right) \\
&= -(\mathbf{l}' + \mathbf{v}) + 2\,\langle (\mathbf{l}' + \mathbf{v}), \mathbf{n} \rangle\,\mathbf{n} = \text{reflect}(\mathbf{l}' + \mathbf{v}, \mathbf{n})
\end{aligned} \tag{11}$$

and therefore $\|\mathbf{v}' + \mathbf{l}\| = \|\mathbf{l}' + \mathbf{v}\|$ as well. From that we can conclude

$$\begin{aligned}
\langle \mathbf{n}, \mathbf{h}(\mathbf{v}', \mathbf{l}) \rangle &= \langle \mathbf{n}, \mathbf{h}(\mathbf{l}', \mathbf{v}) \rangle \\
\langle \mathbf{t_1}, \mathbf{h}(\mathbf{v}', \mathbf{l}) \rangle &= -\langle \mathbf{t_1}, \mathbf{h}(\mathbf{l}', \mathbf{v}) \rangle \\
\langle \mathbf{t_2}, \mathbf{h}(\mathbf{v}', \mathbf{l}) \rangle &= -\langle \mathbf{t_2}, \mathbf{h}(\mathbf{l}', \mathbf{v}) \rangle.
\end{aligned} \tag{12}$$

As anisotropic Phong, Beckmann, and GGX distributions are reflection-symmetric around the normal, i.e. they take the form $D(\mathbf{h}) = D\left(\langle \mathbf{n}, \mathbf{h} \rangle, |\langle \mathbf{t_1}, \mathbf{h} \rangle|, |\langle \mathbf{t_2}, \mathbf{h} \rangle|\right)$, we can thus infer that using them with the back-vector obeys symmetry. Further, the reflection symmetry of D along with equation (10) gives

$$\begin{aligned}
G_{1,\text{Smith}}(\mathbf{v}) &= \frac{\langle \mathbf{v}, \mathbf{n} \rangle}{\int_{\{\mathbf{h} \in \Omega : \langle \mathbf{v}, \mathbf{h} \rangle \geq 0\}} D(\mathbf{h})\,\langle \mathbf{v}, \mathbf{h} \rangle\,d\mathbf{h}} \\
&= \frac{\langle \mathbf{v}', \mathbf{n} \rangle}{\int_{\{\mathbf{h} \in \Omega : \langle \mathbf{v}', \mathbf{h} \rangle \geq 0\}} D(\mathbf{h})\,\langle \mathbf{v}', \mathbf{h} \rangle\,d\mathbf{h}} = G_{1,\text{Smith}}(\mathbf{v}')
\end{aligned} \tag{13}$$

for Smith-masking. Next we show

$$\langle \mathbf{v}', \mathbf{l} \rangle = -\langle \mathbf{v}, \mathbf{l} \rangle + 2\,\langle \mathbf{v}, \mathbf{n} \rangle\,\langle \mathbf{l}, \mathbf{n} \rangle = \langle \mathbf{v}, -\mathbf{l} + 2\,\langle \mathbf{l}, \mathbf{n} \rangle\,\mathbf{n} \rangle = \langle \mathbf{v}, \mathbf{l}' \rangle \tag{14}$$

and therefore

$$\langle \mathbf{v}', \mathbf{h}(\mathbf{v}', \mathbf{l}) \rangle = \frac{1 + \langle \mathbf{l}, \mathbf{v}' \rangle}{\|\mathbf{v}' + \mathbf{l}\|} = \frac{1 + \langle \mathbf{l}', \mathbf{v} \rangle}{\|\mathbf{l}' + \mathbf{v}\|} = \langle \mathbf{l}', \mathbf{h}(\mathbf{l}', \mathbf{v}) \rangle. \tag{15}$$

Using this along with equations (12) and (10) we get

$$\begin{aligned}
G_1(\mathbf{v}', \mathbf{l}) &= G_{1,\text{vc}}\left(\langle \mathbf{v}', \mathbf{n} \rangle, \langle \mathbf{n}, \mathbf{h}(\mathbf{v}', \mathbf{l}) \rangle, \langle \mathbf{v}', \mathbf{h}(\mathbf{v}', \mathbf{l}) \rangle\right) \\
&= G_{1,\text{vc}}\left(\langle \mathbf{v}, \mathbf{n} \rangle, \langle \mathbf{n}, \mathbf{h}(\mathbf{l}', \mathbf{v}) \rangle, \langle \mathbf{l}', \mathbf{h}(\mathbf{l}', \mathbf{v}) \rangle\right) \\
&= G_{1,\text{vc}}\left(\langle \mathbf{v}, \mathbf{n} \rangle, \langle \mathbf{n}, \mathbf{h}(\mathbf{v}, \mathbf{l}') \rangle, \langle \mathbf{l}', \mathbf{h}(\mathbf{v}, \mathbf{l}') \rangle\right) \\
&= G_1(\mathbf{v}, \mathbf{l}')
\end{aligned} \tag{16}$$

4

and similarly $G_1(\mathbf{l}, \mathbf{v}') = G_1(\mathbf{l}', \mathbf{v})$ for the v-cavity masking function. In summary, we can conclude the symmetry of the BRDF

$$
\begin{aligned}
f_{\text{retro}}(\mathbf{v}, \mathbf{l}) = f(\mathbf{v}', \mathbf{l}) &= \frac{D(\mathbf{h}(\mathbf{v}', \mathbf{l}))G_2(G_1(\mathbf{v}', \mathbf{l}), G_1(\mathbf{l}, \mathbf{v}'))}{4\langle \mathbf{v}', \mathbf{n}\rangle \langle \mathbf{l}, \mathbf{n}\rangle} \\
&= \frac{D(\mathbf{h}(\mathbf{l}', \mathbf{v}))G_2(G_1(\mathbf{v}, \mathbf{l}'), G_1(\mathbf{l}', \mathbf{v}))}{4\langle \mathbf{v}, \mathbf{n}\rangle \langle \mathbf{l}', \mathbf{n}\rangle} = f(\mathbf{l}', \mathbf{v}) = f_{\text{retro}}(\mathbf{l}, \mathbf{v}).
\end{aligned}
\tag{17}
$$

For the albedo we simply have

$$
\rho_{\text{retro}}(\mathbf{v}) = \int_\Omega f_{\text{retro}}(\mathbf{v}, \mathbf{l}) \langle \mathbf{l}, \mathbf{n}\rangle \, d\mathbf{l} = \int_\Omega f(\mathbf{v}', \mathbf{l}) \langle \mathbf{l}, \mathbf{n}\rangle \, d\mathbf{l} = \rho(\mathbf{v}')
\tag{18}
$$

i.e. we get the albedo of the regular microfacet BRDF for the reflected direction. Which, using equation (3) and $\frac{d\mathbf{h}(\mathbf{v}', \mathbf{l})}{d\mathbf{l}} = \frac{1}{4\langle \mathbf{l}, \mathbf{h}(\mathbf{v}', \mathbf{l})\rangle} = \frac{1}{4\langle \mathbf{v}', \mathbf{h}(\mathbf{v}', \mathbf{l})\rangle}$ [Walter et al. 2007], can be shown to fulfill energy conservation

$$
\begin{aligned}
\rho(\mathbf{v}') &= \int_\Omega \frac{D(\mathbf{h}(\mathbf{v}', \mathbf{l}))G_2(\mathbf{v}', \mathbf{l})}{4\langle \mathbf{v}', \mathbf{n}\rangle \langle \mathbf{l}, \mathbf{n}\rangle} \langle \mathbf{l}, \mathbf{n}\rangle \, d\mathbf{l} \\
&\leq \int_{\{\mathbf{h}\in\Omega:\langle \mathbf{v}', \mathbf{h}\rangle \geq 0\}} \frac{D(\mathbf{h})G_1(\mathbf{v}', \text{reflect}(\mathbf{v}', \mathbf{h}))}{\langle \mathbf{v}', \mathbf{n}\rangle} \langle \mathbf{v}', \mathbf{h}\rangle \, d\mathbf{h} = 1.
\end{aligned}
\tag{19}
$$

5. Implementation Notes

Given an implementation of a regular microfacet BRDF, extending it to retro-reflection is straightforward:

- Evaluation merely needs to replace $\mathbf{v}$ with $\mathbf{v}'$ upfront.

- Similarly, importance sampling of $\mathbf{l}$ given $\mathbf{v}$ can be realized by replacing $\mathbf{v}$ with $\mathbf{v}'$ upfront and then importance sampling the regular microfacet BRDF. This may include low variance sampling using the domain of visible microfacets [Heitz and d'Eon 2014].

- As the albedos of standard BRDF and retro-reflective BRDF are essentially identical, compensating for energy loss in the sense of [Kelemen and Szirmay-Kalos 2001] can be realized using the same data tables.

- Pseudo-code is provided in Listing 1.

```glsl
vec3 retroGGX(vec3 L, vec3 V, vec3 N, vec3 X, vec3 Y)
{
    vec3 Vp = -reflect(V,N); // jp - is this wrong? Why the minus sign
    float NdotL = dot(N, L);
    float NdotV = dot(N, Vp);
    if (NdotL < 0 || NdotV < 0) return vec3(0);

    vec3 B = normalize(L+Vp);
    float NdotH = dot(N, B);
    vec3 wB = vec3(dot(B,X),  dot(B,Y),  dot(B,N));
    vec3 wL = vec3(dot(L,X),  dot(L,Y),  dot(L,N));
    vec3 wV = vec3(dot(Vp,X), dot(Vp,Y), dot(Vp,N));

    float D = D_GGX(wB, ax, ay);
    float G = G2_GGX(wV, wL, ax, ay);

    float c = dot(L, B);
    float F = schlick(f0, c); // I don't think we need to give the form of
    the Fresnel

    float val = Ks * D * G * F / (4 * NdotL * NdotV);
    return vec3(val);
}
```

Listing 1. Pseudo code to implement the retro-reflective microfacet model.

6. Implementation Notes

Given an implementation of a regular microfacet BRDF, extending it to retro-reflection is straightforward:

- Evaluation merely needs to replace $\mathbf{v}$ with $\mathbf{v}'$ upfront.

- Similarly, importance sampling of $\mathbf{l}$ given $\mathbf{v}$ can be realized by replacing $\mathbf{v}$ with $\mathbf{v}'$ upfront and then importance sampling the regular microfacet BRDF. This may include low variance sampling using the domain of visible microfacets [Heitz and d'Eon 2014].

- As the albedos of standard BRDF and retro-reflective BRDF are essentially identical, compensating for energy loss in the sense of [Kelemen and Szirmay-Kalos 2001] can be realized using the same data tables.

References

BELCOUR, L., PACANOWSKI, R., DELAHAIE, M., LAVILLE-GEAY, A., AND EU-PHERTE, L. BRDF Measurements and Analysis of Retroreflective Materials. *Journal of the Optical Society of America*, 31(12):2561–2572, December 2014. URL: https://inria.hal.science/hal-01083366. 1, 2, 3

HEITZ, E. Understanding the masking-shadowing function in microfacet-based brdfs. *Journal of Computer Graphics Techniques (JCGT)*, 3(2):48–107, June 2014. ISSN 2331-7418. URL: http://jcgt.org/published/0003/02/03/. 1, 2

HEITZ, E. AND D'EON, E. Importance Sampling Microfacet-Based BSDFs using the Distribution of Visible Normals. *Computer Graphics Forum*, 33(4):103–112, July 2014. URL: https://inria.hal.science/hal-00996995. 5, 6

KELEMEN, C. AND SZIRMAY-KALOS, L. A Microfacet Based Coupled Specular-Matte BRDF Model with Importance Sampling. In *Eurographics 2001 - Short Presentations*. Eurographics Association, 2001. URL: https://doi.org//10.2312/egs.20011003. 5, 6

WALTER, B., MARSCHNER, S. R., LI, H., AND TORRANCE, K. E. Microfacet Models for Refraction through Rough Surfaces. In *Rendering Techniques*. The Eurographics Association, 2007. ISBN 978-3-905673-52-4. URL: https://doi.org//10.2312/EGWR/EGSR07/195-206. 1, 2, 3, 5

Author Contact Information

Matthias Raab	Laurent Belcour
matthias.raab@gmail.com	laurent.belcour@gmail.com
Frankie Liu	Jamie Portsmouth
frankie.liu@gmail.com	jamports@mac.com