

Contents

1	Guide for trident v1.4.1.0 to v1.5.0.1	1
1.1	Installation	1
1.2	The trident CLI	1
1.2.1	General notes	3
1.3	Package creation and manipulation commands	4
1.3.1	Init command	4
1.3.2	Fetch command	6
1.3.3	Forge command	7
1.3.4	Genoconvert command	14
1.3.5	Jannocoalesce command	16
1.3.6	Rectify command	17
1.4	Inspection commands	18
1.4.1	List command	18
1.4.2	Summarise command	20
1.4.3	Survey command	20
1.4.4	Validate command	21

1 Guide for trident v1.4.1.0 to v1.5.0.1

1.1 Installation

See the Poseidon website (<https://www.poseidon-adna.org/#/trident>) or the GitHub repository (<https://github.com/poseidon-framework/poseidon-hs>) for up-to-date installation instructions.

1.2 The trident CLI

Trident is a command line software tool structured in multiple subcommands. If you installed it properly you can call it on the command line by typing **trident**. This will show an overview of the general options and all subcommands, which are explained in detail below.

```
Usage: trident [--version] [--logMode MODE | --debug] [--errLength INT]
      [--inPlinkPopName MODE] (COMMAND | COMMAND)
```

trident is a management and analysis tool for Poseidon packages. Report issues here: <https://github.com/poseidon-framework/poseidon-hs/issues>

Available options:

<code>-h, --help</code>	Show this help text
<code>--version</code>	Show version number
<code>--logMode MODE</code>	How information should be reported: NoLog, SimpleLog, DefaultLog, ServerLog or VerboseLog. (default: DefaultLog)
<code>--debug</code>	Short for --logMode VerboseLog.
<code>--errLength INT</code>	After how many characters should a potential error message be truncated. "Inf" for no truncation.

```

--inPlinkPopName MODE      (default: CharCount 1500)
                           Where to read the population/group name from the FAM
                           file in Plink-format. Three options are possible:
                           asFamily (default) | asPhenotype | asBoth.

```

Package creation and manipulation commands:

```

init                       Create a new Poseidon package from genotype data
fetch                     Download data from a remote Poseidon repository
forge                     Select packages, groups or individuals and create a
                           new Poseidon package from them
genoconvert               Convert the genotype data in a Poseidon package to a
                           different file format
jannocoalesce             Coalesce information from one or multiple janno files
                           to another one
rectify                   Adjust POSEIDON.yml files automatically to package
                           changes

```

Inspection commands:

```

list                      List packages, groups or individuals from local or
                           remote Poseidon repositories
summarise                 Get an overview over the content of one or multiple
                           Poseidon packages
survey                   Survey the degree of context information completeness
                           for Poseidon packages
validate                  Check Poseidon packages or package components for
                           structural correctness

```

26 **trident** allows to work directly with genotype data (see **-p** below), but it is optimized for the interaction
 27 with Poseidon packages, which wrap and contextualize the data. Most **trident** subcommands therefore have a
 28 central parameter, called **--baseDir** or simply **-d** to specify one or more base directories to look for packages.
 29 For example, if all Poseidon packages live inside a repository at **/path/to/poseidon/packages** you would
 30 simply say **trident <subcommand> -d /path/to/poseidon/dirs/** and **trident** would automatically search
 31 all subdirectories inside of the repository for valid Poseidon packages (as identified by valid POSEIDON.yml
 32 files).

33 You can arrange a Poseidon repository in a hierarchical way. For example:

```

/path/to/poseidon/packages
  /modern
    /2019_poseidon_package1
    /2019_poseidon_package2
  /ancient
    /...
    /...
  /Reference_Genomes
    /...
    /...

```

34 This structure then allows to select only the level of packages you are interested in, even individual ones. `-d`
35 can be given multiple times, which is particularly useful as you may have your own data to co-analyse with
36 external reference data. In this case you simply need to provide your own genotype data as yet another Poseidon
37 package to be added to your `trident` command. For example, you may have genotype data in EIGENSTRAT
38 format (`trident` supports EIGENSTRAT and PLINK as formats.):

```
~/my_project/my_project.geno  
~/my_project/my_project.snp  
~/my_project/my_project.ind
```

39 Then you can transform that into a skeleton Poseidon package with the `init` command. You can also do it
40 manually by simply adding a POSEIDON.yml file, with, for example, the following content:

```
poseidonVersion: 2.7.1  
title: My_awesome_project  
description: Unpublished genetic data from my awesome project  
contributor:  
  - name: Stephan Schiffels  
    email: schiffels@institute.org  
packageVersion: 0.1.0  
lastModified: 2020-10-07  
genotypeData:  
  format: EIGENSTRAT  
  genoFile: my_project.geno  
  snpFile: my_project.snp  
  indFile: my_project.ind  
jannoFile: my_project.janno  
bibFile: sources.bib
```

41 Two remarks: 1) All file paths in this POSEIDON.yml file are considered *relative* to the directory in which
42 POSEIDON.yml resides. For this example we assume that this file is added into the same directory as the three
43 genotype files. 2) Besides the genotype data files there are two (technically optional) files referenced in this
44 example: `sources.bib` and `my_project.janno`. Of course you can add them manually - `init` automatically
45 creates empty dummy versions.

46 Once you have set up your own Poseidon package (which is really only a skeleton so far), you can add it to your
47 `trident` analysis, by simply adding your project directory to the command using `-d`, for example:

```
trident list -d /path/to/poseidon/packages/modern \  
  -d /path/to/poseidon/packages/ReferenceGenomes \  
  -d ~/my_project \  
  --packages
```

48 1.2.1 General notes

49 **1.2.1.1 Logging and command line output** For all subcommands the general argument `--logMode`
50 defines how `trident` reports messages (to `stderr`) on the command line:

- 51 • *NoLog*: Hides all messages.
- 52 • *SimpleLog*: Plain and simple output.

- *DefaultLog*: Adds the severity indicators (log levels) **Info**, **Warning** and **Error** before each message. This is the default setting.
- *ServerLog*: Additionally adds timestamps before each message.
- *VerboseLog*: Shows not just messages on the log levels **Info**, **Warning** and **Error** like the other modes, but also on the more verbose level **Debug**. Use this mostly relevant for debugging.

`--debug` is short for `--logMode VerboseLog` to activate this important log level more easily.

1.2.1.2 Package duplicates and versions

- For **trident** multiple packages in a set of base directories can share the same **title**, if they have different **packageVersion** numbers. If the version numbers are also identical or missing, then **trident** stops with an exception.
- The **trident** subcommands **genoconvert**, **list**, **rectify**, **survey** and **validate** by default consider all versions of each Poseidon package in the given base directories. The `--onlyLatest` flag causes them to instead only consider the latest versions.
- **fetch** and **forge** generally consider all package versions. Their selection language (see below) allows for detailed version handling.
- **summarize** and **jannocoalesce** consider always only the latest package versions.

1.2.1.3 Individual/Sample duplicates

- Poseidon_IDs (so individual/sample names) within one package have to be unique, or **trident** will stop.
- We also discourage sample duplicates across packages in package repositories, but **trident** will generally continue with them. **validate** will fail though, if the `--ignoreDuplicates` flag is not set.
- **forge** offers a special mechanism to resolve sample duplicates within its selection language.

1.2.1.4 Group names in .fam files The **.fam** file of PLINK-formatted genotype data is used inconsistently across different popular aDNA software tools to store group/population name information. The (global) **trident** option `--inPlinkPopName` with the arguments **asFamily** (default), **asPhenotype** and **asBoth** allows to control the reading of the population name from PLINK **.fam** files. The subcommands that write genotype data (**forge**, **genoconvert**) have a corresponding option `--outPlinkPopName` to specify this for the output.

1.2.1.5 Whitespaces in the .janno file While reading the **.janno** file **trident** trims all leading and trailing whitespaces around individual cells. Also all instances of the **No-Break Space** unicode character will be removed. This means these whitespaces will not be preserved when a package is **forged**.

1.3 Package creation and manipulation commands

1.3.1 Init command

init creates a new Poseidon package from genotype data files. It adds a **POSEIDON.yml** file, a dummy **.janno** file for context information and an empty **.bib** file for literature references.

Command line details

```
Usage: trident init ((-p|--genoOne FILE) | --inFormat FORMAT --genoFile FILE
                  --snpFile FILE --indFile FILE) [--snpSet SET]
                  (-o|--outPackagePath DIR) [-n|--outPackageName STRING]
                  [--minimal]
```

Create a new Poseidon package from genotype data

Available options:

<code>-h,--help</code>	Show this help text
<code>-p,--genoOne FILE</code>	One of the input genotype data files. Expects .bed, .bim or .fam for PLINK and .geno, .snp or .ind for EIGENSTRAT. The other files must be in the same directory and must have the same base name.
<code>--inFormat FORMAT</code>	The format of the input genotype data: EIGENSTRAT or PLINK. Only necessary for data input with <code>--genoFile</code> + <code>--snpFile</code> + <code>--indFile</code> .
<code>--genoFile FILE</code>	Path to the input geno file.
<code>--snpFile FILE</code>	Path to the input snp file.
<code>--indFile FILE</code>	Path to the input ind file.
<code>--snpSet SET</code>	The snpSet of the package: 1240K, HumanOrigins or Other. Only relevant for data input with <code>-p --genoOne</code> or <code>--genoFile</code> + <code>--snpFile</code> + <code>--indFile</code> , because the packages in a <code>-d --baseDir</code> already have this information in their respective POSEIDON.yml files. (default: Other)
<code>-o,--outPackagePath DIR</code>	Path to the output package directory.
<code>-n,--outPackageName STRING</code>	The output package name. This is optional: If no name is provided, then the package name defaults to the basename of the (mandatory) <code>--outPackagePath</code> argument. (default: Nothing)
<code>--minimal</code>	Should the output data be reduced to a necessary minimum and omit empty scaffolding?

87 The command

```
trident init \  
  --inFormat EIGENSTRAT/PLINK \  
  --genoFile path/to/genoFile \  
  --snpFile path/to/snpFile \  
  --indFile path/to/indFile \  
  --snpSet 1240K|HumanOrigins|Other \  
  -o path/to/new_package_name
```

88 requires the format (`--inFormat`) of your input data (either EIGENSTRAT or PLINK), the paths to the respective
89 files (`--genoFile`, `--snpFile`, `--indFile`), and optionally the “shape” of these files (`--snpSet`), so if they cover
90 the 1240K, the HumanOrigins or an Other SNP set.

91 A simpler interface is available with `-p` (+ `--snpSet`), which only requires a path to one of the genotype data
92 files and automatically discovers the others if they share the same base name:

```

trident init \
  -p path/to/genoFile \
  --snpSet 1240K|HumanOrigins|Other \
  -o path/to/new_package_name

```

93 The following file extensions are expected:

	EIGENSTRAT	PLINK
genoFile	.geno	.bed
snpFile	.snp	.bim
indFile	.ind	.fam

94 The output package created by `init` is located in a new directory `-o`, which should not already exist when `init`
 95 is called, and gets the package title corresponding to the basename of `-o`. You can also set the title explicitly
 96 with `-n`.

97 The `--minimal` flag causes `init` to create a minimal package with a very basic POSEIDON.yml and no `.bib`
 98 and `.janno` files.

99 1.3.2 Fetch command

100 `fetch` allows to download Poseidon packages from a remote Poseidon server via a Web API. This server provides
 101 all packages in the Poseidon public archives.

102 Command line details

```

Usage: trident fetch (-d|--baseDir DIR)
      (--downloadAll |
      (--fetchFile FILE | (-f|--fetchString DSL)))
      [--remoteURL URL] [--archive STRING]

```

Download data from a remote Poseidon repository

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>--downloadAll</code>	Download all packages the server is offering.
<code>--fetchFile FILE</code>	A file with a list of packages. Works just as <code>-f</code> , but multiple values can also be separated by newline, not just by comma. <code>-f</code> and <code>--fetchFile</code> can be combined.
<code>-f,--fetchString DSL</code>	List of packages to be downloaded from the remote server. Package names should be wrapped in asterisks: <code>*package_title*</code> . You can combine multiple values with comma, so for example: <code>"*package_1*, *package_2*, *package_3*"</code> . <code>fetchString</code> uses the same parser as <code>forgeString</code> , but does not allow excludes. If groups or individuals are specified, then packages which

	include these groups or individuals are included in the download.
<code>--remoteURL URL</code>	URL of the remote Poseidon server. (default: "https://server.poseidon-adna.org")
<code>--archive STRING</code>	The name of the Poseidon package archive that should be queried. If not given, then the query falls back to the default archive of the server selected with <code>--remoteURL</code> . See the archive documentation at https://www.poseidon-adna.org/#/archive_overview for a list of archives currently available from the official Poseidon Web API. (default: Nothing)

103 It works with

```
trident fetch -d ... -d ... \
  -f "*package_title_1*,*package_title_2-1.0.1*,group_name,<individual1>"
```

104 and the entities you want to download must be listed either in a simple string of comma-separated values, which
105 can be passed via `-f/--fetchString`, or in a text file (`--fetchFile`). Entities are then combined from these
106 sources.

107 Entities are specified using a special syntax (see also the documentation of `forge` below): packages are
108 wrapped in asterisks, with or without a version number appended after a dash (e.g. `*package_title*` or
109 `*package_title-1.2.3`), group names are spelled as is, and individual names are wrapped in angular brackets
110 (e.g. `<individual1>`). Fetch will figure out which packages need to be downloaded to include all specified entities.

111 `--downloadAll`, which can be given instead of `-f` and `--fetchFile`, causes fetch to download all packages from
112 the server. The downloaded packages are added in the first (!) `-d` directory (which gets created if it doesn't
113 exist), but downloads are only performed if the respective packages are not already present in the latest version
114 in any of the `-d` directories.

115 Note that `trident fetch` is usually used in a workflow with `trident list --remote`: First one inspects what
116 is available on the server with `list`, to then compile a custom, targeted `fetch` command.

117 `fetch` has the optional arguments `--remote https://..."` to name an alternative Poseidon server and
118 `--archive` to select a specific Poseidon archive on the server.

119 1.3.3 Forge command

120 `forge` creates new Poseidon packages by extracting and merging packages, populations and individuals/samples
121 from Poseidon repositories.

122 Command line details

```
Usage: trident forge ((-d|--baseDir DIR) |
  ((-p|--genoOne FILE) | --inFormat FORMAT --genoFile FILE
    --snpFile FILE --indFile FILE) [--snpSet SET])
  [--forgeFile FILE | (-f|--forgeString DSL)]
  [--selectSnps FILE] [--intersect] [--outFormat FORMAT]
  [--minimal] [--onlyGeno] (-o|--outPackagePath DIR)
  [-n|--outPackageName STRING] [--packagewise]
```

[--outPlinkPopName MODE]

Select packages, groups or individuals and create a new Poseidon package from them

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>-p,--genoOne FILE</code>	One of the input genotype data files. Expects .bed, .bim or .fam for PLINK and .geno, .snp or .ind for EIGENSTRAT. The other files must be in the same directory and must have the same base name.
<code>--inFormat FORMAT</code>	The format of the input genotype data: EIGENSTRAT or PLINK. Only necessary for data input with --genoFile + --snpFile + --indFile.
<code>--genoFile FILE</code>	Path to the input geno file.
<code>--snpFile FILE</code>	Path to the input snp file.
<code>--indFile FILE</code>	Path to the input ind file.
<code>--snpSet SET</code>	The snpSet of the package: 1240K, HumanOrigins or Other. Only relevant for data input with -p --genoOne or --genoFile + --snpFile + --indFile, because the packages in a -d --baseDir already have this information in their respective POSEIDON.yml files. (default: Other)
<code>--forgeFile FILE</code>	A file with a list of packages, groups or individual samples. Works just as -f, but multiple values can also be separated by newline, not just by comma. Empty lines are ignored and comments start with "#", so everything after "#" is ignored in one line. Multiple instances of -f and --forgeFile can be given. They will be evaluated according to their input order on the command line.
<code>-f,--forgeString DSL</code>	List of packages, groups or individual samples to be combined in the output package. Packages follow the syntax *package_title*, populations/groups are simply group_id and individuals <individual_id>. You can combine multiple values with comma, so for example: "*package_1*, <individual_1>, <individual_2>, group_1". Duplicates are treated as one entry. Negative selection is possible by prepending "-" to the entity you want to exclude (e.g. "*package_1*, -<individual_1>, -group_1"). forge will apply excludes and includes in order. If the first entity is negative, then forge will assume you want to merge all individuals in the packages found in the baseDirs

(except the ones explicitly excluded) before the exclude entities are applied. An empty forgeString (and no --forgeFile) will therefore merge all available individuals. If there are individuals in your input packages with equal individual id, but different main group or source package, they can be specified with the special syntax "<package:group:individual>".

--selectSnps FILE To extract specific SNPs during this forge operation, provide a Snp file. Can be either Eigenstrat (file ending must be '.snp') or Plink (file ending must be '.bim'). When this option is set, the output package will have exactly the SNPs listed in this file. Any SNP not listed in the file will be excluded. If option '--intersect' is also set, only the SNPs overlapping between the SNP file and the forged packages are output. (default: Nothing)

--intersect Whether to output the intersection of the genotype files to be forged. The default (if this option is not set) is to output the union of all SNPs, with genotypes defined as missing in those packages which do not have a SNP that is present in another package. With this option set, the forged dataset will typically have fewer SNPs, but less missingness.

--outFormat FORMAT The format of the output genotype data: EIGENSTRAT or PLINK. (default: PLINK)

--minimal Should the output data be reduced to a necessary minimum and omit empty scaffolding?

--onlyGeno Should only the resulting genotype data be returned? This means the output will not be a Poseidon package.

-o,--outPackagePath DIR Path to the output package directory.

-n,--outPackageName STRING The output package name. This is optional: If no name is provided, then the package name defaults to the basename of the (mandatory) --outPackagePath argument. (default: Nothing)

--packagewise Skip the within-package selection step in forge. This will result in outputting all individuals in the relevant packages, and hence a superset of the requested individuals/groups. It may result in better performance in cases where one wants to forge entire packages or almost entire packages. Details: Forge conceptually performs two types of selection: First, it identifies which packages in the supplied base directories are relevant to the requested forge, i.e.

whether they are either explicitly listed using `*PackageName*`, or because they contain selected individuals or groups. Second, within each relevant package, individuals which are not requested are removed. This option skips only the second step, but still performs the first.

`--outPlinkPopName MODE` Where to write the population/group name into the FAM file in Plink-format. Three options are possible: `asFamily` (default) | `asPhenotype` | `asBoth`. See also `--inPlinkPopName`.

123 `forge` can be used with

```
trident forge -d ... -d ... \
  -f "*package_name*, group_id, <individual_id>" \
  -o path/to/new_package_name
```

124 where the entities (packages, groups/populations, individuals/samples) you want in the output package can be
 125 denoted either as a string on the command line (`-f/--forgeString`), or in an input text file (`--forgeFile`).
 126 See the section below for the syntax of this selection language. Do not forget to wrap the `--forgeString` query
 127 in quotes.

128 Including one or multiple Poseidon packages with `-d` is not the only way to include data for a forge operation.
 129 It is also possible to consider unpackaged genotype data directly with `-p` (+ `--snpSet`) or `--inFormat` +
 130 `--genoFile` + `--snpFile` + `--indFile` (+ `--snpSet`). This makes the following example possible, where we
 131 merge data from one Poseidon package and two unpackaged genotype datasets to get a new EIGENSTRAT
 132 dataset.

```
trident forge \
  -d 2017_GonzalesFortesCurrentBiology \
  -p 2018_VeeramahPNAS/2018_VeeramahPNAS.fam \
  --inFormat PLINK \
  --genoFile 2017_HaberAJHG/2017_HaberAJHG.bed \
  --snpFile 2017_HaberAJHG/2017_HaberAJHG.bim \
  --indFile 2017_HaberAJHG/2017_HaberAJHG.fam \
  -f "<STR241.SG>,<ERS1790729.SG>,Iberia_HG.SG" \
  -o testpackage \
  --outFormat EIGENSTRAT \
  --onlyGeno
```

133 **1.3.3.1 The forge selection language** The text in `--forgeString` and `--forgeFile` (and with a reduced
 134 syntax also in `--fetchString` and `--fetchFile`) are parsed as a domain specific query language that describes
 135 precisely which entities should be compiled in the output package of a given `forge` operation. The language has
 136 multiple syntactic elements and a specific evaluation logic.

137 In general a `--forgeString` query consists of multiple entities, separated by `,`. The main entities are Poseidon
 138 packages, groups/populations and individuals/samples:

- 139 • Each package title is surrounded by `*`: `*package*`. That means if you want all individuals of the Poseidon

140 package 2019_Jeong_InnerEurasia in the output package you would add `*2019_Jeong_InnerEurasia*`
 141 to the query.

- 142 • Groups/populations are not specially marked: `group`. So to get all individuals of the group
 143 `Swiss_Roman_Period`, you would simply add `Swiss_Roman_Period`.
- 144 • Individuals/samples are surrounded by `<` and `>`: `<individual>`. ALA026 therefore becomes `<ALA026>`. A sec-
 145 ond way to denote individuals is with the more verbose and specific syntax `<package:group:individual>`.
 146 Such defined individuals take precedence over differently defined ones (so directly with `<individual>` or
 147 as a subset of `*package*` or `group`). This allows to resolve duplication issues precisely – at least in cases
 148 where the duplicated individuals differ in source package or primary group.
- 149 • Package versions can be appended to package names, such as `*package-1.2.3*`.
- 150 • This also works with the verbose individual syntax: `<package-1.2.3:group:individual>`.

151 In the `--forgeFile` each line is treated as a separate `forgeString`, empty lines are ignored and `#` symbols start
 152 comments. So this is a valid example of a `forgeFile`:

```
# Packages
*pac1*, *pac2-1.2.3*

# Groups and individuals from other packages beyond pac1 and pac2
group1, <ind1>, group2, <ind2>, <pac3:group3:ind3>

# pac2 has two outlier individuals that should be ignored
-<ind4>           # This one has very low coverage
-<pac2:group4:ind5> # This one is from a different time period
```

153 By prepending `-` to entities, we can exclude them from the forged package (this feature is not available for
 154 `fetch`). `forge` figures out the final list of samples to include by interpreting all `forge`-entities in order. So an
 155 entity list `*pac1*, -<ind1>, group1` may result in a different outcome than `*pac1*, group1, -<ind1>`, depending
 156 on whether `<ind1>` belongs to `group1` or not.

157 If the `forge` entity list starts with a negative entity, or if the entity list is empty, `forge` will implicitly assume
 158 you want to include all individuals in all **latest** versions of packages found in the base directories (except the
 159 ones explicitly excluded, of course).

160 The specific semantics of the various ways to include or exclude entities are as follows:

161 1.3.3.1.1 Inclusion queries

- 162 • `*pac1*`: Select all individuals in the latest version of package “pac1”
- 163 • `*pac1-1.0.1*`: Select all individuals in package “pac1” with version “1.0.1”
- 164 • `group1`: Select all individuals associated with “group1” in all latest versions of all packages
- 165 • `<ind1>`: Select the individual named “ind1”, searching in all latest packages.
- 166 • `<pac1:group1:ind1>`: Select the individual named “ind1” associated with “group1” in the latest version
 167 of package “pac1”
- 168 • `<pac1-1.0.1:group1:ind1>`: Select the individual named “ind1” associated with “group1” in the package
 169 “pac1” with version “1.0.1”

170 1.3.3.1.2 Exclusion queries

- 171 • `-*pac1*`: Remove all individuals in all versions of package “pac1”

- `-*pac1-1.0.1*`: Remove only individuals in package “pac1” with version “1.0.1” (but leave other versions in)
- `-group1`: Remove all individuals associated with “group1” in all versions of all packages (not just the latest)
- `-<ind1>`: Remove all individuals named “ind1” in all versions of all packages (not just the latest)
- `-<pac1:group1:ind1>`: Remove the individual named “ind1” associated with “group1”, searching in all versions of package “pac1”
- `-<pac1-1.0.1:group1:ind1>`: Remove the individual named “ind1” associated with “group1”, but only if they are in “pac1” with version “1.0.1”

If a query results in multiple individuals with the same name, forge will throw an error.

1.3.3.2 Treatment of the genotype data while merging Forge performs a series of steps to merge the genotype data of multiple source files:

1. Genotype data from each package is streamed in parallel. Because our packages may have different SNP locations (specified by chromosome-position pairs) listed in their `.bim/.snp` file, we first perform a zipping-operation, whose behaviour depends on whether `--intersect` is set or not. Without `--intersect`, any SNP position listed in any package will be forwarded to the output, with missing values being filled in in all packages that do not list that particular SNP. With `--intersect`, only SNP positions that are present in all packages are considered. Note that relevant for this step is only whether a given SNP position is part of the genotype data, not whether the actual genotypes are missing or not.
2. At each SNP, the consensus alleles are selected, by collecting all reference and alternative alleles from all sources. If more than two non-dummy alleles (alleles different from N) are present in that collection, an error is thrown. If exactly two non-dummy alleles are present (which should be the case for binary SNPs), the two alleles are declared “reference” and “alternative” alleles for the output. If only one non-dummy allele is present, it is set to be the reference allele, and “N” is set to be the alternative.
3. All source genotype data is then read and recoded in terms of the two chosen consensus alleles. This will make sure that source data with flipped reference and alternative allele gets correctly merged in.
4. SNP IDs, as part of PLINK `.bim` files are checked across the source files. If all SNP IDs for a given SNP are missing, then the result will also be missing. If there is only one SNP ID present in some or all source packages, that ID gets forwarded to the output. In the (unusual) case that there are multiple different non-missing SNP IDs (of the form “rs” followed by a number), then a debug warning is output (which gets printed to the screen when `--debug` is selected), and simply the first value is chosen to be output into the forged `.bim` file. We decided not to throw an error in that case, because we consider the physical position of the SNP (specified by Chromosome and position) to be definitive, and the SNP ID to be of secondary importance.
5. Genetic positions, as part of PLINK `.bim` files are checked in a similar manner, with “0.0” being interpreted as missing.

1.3.3.3 Treatment of the .janno file while merging `forge` merges and subsets `.janno` files along with the genotype data. If a package lacks a `.janno` file, then a basic one will be created internally on-the-fly based on the information in the genotype data, and used for the output. Missing columns across packages will be filled with `n/a`.

For merging two `.janno` files **A** and **B** the following rules apply regarding undefined, arbitrary additional columns:

- If **A** has an additional column which is not in **B** then empty cells in the rows imported from **B** are filled with **n/a**.
- If **A** and **B** share additional columns with identical column name, then they are treated as semantically identical units and merged accordingly.
- In the resulting **.janno** file, all additional columns from both **A** and **B** are sorted alphabetically and appended after the normal, specified variables.

The following example illustrates the described behaviour:

A.janno

Poseidon_ID	Group_Name	Genetic_Sex	AdditionalColumn1	AdditionalColumn2
XXX011	POP1	M	A	D
XXX012	POP2	F	B	E
XXX013	POP1	M	C	F

B.janno

Poseidon_ID	Group_Name	Genetic_Sex	AdditionalColumn3	AdditionalColumn2
YYY022	POP5	F	G	J
YYY023	POP5	F	H	K
YYY024	POP5	M	I	L

A.janno + B.janno

Poseidon_ID	Group_Name	Genetic_Sex	AdditionalColumn1	AdditionalColumn2	AdditionalColumn3
XXX011	POP1	M	A	D	n/a
XXX012	POP2	F	B	E	n/a
XXX013	POP1	M	C	F	n/a
YYY022	POP5	F	n/a	J	G
YYY023	POP5	F	n/a	K	H
YYY024	POP5	M	n/a	L	I

1.3.3.4 Treatment of the .ssf file while merging The Sequencing Source File (short **.ssf** file) is forged in exactly the same way as the **.janno** file. **.ssf** files that are present are included in the forge product, following selection of those entities which are listed in the **poseidon_IDs** columns. Columns that are only present in some packages, including those not defined in the Poseidon package specification, are also included in the forged product in the same way as described for **.janno** files above.

1.3.3.5 Treatment of the .bib file while merging In the forge process all relevant samples for the output package are determined. This includes their **.janno** entries and therefore the information on the publication keys documented for them in the **.janno Publication** column. The output **.bib** file compiles only the relevant references for the samples in the output package. It includes the references exactly once and is sorted alphabetically by key.

234 **1.3.3.6 Other options** Just as for `init` the output package of `forge` is created as a new directory `-o`. The
235 title can also be explicitly defined with `-n`.

236 `--minimal` allows for the creation of a minimal output package without `.bib` and `.janno`. This is especially
237 useful for data analysis pipelines, where only the genotype data is required. Even more basic output comes with
238 `--onlyGeno`, which means that only the genotype data is returned without any Poseidon package.

239 `forge` has a an optional flag `--intersect`, that defines, if the genotype data from different packages should be
240 merged with a union or an intersect operation. See *Treatment of the genotype data while merging* above.

241 `--intersect` also influences the automatic determination of the `snpSet` field in the `POSEIDON.yml` file for the
242 resulting package. If the `snpSets` of all input packages are identical, then the resulting package will just inherit
243 this configuration. Otherwise `forge` applies the following pairwise merging logic:

Input snpSet A	Input snpSet B	<code>--intersect</code>	Ouput snpSet
Other	*	*	Other
1240K	HumanOrigins	True	HumanOrigins
1240K	HumanOrigins	False	1240K

244 `--selectSnps` allows to provide `forge` with a SNP file in EIGENSTRAT (`.snp`) or PLINK (`.bim`) format to
245 create a package with a specific selection. When this option is set, the output package will have exactly the
246 SNPs listed in this file. Any SNP not listed in the file will be excluded. If `--intersect` is also set, only the
247 SNPs overlapping between the SNP file and the forged packages are output.

248 With `--packagewise` the within-package selection step in `forge` can be skipped. This will result in outputting
249 all individuals in the relevant packages, and hence a superset of the requested individuals/groups. It may result
250 in better performance in cases where one wants to forge entire packages.

251 1.3.4 Genoconvert command

252 `genoconvert` converts the genotype data in a Poseidon package to a different file format. The respective entries
253 in the `POSEIDON.yml` file are changed accordingly.

254 Command line details

```
Usage: trident genoconvert ((-d|--baseDir DIR) |
                           ((-p|--genoOne FILE) | --inFormat FORMAT
                           --genoFile FILE --snpFile FILE --indFile FILE)
                           [--snpSet SET]) --outFormat FORMAT [--onlyGeno]
                           [-o|--outPackagePath DIR] [--removeOld]
                           [--outPlinkPopName MODE] [--onlyLatest]
```

Convert the genotype data in a Poseidon package to a different file format

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>-p,--genoOne FILE</code>	One of the input genotype data files. Expects <code>.bed</code> , <code>.bim</code> or <code>.fam</code> for PLINK and <code>.geno</code> , <code>.snp</code> or <code>.ind</code> for

	EIGENSTRAT. The other files must be in the same directory and must have the same base name.
<code>--inFormat FORMAT</code>	The format of the input genotype data: EIGENSTRAT or PLINK. Only necessary for data input with <code>--genoFile</code> + <code>--snpFile</code> + <code>--indFile</code> .
<code>--genoFile FILE</code>	Path to the input geno file.
<code>--snpFile FILE</code>	Path to the input snp file.
<code>--indFile FILE</code>	Path to the input ind file.
<code>--snpSet SET</code>	The snpSet of the package: 1240K, HumanOrigins or Other. Only relevant for data input with <code>-p --genoOne</code> or <code>--genoFile</code> + <code>--snpFile</code> + <code>--indFile</code> , because the packages in a <code>-d --baseDir</code> already have this information in their respective POSEIDON.yml files. (default: Other)
<code>--outFormat FORMAT</code>	the format of the output genotype data: EIGENSTRAT or PLINK.
<code>--onlyGeno</code>	Should only the resulting genotype data be returned? This means the output will not be a Poseidon package.
<code>-o,--outPackagePath DIR</code>	Path to the output package directory. This is optional: If no path is provided, then the output is written to the directories where the input genotype data file (.bed/.geno) is stored. (default: Nothing)
<code>--removeOld</code>	Remove the old genotype files when creating the new ones.
<code>--outPlinkPopName MODE</code>	Where to write the population/group name into the FAM file in Plink-format. Three options are possible: asFamily (default) asPhenotype asBoth. See also <code>--inPlinkPopName</code> .
<code>--onlyLatest</code>	Consider only the latest versions of packages, or the groups and individuals within the latest versions of packages, respectively.

255 With the default setting

```
trident genoconvert -d ... -d ... --outFormat EIGENSTRAT|PLINK
```

256 all packages in `-d` will be converted to the desired `--outFormat` (either EIGENSTRAT or PLINK), if the data is
257 not already in this format. This includes updating the respective POSEIDON.yml files.

258 The “old” data is not deleted, but kept around. That means conversion can result in a package with both PLINK
259 and EIGENSTRAT data, but only one is linked in the POSEIDON.yml file, and that is what will be used by
260 **trident**. To delete the old data in the conversion you can add the `--removeOld` flag.

261 `-p` (+ `--snpSet`) or `--inFormat` + `--genoFile` + `--snpFile` + `--indFile` (+ `--snpSet`) allow to directly
262 convert genotype data that is not wrapped in a Poseidon package and store it to a directory given in `-o`. See
263 this example:

```
trident genoconvert \
  -p 2018_Mittnik_Baltic/Mittnik_Baltic.bed \
  --outFormat EIGENSTRAT \
  -o my_directory
```

264 1.3.5 Jannocoalesce command

265 jannocoalesce merges information from one or multiple source .janno files into a target .janno file.

266 Command line details

```
Usage: trident jannocoalesce ((-s|--sourceFile FILE) | (-d|--baseDir DIR))
      (-t|--targetFile FILE) [-o|--outFile FILE]
      [--includeColumns ARG | --excludeColumns ARG]
      [-f|--force] [--sourceKey ARG] [--targetKey ARG]
      [--stripIdRegex ARG]
```

Coalesce information from one or multiple janno files to another one

Available options:

-h,--help	Show this help text
-s,--sourceFile FILE	The source .janno file.
-d,--baseDir DIR	A base directory to search for Poseidon packages.
-t,--targetFile FILE	The target .janno file to fill.
-o,--outFile FILE	An optional file to write the results to. If not specified, change the target file in place. (default: Nothing)
--includeColumns ARG	A comma-separated list of .janno column names to coalesce. If not specified, all columns that can be found in the source and target will get filled.
--excludeColumns ARG	A comma-separated list of .janno column names NOT to coalesce. All columns that can be found in the source and target will get filled, except the ones listed here.
-f,--force	With this option, potential non-missing content in target columns gets overridden with non-missing content in source columns. By default, only missing data gets filled-in.
--sourceKey ARG	The .janno column to use as the source key. (default: "Poseidon_ID")
--targetKey ARG	The .janno column to use as the target key. (default: "Poseidon_ID")
--stripIdRegex ARG	An optional regular expression to identify parts of the IDs to strip before matching between source and target. Uses POSIX Extended regular expressions.

267 A most basic run may just include two arguments:


```

trident jannocoalesce \
  --sourceFile path/to/source.janno \
  --targetFile path/to/target.janno

```

268 jannocoalesce generally works by reading a source .janno file with `-s|--sourceFile` (or all .janno files in a
 269 `-d|--baseDir`) and a target .janno file with `-t|--targetFile`.

270 It then merges these files by a key column, which can be selected with `--sourceKey` and `--targetKey`. The
 271 default for both of these key columns is the `Poseidon_ID`. In case the entries in the key columns slightly and
 272 systematically differ, e.g. because the `Poseidon_ID`s in either have a special suffix (for example `_SG`), then the
 273 `--stripIdRegex` option allows to strip these with a regular expression to thus match the keys.

274 jannocoalesce generally attempts to fill **all** empty cells in the target .janno file with information from the
 275 source. `--includeColumns` and `--excludeColumns` allow to select specific columns for which this should be
 276 done. In some cases it may be desirable to not just fill empty fields in the target, but overwrite the information
 277 already there with the `-f|--force` option. If the target file should be preserved, then the output can be directed
 278 to a new output .janno file with `-o|--outFile`.

279 1.3.6 Rectify command

280 rectify automatically harmonizes POSEIDON.yml files of one or multiple packages. This is not an automatic
 281 update from one Poseidon version to the next, but rather a clean-up wizard after manual modifications.

282 Command line details

```

Usage: trident rectify (-d|--baseDir DIR) [--ignorePoseidonVersion]
      [--poseidonVersion ??.?]
      [--packageVersion VPART [--logText STRING]]
      [--checksumAll | [--checksumGeno] [--checksumJanno]
      [--checksumSSF] [--checksumBib]]
      [--newContributors DSL] [--onlyLatest]

```

Adjust POSEIDON.yml files automatically to package changes

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>--ignorePoseidonVersion</code>	Read packages even if their poseidonVersion is not compatible with trident.
<code>--poseidonVersion ??.?</code>	Poseidon version the packages should be updated to: e.g. "2.5.3".
<code>--packageVersion VPART</code>	Part of the package version number in the POSEIDON.yml file that should be updated: Major, Minor or Patch (see https://semver.org).
<code>--logText STRING</code>	Log text for this version in the CHANGELOG file.
<code>--checksumAll</code>	Update all checksums.
<code>--checksumGeno</code>	Update genotype data checksums.
<code>--checksumJanno</code>	Update .janno file checksum.

<code>--checksumSSF</code>	Update .ssf file checksum
<code>--checksumBib</code>	Update .bib file checksum.
<code>--newContributors DSL</code>	Contributors to add to the POSEIDON.yml file in the form "[Firstname Lastname](Email address);...".
<code>--onlyLatest</code>	Consider only the latest versions of packages, or the groups and individuals within the latest versions of packages, respectively.

It can be called with a lot of optional arguments. Note that `rectify` by default does **not** apply any changes if none of these arguments are set. Each change requires explicit opt-in.

```
trident rectify -d ... -d ... \
  --poseidonVersion "X.X.X" \
  --packageVersion Major|Minor|Patch \
  --logText "short description of the update" \
  --checksumAll \
  --newContributors "[Firstname Lastname](Email address);..."
```

The following arguments determine which fields of the POSEIDON.yml file should be modified:

- `--poseidonVersion` allows a simple change of the `poseidonVersion` field in the POSEIDON.yml file.
- `--packageVersion` increments the package version number in the first, the second or the third position. It can optionally be called with `--logText`, which appends an entry to the CHANGELOG file for the respective package version update. `--logText` also creates a new CHANGELOG.md file if it does not exist yet.
- `--checksumGeno`, `--checksumJanno`, `--checksumSSF` and `--checksumBib` add or modify the respective checksum fields in the POSEIDON.yml file. `--checksumAll` is a wrapper to call all of them at once.
- `--newContributors` adds new contributors.

As `rectify` reads and rewrites POSEIDON.yml files, it may change their inner order, layout or even content (e.g. if they have fields which are not in the POSEIDON.yml specification). Create a backup of the POSEIDON.yml file before running `rectify` if you are uncertain if this might affect you negatively.

1.4 Inspection commands

1.4.1 List command

`list` lists packages, groups and individuals of local datasets, or of packages available in the archives on the web server.

Command line details

```
Usage: trident list ((-d|--baseDir DIR) | --remote [--remoteURL URL]
  [--archive STRING])
  (--packages | --groups | --individuals
  [-j|--jannoColumn COLNAME]) [--raw] [--onlyLatest]
```

List packages, groups or individuals from local or remote Poseidon repositories

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>--remote</code>	List packages from a remote server instead the local file system.
<code>--remoteURL URL</code>	URL of the remote Poseidon server. (default: "https://server.poseidon-adna.org")
<code>--archive STRING</code>	The name of the Poseidon package archive that should be queried. If not given, then the query falls back to the default archive of the server selected with <code>--remoteURL</code> . See the archive documentation at https://www.poseidon-adna.org/#/archive_overview for a list of archives currently available from the official Poseidon Web API. (default: Nothing)
<code>--packages</code>	List all packages.
<code>--groups</code>	List all groups, ignoring any group names after the first as specified in the <code>.janno-file</code> .
<code>--individuals</code>	List all individuals/samples.
<code>-j,--jannoColumn COLNAME</code>	List additional fields from the janno files, using the <code>.janno</code> column heading name, such as "Country", "Site", "Date_C14_Uncal_BP", etc..
<code>--raw</code>	Return the output table as tab-separated values without header. This is useful for piping into <code>grep</code> or <code>awk</code> .
<code>--onlyLatest</code>	Consider only the latest versions of packages, or the groups and individuals within the latest versions of packages, respectively.

302 To list packages from your local repositories, as seen above you can run

```
trident list -d ... -d ... --packages
```

303 This will yield a nicely formatted table of all packages, their version and the number of individuals in them.

304 You can use `--remote` to show packages on the remote server. For example

```
trident list --packages --remote --archive "community-archive"
```

305 will result in a view of all packages available in one of the public Poseidon archives. Just as for `fetch`, the
306 `--archive` flag allows to choose which public archive to query.

307 Independent of whether you query a local or an online archive, you can not just list packages, but also groups,
308 as defined in the third column of EIGENSTRAT `.ind` files (or the first/last column of a PLINK `.fam` file), and
309 individuals with the flags `--groups` and `--individuals` (instead of `--packages`).

310 The `--individuals` flag additionally provides a way to immediately access information from `.janno` files
311 on the command line. This works with the `-j|--jannoColumn` option. For example adding `-j Country -j`
312 `Date_C14_Uncal_BP` to the commands above will add the `Country` and the `Date_C14_Uncal_BP` columns to the
313 respective output tables.

314 Note that if you want a less ornate table, for example because you want to load this into Excel, or pipe into
315 another command that cannot deal with the table layout, you can use the `--raw` option to output that table as
316 a simple tab-delimited stream.

317 1.4.2 Summarise command

318 `summarise` prints some general summary statistics for a given Poseidon dataset taken from the `.janno` files.

319 Command line details

```
Usage: trident summarise (-d|--baseDir DIR) [--raw]
```

Get an overview over the content of one or multiple Poseidon packages

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>--raw</code>	Return the output table as tab-separated values without header. This is useful for piping into <code>grep</code> or <code>awk</code> .

320 You can run it with

```
trident summarise -d ... -d ...
```

321 which will show you context information like – among others – the number of individuals in the dataset, their sex
322 distribution, the mean age of the samples or the mean coverage on the 1240K SNP array in a table. `summarise`
323 depends on complete `.janno` files and will silently ignore missing information.

324 You can use the `--raw` option to output the summary table in a simple, tab-delimited layout.

325 1.4.3 Survey command

326 `survey` tries to indicate package completeness (mostly focused on `.janno` files) for Poseidon datasets.

327 Command line details

```
Usage: trident survey (-d|--baseDir DIR) [--raw] [--onlyLatest]
```

Survey the degree of context information completeness for Poseidon packages

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>--raw</code>	Return the output table as tab-separated values without header. This is useful for piping into <code>grep</code> or <code>awk</code> .
<code>--onlyLatest</code>	Consider only the latest versions of packages, or the groups and individuals within the latest versions of packages, respectively.

328 Running

```
trident survey -d ... -d ...
```

will yield a table with one row for each package. See `trident survey -h` for a legend which cell of this table means what.

Again you can use the `--raw` option to output the survey table in a tab-delimited format.

1.4.4 Validate command

`validate` checks Poseidon packages and individual package components for structural correctness.

Command line details

```
Usage: trident validate ((-d|--baseDir DIR) [--ignoreGeno] [--fullGeno]
                        [--ignoreDuplicates] [-c|--ignoreChecksums]
                        [--ignorePoseidonVersion] |
                        --pyml FILE | (-p|--genoOne FILE) | --inFormat FORMAT
                        --genoFile FILE --snpFile FILE --indFile FILE |
                        --janno FILE | --ssf FILE | --bib FILE) [--noExitCode]
                        [--onlyLatest]
```

Check Poseidon packages or package components for structural correctness

Available options:

<code>-h,--help</code>	Show this help text
<code>-d,--baseDir DIR</code>	A base directory to search for Poseidon packages.
<code>--ignoreGeno</code>	Ignore snp and geno file.
<code>--fullGeno</code>	Test parsing of all SNPs (by default only the first 100 SNPs are probed).
<code>--ignoreDuplicates</code>	Do not stop on duplicated individual names in the package collection.
<code>-c,--ignoreChecksums</code>	Whether to ignore checksums. Useful for speedup in debugging.
<code>--ignorePoseidonVersion</code>	Read packages even if their poseidonVersion is not compatible with trident.
<code>--pyml FILE</code>	Path to a POSEIDON.yml file.
<code>-p,--genoOne FILE</code>	One of the input genotype data files. Expects .bed, .bim or .fam for PLINK and .geno, .snp or .ind for EIGENSTRAT. The other files must be in the same directory and must have the same base name.
<code>--inFormat FORMAT</code>	The format of the input genotype data: EIGENSTRAT or PLINK. Only necessary for data input with --genoFile + --snpFile + --indFile.
<code>--genoFile FILE</code>	Path to the input geno file.
<code>--snpFile FILE</code>	Path to the input snp file.
<code>--indFile FILE</code>	Path to the input ind file.
<code>--janno FILE</code>	Path to a .janno file.
<code>--ssf FILE</code>	Path to a .ssf file.

<code>--bib FILE</code>	Path to a .bib file.
<code>--noExitCode</code>	Do not produce an explicit exit code.
<code>--onlyLatest</code>	Consider only the latest versions of packages, or the groups and individuals within the latest versions of packages, respectively.

335 You can run it with

```
336 trident validate -d ... -d ...
```

336 to check packages and it will either report a success (**Validation passed**) or failure with specific error messages.

337 Instead of validating entire packages with `-d` you can also apply it to individual files and package components: `--pym` (POSEIDON.yml), `-p | --inFormat + --genoFile + --snpFile + --indFile` (genotype data), `--janno` (.janno file), `--ssf` (.ssf file) or `--bib` (.bib file). In this case `validate` attempts to read and parse the respective files individually and reports any issues it encounters. Note that this considers the files in isolation and does not include any cross-file consistency checks.

342 When applied to packages, `validate` tries to ensure that each package adheres to the Poseidon package specification. Here is a list of what is checked:

- 344 • Structural correctness of the POSEIDON.yml file.
- 345 • Presence of all files references in the POSEIDON.yml file.
- 346 • Full structural correctness of .janno, .ssf and .bib file.
- 347 • Superficial correctness of genotype data files by parsing the first 100 SNPs. A full check that parses all SNPs can be triggered with the `--fullGeno` option. `--ignoreGeno`, on the other hand, causes `validate` to ignore the genotype data entirely, which speeds up the validation significantly.
- 349 • Correspondence of BibTeX keys in .bib and .janno
- 350 • Correspondence of sample IDs in .janno and .ssf.
- 351 • Correspondence of sample and group IDs in .janno and genotype data files.

353 In fact much of this validation already runs as part of the general package reading pipeline invoked for other `trident` subcommands (e.g. `forge`). `validate` is meant to be more thorough and brittle, though, and will explicitly fail if even a single package is broken. For special cases more flexibility can be enabled with the options `--ignoreDuplicates`, `--ignoreChecksums` and `--ignorePoseidonVersion`.

357 Remember to run `validate` with `--debug` to get more information in case the default output is not sufficient to analyse an issue.