

Preprocessing data with *recipes* : : CHEAT SHEET



Basics

Get your data ready for modeling using 'pipable' sequences of feature engineering steps with **recipes**

```
#----- Initialize the recipe and add steps -----
rec <- recipe(x ~ ., data = train_data) |>
  step_normalize(all_numeric_predictors())

#----- Run the steps using training data -----
pr <- prep(rec, training = train_data)

#----- Apply estimates to new data -----
bake(pr, new_data = new_data)
```

recipe(x, ...) - Begins a new recipe specification.

prep(x, ...) - Prepares the recipe with training data.

bake(object, ...) - Applies estimates from `prep()`.

update(object, ...) - Updates and re-fits a model.

COMMON `STEP\_` ARGUMENTS

recipe A recipe object. New steps are appended to the recipe.

... Arguments passed to the external R function accessed by the step function

options Selector functions to choose variables for this step

Filters

step_*(recipe, ...)

step_nzv(freq_cut = 95/5, unique_cut = 10, options = list(freq_cut = 95/5)) - Removes variables that are highly sparse and unbalanced.

step_zv(group = NULL) - Removes variables that contain only a single value.

step_lincomb(max_steps = 5) - Removes numeric variables that have exact linear combinations between them.

step_corr(threshold = 0.9, use = "pairwise.complete.obs", method = "pearson") - Removes variables that have large absolute correlations with other variables.

step_filter_missing(threshold = 0.1) - Removes variables that have too many missing values.

step_rm() - Removes selected variables.

In-place Transformations

step_mutate(recipe, ..., pkgs = character()) - General purpose transformer using `dpLyr`.

step_relu(recipe, ..., shift = 0, reverse = FALSE, smooth = FALSE, prefix = "right_relu_") - Applies smoothed rectified linear transformation.

step_sqrt(recipe, ...) - Applies square root transformation.

BASIS FUNCTIONS

step_*(recipe, ..., keep_original_cols = FALSE)

step_spline_natural(deg_free = 10, options = NULL) - Creates a natural spline (a.k.a restricted cubic spline) features.

step_spline_b(deg_free = 10, degree = 3, options = NULL) - Creates b-spline features.

step_spline_convex(deg_free = 10, degree = 3, options = NULL)

step_spline_monotone(deg_free = 10, degree = 3, options = NULL)

step_spline_nonnegative(deg_free = 10, degree = 3, options = NULL)

step_poly(degree = 2L, options = list()) - Creates new columns that are basis expansions of variables using orthogonal polynomials.

step_poly_bernstein(degree = 10, options = NULL, results = NULL) - Creates Bernstein polynomial features.

NORMALIZATION

step_*(recipe, ...)

step_normalize(na_rm = TRUE) - Normalizes to have a standard deviation of 1 and mean of 0.

step_YeoJohnson() - Makes data look more like a normal distribution.

step_percentile(options = list(probs = (0:100)/100), outside = "none") - Replaces the value of a variable with its percentile from the training set.

step_range(min = 0, max = 1, clipping = TRUE) - Normalizes numeric data to be within a pre-defined range of values.

step_spatialsign(na_rm = TRUE) - Converts numeric data into a projection on to a unit sphere.

DISCRETIZE

step_*(recipe, ...)

step_discretize(num_breaks = 4, min_unique = 10, options = list(prefix = "bin")) - Converts numeric data into a factor with bins having approximately the same number of data points.

step_cut(breaks, include_outside_range = FALSE) - Cuts a numeric variable into a factor based on provided boundary values.

Imputation

step_*(recipe, ...)

step_impute_bag(impute_with = all_predictors(), trees = 25, options = list(keepX = FALSE)) - Creates a bagged tree model for data. Good for categorical data.

step_impute_knn(neighbors = 5, impute_with = all_predictors(), options = list(nthread = 1, eps = 1e-08)) - Uses Gower's distance which can be used for mixtures of nominal and numeric data.

step_impute_linear(impute_with = all_predictors()) - Creates linear regression models to impute missing data.

step_impute_lower(threshold = NULL) - Substitutes the truncated value by a random number between zero and the truncation point.

step_impute_mean(trim = 0) - Substitutes missing values of numeric variables by the training set mean of those variables.

step_impute_median() - Substitutes missing values of numeric variables by the training set median of those variables.

step_impute_mode() - Imputes nominal data using the most common value.

step_impute_roll(statistic = median, window = 5L) - Imputes numeric data using a rolling window statistic.

step_unknown(new_level = "unknown") - Assigns a missing value in a factor level to "unknown".

Encodings

step_*(recipe, ...)

TYPE CONVERTERS

step_factor2string() - Converts one or more factor vectors to strings.

step_string2factor() - Converts one or more character vectors to factors (ordered or unordered).

step_num2factor(transform = function(x) x) - Converts one or more numeric vectors to factors (ordered or unordered). This can be useful when categories are encoded as integers.

step_integer(strict = TRUE, zero_based = FALSE) - Converts data into a set of ascending integers based on the ascending order from the training data.

VALUE CONVERTERS

step_indicate_na(sparse = "auto", keep_original_cols = TRUE) - Creates and append additional binary columns to the data set to indicate which observations are missing.

step_ordinalscore(convert = as.numeric) - Converts ordinal factor variables into numeric scores.

step_unorder() - Turns ordered factor variables into unordered factor variables.

OTHER

step_relevel(ref_level) - Reorders factor columns so that the level specified by `ref_level` is first. This is useful for `contr.treatment()` contrasts which take the first level as the reference.

step_novel(new_level = "new") - Assigns a previously unseen factor level to "new".

step_other(threshold = 0.05, other = "other") - Pools infrequently occurring values into an "other" category.


Preprocessing data with *recipes* : : CHEAT SHEET



Dummy Variables

```
step_dummy*(recipe, ..., sparse = "auto",
keep_original_cols = FALSE)
```

 **step_dummy**(threshold = 0, other = "other",
naming = dummy_names, prefix = NULL) -
Standard dummy variable converter.

 **step_dummy_extract**(sep = NULL, pattern
= NULL, threshold = 0, other = "other") -
Converts multiple nominal data into one or
more numeric integer terms for the levels of
the original data.

 **step_dummy_multi_choice**(threshold = 0,
other = "other") - Converts multiple nominal
data into one or more numeric binary terms
for the levels of the original data.

CONVERT

 **step_bin2factor**(recipe, ..., levels = c("yes",
"no"), ref_first = TRUE) - Converts dummy
variable into 2-level factor.

TEXT

```
step_*(recipe, ..., pattern = "", options = list(), result =
make.names(pattern), sparse = "auto",
keep_original_cols = TRUE)
```

 **step_regex**(options = list()) - Creates a
dummy variable that detects the given
regular expression.

 **step_count**(normalize = FALSE) - Create
counts of patterns using regular expressions.

Date & Time

```
step_*(recipe, ..., keep_original_cols = TRUE)
```

 **step_date**(features = c("dow", "month",
"year"), abbr = TRUE, label = TRUE, ordinal =
FALSE, locale = clock::clock_locale()\$labels)
- Converts date data into one or more factor
or numeric variables (dow = day of week).


 **step_time**(features = c("hour", "minute",
"second")) - Converts date-time data into
one or more factor or numeric variables.

 **step_holiday**(holidays = c("LaborDay",
"NewYearsDay", "ChristmasDay"), sparse =
"auto") - Converts date data into binary
indicators variables for common holidays.

Multivariate Transformations

SIGNAL EXTRACTION

```
step_*(recipe, ..., keep_original_cols = FALSE)
```



step_pca(num_comp = 5, threshold = NA, options =
list()) - Converts numeric variables into one or more
principal components.

step_ica(num_comp = 5, options = list(method = "C"))
- Converts numeric data into one or more independent
components.

step_kpca_poly(num_comp = 5, degree = 2,
scale_factor = 1, offset = 1) - Converts numeric data
into principal components using a polynomial kernel
basis expansion.

step_kpca_rbf(num_comp = 5, sigma = 0.2) - Converts
numeric data into principal components using a radial
basis function kernel basis expansion.

step_isomap(num_terms = 5, neighbors = 50, options
= list(.mute = c("message", "output"))) - Uses
multidimensional scaling to convert numeric data into
new dimensions.

step_nnmf_sparse(num_comp = 2, penalty = 0.001,
options = list()) - Converts numeric data into non-
negative components.

step_pls(num_comp = 2, predictor_prop = 1, outcome
= NULL, options = list(scale = TRUE), preserve =
deprecated(), prefix = "PLS") - Converts numeric data
into one or more new dimensions.

CENTROIDS

```
step_*(recipe, ..., keep_original_cols = FALSE)
```



step_classdist(class, mean_func = mean, cov_func =
cov, pool = FALSE, log = TRUE, prefix = "classdist") -
Converts numeric data into *Mahalanobis* distance
measurements to the data centroid.

step_classdist_shrunken(class = NULL, threshold =
1/2, sd_offset = 1/2, log = TRUE, prefix = "classdist") -
Converts numeric data into *Euclidean* distance to the
regularized class centroid.

step_depth(class, metric = "halfspace", options =
list(), data = NULL, prefix = "depth") - Converts
numeric data into a measurement of data depth by
category

OTHER



step_geodist(recipe, lat = NULL, lon = NULL,
ref_lat = NULL, ref_lon = NULL, is_lat_lon =
TRUE, log = FALSE, name = "geo_dist",
keep_original_cols = TRUE) - Calculates the
distance between points on a map to a
reference location.



step_ratio(recipe, ..., denom =
denom_vars(), naming = function(number,
denom) {make.names(paste(number, denom,
sep = "_o_"))}, keep_original_cols = TRUE) -
Creates ratios from selected numeric
variables (denom).

Row operations

```
step_*(recipe, ...)
```



step_naomit() - Removes observations if
they contain NA or NaN values.



step_sample(size = NULL, replace = FALSE)
- Samples rows using `dplyr::sample_n()`
or `dplyr::sample_frac()`.



step_shuffle() - Randomly changes the
order of rows for selected variables.



step_slice() - Filters rows using
`dplyr::slice()`.

Other



step_interact(recipe, terms, sep = "_x_",
keep_original_cols = TRUE) - Creates new
columns that are interaction terms between
two or more variables.



step_rename(recipe, ...) - Adds variables
using `dplyr::rename()`.



step_window(recipe, ..., size = 3, na_rm =
TRUE, statistic = "mean", keep_original_cols
= TRUE) - Creates new columns that are the
results of functions that compute statistics
across moving windows.

Role & type

SELECTORS

all_outcomes() / **all_predictors()** - Select variables
from formula based on the most common two roles.

has_role(match = "predictor") - Select by passing the
role name required.

has_type(match = "numeric") - Select by type of
variable.

CONVENIENCE SELECTORS

all_string_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_logical_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_numeric_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_integer_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_double_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_factor_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_ordered_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_unordered_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_nominal_predictors() 1.1 3L A ☒ ☐ ☐ ☐

all_date_predictors() / **all_datetime_predictors()**

ROLE MANAGEMENT

*In case a variable is not a outcome or predictor but needs to be
retained. Create new role, and set it to not 'bake'.*

```
rec <- recipe(x ~ ., data = train_data) |>
  update_role(my_id, new_role = "id") |>
  update_role_requirements(rec, "id", bake = FALSE)
```

add_role(recipe, ..., new_role = "predictor", new_type
= NULL) - Adds an additional role to variables that
already have a role in the recipe.

update_role(recipe, ..., new_role = "predictor",
old_role = NULL) - Alters an existing role in the recipe
or assigns an initial role to variables that do not yet
have a declared role.

remove_role(recipe, ..., old_role) - Eliminates a single
existing role in the recipe.

update_role_requirements(recipe, ..., bake = NULL) -
Allows for fine tunes requirements of the various roles
you might come across in recipes.