

create.R — usethis

0%

New

Open

<

>

Search

R 4.4.2

usethis

EXPLORER

OPEN EDITORS

create.R R

USETHIS

> .github

> .Rproj.user

> .vscode

> docs

> inst

> man

> pkgdown

R

addin.R

air.R

author.R

badge.R

block.R

browse.R

ci.R

citation.R

code-of-conduct.R

course.R

coverage.R

cpp11.R

cran.R

create.R

data-table.R

data.R

description.R

directory.R

OUTLINE

TIMELINE

create.R

R > create.R > ...

1 #' Create a package or project

2 #'

3 #' @description

4 #' These functions create an R project:

5 #' * `create\_package()` creates an R package

6 #' * `create\_project()` creates a non-package project, i.e. a data analysis

7 #' project

8 #'

9 #' Both functions can be called on an existing project; you will be asked before

10 #' any existing files are changed.

11 #'

12 #' @inheritParams use_description

13 #' @param fields A named list of fields to add to `DESCRIPTION`, potentially

14 #' overriding default values. See [use_description()] for how you can set

15 #' personalized defaults using package options.

16 #' @param path A path. If it exists, it is used. If it does not exist, it is

17 #' created, provided that the parent path exists.

18 #' @param roxygen Do you plan to use roxygen2 to document your package?

19 #' @param rstudio If `TRUE`, calls [use_rstudio()] to make the new package or

20 #' project into an [RStudio

21 #' Project](https://r-pkgs.org/workflow101.html#sec-workflow101-rstudio-projects).

22 #' If `FALSE` and a non-package project, a sentinel `.here` file is placed so

23 #' that the directory can be recognized as a project by the

24 #' [here](https://here.r-lib.org) or

CONSOLE

TERMINAL

PROBLEMS

TEST RESULTS

OUTPUT

PORTS

~/rrr/usethis

>

SESSION

VARIABLES

R 4.4.2

filter

No variables have been created.

PLOTS

+

+

+

+

+

R 4.4.2

R 4.5.0

R 4.5.0

R 4.3.3

main

0

1

0

0

usethis

Quarto: 1.7.31

Ln 1, Col 1

Spaces: 2

UTF-8

LF

R

Your Turn

**Start a session with the
interpreter you want to
work with today**