

New

Open

EXPLORER

OPEN EDITORS

USETHIS

R

OUTLINE

TIMELINE

create.R

create.R

addin.R

air.R

author.R

badge.R

block.R

browse.R

ci.R

citation.R

code-of-conduct.R

course.R

coverage.R

cpp11.R

cran.R

create.R

data-table.R

data.R

description.R

directory.R

create.R

1 #' Create a package or project

2 #'

3 #' @description

4 #' These functions create an R project:

5 #' * `create\_package()` creates an R package

6 #' * `create\_project()` creates a non-package project, i.e. a data analysis

7 #' project

8 #'

9 #' Both functions can be called on an existing project; you will be asked before

10 #' any existing files are changed.

11 #'

12 #' @inheritParams use_description

13 #' @param fields A named list of fields to add to `DESCRIPTION`, potentially

CONSOLE

TERMINAL

PROBLEMS

OUTPUT

PORTS

DEBUG CONSOLE

~/rrr/usethis

R is free software and comes with ABSOLUTELY NO WARRANTY.
You are welcome to redistribute it under certain conditions.
Type 'license()' or 'licence()' for distribution details.

Natural language support but running in an English locale

R is a collaborative project with many contributors.
Type 'contributors()' for more information and
'citation()' on how to cite R or R packages in publications.

Type 'demo()' for some demos, 'help()' for on-line help, or
'help.start()' for an HTML browser interface to help.
Type 'q()' to quit R.

> devtools::load_all()
i Loading usethis
>

main*

usethis

Quarto: 1.7.31

R 4.4.2

usethis

SESSION

HELP

Ln 1, Col 1

Spaces: 2

UTF-8

LF

R

Select Interpreter Session

R 4.4.2 Currently Selected
/Library/Frameworks/R.framework/Versions/4.4-arm64/Resource...

New Interpreter Session...

New

Open

EXPLORER

OPEN EDITORS

create.R R

USETHIS

.github

.Rproj.user

.vscode

docs

inst

man

pkgdown

R

addin.R

air.R

author.R

badge.R

block.R

browse.R

ci.R

citation.R

code-of-conduct.R

course.R

coverage.R

cpp11.R

cran.R

create.R

data-table.R

data.R

description.R

directory.R

OUTLINE

TIMELINE

create.R

R >

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

#' overriding default values. See [use_description()] for how you can set

#' personalized defaults using package options.

#' @param path A path. If it exists, it is used. If it does not exist, it is

#' created, provided that the parent path exists.

#' @param roxygen Do you plan to use roxygen2 to document your package?

#' @param rstudio If `TRUE`, calls [use_rstudio()] to make the new package or

#' project into an [RStudio

#' Project](https://r-pkgs.org/workflow101.html#sec-workflow101-rstudio-projects).

#' If `FALSE` and a non-package project, a sentinel `.here` file is placed so

#' that the directory can be recognized as a project by the

#' [here](https://here.r-lib.org) or

CONSOLE

TERMINAL

PROBLEMS

TEST RESULTS

OUTPUT

PORTS

...

~/rrr/usethis

>

Start New Interpreter Session

Python 3.11.11 (Pyenv)

~/.pyenv/versions/3.11.11/bin/python

Pyenv

Python 3.10.16 (Pyenv)

~/.pyenv/versions/3.10.16/bin/python

Pyenv

Python 3.13.3 (Global)

/opt/homebrew/bin/python3

Global

Python 3.9.6 (Global)

/usr/bin/python3

Global

R 4.4.2

/Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/bin/R

System

R 4.5.0

/Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/bin/R

System

R 4.3.3

/Library/Frameworks/R.framework/Versions/4.3-arm64/Resources/bin/R

System

R 4.4.2

usethis

SESSION

VARIABLES

R 4.4.2

filter

No variables have been created.

PLOTS

main

0↓ 1↑

0 0

usethis

Quarto: 1.7.31

Ln 1, Col 1

Spaces: 2

UTF-8

LF

R