

Studio Projects vs. Positr??s

- RStudio places an `.Rproj` file in a folder to designate it as an RStudio Project.
- Used for storing project-level preferences, launching projects, and for identifying the project root (e.g., for `here::here()`).

- Positron doesn't place anything that functions exactly like an Rproj file in every folder.
- Unless you set workspace-level preferences, which prompts the creation of a `.vscode/settings.json` file that stores these preferences.
- Note: In Positron, `here::here()` will find the folder root, typically through finding a `.git` folder.



2

2

RStudio Projects vs. Positron ???s

- RStudio places an `.Rproj` file in a folder to designate it as an RStudio Project.
- Used for storing project-level preferences, launching projects, and for identifying the project root (e.g., for `here::here()`).
- Positron doesn't place anything that functions exactly like an Rproj file in every folder.
- Unless you set workspace-level preferences, which prompts the creation of a `.vscode/settings.json` file that stores these preferences.
- Note: In Positron, `here::here()` will find the folder root, typically through finding a `.git` folder.



Positron and the `.Rproj` file

- Positron doesn't do anything with the contents of an `.Rproj` file.
- For example, your `.Rproj` file might indicate preferences like using spaces for tabs (`UseSpacesForTab: Yes`) or using line breaks after each sentence in Quarto or R Markdown files (`MarkdownWrap: Sentence`).
- We'll discuss expressing some of these as Positron settings in a later module.
- For Quarto projects, some might be best set in `_quarto.yml`.

r4ds.Rproj	
Version:	1.0
RestoreWorkspace:	Default
SaveWorkspace:	Default
AlwaysSaveHistory:	Default
EnableCodeIndexing:	Yes
UseSpacesForTab:	Yes
NumSpacesForTab:	2
Encoding:	UTF-8
RnwWeave:	Sweave
LaTeX:	XeLaTeX
StripTrailingWhitespace:	Yes
BuildType:	None
UseNativePipeOperator:	Yes
MarkdownWrap:	Sentence
MarkdownCanonical:	Yes
SpellingDictionary:	en_US