

New

Open

EXPLORER

OPEN EDITORS

create.R R

USETHIS

.github

.Rproj.user

.vscode

docs

inst

man

pkgdown

R

addin.R

air.R

author.R

badge.R

block.R

browse.R

ci.R

citation.R

code-of-conduct.R

course.R

coverage.R

cpp11.R

cran.R

create.R

data-table.R

data.R

description.R

directory.R

OUTLINE

TIMELINE

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

Python 3.11.11 (Pyenv)

~/pyenv/versions/3.11.11/bin/python

Python 3.10.16 (Pyenv)

~/pyenv/versions/3.10.16/bin/python

Python 3.13.3 (Global)

/opt/homebrew/bin/python3

Python 3.9.6 (Global)

/usr/bin/python3

R 4.4.2

/Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/bin/R

R 4.5.0

/Library/Frameworks/R.framework/Versions/4.5-arm64/Resources/bin/R

R 4.3.3

/Library/Frameworks/R.framework/Versions/4.3-arm64/Resources/bin/R

Pyenv

Global

System

#' overriding default values. See [use_description()] for how you can set

#' personalized defaults using package options.

#' @param path A path. If it exists, it is used. If it does not exist, it is

#' created, provided that the parent path exists.

#' @param roxygen Do you plan to use roxygen2 to document your package?

#' @param rstudio If `TRUE`, calls [use_rstudio()] to make the new package or

#' project into an [RStudio

#' Project](https://r-pkgs.org/workflow101.html#sec-workflow101-rstudio-projects).

#' If `FALSE` and a non-package project, a sentinel `.here` file is placed so

#' that the directory can be recognized as a project by the

#' [here](https://here.r-lib.org) or

CONSOLE

TERMINAL

PROBLEMS

TEST RESULTS

OUTPUT

PORTS

~/rrr/usethis

R 4.4.2

usethis

SESSION

VARIABLES

R 4.4.2

filter

No variables have been created.

PLOTS

main

0

1

0

0

usethis

Quarto: 1.7.31

Ln 1, Col 1

Spaces: 2

UTF-8

LF

R

create.R — usethis

New

Open

<

>

Search

R 4.4.2

usethis

EXPLORER

OPEN EDITORS

create.R R

USETHIS

.github

.Rproj.user

.vscode

docs

inst

man

pkgdown

R

addin.R

air.R

author.R

badge.R

block.R

browse.R

ci.R

citation.R

code-of-conduct.R

course.R

coverage.R

cpp11.R

cran.R

create.R

data-table.R

data.R

description.R

directory.R

OUTLINE

TIMELINE

create.R

R > create.R > ...

1 #' Create a package or project

2 #'

3 #' @description

4 #' These functions create an R project:

5 #' * `create\_package()` creates an R package

6 #' * `create\_project()` creates a non-package project, i.e. a data analysis

7 #' project

8 #'

9 #' Both functions can be called on an existing project; you will be asked before

10 #' any existing files are changed.

11 #'

12 #' @inheritParams use_description

13 #' @param fields A named list of fields to add to `DESCRIPTION`, potentially

14 #' overriding default values. See [use_description()] for how you can set

15 #' personalized defaults using package options.

16 #' @param path A path. If it exists, it is used. If it does not exist, it is

17 #' created, provided that the parent path exists.

18 #' @param roxygen Do you plan to use roxygen2 to document your package?

19 #' @param rstudio If `TRUE`, calls [use_rstudio()] to make the new package or

20 #' project into an [RStudio

21 #' Project](https://r-pkgs.org/workflow101.html#sec-workflow101-rstudio-projects).

22 #' If `FALSE` and a non-package project, a sentinel `.here` file is placed so

23 #' that the directory can be recognized as a project by the

24 #' [here](https://here.r-lib.org) or

CONSOLE

TERMINAL

PROBLEMS

TEST RESULTS

OUTPUT

PORTS

...

~/rrr/usethis

>

SESSION

VARIABLES

R 4.4.2

filter

No variables have been created.

PLOTS

+

-

×

□

R 4.4.2

R 4.5.0

R 4.5.0

R 4.3.3

main

0 ↓ 1 ↑

0 0

usethis

Quarto: 1.7.31

Ln 1, Col 1

Spaces: 2

UTF-8

LF

R