

# VIP Validation Report

**Deployment:** CI Connect 2026.08.1 + WB 2026.08.2+200.pro1 + PM 2026.08.0  
**Generated:** 2026-09-08 16:44:34 UTC

## Products Under Test

| Product         | URL                   | Version            | Results                       |
|-----------------|-----------------------|--------------------|-------------------------------|
| Connect         | http://localhost:3939 | 2026.08.1          | 7 passed, 2 skipped (9 tests) |
| Workbench       | http://localhost:8787 | 2026.08.2+200.pro1 | 2 passed (2 tests)            |
| Package Manager | http://localhost:4242 | 2026.08.0          | 2 passed, 3 skipped (5 tests) |

## Summary

|         |      |
|---------|------|
| Total   | 25   |
| Passed  | 19   |
| Failed  | 1    |
| Skipped | 5    |
| Status  | FAIL |

## Provenance

|              |                                                   |
|--------------|---------------------------------------------------|
| VIP version  | 2026.9.0                                          |
| Run duration | 52.2s                                             |
| Python       | 3.14.7                                            |
| Platform     | Linux-6.17.0-1022-azure-x86_64-with-glibc2.39     |
| Mode         | full                                              |
| Exit status  | 1 (tests were collected and run, but some failed) |

## Failures & Skips

Every check that did not pass, in full. Passing checks are counted above, and every check appears in Detailed Results below.

### Failed (1)

**FAIL**

**This check intentionally fails to demonstrate failure rendering**

Prerequisites

*As someone evaluating a VIP report*  
src/vip\_tests/prerequisites/test\_expected\_failure.py::test\_intentional\_failure 0.00s

**Test procedure**

- > Given a check that is written to fail on purpose
- > When the check runs as part of this example report
- > Then it fails by design, not because anything is actually broken

**test\_intentional\_failure: This failure is intentional: it exists only to show how a failed check renders in this example report.**  
**No product configuration will resolve it.**  
**assert 'fail (by design)' == 'pass'**  
**- pass**  
**+ fail (by design)**

```

fixturefunc = <function check_fails_by_design at 0x7efef5234bf0>
request = <FixtureRequest for <Function test_intentional_failure>>
kwargs = {'demo_outcome': {'expected': 'pass', 'actual': 'fail (by design)'}}

def call_fixture_func(
    fixturefunc: _FixtureFunc[FixtureValue], request: FixtureRequest, kwargs
) -> FixtureValue:
    if inspect.isgeneratorfunction(fixturefunc):
        fixturefunc = cast(Callable[..., Generator[FixtureValue]], fixturefunc)
        generator = fixturefunc(**kwargs)
        try:
            fixture_result = next(generator)
        except StopIteration:
            raise ValueError(f"{request.fixturename} did not yield a value") from None
        finalizer = functools.partial(_teardown_yield_fixture, fixturefunc, generator)
        request.addfinalizer(finalizer)
    else:
        fixturefunc = cast(Callable[..., FixtureValue], fixturefunc)
    > fixture_result = fixturefunc(**kwargs)
        ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^

.venv/lib/python3.14/site-packages/_pytest/fixtures.py:1005:
-----
demo_outcome = {'expected': 'pass', 'actual': 'fail (by design)'

    @then("it fails by design, not because anything is actually broken")
    def check_fails_by_design(demo_outcome):
    >     assert demo_outcome["actual"] == demo_outcome["expected"], (
        "This failure is intentional: it exists only to show how a failed check "
        "renders in this example report. No product configuration will resolve it."
    )
E       AssertionError: This failure is intentional: it exists only to show how a failed check
renders in this example report. No product configuration will resolve it.
E       assert 'fail (by design)' == 'pass'
E
E       - pass
E       + fail (by design)

src/vip_tests/prerequisites/test_expected_failure.py:49: AssertionError

```

#### Likely causes:

- This check is designed to always fail, so the example report has a failure card to show
- No product or configuration problem is involved

#### Suggested next steps:

1. No action needed. This failure is intentional and does not indicate a real problem
2. It only runs when VIP\_ENABLE\_EXPECTED\_FAILURE\_DEMO=1 is set

**Documentation:** <https://github.com/posit-dev/vip/issues/73>

## Skipped (5)

### SKIP Expected R versions are available on Connect Connect

No expected R versions specified in vip.toml [runtimes]

src/vip\_tests/connect/test\_runtime\_versions.py::test\_r\_versions 0.16s

#### Test procedure

- > Given Connect is accessible at the configured URL
- > And expected R versions are specified in vip.toml
- > When I query Connect for available R versions
- > Then all expected R versions are present

### SKIP Expected Python versions are available on Connect Connect

No expected Python versions specified in vip.toml [runtimes]

src/vip\_tests/connect/test\_runtime\_versions.py::test\_python\_versions 0.16s

#### Test procedure

- › Given Connect is accessible at the configured URL
- › And expected Python versions are specified in vip.toml
- › When I query Connect for available Python versions
- › Then all expected Python versions are present

**SKIP** PyPI mirror is accessible **Package Manager**

PyPI package 'requests' not available in any of ['pypi-all'] — repo may not be synced yet

src/vip\_tests/package\_manager/test\_repos.py::test\_pypi\_mirror 0.03s

**Test procedure**

- › Given Package Manager is running
- › When I query the PyPI repository for the "requests" package
- › Then the package is found in the repository

**SKIP** Bioconductor mirror is accessible **Package Manager**

No Bioconductor repository configured in Package Manager

src/vip\_tests/package\_manager/test\_repos.py::test\_bioconductor\_mirror 0.02s

**Test procedure**

- › Given Package Manager is running
- › When I query the Bioconductor repository for the "BiocGenerics" package
- › Then the package is found in the repository

**SKIP** OpenVSX mirror is accessible **Package Manager**

No OpenVSX repository configured in Package Manager

src/vip\_tests/package\_manager/test\_repos.py::test\_opensvx\_mirror 0.02s

**Test procedure**

- › Given Package Manager is running
- › When I query the OpenVSX repository for the "golang.Go" extension
- › Then the package is found in the repository

## Detailed Results

### Connect

9 tests — 7 passed, 2 skipped

**PASS** User can log in via the web UI **Connect**

src/vip\_tests/connect/test\_auth.py::test\_connect\_login\_ui 2.47s

**Test procedure**

- › Given Connect is accessible at the configured URL
- › When a user navigates to the Connect login page
- › And enters valid credentials
- › Then the user is successfully authenticated
- › And the Connect dashboard is displayed

**PASS** API key authentication works **Connect**

src/vip\_tests/connect/test\_auth.py::test\_connect\_login\_api 0.31s

**Test procedure**

- › Given Connect is accessible at the configured URL
- › And a valid API key is configured
- › When I request the current user via the API
- › Then the API returns user information

**PASS** Admin user exists and has admin privileges **Connect**

src/vip\_tests/connect/test\_users.py::test\_admin\_user 0.31s

**Test procedure**

- › Given Connect is accessible at the configured URL
- › When I retrieve the current user profile
- › Then the user has admin privileges

**PASS** Users can be listed **Connect**

src/vip\_tests/connect/test\_users.py::test\_list\_users 0.31s

**Test procedure**

- › Given Connect is accessible at the configured URL
- › When I list all users
- › Then the user list is not empty
- › And the test user exists in the user list

**PASS** Groups can be listed **Connect**

src/vip\_tests/connect/test\_users.py::test\_list\_groups 0.31s

**Test procedure**

- › Given Connect is accessible at the configured URL
- › When I list all groups
- › Then the response is successful

**SKIP** Expected R versions are available on Connect **Connect**

No expected R versions specified in vip.toml [runtimes]

src/vip\_tests/connect/test\_runtime\_versions.py::test\_r\_versions 0.16s

**Test procedure**

- › Given Connect is accessible at the configured URL
- › And expected R versions are specified in vip.toml
- › When I query Connect for available R versions
- › Then all expected R versions are present

**SKIP** Expected Python versions are available on Connect **Connect**

No expected Python versions specified in vip.toml [runtimes]

src/vip\_tests/connect/test\_runtime\_versions.py::test\_python\_versions 0.16s

**Test procedure**

- › Given Connect is accessible at the configured URL
- › And expected Python versions are specified in vip.toml
- › When I query Connect for available Python versions
- › Then all expected Python versions are present

**PASS** Expected Quarto versions are available **Connect**

```
src/vip_tests/connect/test_runtime_versions.py::test_quarto_versions 0.31s
```

#### Test procedure

- › Given Connect is accessible at the configured URL
- › When I query Connect for available Quarto versions
- › Then at least one Quarto version is available

**PASS** Connect system checks can be run and the report downloaded **Connect**

```
src/vip_tests/connect/test_system_checks.py::test_connect_system_checks 25.94s
```

#### Test procedure

- › Given Connect is accessible at the configured URL
- › And a valid API key is configured
- › When I trigger a new system check run via the Connect API
- › Then the system check report is returned
- › And I can download the system check report artifact

## Package Manager

5 tests — 2 passed, 3 skipped

**SKIP** PyPI mirror is accessible **Package Manager**

PyPI package 'requests' not available in any of ['pypi-all'] — repo may not be synced yet

```
src/vip_tests/package_manager/test_repos.py::test_pypi_mirror 0.03s
```

#### Test procedure

- › Given Package Manager is running
- › When I query the PyPI repository for the "requests" package
- › Then the package is found in the repository

**SKIP** Bioconductor mirror is accessible **Package Manager**

No Bioconductor repository configured in Package Manager

```
src/vip_tests/package_manager/test_repos.py::test_bioconductor_mirror 0.02s
```

#### Test procedure

- › Given Package Manager is running
- › When I query the Bioconductor repository for the "BiocGenerics" package
- › Then the package is found in the repository

**SKIP** OpenVSX mirror is accessible **Package Manager**

No OpenVSX repository configured in Package Manager

```
src/vip_tests/package_manager/test_repos.py::test_opensvx_mirror 0.02s
```

#### Test procedure

- › Given Package Manager is running
- › When I query the OpenVSX repository for the "golang.Go" extension
- › Then the package is found in the repository

**PASS** At least one repository is configured **Package Manager**

```
src/vip_tests/package_manager/test_repos.py::test_repo_exists 0.03s
```

#### Test procedure

- › Given Package Manager is running
- › When I list all repositories
- › Then at least one repository exists

**PASS** CRAN mirror is accessible **Package Manager**

```
src/vip_tests/package_manager/test_repos.py::test_cran_mirror 0.84s
```

#### Test procedure

- › Given Package Manager is running
- › When I query the CRAN repository for the "Matrix" package
- › Then the package is found in the repository

## Prerequisites

6 tests — 5 passed, 1 failed

### **PASS** Workbench server is reachable **Prerequisites**

src/vip\_tests/prerequisites/test\_components.py::test\_product\_server\_is\_reachable[Workbench]  
0.11s

#### Test procedure

- > Given <product> is configured in vip.toml
- > When I request the <product> health endpoint
- > Then the server responds with a successful status code

### **PASS** Package Manager server is reachable **Prerequisites**

src/vip\_tests/prerequisites/test\_components.py::test\_product\_server\_is\_reachable[Package  
Manager] 0.03s

#### Test procedure

- > Given <product> is configured in vip.toml
- > When I request the <product> health endpoint
- > Then the server responds with a successful status code

### **FAIL** This check intentionally fails to demonstrate failure rendering **Prerequisites**

*As someone evaluating a VIP report*

src/vip\_tests/prerequisites/test\_expected\_failure.py::test\_intentional\_failure 0.00s

#### Test procedure

- > Given a check that is written to fail on purpose
- > When the check runs as part of this example report
- > Then it fails by design, not because anything is actually broken

**test\_intentional\_failure: This failure is intentional: it exists only to show how a failed check renders in this example report.**

**No product configuration will resolve it.**

**assert 'fail (by design)' == 'pass'**

**- pass**

**+ fail (by design)**

```
fixturefunc = <function check_fails_by_design at 0x7efef5234bf0>
request = <FixtureRequest for <Function test_intentional_failure>>
kwargs = {'demo_outcome': {'expected': 'pass', 'actual': 'fail (by design)'}}

def call_fixture_func(
    fixturefunc: _FixtureFunc[FixtureValue], request: FixtureRequest, kwargs
) -> FixtureValue:
    if inspect.isgeneratorfunction(fixturefunc):
        fixturefunc = cast(Callable[..., Generator[FixtureValue]], fixturefunc)
        generator = fixturefunc(**kwargs)
        try:
            fixture_result = next(generator)
        except StopIteration:
            raise ValueError(f"{request.fixturename} did not yield a value") from None
        finalizer = functools.partial(_teardown_yield_fixture, fixturefunc, generator)
        request.addfinalizer(finalizer)
    else:
        fixturefunc = cast(Callable[..., FixtureValue], fixturefunc)
    > fixture_result = fixturefunc(**kwargs)
        AAAAAAAAAAAAAAAAAAAAAAAAAA

.venv/lib/python3.14/site-packages/_pytest/fixtures.py:1005:
-----
demo_outcome = {'expected': 'pass', 'actual': 'fail (by design)'

    @then("it fails by design, not because anything is actually broken")
    def check_fails_by_design(demo_outcome):
    >     assert demo_outcome["actual"] == demo_outcome["expected"], (
        "This failure is intentional: it exists only to show how a failed check "
        "renders in this example report. No product configuration will resolve it."
    )
E     AssertionError: This failure is intentional: it exists only to show how a failed check
renders in this example report. No product configuration will resolve it.
E     assert 'fail (by design)' == 'pass'
```

```
E
E      - pass
E      + fail (by design)
```

```
src/vip_tests/prerequisites/test_expected_failure.py:49: AssertionError
```

#### Likely causes:

- This check is designed to always fail, so the example report has a failure card to show
- No product or configuration problem is involved

#### Suggested next steps:

1. No action needed. This failure is intentional and does not indicate a real problem
2. It only runs when VIP\_ENABLE\_EXPECTED\_FAILURE\_DEMO=1 is set

**Documentation:** <https://github.com/posit-dev/vip/issues/73>

#### PASS Connect version matches configuration Prerequisites

```
src/vip_tests/prerequisites/test_versions.py::test_connect_version 0.16s
```

##### Test procedure

- › Given Connect is configured in vip.toml with a version expectation
- › When I fetch the Connect server version
- › Then the Connect version matches the configured value

#### PASS Package Manager version matches configuration Prerequisites

```
src/vip_tests/prerequisites/test_versions.py::test_package_manager_version 0.03s
```

##### Test procedure

- › Given Package Manager is configured in vip.toml with a version expectation
- › When I fetch the Package Manager server version
- › Then the Package Manager version matches the configured value

#### PASS Connect server is reachable Prerequisites

```
src/vip_tests/prerequisites/test_components.py::test_product_server_is_reachable[Connect] 0.01s
```

##### Test procedure

- › Given <product> is configured in vip.toml
- › When I request the <product> health endpoint
- › Then the server responds with a successful status code

## Security

3 tests — 3 passed

#### PASS Unauthenticated API request returns 401 Security

```
src/vip_tests/security/test_error_handling.py::test_unauthenticated_api_request_returns_401 0.01s
```

##### Test procedure

- › Given Connect is configured in vip.toml
- › When I make an unauthenticated API request to Connect
- › Then the response status is 401

#### PASS Invalid API key returns 401 Security

```
src/vip_tests/security/test_error_handling.py::test_invalid_api_key_returns_401 4.68s
```

##### Test procedure

- › Given Connect is configured in vip.toml
- › When I make an API request to Connect with an invalid key
- › Then the response status is 401

#### PASS Non-existent endpoint returns 404 Security

```
src/vip_tests/security/test_error_handling.py::test_nonexistent_endpoint_returns_404 0.01s
```

##### Test procedure

- › Given Connect is configured in vip.toml
- › When I request a non-existent endpoint on Connect
- › Then the response status is 404

## Workbench

2 tests — 2 passed

### **PASS** User can sign out of Workbench **Workbench**

src/vip\_tests/workbench/test\_auth.py::test\_workbench\_signout[chromium] 0.77s

#### Test procedure

- › Given Workbench is accessible and I am logged in
- › When I sign out of Workbench
- › Then I am redirected to the Workbench login page

### **PASS** User can log in to Workbench via the web UI **Workbench**

src/vip\_tests/workbench/test\_auth.py::test\_workbench\_login[chromium] 5.00s

#### Test procedure

- › Given Workbench is accessible at the configured URL
- › When a user navigates to the Workbench login page and enters valid credentials
- › Then the Workbench homepage is displayed
- › And the current user element is visible and non-empty in the header