

Lokum “Lunderquist” Guide Wire



- “Lunderquist” Extra Stiff Guide Wire Where High Stability Is Needed
- High PTFE Coating Performance
- Extra Steerable And Pushable For Increased Control



Lokum
Lunderquist Guide Wire

- The LOKUM Lunderquist Guide Wire is especially designed for extra strong support and high pushability in difficult procedures.
- The high performance PTFE coating combined with extra stiff stainless steel LOKUM Lunderquist is an excellent choice to treat difficult vascular and non-vascular lesions.
- The Lokum Lunderquist Type guide wire is intended to use for complex diagnostic and interventional procedures where increased stability, and low surface friction of the guidewire is needed.

Technical Information:

Guide Wire Material:	Extra Tempered Stainless Steel
Coating:	PTFE
Diameter:	0.035" / 0.89 mm
Distal Tip:	Straight / 3mm J-Tip / 6mm J-Tip
Tip Configuration:	5 cm / 10cm / 15cm Flexible Tip
Shaft Length:	150cm / 180cm / 260 cm

* a choice of various sizes will assist your patient's needs.

LOKUM "Lunderquist" Order Codes (5 per Box)				
0.035" / 0.89mm Tip / Shaft Length	Straight Tip	3mm J-Tip	6mm J-Tip	
5 cm / 150 cm	LOLU-05-150-ST	LOLU-05-150-3T	LOLU-05-150-6T	
5 cm / 180 cm	LOLU-05-180-ST	LOLU-05-180-3T	LOLU-05-180-6T	
5 cm / 260 cm	LOLU-05-260-ST	LOLU-05-260-3T	LOLU-05-260-6T	
10 cm / 150 cm	LOLU-10-150-ST	LOLU-10-150-3T	LOLU-10-150-6T	
10 cm / 180 cm	LOLU-10-180-ST	LOLU-10-180-3T	LOLU-10-180-6T	
10 cm / 260 cm	LOLU-10-260-ST	LOLU-10-260-3T	LOLU-10-260-6T	
15 cm / 150 cm	LOLU-15-150-ST	LOLU-15-150-3T	LOLU-15-150-6T	
15 cm / 180 cm	LOLU-15-180-ST	LOLU-15-180-3T	LOLU-15-180-6T	
15 cm / 260 cm	LOLU-15-260-ST	LOLU-15-260-3T	LOLU-15-260-6T	



Andratec 
Advanced Interventional Technologies

AndraTec GmbH
Simmernerstr. 70
D-56075 Koblenz
Tel: +49 261 29675 172
Fax: +49 261 29675 173
www.andratec.com

Revision 1 28.05.2014