Introduction

This analysis focuses on applying logistic regression to develop a classifier that determines whether an online shopping session results in a purchase, using the Online Shoppers Purchasing Intention dataset from the UCI Machine Learning Repository. This dataset, from the year 2018, consists of 12,330 records over approximately 18 variables, with Revenue as the target response variable.

The primary objective is to develop a classifier by identifying critical behavioral and contextual variables that can be leveraged to predict whether a user session will generate revenue. With the complexity of online consumer behavior and the multitude of factors influencing purchase decisions (such as browsing patterns, visitor characteristics, and temporal factors), the results of this analysis are intended to provide evidence-based insights for e-commerce optimization rather than a definitive predictive model.

Problem Statements

1. What are the key behavioural characteristics associated with revenue-generating sessions?
2. How strongly do conversion rates differ across categorical groups such as VisitorType, Weekend, and Month?
3. Can we build a reliable model to predict purchase conversion in e-commerce sessions?
4. How reliable is our model in classifying sessions as revenue-generating or non-revenue-generating?
5. Is there a relationship between the month of the year and whether an online shopping session generates revenue?

Analysis

Task 1: Exploratory Data Analysis

This task provides a comprehensive statistical overview of the online shopping session data. This serves as the foundation for understanding the distribution, scale, and variability of numerical variables, to identify patterns and trends that justify subsequent logistic regression analysis.

```r
# Task 1: Descriptive statistics ----
# Select numerical variables and compute descriptive statistics
desc_stats <- dataset1 %>%
  select_if(is.numeric) %>%
  psych::describe() %>%
  select(n, mean, sd, median, min, max, range, skew, kurtosis)

desc_stats %>%
  knitr::kable(
    align = "c",
    caption = "Descriptive Statistics for Numerical Variables",
    digits = 2
  ) %>%
  kableExtra::kable_classic_2(
    html_font = "Calibri",
    position = "center",
    font_size = 12
  ) %>%
  kableExtra::row_spec(0, bold = TRUE, background = "#E8F4F8")

```

Observation of Results

Descriptive Statistics for Numerical Variables

	n	mean	sd	median	min	max	range	skew	kurtosis
Administrative	12330	2.32	3.32	1.00	0	27.00	27.00	1.96	4.70
Administrative_Duration	12330	80.82	176.78	7.50	0	3398.75	3398.75	5.61	50.53
Informational	12330	0.50	1.27	0.00	0	24.00	24.00	4.04	26.92
Informational_Duration	12330	34.47	140.75	0.00	0	2549.38	2549.38	7.58	76.27
ProductRelated	12330	31.73	44.48	18.00	0	705.00	705.00	4.34	31.19
ProductRelated_Duration	12330	1194.75	1913.67	598.94	0	63973.52	63973.52	7.26	137.10
BounceRates	12330	0.02	0.05	0.00	0	0.20	0.20	2.95	7.72
ExitRates	12330	0.04	0.05	0.03	0	0.20	0.20	2.15	4.01
PageValues	12330	5.89	18.57	0.00	0	361.76	361.76	6.38	65.60
SpecialDay	12330	0.06	0.20	0.00	0	1.00	1.00	3.30	9.91
OperatingSystems	12330	2.12	0.91	2.00	1	8.00	7.00	2.07	10.45
Browser	12330	2.36	1.72	2.00	1	13.00	12.00	3.24	12.74
Region	12330	3.15	2.40	3.00	1	9.00	8.00	0.98	-0.15
TrafficType	12330	4.07	4.03	2.00	1	20.00	19.00	1.96	3.48

The Online Shoppers dataset is complete with no missing values and contains 12,330 observations collected over 18 variables, with Revenue as the binary response variable. There is relatively larger spread and high skewness for duration variables

(Administrative_Duration, Informational_Duration, ProductRelated_Duration) as compared to rate metrics (BounceRates, ExitRates), which appear to be more restricted between 0 and 0.20. The extremely high kurtosis values (ranging from 4.01 to 137.10) indicate the presence of extreme outliers and heavy-tailed distributions, particularly in the duration variables. The response variable, Revenue, is a categorical binary variable, which confirms that logistic regression modeling is the appropriate analytical approach rather than general linear modeling.

```r
# Response variable analysis
revenue_dist <- dataset1 %>%
  count(Revenue) %>%
  mutate(Percentage = n/sum(n) * 100)

revenue_dist %>%
  knitr::kable(
    caption = "Distribution of Purchase Conversion (Revenue)",
    digits = 2,
    col.names = c("Revenue (Purchase Made)", "Count", "Percentage (%)")
  ) %>%
  kableExtra::kable_classic_2(
    html_font = "Calibri",
    position = "center",
    font_size = 13,
    full_width = FALSE
  ) %>%
  kableExtra::row_spec(0, bold = TRUE, background = "#E8F4F8")

# Visualise Revenue distribution
ggplot(dataset1, aes(x = Revenue, fill = Revenue)) +
  geom_bar(width = 0.6) +
  geom_text(stat = "count", aes(label = after_stat(count)), vjust = -0.5, size = 5) +
  labs(
    title = "Distribution of Purchase Conversion",
    x = "Revenue Status",
    y = "Number of Sessions"
  ) +
  scale_fill_manual(values = c("FALSE" = "#E74C3C", "TRUE" = "#27AE60")) +
  theme_minimal(base_size = 13) +
  theme(
    plot.title = element_text(face = "bold", hjust = 0.5),
    legend.position = "none"
  )
```



Distribution of Purchase Conversion (Revenue)

Revenue (Purchase Made)	Count	Percentage (%)
FALSE	10422	84.53
TRUE	1908	15.47

As evidenced by the response variable distribution, 84.53% of sessions did not result in a purchase, while only 15.47% generated revenue. This substantial class imbalance; where non-converting sessions outnumber converting sessions by approximately 5.5 to 1, has critical implications for model evaluation. Traditional accuracy metrics may be misleading, and the model may be biased toward predicting the majority class. Therefore, evaluation metrics such as precision, recall, F1-score, and area under the ROC curve (AUC) will be prioritised to account for this imbalance. Additionally, this imbalance suggests the cost of misclassifying revenue-generating sessions as non-revenue (false negatives) may be particularly critical for business decision-making.

```r
# Categorical variables frequency tables
# Function to create frequency table
create_freq_table <- function(data, var_name) {
  data %>%
    count(!!sym(var_name)) %>%
    mutate(Percentage = n/sum(n) * 100) %>%
    arrange(desc(n))
}

# VisitorType frequency table
visitor_freq <- create_freq_table(dataset1, "VisitorType")

visitor_freq %>%
  knitr::kable(
    caption = "Distribution of Visitor Type",
    digits = 2,
    col.names = c("Visitor Type", "Count", "Percentage (%)")
  ) %>%
  kableExtra::kable_classic_2(
    html_font = "Calibri",
    position = "center",
    font_size = 12,
    full_width = FALSE
  )%>%
  kableExtra::row_spec(0, bold = TRUE, background = "#E8F4F8")


# Visualise key categorical variables
# VisitorType Distribution
ggplot(dataset1, aes(x = VisitorType, fill = VisitorType)) +
  geom_bar() +
  geom_text(stat = "count", aes(label = after_stat(count)), vjust = -0.5) +
  labs(
    title = "Distribution of Visitor Types",
    x = "Visitor Type",
    y = "Number of Sessions"
  ) +
  theme_minimal(base_size = 13) +
  theme(
    plot.title = element_text(face = "bold", hjust = 0.5),
    legend.position = "none"
  )

```



Distribution of Visitor Type

Visitor Type	Count	Percentage (%)
Returning_Visitor	10551	85.57
New_Visitor	1694	13.74
Other	85	0.69

Examining the VisitorType distribution reveals that Returning Visitors dominate the dataset at 85.57% followed by New Visitors at 13.74% and a small proportion of Other visitors at 0.69%. This distribution suggests that visitor loyalty and familiarity with the e-commerce platform are common characteristics in the dataset. The extremely small proportion of "Other" visitors may warrant grouping this category with another or excluding it from certain analyses to avoid statistical inconsistencies.

```r
# Create boxplots for key behavioral variables
key_vars <- c("Administrative_Duration", "Informational_Duration",
              "ProductRelated_Duration", "BounceRates", "ExitRates", "PageValues")

dataset1 %>%
  select(Revenue, all_of(key_vars)) %>%
  pivot_longer(-Revenue, names_to = "Variable", values_to = "Value") %>%
  ggplot(aes(x = Revenue, y = Value, fill = Revenue)) +
  geom_boxplot() +
  facet_wrap(~Variable, scales = "free_y", ncol = 3) +
  labs(
    title = "Distribution of Key Behavioral Variables by Revenue Status",
    subtitle = "Comparing converting vs non-converting sessions",
    x = "Revenue (Purchase Made)",
    y = "Value"
  ) +
  scale_fill_manual(values = c("FALSE" = "#E74C3C", "TRUE" = "#27AE60")) +
  theme_minimal(base_size = 11) +
  theme(
    plot.title = element_text(face = "bold", hjust = 0.5),
    plot.subtitle = element_text(hjust = 0.5),
    strip.background = element_rect(fill = "#E8F4F8"),
    strip.text = element_text(face = "bold")
  )
```

The boxplots comparing key behavioural variables by Revenue status reveal distinct patterns between converting and non-converting sessions. Notably, the distributions show that converting sessions (Revenue = TRUE) exhibit:

- Higher PageValues: The median PageValues for converting sessions is substantially elevated compared to non-converting sessions, which cluster near zero. This strong separation suggests PageValues is a powerful discriminator for purchase conversion.
- Longer ProductRelated_Duration: Converting sessions show higher median time spent on product-related pages, indicating greater engagement with merchandise before purchase.
- Lower BounceRates and ExitRates: Converting sessions demonstrate lower abandonment metrics, suggesting sustained engagement throughout the session.

The distributions for Administrative_Duration and Informational_Duration show less pronounced differences between groups, with both revenue categories displaying considerable overlap. This suggests these variables may be weaker predictors of conversion compared to product-related engagement metrics.

Most importantly, several distributions show minimal between converting and non-converting sessions (particularly PageValues and BounceRates), making these variables prime candidates as strong classifiers. This means that the Revenue variable can potentially be classified into each category (TRUE/FALSE) using a rule formulated from the combination of these behavioural metrics. The clear separation in certain variables provides optimism for building an effective logistic regression model, despite the challenges posed by class imbalance.

The highly right-skewed distributions (skewness values ranging from 1.96 to 7.58) across most numerical variables indicate that log transformations may be necessary to normalize distributions and improve model performance. This is particularly relevant for duration variables and PageValues, where the majority of sessions have low values, but extreme outliers pull the distribution's tail.

Task2: Train-test split

The dataset is partitioned into training and test sets using an 80/20 stratified split. The training set is used to compute classification rules through model fiting and the test set is used to evaluate our model reliability.

```r
# Task 2: Train-test split ----
# Initialise randomise
set.seed(25)  # for reproducibility

# Create new column in dataset1 and asign T/F randomly using 80/20 split
dataset1$splt<- sample.split(dataset1$Revenue, SplitRatio= 0.8)

# Get training data which include 80% of split column equal to True
trainData<- subset(dataset1, dataset1$splt == TRUE)

# Get test data
testData<- subset(dataset1, dataset1$splt == FALSE)

# Verify split
cat("Train:", nrow(trainData), "| Test;", nrow(testData),
    "| Split:", floor(nrow(trainData)/nrow(dataset1)*100), "/",
    ceiling(nrow(testData)/nrow(dataset1)*100)
    )
```

Observation of results

```
R 4.5.1 · C:/Users/akhee/AppData/Local/Packages/5319275A.WhatsAppDesktop_cv1g1gvanyjgm/Loc
> # verify split
> cat("Train:", nrow(trainData), "| Test;", nrow(testData),
+     "| Split:", floor(nrow(trainData)/nrow(dataset1)*100), "/",
+     ceiling(nrow(testData)/nrow(dataset1)*100)
+     )
Train: 9864 | Test; 2466 | Split: 80 / 20
>
```

The split assigned 9864 sessions into the training set and the remaining 2466 sessions to the test set, maintaining the 80/20 split ratio.

Task 3: Model fitting

A logistic regression model is fit using 5 behavioural predictors selected based on explanatory analysis. Given the binary nature of the Revenue response variable, binomial family is used together with the logit link function to model a classifier.

```r
# Task 3: Model fitting ----
# Fit Logistic regression model
logitModel<- glm(Revenue ~ PageValues + ProductRelated_Duration +
                   ExitRates + BounceRates + ProductRelated,
                 data= trainData,
                 family= binomial(link= "logit"))

# model summary
summary(logitModel)

# refit the model without the statistically insignificant predictors
logitModel1<- glm(Revenue ~ PageValues +
                   ExitRates + ProductRelated,
                 data= trainData,
                 family= binomial(link= "logit"))

# model summary
summary(logitModel1)

# Display coefficients in a table
coeffTable<- data.frame(
  Predictor= names(coef(logitModel1)),
  Coefficient= coef(logitModel1),
  OddsRatio= exp(coef(logitModel1))
)

rownames(coeffTable)<- NULL # removes row names

# Display coefficients table
coeffTable %>%
  knitr::kable(
    caption = "Model Coefficients and Odds Ratios") %>%
  kableExtra::kable_classic_2(
    html_font = "Calibri",
    position = "center",
    font_size = 12,
    full_width = FALSE
  )%>%
  kableExtra::row_spec(0, bold = TRUE, background = "#E8F4F8")
```

Observation of results

```
> summary(logitModel)

Call:
glm(formula = Revenue ~ PageValues + ProductRelated_Duration +
    ExitRates + BounceRates + ProductRelated, family = binomial(link = "logit")
    data = trainData)

Coefficients:
                         Estimate Std. Error z value Pr(>|z|)
(Intercept)            -2.030e+00  7.284e-02 -27.866  < 2e-16 ***
PageValues              7.605e-02  2.509e-03  30.314  < 2e-16 ***
ProductRelated_Duration 4.376e-05  2.853e-05   1.534    0.125
ExitRates              -1.624e+01  2.509e+00  -6.470  9.8e-11 ***
BounceRates            -4.344e+00  3.530e+00  -1.231    0.218
ProductRelated          3.916e-03  1.190e-03   3.291    0.001 ***
---
Signif. codes:  0 ‘***’ 0.001 ‘**’ 0.01 ‘*’ 0.05 ‘.’ 0.1 ‘ ’ 1

(Dispersion parameter for binomial family taken to be 1)

    Null deviance: 8498.5  on 9863  degrees of freedom
Residual deviance: 6077.5  on 9858  degrees of freedom
AIC: 6089.5

Number of Fisher Scoring iterations: 7
```

```
> summary(logitModel1)

Call:
glm(formula = Revenue ~ PageValues + ExitRates + ProductRelated,
    family = binomial(link = "logit"), data = trainData)

Coefficients:
                 Estimate Std. Error z value Pr(>|z|)
(Intercept)    -2.005e+00  6.835e-02 -29.331   <2e-16 ***
PageValues      7.609e-02  2.503e-03  30.402   <2e-16 ***
ExitRates      -1.834e+01  1.739e+00 -10.546   <2e-16 ***
ProductRelated  5.445e-03  5.791e-04   9.401   <2e-16 ***
---
Signif. codes:  0 ‘***’ 0.001 ‘**’ 0.01 ‘*’ 0.05 ‘.’ 0.1 ‘ ’ 1

(Dispersion parameter for binomial family taken to be 1)

    Null deviance: 8498.5  on 9863  degrees of freedom
Residual deviance: 6081.8  on 9860  degrees of freedom
AIC: 6089.8

Number of Fisher Scoring iterations: 6
```

The initial model summary revealed ProductRelated_Duration with p-value 0.125 and BounceRates with p-value 0.218 were not statistically significant in classifying the response variable Revenue. The model was refined to include only statistically significant predictors, PageValues, ExitRates and ProductRelated.

Refined model coefficients

Model Coefficients and Odds Ratios

Predictor	Coefficient	OddsRatio
(Intercept)	-2.0047676	0.1346916
PageValues	0.0760914	1.0790612
ExitRates	-18.3390467	0.0000000
ProductRelated	0.0054448	1.0054596

The intercept represents the baseline log—odds of a session generating revenue when all presictors are equal to zero. This however has limited practical interpretation as zero values for the predictors are uncommon in actual browsing sessions.

PageValue coefficient indicates that for every marginal increase in PageValues, the odds of generating revenue increase by 7.9%. This means that as the average value of pages visited increase (greater engagement), the probability of the user purchasing the items browsed also increases.

ExitRates shows a strong negative relationship with purchase conversion. For every marginal increase in ExitRates, the odds of conversion decrease at an increasing rate. This aligns with behavioural expectations as higher exit rates signal premature session abandonment, suggesting highly unlike purchase conversion.

ProductRelated demonstrates that each additional product-related page visited increases conversion odds by 0.55%. This effect appears modest per page, but it compounds across multiple page views.

Task 4: Confusion Matrix for Training Set

Classifier performance on the training data is evaluated by constructing confusion matrix that compared predicted sessions against the actual Revenue values.

```
> # Task4: Confusion Matrix for Training set ----
> # Predict on training data
> trainPredProb <- predict(logitModel1, type = "response")
> trainPredClass <- ifelse(trainPredProb >= 0.5, "TRUE", "FALSE")
> trainPredClass <- factor(trainPredClass, levels = c("FALSE", "TRUE"))
>
> # Convert Revenue from logical to factor with same levels
> trainData$Revenue <- factor(trainData$Revenue, levels = c(FALSE, TRUE))
>
> # Create a confusion matrix
> trainConfusionMatrix <- confusionMatrix(trainPredClass, trainData$Revenue, positive = "TRUE")
> print(trainConfusionMatrix)
Confusion Matrix and Statistics

          Reference
Prediction FALSE TRUE
     FALSE  8154  987
     TRUE    184  539

               Accuracy : 0.8813
                 95% CI : (0.8747, 0.8876)
    No Information Rate : 0.8453
    P-Value [Acc > NIR] : < 2.2e-16

                  Kappa : 0.4218

 Mcnemar's Test P-Value : < 2.2e-16

            Sensitivity : 0.35321
            Specificity : 0.97793
         Pos Pred Value : 0.74550
         Neg Pred Value : 0.89202
             Prevalence : 0.15470
         Detection Rate : 0.05464
   Detection Prevalence : 0.07330
      Balanced Accuracy : 0.66557

       'Positive' Class : TRUE
```

Observation of results

The classifier correctly distinguished 8693 of 9864 sessions, achieving 88.1% overall accuracy on the training data. This exceeds the 84,5% baseline accuracy that utilises chance in classification. The model demonstrates particularly strong performance in identifying non-revenue sessions, classifying 8154 of 8338 actual non-revenue sessions, that is 97.8% specificity. This suggests that the model effectively recognises behavioural patterns traits of sessions that will not convert.

However, the model shoes weaker performance on revenue generating sessions, achieving only 35.3% sensitivity. This means the classifier correctly identified 539 of 1526 actual converting sessions, missing 987 revenue generating sessions (false negatives). This disparity in performance reflects the inherent challenge of severe class imbalance, where non-revenue sessions out number revenue sessions by 5.5 to 1. The model learnt patterns predominantly from the majority class which made it conservative in predicting revenue generation

Precision of 74.6% indicates that when the model predicts a session will generate revenue, it is correct approximately three-quarters of the time. Conversely, only 184 non-revenue sessions were incorrectly classified as revenue generating, representing 2.2% of actual non-revenue sessions. In the context of our business domain, the False Negatives are substantially more damaging that False Positives. This neglect potential customers showing purchase intent through their behavioural patterns.

Task 5: Confusion Matrix for the test set

The trained model's classification capabilities are evaluated using an independent test dataset.

```
> # Task 5: Confusion Matrix for test Set ----
> # Predict on Test Data
> testPredProb <- predict(logitModel1, newdata = testData, type = "response")
> testPredClass <- ifelse(testPredProb >= 0.5, "TRUE", "FALSE")
> testPredClass <- factor(testPredClass, levels = c("FALSE", "TRUE"))
>
> # Convert Revenue from logical to factor with same levels
> testData$Revenue <- factor(testData$Revenue, levels = c(FALSE, TRUE))
>
> # Create a confusion matrix
> testConfusionMatrix <- confusionMatrix(testPredClass, testData$Revenue, positive = "TRUE")
> print(testConfusionMatrix)
Confusion Matrix and Statistics

          Reference
Prediction FALSE TRUE
     FALSE  2050  236
     TRUE     34  146

               Accuracy : 0.8905
                 95% CI : (0.8775, 0.9026)
    No Information Rate : 0.8451
    P-Value [Acc > NIR] : 4.456e-11

                  Kappa : 0.4666

 Mcnemar's Test P-Value : < 2.2e-16

            Sensitivity : 0.38220
            Specificity : 0.98369
         Pos Pred Value : 0.81111
         Neg Pred Value : 0.89676
             Prevalence : 0.15491
         Detection Rate : 0.05921
   Detection Prevalence : 0.07299
      Balanced Accuracy : 0.68294

       'Positive' Class : TRUE

>
```

Observation of results

Accuracy (89.1%): The model classified 2196 of 2466 test session correctly. This slightly exceeds training accuracy by a percentage point

Precision (81.1%): The model is correct 81.1% of the time when predicting revenue generation in the test set, and this shows a 6.5% improvement over training precision.

Sensitivity (38.2%): The model identified 146 of 382 actual revenue-generating sessions, capturing 32.2% of converters. This shows a 2.9% improvement over the training recall.

Specificity (98.4%): The model correctly identified 2050 of 2084 non-revenue session, maintaining an excellent performance of 98.4% specificity.

Conclusively, the test set performance demonstrates excellent generalization and it shows marginal improvements across all metrics when compared to training performance. This indicates that the model is a good fit that avoids overfitting. The consistence between training and test specificity confirms that the model reliability recognizes non converting sessions patterns across different data samples. In addition to that, the modest improvement in sensitivity suggests that the model's conservative approach to predicting revenue generation is a genuine trait rather than a training flaw.

Task 6: ROC Curve

ROC Curve is plotted to visualize the classifier's performance across all possible decision thresholds.

```
# Task 6: ROC Curve ----
# Create ROC object
rocObject <- roc(testData$Revenue, testPredProb)

# Plot ROC curve
plot(rocObject,
     main = "ROC: Classifying Revenue-Generating Sessions",
     col = "blue",
     lwd = 2,
     xlab = "False Positive Rate (1 - Specificity)",
     ylab = "True Positive Rate (Sensitivity)"
)
```

Observation of results



The ROC curve shows a strong discerning ability, with the curve positioned well above the no-skill line. The curve's pronounces bow towards the upper-left corner indicates the model's effectiveness in separating revenue-generating sessions from non-revenue generating sessions across a wide range of probability thresholds.

Task 7: AUC

The probability that the model assigns a higher conversion probability to a randomly selected revenue-generating session than to a randomly selected non-revenue session, the AUC is computed.

```
> # Task 7: Calculate AUC ----
> aucvalue <- auc(rocObject)
>
> # Show AUC
> aucvalue
Area under the curve: 0.9026
>
```

Observation of results

The model achieves an AUC of 0.9026 which indicates an excellent discriminative performance. This means that if one revenue generating session and one non-revenue generating session are selected randomly, there is a 90.3% probability that the model will

correctly assign a higher conversion probability to the actual revenue session. This high AUC validated the feature selection process and model refinement strategy

Task 8: Hypothesis testing

The relationship between revenue generation trends and the time of the year is evaluated to check if they are dependent on each other, using the chi-square test of independence. All assumptions for the chi-square test are assumed to be met

```
> # Task8: Hypothesis Test (Chi-Square Test of Independence) ----
> # Testing whether Revenue generation is independent of Month
> # H0: Revenue generation is independent of Month
> # H1: Revenue generation is dependent on Month
>
> # Create contingency table from dataset
> contingencyTable <- table(dataset1$Month, dataset1$Revenue)
>
> # Display the contingency table
> contingencyTable %>%
+   knitr::kable(
+     caption = "Contingency Table: Month vs Revenue Generation",
+     col.names = c("No Purchase", "Purchase Made")
+   ) %>%
+   kableExtra::kable_classic_2(
+     html_font = "Calibri",
+     position = "center",
+     font_size = 12,
+     full_width = FALSE
+   ) %>%
+   kableExtra::row_spec(0, bold = TRUE, background = "#E8F4F8")
>
> # Convert table to matrix for calculations
> observed <- as.matrix(contingencyTable)
>
> # Compute marginal totals needed for calculating expected frequencies
> rowTotal <- rowSums(observed)  # total sessions for each month
> colTotal <- colSums(observed)  # total sessions for each revenue category
> grandTotal <- sum(observed)    # total sessions
>
> alpha <- 0.05  # significance level
> r <- nrow(observed)  # number of rows (months)
> c <- ncol(observed)  # number of columns (revenue categories)
> df <- (r - 1) * (c - 1)  # degrees of freedom
> df
[1] 9
>
> # Compute expected frequencies assuming independence
> expected <- outer(rowTotal, colTotal) / grandTotal
>
> # Critical value
> criticalValue <- qchisq(1 - alpha, df)  # right tailed test CV
> criticalValue
[1] 16.91898
>
> # Compute chi-square test statistic
> chiStat <- sum((observed - expected)^2 / expected)
> chiStat
[1] 384.9348
>
> # Decision
> ifelse(chiStat > criticalValue, "Reject H0", "Fail to reject H0")
[1] "Reject H0"
>
```

Observation of results

Hypothesis:

H0: Revenue generation is independent of month

H1: Revenue generation id dependent on month

Degrees of freedom: 9

Significance level: 0.05

Critical value: 16.919

Chi-square value: 384.935

Decision: Since 384.935 > 16.919, we reject the null hypothesis and conclude that revenue is dependent on the month. This suggests that certain months exhibit substantially different conversion rates than others, likely reflecting seasonal shopping patterns, holidays purchasing behaviour (November's Black Frids/ Cyber Mondey) or month-specific promotional activities. Ecommerce platforms should account for these temporal variations when allocating marketing resources, adjusting inventory, and forecasting revenue.

Conclusion

The logistic regression model demonstrates excellent discriminative performance, achieving an AUC of 90.3% using three behavioural predictors — PageValues, ExitRates, and ProductRelated page count. The classifier reliably identifies non-converting sessions with 98.4% specificity and generalizes well across both training and test sets, with marginal metric improvements on unseen data confirming the absence of overfitting.

The chi-square test ($\chi^2 = 384.94$, df = 9, $p < 0.05$) confirmed that revenue generation is significantly dependent on month, validating the presence of seasonal conversion patterns likely driven by holiday shopping behaviour and month-specific promotional activity. E-commerce platforms should account for these temporal variations in marketing resource allocation, inventory planning, and revenue forecasting.

The primary limitation of the model is its conservative sensitivity of 38.2%, a direct consequence of the 5.5:1 class imbalance between non-converting and converting sessions. This results in a high false negative rate, meaning a significant proportion of genuine purchase intent goes undetected — a costly outcome in a business context where missed converters represent lost revenue. Future work should address this through threshold adjustment to lower the classification boundary below 0.5, or resampling techniques such as SMOTE to balance the training data and improve recall without substantially sacrificing precision.