



A Common Framework for Attitude Synchronization of Unit Vectors in Networks with Switching Topology

Pedro Pereira, Dimitris Boskos and Dimos V. Dimarogonas

Department of Automatic Control,
KTH Royal Institute of Technology

December 13th



Problem formulation


Problem

Design angular velocity control laws that guarantee total or partial orientation synchronization among group of agents.

Problem formulation

Problem


Design angular velocity control laws that guarantee total or partial orientation synchronization among group of agents.




Problem formulation

Problem


Design angular velocity control laws that guarantee total or partial orientation synchronization among group of agents.



Complete Synchronization




(a) Two rotation matrices not synchronized, i.e., $\mathcal{R}_1 \neq \mathcal{R}_2$



(b) Two rotation matrices synchronized, i.e., $\mathcal{R}_1 = \mathcal{R}_2$

- In complete synchronization, $\mathcal{R}_1 = \dots = \mathcal{R}_N \in \mathbb{SO}^3$

Incomplete Synchronization ($\bar{\mathbf{n}}_1 \neq \bar{\mathbf{n}}_2$)




(a) Not synchronized, $\mathbf{n}_1 \neq \mathbf{n}_2$.


(b) Synchronized, $\mathbf{n}_1 = \mathbf{n}_2$.

- Body axis to be synchronized, $\bar{\mathbf{n}}_1, \dots, \bar{\mathbf{n}}_N \in \mathbb{S}^2$.
- In incomplete synchronization, $\mathcal{R}_1\bar{\mathbf{n}}_1 = \dots = \mathcal{R}_N\bar{\mathbf{n}}_N \in \mathbb{S}^2$.
- Complete synchronization $\not\Rightarrow$ Incomplete synchronization


Output Feedback



Output Feedback



Output Feedback





Complete Synchronization: Agents dynamics

Agent $i \in \{1, \dots, N\}$

- State: rotation matrix $\mathcal{R}_i \in \mathbb{SO}^3$
- Input: angular velocity $\omega_i \in \mathbb{R}^3$


Complete Synchronization: Agents dynamics

Agent $i \in \{1, \dots, N\}$

- State: rotation matrix $\mathcal{R}_i \in \text{SO}^3$
- Input: angular velocity $\omega_i \in \mathbb{R}^3$

Agent dynamics

$$\dot{\mathcal{R}}_i = \mathbf{f}_R(\mathcal{R}_i, \omega_i) := \mathcal{R}_i \mathcal{S}(\omega_i)$$



Agents output functions

At each time instant t , agent $i \in \{1, \dots, N\}$ makes $|\mathcal{N}_i(t)|$ measurements

- neighbors rotation matrices projected in body framed

Agent output function

Denote $\mathcal{R} = (\mathcal{R}_1, \dots, \mathcal{R}_N) \in (\mathbb{SO}^3)^N$ and $\mathcal{N}_i =: \{i_1, \dots, i_{|\mathcal{N}_i|}\}$,

$$\mathbf{h}_i(t, \mathcal{R}) := (\mathcal{R}_i^T \mathcal{R}_{i_1}, \dots, \mathcal{R}_i^T \mathcal{R}_{i_{|\mathcal{N}_i(t)|}}) \in (\mathbb{SO}^3)^{|\mathcal{N}_i(t)|}$$

Agents output functions


At each time instant t , agent $i \in \{1, \dots, N\}$ makes $|\mathcal{N}_i(t)|$ measurements

- neighbors rotation matrices projected in body framed

Agent output function

Denote $\mathcal{R} = (\mathcal{R}_1, \dots, \mathcal{R}_N) \in (\mathbb{SO}^3)^N$ and $\mathcal{N}_i =: \{i_1, \dots, i_{|\mathcal{N}_i|}\}$,


$$\mathbf{h}_i(t, \mathcal{R}) := (\mathcal{R}_i^T \mathcal{R}_{i_1}, \dots, \mathcal{R}_i^T \mathcal{R}_{i_{|\mathcal{N}_i(t)|}}) \in (\mathbb{SO}^3)^{|\mathcal{N}_i(t)|}$$



Agents output-feedback control law

Output-feedback control law


$$\boldsymbol{\omega}_i^h(t, \mathbf{h}_i) := -k \sum_{l=1}^{l=|\mathcal{N}_i(t)|} \mathcal{S}^{-1}(\mathbf{h}_{i,l} - \mathbf{h}_{i,l}^T) \in \mathbb{R}^3.$$



Closed loop dynamics: Complete synchronization

Closed loop dynamics

$$\dot{\mathcal{R}}_i = \mathbf{f}_R^{cl}(t, \mathcal{R}) := \mathbf{f}_R(\mathcal{R}_i, \omega_i^h \circ \mathbf{h}_i).$$




Incomplete synchronization: Agents dynamics

Agent $i \in \{1, \dots, N\}$

- State: rotation matrix $\mathcal{R}_i \in \text{SO}^3$
- Input: angular velocity $\omega_i \in \mathbb{R}^3$
- **Body axis to synchronize:** $\bar{\mathbf{n}}_i$

Agent dynamics

$$\dot{\mathcal{R}}_i(t) = \mathbf{f}_R(\mathcal{R}_i, \omega_i) := \mathcal{R}_i \mathcal{S}(\omega_i)$$



Agents output functions

At each time instant t , agent $i \in \{1, \dots, N\}$ makes $|\mathcal{N}_i(t)|$ measurements

- neighbors axis projected in body frame

Agent output function

Denote $\mathcal{R} = (\mathcal{R}_1, \dots, \mathcal{R}_N) \in (\mathbb{SO}^3)^N$ and $\mathcal{N}_i =: \{i_1, \dots, i_{|\mathcal{N}_i|}\}$,

$$\mathbf{h}_i(t, \mathcal{R}) := (\mathcal{R}_i^T \mathcal{R}_{i_1} \bar{\mathbf{n}}_{i_1}, \dots, \mathcal{R}_i^T \mathcal{R}_{i_{|\mathcal{N}_i(t)|}} \bar{\mathbf{n}}_{i_{|\mathcal{N}_i(t)|}}) \in (\mathbb{S}^2)^{|\mathcal{N}_i(t)|}$$

Agents output functions


At each time instant t , agent $i \in \{1, \dots, N\}$ makes $|\mathcal{N}_i(t)|$ measurements

- neighbors axis projected in body frame

Agent output function

Denote $\mathcal{R} = (\mathcal{R}_1, \dots, \mathcal{R}_N) \in (\mathbb{SO}(3))^N$ and $\mathcal{N}_i =: \{i_1, \dots, i_{|\mathcal{N}_i|}\}$,


$$\mathbf{h}_i(t, \mathcal{R}) := (\mathcal{R}_i^T \mathcal{R}_{i_1} \bar{\mathbf{n}}_{i_1}, \dots, \mathcal{R}_i^T \mathcal{R}_{i_{|\mathcal{N}_i(t)|}} \bar{\mathbf{n}}_{i_{|\mathcal{N}_i(t)|}}) \in (\mathbb{S}^2)^{|\mathcal{N}_i(t)|}$$



Agents output-feedback control law

Output-feedback control law


$$\omega_i^h(t, \mathbf{h}_i) := -k \sum_{l=1}^{l=|\mathcal{N}_i(t)|} \mathcal{S}(\bar{\mathbf{n}}_i) \mathbf{h}_{i,l} \in T_{\bar{\mathbf{n}}_i} \mathbb{S}^2.$$



Closed loop dynamics: Incomplete synchronization

Closed loop dynamics

$$\dot{\mathcal{R}}_i = \mathbf{f}_R^{cl}(t, \mathcal{R}) := \mathbf{f}_R(\mathcal{R}_i, \omega_i^h \circ \mathbf{h}_i).$$



Common Framework

Complete synchronization as synchronization in \mathbb{S}^3

$$\begin{bmatrix} \mathbb{SO}^3 \ni \mathcal{R}_1 \\ \vdots \\ \mathbb{SO}^3 \ni \mathcal{R}_N \end{bmatrix} \implies \begin{bmatrix} \frac{1}{2} \left(\frac{\mathcal{S}^{-1}(\mathcal{R}_1 - \mathcal{R}_1^T)}{\sqrt{1 + \text{tr}(\mathcal{R}_1)}}, \sqrt{1 + \text{tr}(\mathcal{R}_1)} \right) =: \boldsymbol{\nu}_1 \in \mathbb{S}^3 \\ \vdots \\ \frac{1}{2} \left(\frac{\mathcal{S}^{-1}(\mathcal{R}_N - \mathcal{R}_N^T)}{\sqrt{1 + \text{tr}(\mathcal{R}_N)}}, \sqrt{1 + \text{tr}(\mathcal{R}_N)} \right) =: \boldsymbol{\nu}_N \in \mathbb{S}^3 \end{bmatrix}$$

$$\dot{\mathcal{R}}_i = \mathbf{f}_R^{cl}(t, \mathcal{R}) \implies \dot{\boldsymbol{\nu}}_i = \sum_{j \in \mathcal{N}_i(t)} w(\boldsymbol{\nu}_i, \boldsymbol{\nu}_j) \Pi(\boldsymbol{\nu}_i) \boldsymbol{\nu}_j$$

$$w(\boldsymbol{\nu}_i, \boldsymbol{\nu}_j) = \boldsymbol{\nu}_i^T \boldsymbol{\nu}_j$$

Common Framework

Incomplete synchronization as synchronization in \mathbb{S}^2

$$\begin{bmatrix} \mathbb{SO}^3 \ni \mathcal{R}_1 \\ \vdots \\ \mathbb{SO}^3 \ni \mathcal{R}_N \end{bmatrix} \implies \begin{bmatrix} \mathcal{R}_1 \bar{\mathbf{n}}_1 =: \boldsymbol{\nu}_1 \in \mathbb{S}^2 \\ \vdots \\ \mathcal{R}_N \bar{\mathbf{n}}_N =: \boldsymbol{\nu}_N \in \mathbb{S}^2 \end{bmatrix}$$

$$\dot{\mathcal{R}}_i = \mathbf{f}_R^{cl}(t, \mathcal{R}) \implies \dot{\boldsymbol{\nu}}_i = \sum_{j \in \mathcal{N}_i(t)} w(\boldsymbol{\nu}_i, \boldsymbol{\nu}_j) \Pi(\boldsymbol{\nu}_i) \boldsymbol{\nu}_j$$


$$w(\boldsymbol{\nu}_i, \boldsymbol{\nu}_j) = 1$$

Cone

Cone

Notion of neighborhood in sphere:

$$\mathcal{C}(\alpha, \bar{\nu}) = \{\nu \in \mathbb{S}^n : \nu^T \bar{\nu} > \cos(\alpha)\}$$





Cone

Cone

Consider a group of unit vectors $\nu = (\nu_1, \dots, \nu_N) \in (\mathbb{S}^n)^N$.


Cone

Cone

Consider a group of unit vectors $\nu = (\nu_1, \dots, \nu_N) \in (\mathbb{S}^n)^N$.

ν belongs to α -cone : $\Leftrightarrow \nu = (\nu_1, \dots, \nu_N) \in \mathcal{C}(\alpha, \bar{\nu})^N$ for some $\bar{\nu} \in \mathbb{S}^n$


$$\nu = (\nu_1, \nu_2, \nu_3) \in \mathcal{C}(30^\circ, \bar{\nu})^3$$



Synchronization in \mathbb{S}^n

$$\begin{bmatrix} \mathbb{S}^n \ni \nu_1 \\ \vdots \\ \mathbb{S}^n \ni \nu_N \end{bmatrix} \Leftrightarrow \begin{bmatrix} Q_{\bar{\nu}} \nu_1 =: \mathbf{x}_1 \in \mathbb{R}^n \\ \vdots \\ Q_{\bar{\nu}} \nu_N =: \mathbf{x}_N \in \mathbb{R}^n \end{bmatrix} =: \mathbf{x}$$

$$\dot{\nu}_i = \sum_{j \in \mathcal{N}_i(t)} w(\nu_i, \nu_j) \Pi(\nu_i) \nu_j \Leftrightarrow \dot{\mathbf{x}}_i = \mathbf{f}_i(t, \mathbf{x})$$



Main result

Main result


If

- $\nu(0)$ belongs to α -cone,
- and the network graph is connected at all times,


then

- the group of unit vectors remains in the cone it starts on;
- all unit vectors converges to one another;
- all unit vectors converge to a constant unit vector.

Simulation: Complete synchronization



Simulation: Incomplete synchronization



Future research directions


Research directions

- Develop strategies for disturbance removal: $\dot{\mathcal{R}} = \mathcal{RS}(\omega + \mathbf{d})$.
- Determine and study the stability of other equilibria.
- Determine constant unit vector that network converges to.



Thank you! Questions?

Incomplete Synchronization ($\bar{\mathbf{n}}_1 = \bar{\mathbf{n}}_2$)



- Body axis to be synchronized, $\bar{\mathbf{n}}_1, \dots, \bar{\mathbf{n}}_N \in \mathbb{S}^2$.
- In incomplete synchronization, $\mathcal{R}_1\bar{\mathbf{n}}_1 = \dots = \mathcal{R}_N\bar{\mathbf{n}}_N \in \mathbb{S}^2$.
- Incomplete synchronization $\not\Rightarrow$ Complete synchronization