CASE STUDY - CONTAINERIZATION USING DOCKER I

Problem Statement:

You work as a Devops Engineer in a leading Software Company. You have been asked to Dockerize the applications on the production server. The company uses custom software, therefore there is no pre-built container which can be used.

Assume the following things:

- 1. Assume the software to be installed is apache
- 2. Use an Ubuntu container

The company wants the following things:

- 1. Push a container to DockerHub with the above config
- 2. The Developers will not be working with Docker, hence from their side you will just get the code. Write a Dockerfile which could put the code in the custom image that you have built

Solution:

We need to create a Dockerfile that installs Apache, copies the provided code into the container, and builds a Docker image. Then, push the Docker image to DockerHub.

1) Create a Dockerfile with the following content:

Use the official Ubuntu image from the Docker Hub FROM ubuntu:latest

Install Apache2
RUN apt-get update && apt-get install -y apache2

Copy application code to the Apache default directory COPY . /var/www/html/

Ensure Apache2 runs when the container starts CMD ["apache2ctl", "-D", "FOREGROUND"]

Expose port 80 EXPOSE 80

```
GNU nano 7.2 dockerfile *

FROM ubuntu:latest
RUN apt-get update && apt-get install -y apache2

COPY . /var/www/html/

CMD ("apache2ctl", "-D", "FOREGROUND")

EXPOSE 80

AG Help

CWrite Out

WWhere Is

Read File

Replace

U Paste

J Justify

Josephin Accepted

Location

M-U

AREA

AT Execute

C Location

AT Execute

C Location

AT Execute

AT Execute

C Location

AT Execute

AT Execute

C Location

AT Execute

AT Exec
```

```
ubuntu@ip-172-31-0-75:~/my-casestudy$ nano Dockerfile
ubuntu@ip-172-31-0-75:~/my-casestudy$ 11
total 12
drwxrwxr-x 2 ubuntu ubuntu 4096 Feb 9 18:12 ./
drwxr-x--- 6 ubuntu ubuntu 4096 Feb 9 18:12 ../
-rw-rw-r-- 1 ubuntu ubuntu 139 Feb 9 18:12 Dockerfile
ubuntu@ip-172-31-0-75:~/my-casestudy$
```

2) Build the Docker Image:

Navigate to the directory containing your Dockerfile and application code.

Build the Docker image: docker build -t my-custom-apache.

```
Running hooks in /etc/ca-certificates/update.d...
done.
---> Removed intermediate container 848955d4afcb
 ---> 92905e4f6b84
Step 3/5 : COPY . /var/www/html/
---> 3b230ae95ee4
Step 4/5 : CMD ["apache2ctl", "-D", "FOREGROUND"]
 ---> Running in 5d393fd6a34c
 ---> Removed intermediate container 5d393fd6a34c
 ---> bd4b64805c07
Step 5/5 : EXPOSE 80
---> Running in 33391f15cb17
 ---> Removed intermediate container 33391f15cb17
---> 3c529027038a
Successfully built 3c529027038a
Successfully tagged my-custom-apache:latest
ubuntu@ip-172-31-0-75:~/my-casestudy$
```

3) Push the Docker Image to Docker Hub: docker login

```
Successfully tagged my-custom-apache:latest
ubuntu@ip-172-31-0-75:-/my-casestudy$ docker login
Log in with your Docker ID or email address to push and pull images from Docker Hub. If you don't have a Docker ID, head over to https://hub.docker.
m/ to create one.
You can log in with your password or a Personal Access Token (PAT). Using a limited-scope PAT grants better security and is required for organizatio
using SSO. Learn more at https://docs.docker.com/go/access-tokens/
Username: poulomibhattacharjee
```

i_0119374297f23280d (mv_cerver)

```
ubuntu@ip-172-31-0-75:~/my-casestudy$ docker login
Log in with your Docker ID or email address to push and pull images from Docker Hub. If you don't have a Docker
m/ to create one.
You can log in with your password or a Personal Access Token (PAT). Using a limited-scope PAT grants better securing SSO. Learn more at https://docs.docker.com/go/access-tokens/
Username: poulomibhattacharjee
Password:
WARNING! Your password will be stored unencrypted in /home/ubuntu/.docker/config.json.
Configure a credential helper to remove this warning. See
https://docs.docker.com/engine/reference/commandline/login/#credentials-store
Login Succeeded
ubuntu@ip-172-31-0-75:~/my-casestudy$
```

4) **Tag the Docker image:** docker tag my-custom-apache poulomibhattacharjee/my-custom-apache

```
 ubuntu@ip-172-31-0-75: $$ \sim/my-casestudy$ docker tag my-custom-apache poulomibhattacharjee/my-custom-apache ubuntu@ip-172-31-0-75: $$ \sim/my-casestudy$ $$ $$
```

5) **Push the Docker image**: docker push poulomibhattacharjee/my-custom-apache

```
ubuntu@ip-172-31-0-75:~/my-casestudy$ docker push poulomibhattacharjee/my-custom-apache
Using default tag: latest
The push refers to repository [docker.io/poulomibhattacharjee/my-custom-apache]
2346e278161a: Pushed
18d88dca6efa: Pushed
4b7c0led0534: Mounted from library/ubuntu
latest: digest: sha256:9abf317b0c7dab7e53843f9aa5add841c0b0d5541914baf468d09e02c74167ef size: 948
ubuntu@ip-172-31-0-75:~/my-casestudy$
```

6) We can check it from DockerHub whether the image is presen.

