



# EMC TEST REPORT

Test item description: Volume Knob Kit

Trademark(s): /

Model/Type reference: RE\_SWC

S/N: /

Report No.: CTB26011913201E01

Applicant's name: Pounamu Electronics

Address: 22 Peony Mews, Oteha, Auckland 0632, New Zealand

Manufacturer: Pounamu Electronics

Address: 22 Peony Mews, Oteha, Auckland 0632, New Zealand

Prepared by: Shenzhen CTB Testing Technology Co., Ltd.

Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China

Sample No.: 26011913201

Date of Receipt: Jan. 19, 2026

Date of Test(s): Jan. 19, 2026 ~ Jan. 20, 2026

Date of Issue: Jan. 30, 2026

Test Standard(s): 47 CFR Part 15 Subchapter B, ANSI C63.4: 2014

Test Result: Pass

In the configuration tested, the EUT complied with the standards specified above.

Compiled by:

Reviewed by:

Approved by:

Ice Chen

Bin Mei

Rita Xiao

Ice Chen

Bin Mei

Rita Xiao

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. The tested sample(s) and the sample information are provided by the applicant. The authenticity, accuracy, and completeness of the provided information are the sole responsibility of the applicant. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The result decision rules of our laboratory are based solely on the direct comparison between the actual measured values of test results and the standard limits, without considering the measurement uncertainty. "★" indicates the testing items were fulfilled by subcontracted lab. "×" indicates the items are not in CNAS accreditation scope.

## Table of Contents

|                                                                |    |
|----------------------------------------------------------------|----|
| 1. Description of version .....                                | 3  |
| 2. Test summary .....                                          | 4  |
| 3. Measurement uncertainty .....                               | 5  |
| 4. General information .....                                   | 6  |
| 4.1. Description of EUT .....                                  | 6  |
| 4.2. Description of accessory device .....                     | 6  |
| 4.3. Test conditions .....                                     | 6  |
| 4.4. Block diagram of EUT configuration .....                  | 7  |
| 4.5. Operating condition of EUT .....                          | 7  |
| 5. List of Test and Measurement Instruments .....              | 8  |
| 6. Conducted Emission .....                                    | 10 |
| 6.1. Limit .....                                               | 10 |
| 6.2. Test setup .....                                          | 10 |
| 6.3. EMI test receiver setup .....                             | 10 |
| 6.4. Test procedure .....                                      | 10 |
| 6.5. Test results .....                                        | 11 |
| 7. Radiated emissions .....                                    | 13 |
| 7.1. Limit .....                                               | 13 |
| 7.2. Test setup .....                                          | 13 |
| 7.3. EMI test receiver setup and spectrum analyzer setup ..... | 14 |
| 7.4. Test procedure .....                                      | 14 |
| 7.5. Corrected Amplitude & Margin Calculation .....            | 14 |
| 7.6. Test results .....                                        | 15 |
| 8. Photographs of test setup .....                             | 17 |
| 9. Photographs of EUT .....                                    | 18 |

1. Description of version

| Report No.        | Issue Date    | Description | Approved |
|-------------------|---------------|-------------|----------|
| CTB26011913201E01 | Jan. 30, 2026 | Original    | Valid    |
|                   |               |             |          |



## 2. Test summary

Test procedures according to the technical standards:

| Standard | Test Item          | Test Result |
|----------|--------------------|-------------|
| §15.107  | Conducted Emission | PASS        |
| §15.109  | Radiated Emission  | PASS        |

### 3. Measurement uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %

| Test Item          | Frequency            | Expanded Uncertainty ( $U_{Lab}$ )      |
|--------------------|----------------------|-----------------------------------------|
| Conducted Emission | 150 kHz to 30 MHz    | No.1 $\pm 3.4$ dB<br>No.2 $\pm 3.5$ dB  |
| Radiated Emission  | 30 MHz to 1000 MHz   | No.1 $\pm 4.9$ dB<br>No.2 $\pm 4.6$ dB  |
| Radiated Emission  | 1000 MHz to 6000 MHz | No.1 $\pm 4.9$ dB,<br>No.2 $\pm 4.8$ dB |

#### 4. General information

##### 4.1. Description of EUT

|                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test item description                                    | Volume Knob Kit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Trademark(s)                                             | /                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Model/Type reference                                     | RE_SWC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Serial Model No.                                         | /                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Model Difference                                         | /                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Rated Power                                              | /                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Rated Voltage& current                                   | DC 5V 100mA from adapter(AC 230V/50Hz) or DC 5V from Laptop                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Highest Internal Frequency                               | 48MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Configuration                                            | <input checked="" type="checkbox"/> Table-top <input type="checkbox"/> Floor-standing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Classification                                           | <input type="checkbox"/> Class A <input checked="" type="checkbox"/> Class B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| The highest frequency of the internal sources of the EUT | <input type="checkbox"/> below 1.705 MHz, the measurement shall only be made up to 30 MHz.<br><input checked="" type="checkbox"/> between 1.705 MHz and 108 MHz, the measurement shall only be made up to 1 GHz.<br><input type="checkbox"/> between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz.<br><input type="checkbox"/> between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.<br><input type="checkbox"/> above 1 GHz, the measurement shall be made up to 5th harmonic of the highest frequency or 40 GHz, whichever is lower. |
| Adapter Information                                      | /                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

**Note:** The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

##### 4.2. Description of accessory device

| Description | Manufacturer | Model        | Specification                                    | Note                                                                       |
|-------------|--------------|--------------|--------------------------------------------------|----------------------------------------------------------------------------|
| Adapter     | HUAWEI       | HW-050100C01 | Input: 100-240V~ 50/60Hz 0.2A<br>Output: 5V---1A | <input type="checkbox"/> Applicant <input checked="" type="checkbox"/> CTB |
| Laptop      | Lenovo       | 21CU-A0F0CD  | /                                                | <input type="checkbox"/> Applicant <input checked="" type="checkbox"/> CTB |


##### External I/O Cable

| Cable Description | Shielded Type                                                           | Ferrite Core                                             | Length(m) | Note                                                            |
|-------------------|-------------------------------------------------------------------------|----------------------------------------------------------|-----------|-----------------------------------------------------------------|
| /                 | <input type="checkbox"/> Shielded <input type="checkbox"/> Non-shielded | <input type="checkbox"/> Yes <input type="checkbox"/> No | /         | <input type="checkbox"/> Applicant <input type="checkbox"/> CTB |

##### 4.3. Test conditions

Temperature: 15-25℃  
 Relative Humidity: 30-60%RH  
 Atmospheric pressure: 800hPa-1060hPa

#### 4.4. Block diagram of EUT configuration



#### 4.5. Operating condition of EUT

The test system was pre-tested based on the consideration of all possible combinations of EUT operation modes according to test plan. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively. All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, (\*)the worst data were recorded and reported.

| Pretest Test Mode | Description | Test Voltage |
|-------------------|-------------|--------------|
| Mode 1*           | Working     | AC 120V/60Hz |
| Mode 2*           | Working     | DC 5V        |

| Conducted emission test |             |              |
|-------------------------|-------------|--------------|
| Final Test Mode         | Description | Test Voltage |
| Mode 1*                 | Working     | AC 120V/60Hz |

| Radiated emission test |             |              |
|------------------------|-------------|--------------|
| Final Test Mode        | Description | Test Voltage |
| Mode 2*                | Working     | DC 5V        |



## 5. List of Test and Measurement Instruments

| No.1 Continuous disturbance |                   |               |                      |                            |                  |                  |
|-----------------------------|-------------------|---------------|----------------------|----------------------------|------------------|------------------|
| No.                         | Equipment         | Manufacturer  | Model No.            | Serial No.                 | Firmware version | Calibrated until |
| 1                           | 843 Shield Room   | C/ R/ T       | 843                  | /                          | /                | 2027/6/21        |
| 2                           | LISN              | ROHDE&SCHWARZ | ESH3-Z5              | 100318                     | /                | 2026/5/21        |
| 3                           | Pulse limiter     | ROHDE&SCHWARZ | ESH3-Z2              | 0357.8810.54-1<br>02700-NB | /                | 2026/5/21        |
| 4                           | EMI TEST RECEIVER | R&S           | ESCI                 | 100428                     | V4.42.SP3        | 2026/5/21        |
| 5                           | Coaxial cable     | Agilent       | UCE500-SMNM-1.<br>5M | /                          | /                | 2026/5/21        |
| 6                           | ISN               | Schwarzbeck   | NTFM8158             | 183                        | /                | 2026/6/17        |
| 7                           | ISN               | Schwarzbeck   | CAT5 8158            | 473                        | /                | 2026/6/17        |
| 8                           | Voltage Probe     | Schwarzbeck   | TK 9420              | 01189                      | /                | 2026/9/18        |
| 9                           | EMI test software | Frad          | EZ-EMC               | Ver/<br>EMC-con3A1/1       | /                | /                |
| 10                          | Current Probe     | FCC           | F-52B                | 199453                     | /                | 2026/5/23        |

| Radiated emission(No.1 Chamber) |                                         |                   |                        |            |                            |                  |
|---------------------------------|-----------------------------------------|-------------------|------------------------|------------|----------------------------|------------------|
| No.                             | Equipment                               | Manufacturer      | Model No.              | Serial No. | Firmware version           | Calibrated until |
| 1                               | 966 Chamber                             | C/ R/ T           | 966                    | /          | /                          | 2027/6/21        |
| 2                               | Double Ridged<br>Broadband Horn Antenna | Schwarzbeck       | BBHA 9120 D            | 01911      | /                          | 2026/6/1         |
| 3                               | TRILOG Broadband<br>Antenna             | Schwarzbeck       | VULB 9168              | 00869      | /                          | 2026/6/28        |
| 4                               | Preamplifier                            | Agilent           | 8449B                  | 3008A01838 | /                          | 2026/6/3         |
| 5                               | Amplifier                               | HP                | 8447E                  | 2945A02747 | /                          | 2026/5/23        |
| 6                               | 6dB attenuator                          | Agilent           | 6dB (8491B)            | MY39170906 | /                          | 2026/5/23        |
| 7                               | loop antenna                            | Schwarzbeck       | FMZB 1519B             | 1519B-224  | /                          | 2026/6/1         |
| 8                               | EMI TEST RECEIVER                       | ROHDE&SCHWA<br>RZ | ESPI                   | 100362     | RF_ATTEN_7<br>(104489/003) | 2026/5/23        |
| 9                               | Spectrum Analyzer                       | KEYSIGHT          | N9020A                 | MY51289897 | A.14.16                    | 2026/5/22        |
| 10                              | 26.5G cable                             | ETS               | RFC-SNS-100-N<br>MS-80 | /          | /                          | 2026/5/23        |
| 11                              | 26.5G cable                             | ETS               | RFC-SN-100-NM<br>S-20  | /          | /                          | 2026/5/23        |
| 12                              | 26.5G cable                             | ETS               | RFC-SNS-100-S          | /          | /                          | 2026/5/23        |



|    |                   |      |                         |                    |   |           |
|----|-------------------|------|-------------------------|--------------------|---|-----------|
|    |                   |      | MS-20                   |                    |   |           |
| 13 | 26.5G cable       | ETS  | RFC-NNS-100-N<br>MS-300 | /                  | / | 2026/5/23 |
| 14 | EMI test software | Frad | EZ-EMC                  | Ver/ FA-03A2<br>RE | / | /         |

## 6. Conducted Emission

### 6.1. Limit

Except for Class A devices:


| Frequency of emission (MHz) | Conducted limit (dBμV) |           |
|-----------------------------|------------------------|-----------|
|                             | Quasi-peak             | Average   |
| 0.15-0.5                    | 66 to 56*              | 56 to 46* |
| 0.5-5                       | 56                     | 46        |
| 5-30                        | 60                     | 50        |

**Note:** Decreases with the logarithm of the frequency.

For Class A devices:

| Frequency of emission (MHz) | Conducted limit (dBμV) |         |
|-----------------------------|------------------------|---------|
|                             | Quasi-peak             | Average |
| 0.15-0.5                    | 79                     | 66      |
| 0.5-30                      | 73                     | 60      |

### 6.2. Test setup



**Note:** 1.Support units were connected to second LISN.  
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

The setup of EUT is according with ANSI C63.4 measurement procedure. Specification used with FCC Part 15 limits.

### 6.3. EMI test receiver setup


|                      |                                            |
|----------------------|--------------------------------------------|
| Frequency Range      | 9kHz-30MHz                                 |
| Resolution Bandwidth | 200Hz (9kHz-150kHz)<br>9kHz (150kHz-30MHz) |

### 6.4. Test procedure

1. Measurement was performed in shielded room, and instruments used were followed clause 4 of ANSI C63.4.
2. Detailed test procedure was following clause 7 of ANSI C63.4.
3. Frequency range 150kHz – 30MHz was checked and EMI receiver measurement bandwidth was set to 9 kHz.

## 6.5. Test results

|                |              |                    |        |
|----------------|--------------|--------------------|--------|
| Temperature:   | 23°C         | Relative Humidity: | 54 %RH |
| Pressure:      | 101kPa       | Phase :            | Line   |
| Test Voltage : | AC 120V/60Hz | Test Mode:         | Mode 1 |




| No. | Mk. | Freq.   | Reading | Correct | Measurement | Limit | Over   |          |
|-----|-----|---------|---------|---------|-------------|-------|--------|----------|
|     |     | MHz     | Level   | Factor  |             |       |        | Detector |
|     |     |         | dBuV    | dB      | dBuV        | dBuV  | dB     |          |
| 1   |     | 0.1780  | 20.88   | 10.08   | 30.96       | 64.58 | -33.62 | QP       |
| 2   |     | 0.1780  | 0.59    | 10.08   | 10.67       | 54.58 | -43.91 | AVG      |
| 3   |     | 0.2620  | 18.71   | 10.08   | 28.79       | 61.37 | -32.58 | QP       |
| 4   |     | 0.2620  | -0.92   | 10.08   | 9.16        | 51.37 | -42.21 | AVG      |
| 5   | *   | 0.6460  | 25.21   | 10.10   | 35.31       | 56.00 | -20.69 | QP       |
| 6   |     | 0.6460  | 7.52    | 10.10   | 17.62       | 46.00 | -28.38 | AVG      |
| 7   |     | 0.9220  | 15.63   | 10.12   | 25.75       | 56.00 | -30.25 | QP       |
| 8   |     | 0.9220  | 0.67    | 10.12   | 10.79       | 46.00 | -35.21 | AVG      |
| 9   |     | 3.1420  | 13.06   | 10.21   | 23.27       | 56.00 | -32.73 | QP       |
| 10  |     | 3.1420  | -1.73   | 10.21   | 8.48        | 46.00 | -37.52 | AVG      |
| 11  |     | 18.0380 | 13.75   | 10.87   | 24.62       | 60.00 | -35.38 | QP       |
| 12  |     | 18.0380 | -2.16   | 10.87   | 8.71        | 50.00 | -41.29 | AVG      |

Note: Result=Reading + Factor  
Over Limit=Result - Limit



|                |              |                    |         |
|----------------|--------------|--------------------|---------|
| Temperature:   | 23°C         | Relative Humidity: | 54 %RH  |
| Pressure:      | 101kPa       | Phase :            | Neutral |
| Test Voltage : | AC 120V/60Hz | Test Mode:         | Mode 1  |



| No. | Mk. | Freq.   | Reading | Correct | Measure- | Limit | Over   |          |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|
|     |     | MHz     | Level   | Factor  | ment     |       |        | Detector |
|     |     |         | dBuV    | dB      | dBuV     | dBuV  | dB     |          |
| 1   |     | 0.2316  | 17.21   | 10.08   | 27.29    | 62.39 | -35.10 | QP       |
| 2   |     | 0.2316  | -0.41   | 10.08   | 9.67     | 52.39 | -42.72 | AVG      |
| 3   | *   | 0.6460  | 23.22   | 10.10   | 33.32    | 56.00 | -22.68 | QP       |
| 4   |     | 0.6460  | 6.97    | 10.10   | 17.07    | 46.00 | -28.93 | AVG      |
| 5   |     | 1.6780  | 13.98   | 10.16   | 24.14    | 56.00 | -31.86 | QP       |
| 6   |     | 1.6780  | -1.45   | 10.16   | 8.71     | 46.00 | -37.29 | AVG      |
| 7   |     | 3.0140  | 9.96    | 10.21   | 20.17    | 56.00 | -35.83 | QP       |
| 8   |     | 3.0140  | -2.41   | 10.21   | 7.80     | 46.00 | -38.20 | AVG      |
| 9   |     | 8.5219  | 8.98    | 10.41   | 19.39    | 60.00 | -40.61 | QP       |
| 10  |     | 8.5219  | -3.02   | 10.41   | 7.39     | 50.00 | -42.61 | AVG      |
| 11  |     | 17.5980 | 14.61   | 10.85   | 25.46    | 60.00 | -34.54 | QP       |
| 12  |     | 17.5980 | -2.96   | 10.85   | 7.89     | 50.00 | -42.11 | AVG      |

Note: Result=Reading + Factor

Over Limit=Result – Limit

## 7. Radiated emissions

### 7.1. Limit

Except for Class A devices (at 3m):


| Frequency of emission<br>(MHz) | Field strength (microvolts/meter) |                |
|--------------------------------|-----------------------------------|----------------|
|                                | (microvolts/meter)                | (dB $\mu$ V/m) |
| 30-88                          | 100                               | 40             |
| 88-216                         | 150                               | 43.5           |
| 216-960                        | 200                               | 46             |
| Above 960                      | 500                               | 54             |

For Class A devices (at 10m):


| Frequency of emission<br>(MHz) | Field strength (microvolts/meter) |                |
|--------------------------------|-----------------------------------|----------------|
|                                | (microvolts/meter)                | (dB $\mu$ V/m) |
| 30-88                          | 90                                | 39             |
| 88-216                         | 150                               | 43.5           |
| 216-960                        | 210                               | 46.4           |
| Above 960                      | 300                               | 49.5           |

### 7.2. Test setup

Radiated Emission Test Set-Up Frequency Below 1 GHz



Radiated Emission Test Set-Up Frequency Above 1GHz



The radiated tests were performed in 3 meter Chamber test site, using the setup accordance with the ANSI C63.4:2014.

### 7.3. EMI test receiver setup and spectrum analyzer setup

During the radiated emission test, the EMI test receiver and Spectrum Analyzer were set with the following configurations:

| Frequency Range | RBW    | Video B/W | IF B/W | Detector |
|-----------------|--------|-----------|--------|----------|
| 30MHz-1000MHz   | 100kHz | 300kHz    | 120kHz | QP       |
| Above 1GHz      | 1MHz   | 3MHz      | /      | PK       |
|                 | 1MHz   | 10Hz      | /      | AVG      |

### 7.4. Test procedure

1. The measurement was performed in a semi-anechoic chamber, and instruments used were followed clause 4 of ANSI C63.4
2. Detailed test procedure was following clause 8 of ANSI C63.4.

### 7.5. Corrected Amplitude & Margin Calculation

1. The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$


2. The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$



## 7.6. Test results


|                |        |                    |            |
|----------------|--------|--------------------|------------|
| Temperature:   | 23°C   | Relative Humidity: | 54 %RH     |
| Pressure:      | 101kPa | Polarization :     | Horizontal |
| Test Voltage : | DC 5V  | Test Mode:         | Mode 2     |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1   |     | 43.7352      | 29.02                    | -6.08                   | 22.94                      | 40.00         | -17.06     | QP       |
| 2   |     | 144.0819     | 30.48                    | -4.98                   | 25.50                      | 43.50         | -18.00     | QP       |
| 3   |     | 167.2368     | 28.89                    | -3.38                   | 25.51                      | 43.50         | -17.99     | QP       |
| 4   |     | 261.5164     | 37.78                    | -4.24                   | 33.54                      | 46.00         | -12.46     | QP       |
| 5   |     | 384.6055     | 34.29                    | -1.15                   | 33.14                      | 46.00         | -12.86     | QP       |
| 6   | *   | 831.8574     | 25.82                    | 8.86                    | 34.68                      | 46.00         | -11.32     | QP       |

Note: Result=Reading+Factor  
Over Limit=Result-Limit

|                |        |                    |          |
|----------------|--------|--------------------|----------|
| Temperature:   | 23°C   | Relative Humidity: | 54 %RH   |
| Pressure:      | 101kPa | Polarization :     | Vertical |
| Test Voltage : | DC 5V  | Test Mode:         | Mode 2   |




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1   |     | 48.5867      | 26.92                    | -6.37                   | 20.55                      | 40.00         | -19.45     | QP       |
| 2   |     | 162.8959     | 25.92                    | -3.41                   | 22.51                      | 43.50         | -20.99     | QP       |
| 3   |     | 311.6326     | 28.01                    | -2.33                   | 25.68                      | 46.00         | -20.32     | QP       |
| 4   |     | 427.2695     | 29.75                    | -0.40                   | 29.35                      | 46.00         | -16.65     | QP       |
| 5   |     | 601.4265     | 26.58                    | 4.02                    | 30.60                      | 46.00         | -15.40     | QP       |
| 6   | *   | 948.7610     | 27.06                    | 9.30                    | 36.36                      | 46.00         | -9.64      | QP       |

Note: Result=Reading+Factor  
Over Limit=Result-Limit

## 8. Photographs of test setup

RE



CE






## 9. Photographs of EUT


EUT photo 1




EUT photo 2



EUT photo 3




EUT photo 4





EUT photo 5



\*\*\*End of report\*\*\*