

Computer Vision-based System for Impaired Human Vision Compensation

Povilas Daniušis, Audrius Indriulionis, Andrius Budrionis

September 24, 2018

1 Introduction

More than 250 million people worldwide have moderate to severe vision impairment, while (≈ 36 million are blind) [2]. During the past decades significant effort was devoted to develop computer vision and other sensor based aids (e.g. [3], [4], [6], [7]) for helping the blind and visually impaired users to perceive the surrounding world. However, computer vision is rapidly evolving field, and systems based on the aforementioned approaches often lack accuracy and reliability in real-world conditions. In this article we describe a system, which employs modern computer vision techniques for compensation of lost or impaired vision function in humans. Many of the previously proposed electronic aids for the blind count on highly specialised hardware, for instance smart glasses [7], Microsoft Kinect sensors [?], helmet-mounted photosensors and cameras [?]. Such advanced and costly technology brings additional complexity into daily tasks, which visually impaired people currently manage by the help of the white cane. This project puts major emphasis on developing a tool, which seamlessly integrates with the hardware visually impaired person already has on-hand and is used to (smartphone). This paper describes the high level architecture of the proposed technology aid for visually impaired people.

2 Method

Following the principles of participatory design [12], [13] we included the final users into the design process of the system. Two visually impaired persons participated in discussion and focus group meetings together with the project team to identify the key properties of the solution. During the six discussion sessions major attention was paid to:

1. Functionality and key features of the solution addressing real-life scenarios of visually impaired persons;

2. Technical feasibility, connecting user needs to the latest development in computer vision and assisted technologies;
3. Interface between the visually impaired person and the assisted technology;
4. Appearance, usability and potential costs of the final product.

Design process involved testing of the existing technological solutions (mobile phone apps) for assisting visually impaired persons (**which ones have we tested?**). Semi-structured tests were performed by the visually impaired participants accompanied by a researcher from a project group. Strengths and weaknesses of the existing solutions are reflected in the design of the proposed system.

3 Results

Following the above methodology we suggest the impaired human vision compensation system (**HVCS**), consisting of **Device** and **Inference** components (see Fig. 1).

Device subsystem is a computational device the user currently uses for completing other daily tasks. It consists of sensors and actuators, integrated into smartphone-based computation core, which was chosen due its availability to wide population, and capability to perform the required computations or forward visual information to the external server via Internet connection. Sensors are mounted on forehead belt include: RGB camera, depth camera, IMU. Actuator set consists of bone conductive headphones, and head belt for presenting tactile-feedback to the user.

Inference subsystem consists of server computer with internet connection and set of computer vision algorithms, selected according to our methodology (see. Sec. 2): Faster RCNN object detector [?], trained to detect important objects (doors, floors, elevators, stairs, corridor junctions, etc.), CNN-RNN-based scene description [8],[11], [5], place recognition [10], face recognition [1], obstacle detection [9], and possibly other modules.

HVCS operation cycle is started by **Device** reading sensor data and transmitting it to the server for an analysis. Server calculates feedback signal and transmits it back to the device for presenting to the user.




Figure 1: Schematics of FRP device.

4 Discussion

In this article we outlined an idea of computer vision-based sensor, which can help to partially compensate impaired or lost human sight. The developed head-mounted tactile device is developed for head position and orientation tracking and could capture an image in front of visually impaired people. The tactile device with integrated 3D depth camera is integrated with smartphone by bluetooth which could preprocess the labeled image features. The developed high quality self navigation system is based on the computer vision methods especially enhancing the capabilities to detect and classify objects (e.g bus station, street crossings,) with their surrounding objects. The authors expect to increase the capabilities of potentially blind to secure navigate especially for the planned destination (e.g. "home-office").

Work left (outdoor/indoor) etc.

References

- [1] Amos, B., Ludwiczuk, B., and Satyanarayanan, M. Openface: A general-purpose face recognition library with mobile applications. Technical report, CMU-CS-16-118, CMU School of Computer Science, 2016.
- [2] Bourne RRA, Flaxman SR, Braithwaite T, Cicinelli MV, Das A, Jonas JB, et al.; Vision Loss Expert Group. Magnitude, temporal trends, and projections of the global prevalence of blindness and distance and near vision impairment: a systematic review and meta-analysis. *Lancet Glob Health*. 2017 Sep;5(9):e888-97.
- [3] Caraiman, S., Morar, A., Owczarek, M., Burlacu, A., Rzeszotarski, D., Botezatu, N., Herghelegiu, P., Moldoveanu, F., Strumillo, P., Moldoveanu, A. Computer Vision for the Visually Impaired: the Sound of Vision System. *IEEE International Conference on Computer Vision Workshops*, pp. 1480-1489, 2017.
- [4] Csapó, A., Wersényi, G., Nagy, H., Stockman, T. A survey of assistive technologies and applications for blind users on mobile platforms: a review and foundation for research. *Journal on Multimodal User Interfaces*. Vol. 9, issue 4, pp. 275-286, 2015.
- [5] Dai, J., Li, Y., He, K., Sun J. R-FCN: Object Detection via Region-based Fully Convolutional Networks. In *Advances in neural information processing systems*, pp. 379-387, 2016.
- [6] Poggi, M., Mattoccia, S. A wearable mobility aid for the visually impaired based on embedded 3d vision and deep learning. *Proceeding of IEEE Symposium on Computers and Communication*, pp. 208-213, 2016.

- [7] Zientara, P.,A., Lee, S., Smith, G., H., Brenner, R., Itti, L., Rosson M., B., Carroll, J., M., Irick K., M., Narayanan, V. Third Eye: A shopping assistant for the visually impaired. *Computer* Vol. 50, Issue 2, pp. 16-24, 2017.
- [8] Liu, Ch., Mao, J., Sha, F., Yuille, A. Attention Correctness in Neural Image Captioning. *Proceedings of the Thirty-First AAAI Conference on Artificial Intelligence*, pp. 4176-4182, 2017.
- [9] Laina, I., Rupprecht, C., Belagiannis, V., Tombari, F., Navab, N. Deeper depth prediction with fully convolutional residual networks. *Fourth International Conference on 3D Vision (3DV)*, pp. 239-248, 2016.
- [10] Ohn-Bar, E., Kitani, K., Asakawa, Ch. Personalized Dynamics Models for Adaptive Assistive Navigation Interfaces. *arXiv:1804.04118, [cs.LG]*, 2018.
- [11] Ren, Sh., He, K., Girshick, R., and Sun, J. Faster R-CNN: Towards real-time object detection with region proposal networks. In *Advances in neural information processing systems*, pp. 91-99, 2015.
- [12] Kensing, F., Simonsen, J., and Bødker, K. MUST: A Method for Participatory Design. *Hum-Comput Interact*, vol. 13, no. 2, pp. 167-198, Jun. 1998.
- [13] Carroll, J. M., Rosson, M. B. Participatory design in community informatics. *Des. Stud.*, vol. 28, no. 3, pp. 243-261, May 2007.
- [14] Owayjan, M., Hayek, A., Nassrallah, H., Eldor, M. Smart Assistive Navigation System for Blind and Visually Impaired Individuals. *2015 International Conference on Advances in Biomedical Engineering (ICABME)*, 2015.
- [15] Dunai, L. D., Lengua, I. L., Tortajada, I., Brusola Simon, F. Obstacle detectors for visually impaired people. *2014 International Conference on Optimization of Electrical and Electronic Equipment (OPTIM)*, 2014.