

CS306: Introduction to IT Security

Assignment Project Exam Help

Fall 2020

<https://powcoder.com>

Lecture 4: Ciphers in Practice (I)

Add WeChat powcoder

Instructor: Nikos Triandopoulos

September 22, 2020



STEVENS
INSTITUTE of TECHNOLOGY
THE INNOVATION UNIVERSITY®

Assignment Project Exam Help

<https://powcoder.com>

4.0 Announcements

Add WeChat powcoder

CS306: Other announcements

- ◆ Homework assignment HW1 is out
 - ◆ due in almost two weeks: Friday, October 2
 - ◆ covering perfect secrecy, classical ciphers and OTP
 - ◆ relevant materials
 - ◆ Lectures 2.2, 2.3, 3.1, 3.2, lecture 4.demo
 - ◆ Lab 2
- ◆ please
 - ◆ start early
 - ◆ ask for help if needed
 - ◆ respect the non-collaboration policy

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

CS306: Tentative Syllabus

| Week | Date | Topics | Reading | Assignment |
|------|--------|---------------------------------|-----------------------|-------------|
| 1 | Sep 1 | Introduction | Lecture 1 | - |
| 2 | Sep 8 | Symmetric-key encryption | Lecture 2 | Lab 1 |
| 3 | Sep 15 | Perfect secrecy | Lecture 3 | Lab 2, HW 1 |
| 4 | Sep 22 | Public-key crypto I | | |
| 5 | Sep 29 | Public-key crypto II | | |
| 6 | Oct 6 | Access control & authentication | | |
| - | Oct 13 | No class (Monday schedule) | | |
| 7 | Oct 20 | Midterm | All materials covered | |

CS306: Tentative Syllabus

(continued)

| Week | Date | Topics | Reading | Assignment |
|------|----------------------|----------------------------------|---------------------------|------------|
| 8 | Oct 27 | Software & Web security | | |
| 9 | Nov 3 | Network security | | |
| 10 | Nov 10 | Database security | | |
| 11 | Nov 17 | Cloud security | | |
| 12 | Nov 24 | Privacy | | |
| 13 | Dec 1 | Economics | | |
| 14 | Dec 8 | Legal & ethical issues | | |
| 15 | Dec 10 (or later) | Final (closed “books”) | All materials covered* | |

Last week

- ◆ Symmetric-key Cryptography

- ◆ Perfect secrecy

- ◆ The One-Time Pad cipher

- ◆ Demo

- ◆ Why encryption matters?

- ◆ Using the Wireshark packet analyser

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Today

- ◆ Ciphers in practice
 - ◆ The big picture
 - ◆ Computational security
 - ◆ Pseudo-randomness
 - ◆ stream ciphers, pseudorandom generators
- ◆ Demo
 - ◆ The Caesar and Vigenère ciphers and their cryptanalysis
 - ◆ Pseudo-randomness in practice

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

**4.1 Introduction to
modern cryptography**

Cryptography / cryptology

- ◆ Etymology

- ◆ two parts: “crypto” + “graphy” / “logy”
- ◆ original meaning: κρυπτός + γράφω / λόγος (in Greek)
- ◆ English translation: secret + write / speech, logic
- ◆ meaning: secret writing / the study of secrets
- ◆ Historically developed/studied for secrecy in communications
 - ◆ message encryption in the symmetric-key setting
 - ◆ main application area: use by military and governments

Classical Vs. modern cryptography

antiquity – ~70s

~80s – today

“the **art** of **writing** and **solving codes**”

“the study of **mathematical techniques** for **securing** information, systems, and distributed computations against **adversarial attacks**”

<https://powcoder.com>

Add WeChat powcoder

◆ approach

- ◆ ad-hoc design
- ◆ trial & error methods
- ◆ empirically evaluated

◆ approach

- ◆ systematic design & analysis
- ◆ formal notions of security (or adversary)
- ◆ rigorous proofs of security (or insecurity)

Example: Classical Vs. modern cryptography for encryption

antiquity – ~70s

~80s – today

“the **art** of **writing** and **solving codes**”

“the study of **mathematical techniques** for **securing** information, systems, and distributed computations against **adversarial attacks**”

<https://powcoder.com>

◆ **ad-hoc study**

- ◆ vulnerabilities/insecurity of
 - ◆ Caesar's cipher
 - ◆ shift cipher
 - ◆ mono-alphabetic substitution cipher
 - ◆ Vigenère cipher

◆ **rigorous study**

- ◆ **problem statement**: secret communication over insecure channel
- ◆ **abstract solution concept**: symmetric encryption, Kerckhoff's principle, perfect secrecy
- ◆ **concrete solution & analysis**: OTP cipher, proof of security

Example: Differences of specific ciphers

Caesar's/shift/mono-alphabetic cipher

The one-time pad

- ◆ substitution ciphers
 - ◆ Caesar's cipher
 - ◆ **shift is always 3**
 - ◆ shift cipher
 - ◆ **shift is unknown and the same for all characters**
 - ◆ mono-alphabetic substitution/Vigènere cipher
 - ◆ **shift is unknown and the same for all/many character occurrences**
- ◆ also, a substitution cipher
 - ◆ **shift is unknown and independent for each character occurrence**

Formal treatment in modern cryptography

Problem is formulated as an abstract crypto primitive

- ◆ captures the essence of the problem at hand, provides clarity and focus

Design & evaluation of crypto primitives follows a systematic process

- ◆ (A) **formal definitions** (what it means for a crypto primitive to be secure?)
<https://powcoder.com>
- ◆ (B) **precise assumptions** (which forms of attacks are allowed – and which aren't?)
Add WeChat powcoder
- ◆ (C) **provable security** (why a candidate solution is secure – or not)?

(A) Formal definitions

abstract but rigorous description of security problem

- ◆ **computing setting** (to be considered)
 - ◆ involved parties, communication model, core functionality
- ◆ **underlying cryptographic scheme** (to be designed)
 - ◆ e.g., symmetric-key encryption scheme
- ◆ **desired properties** (to be achieved)
 - ◆ security related
 - ◆ non-security related
 - ◆ e.g., correctness, efficiency, etc.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

(A) Why formal definitions are important?

- ◆ **successful project management**

- ◆ good design requires clear/specific security goals
 - ◆ helps to avoid critical omissions or over engineering

- ◆ **provable security**

- ◆ rigorous evaluation requires a security definition
 - ◆ helps to separate secure from insecure solutions

- ◆ **qualitative analysis/modular design**

- ◆ thorough comparison requires an exact reference
 - ◆ helps to secure complex computing systems

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example: Problem at hand

abstract but rigorous description of **security problem** (to be solved)

Assignment  **Project communication** **Help**

<https://powcoder.com>

Add WeChat powcoder
Insecure channel




Example: Formal definitions (1)

- ◆ computing setting

(to be considered)


- ◆ e.g., involved parties, communication model, core functionality



Example: Formal definitions (2)

◆ underlying cryptographic scheme

(to be designed)



symmetric-key encryption scheme

- ◆ Alice and Bob share and use a key k
- ◆ Alice encrypts plaintext m to ciphertext c and sends c instead of m
- ◆ Bob decrypts received c to get a message m'

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Example: Formal definitions (3)

- ◆ **desired properties**


(to be achieved)

- ◆ **security (informal)**



Eve “cannot learn” m (from c)

- ◆ **correctness (informal)**



If Alice encrypts m to c , then Bob decrypts c to (the original message) m

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Example: Formal definitions (4)


Perfect correctness

- for any $k \in \mathcal{K}$, $m \in \mathcal{M}$ and any ciphertext c output of $\text{Enc}_k(m)$, it holds that

$$\Pr[\text{Dec}_k(c) = m] = 1$$

Perfect security (or information-theoretic security)

- the adversary should be able to learn no additional information on m



(B) Precise assumptions

precise description of all relevant problem components

- ◆ **adversary / attacker**
 - ◆ type of attacks - a.k.a. **threat model**
 - ◆ **capabilities** (e.g., a priori knowledge, access to information, party corruptions)
 - ◆ **limitations** (e.g., bounded memory, passive Vs. active)
- ◆ **computational assumptions** (about hardness of certain tasks)
 - ◆ e.g., factoring of large composite numbers is hard
- ◆ **computing setting**
 - ◆ system set up, initial state, key distribution, randomness...
 - ◆ means of communication (e.g., channels, rounds, ...)
 - ◆ timing assumptions (e.g., synchronicity, epochs, ...)

(B) Why precise assumptions are important?

- ◆ **basis** for proofs of security
 - ◆ security holds under specific assumptions
- ◆ **comparison** among possible solutions
 - ◆ relations among different assumptions
 - ◆ stronger/weaker (i.e., less/more plausible to hold), “A implies B” or “A and B are equivalent”
 - ◆ refutable Vs. non-refutable
- ◆ **flexibility** (in design & analysis)
 - ◆ **validation** – to gain confidence or refute
 - ◆ **modularity** – to choose among concrete schemes that satisfy the same assumptions
 - ◆ **characterization** – to identify simplest/minimal/necessary assumptions


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Example: Precise assumptions (1)

◆ adversary

- ◆ type of attacks – a.k.a. **threat model**  eavesdropping
- ◆ **capabilities** (e.g., a priori knowledge, access to information, party corruptions)
- ◆ **limitations** (e.g., bounded memory, passive Vs. active)



Eve may know the a priori distribution of messages sent by Alice



Eve doesn't know/learn the secret k (shared by Alice and Bob)



Example: Precise assumptions (2)

- ◆ **computational assumptions** (about hardness of certain tasks)
 - ◆ e.g., factoring of large composite numbers is hard



Assignment Project Exam Help
no computational assumptions
– a.k.a. perfect secrecy (or information-theoretic security)


<https://powcoder.com>

Add WeChat powcoder



Example: Precise assumptions (3)

◆ computing setting

- ◆ **system set up**, initial state, **key distribution**, **randomness**...  key k is generated randomly using the uniform distribution
- ◆ means of **communication** (e.g., channels, rounds, messages...)
- ◆ timing assumptions (e.g., synchronicity, epochs, ...)

 key k is securely distributed to and securely stored at Alice and Bob

 one message m is only communicated  k, m are chosen independently (for simplicity in our initial security definition)




Possible eavesdropping attacks (I)

An attacker may possess a

- ◆ **collection of ciphertexts**

- ◆ **ciphertext only attack** (or simply EAV)



<https://powcoder.com>


Add WeChat powcoder

Possible eavesdropping attacks (II)

An attacker may possess a

- ◆ collection of plaintext/ciphertext pairs

- ◆ known plaintext attack



Possible eavesdropping attacks (III)


An attacker may possess a

Assignment Project Exam Help

<https://powcoder.com>

- ◆ collection of plaintext/ciphertext pairs for plaintexts selected by the attacker
 - ◆ chosen plaintext attack (CPA)

Add WeChat powcoder



➡ **Advanced** threat model

Possible eavesdropping attacks (IV)


An attacker may possess a

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


- ◆ collection of plaintext/ciphertext pairs for ciphertexts selected by the attacker
 - ◆ chosen ciphertext attack (CCA)



Main security properties against eavesdropping

“plain” security

- ◆ protects against ciphertext-only attacks




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

“advanced” security

- ◆ protects against chosen plaintext attacks



(C) Provably security

Security

- ◆ subject to certain **assumptions**, a scheme is proved to be **secure** according to a specific **definition**, against a specific **adversary**
- ◆ in practice the scheme may break if
 - ◆ some assumptions do not hold or the attacker is more powerful

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Insecurity

- ◆ a scheme is proved to be **insecure** with respect to a specific **definition**
- ◆ it suffices to find a **counterexample attack**

(C) Why provable security is important?

Typical performance

- ◆ in some areas of computer science, **formal proofs may not be essential**
- ◆ behavior of hard-to-analyze algorithms is simulated to experimentally study their performance on “typical” inputs
- ◆ in practice, **typical/average case** occurs

Worst case performance

- ◆ in cryptography and secure protocol design, **formal proofs are essential**
- ◆ “experimental” security analysis is not possible
- ◆ the notion of a “typical” adversary makes little sense and is unrealistic
- ◆ in practice, **worst case attacks will occur**
 - ◆ an adversary will use any means in its power to break a scheme

Assignment Project Exam Help

<https://powcoder.com>

4.2 Computational
security

Add WeChat powcoder

The big picture: OTP is perfect but impractical!

We formally defined and constructed the perfectly secure OTP cipher

- ◆ This scheme has some major drawbacks
 - ◆ it employs a very large key which can be used only once!
- ◆ Such limitations are unavoidable and make OTP not practical
 - ◆ why?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Now, what?

Our approach: Relax “perfectness”

Initial model

- ◆ the **perfect secrecy** (or security) requires that
 - ◆ the ciphertext **leaks absolutely no extra information** about the plaintext
 - ◆ to adversaries of **unlimited computational power**

Refined model

- ◆ a relaxed notion of security, called **computational security**, requires that
 - ◆ the ciphertext leaks **a tiny amount of extra information** about the plaintext
 - ◆ to adversaries with **bounded computational power**

Computational security

- ◆ to be contrasted against information-theoretic security
 - ◆ *de facto* way to model security in most settings
 - ◆ an integral part of modern cryptography w/ rigorous mathematical proofs
- ◆ entails two relaxations
 - ◆ security is guaranteed against **efficient** adversaries
 - ◆ if an attacker invests in sufficiently large resources, it may break security
 - ◆ goal: make required resources larger than those available to any realistic attacker!
 - ◆ security is guaranteed in a **probabilistic** manner
 - ◆ with some **small probability**, an attacker may break security
 - ◆ goal: make attack probability sufficiently small so that it can be practically ignored!

Towards a rigorous definition of computational security

Concrete approach

- ◆ “A scheme is (t, ϵ) -secure if any attacker A , running for time at most t , succeeds in breaking the scheme with probability at most ϵ ”

Assignment Project Exam Help

<https://powcoder.com>

Asymptotic approach

- ◆ “A scheme is secure if any efficient attacker A succeeds in breaking the scheme with at most negligible probability”

Add WeChat powcoder

Examples

- ◆ almost optimal security guarantees
 - ◆ if key length n , the number of possible keys is 2^n
 - ◆ attacker running for time t succeeds w/ prob. at most $\sim t/2^n$ (brute-force attack)
- ◆ if $n = 60$, security is enough for attackers running a desktop computer
 - ◆ 4 GHz (4×10^9 cycles/sec), checking all 2^{60} keys require about 9 years
 - ◆ if $n = 80$, a supercomputer would still need ~ 2 years
- ◆ today's recommended security parameter is at least $n = 128$
 - ◆ large difference between 2^{80} and 2^{128} ; e.g., #seconds since Big Bang is $\sim 2^{58}$
 - ◆ a once-in-100-years event corresponds to probability 2^{-30} of happening at a particular sec
 - ◆ if within 1 year of computation attack is successful w/ prob. $1/2^{60}$ then it is more likely that Alice and Bob are hit by lightning

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

**4.3 Symmetric encryption,
revisited: Security**

Three equivalent “looks” of perfect secrecy

1) a posteriori = a priori

For every $\mathcal{D}_{\mathcal{M}}$, $m \in \mathcal{M}$ and $c \in \mathcal{C}$, for which $\Pr[C = c] > 0$, it holds that

$$\Pr[M = m \mid C = c] = \Pr[M = m]$$

2) \mathbf{C} is independent of \mathbf{M}

For every $m, m' \in \mathcal{M}$ and $c \in \mathcal{C}$, it holds that



$$\Pr[\text{Enc}_K(m) = c] = \Pr[\text{Enc}_K(m') = c]$$

3) indistinguishability

For every \mathcal{A} , it holds that

$$\Pr[b' = b] = 1/2$$

ciphertext looks **completely random**



Security relaxation

Perfect security: M , $\text{Enc}_k(M)$ are independent, **unconditionally**

- ◆ no extra information is leaked to any attacker


Computational security: M , $\text{Enc}_k(M)$ are independent, **for all practical purposes**

- ◆ no extra information is leaked **but a tiny amount**
 - ◆ e.g., with prob. 2^{-128} (or much less than the likelihood of being hit by lightning)
- ◆ to **computationally bounded** attackers
 - ◆ e.g., who cannot count to 2^{128} (or invest work of more than one century)
- ◆ attacker's best strategy remains **ineffective**
 - ◆ **random guess** a secret key or **exhaustive search** over key space (brute-force attack)

Recall: Main security properties against eavesdropping

“plain” security

- ◆ protects against ciphertext-only attacks




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

“advanced” security

- ◆ protects against chosen plaintext attacks



Computational EAV-security or indistinguishability

Relax the definition of perfect secrecy that is based on indistinguishability

- ◆ require that target messages m_0, m_1 are chosen by a **PPT** attacker
- ◆ require that no such attacker can distinguish $\text{Enc}_k(m_0)$ from $\text{Enc}_k(m_1)$

Assignment Project Exam Help

<https://powcoder.com> non negligibly better than guessing



3) indistinguishability

For every \mathcal{A} , it holds that


$$\Pr[b' = b] = 1/2 + \text{negligible}$$

PPT

something that can
be safely ignored



Computational CPA-security



Advanced security implies probabilistic encryption – why?

Strengthen the definition of computational plain-security

- ◆ allow attacker to have access to an **encryption “box”**
- ◆ allow the attacker to select m_0, m_1 **after** using this “box” (as many times as desired)

Assignment Project Exam Help

<https://powcoder.com>



3) indistinguishability

For every PPT \mathcal{A} , it holds that

$$\Pr[b' = b] = 1/2 + \text{negligible}$$

PPT

something that can
be safely ignored



Assignment Project Exam Help

<https://powcoder.com>
Add WeChat powder

**4.4 Symmetric encryption,
revisited: OTP with
pseudorandomness**

Perfect secrecy & randomness

Role of randomness in encryption is **integral**

- ◆ in a perfectly secret cipher, the ciphertext **doesn't depend** on the message
 - ◆ the ciphertext appears to be **truly random**
 - ◆ the uniform key-selection distribution is **imposed also onto** produced ciphertexts
 - ◆ e.g., $c = k \text{ XOR } m$ (for uniform k and any distribution over m)

Add WeChat powcoder

When security is computational, randomness is **relaxed** to “pseudorandomness”

- ◆ the ciphertext appears to be “**pseudorandom**”
 - ◆ it **cannot be efficiently distinguished** from truly random

Symmetric encryption as “OPT with pseudorandomness”

Stream cipher

Uses a **short** key to encrypt **long** symbol **streams** into a **pseudorandom** ciphertext

- ◆ based on abstract crypto primitive of **pseudorandom generator (PRG)**

Block cipher


Uses a **short** key to encrypt **blocks** of symbols into **pseudorandom** ciphertext blocks

- ◆ based on abstract crypto primitive of **pseudorandom function (PRF)**

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


**4.4.1 Pseudorandom
generators**

Stream ciphers



Pseudorandom generators (PRGs)

Deterministic algorithm G that
on input a **seed** $s \in \{0,1\}^t$, outputs $G(s) \in \{0,1\}^{l(n)}$



Assignment Project Exam Help
a.k.a. stream cipher

G is a PRG if:

<https://powcoder.com>

- ◆ **expansion**

Add WeChat powcoder


- ◆ for polynomial l , it holds that for any n , $l(n) > n$
- ◆ models the process of **extracting** randomness from a short random string

- ◆ **pseudorandomness**

- ◆ no efficient statistical test can tell apart $G(s)$ from a truly random string

Generic PRG-based symmetric encryption

- ◆ **Fixed-length** message encryption



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

encryption scheme is plain-secure
as long as the underlying PRG is secure

Generic PRG-based symmetric encryption (cont.)

- ◆ **Bounded- or arbitrary-length** message encryption
 - ◆ specified by a mode of operation for using an underlying stateful stream cipher, repeatedly, to encrypt/decrypt a stream of symbols

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Stream ciphers: Modes of operations

- ◆ **Bounded or arbitrary-length** message encryption

on-the-fly computation of new pseudorandom bits, no IV needed, plain-secure



random IV used for every new message is sent along with ciphertext, advanced-secure