

Andrew login ID: \_\_\_\_\_

Full Name: \_\_\_\_\_

Recitation Section: \_\_\_\_\_

## CS 15-213, Spring 2008

### Exam 1

Tue. February 26, 2008

#### Instructions:

- Make sure that your exam is not missing any sheets, then write your full name, Andrew login ID, and recitation section (A–H) on the front.
- Write your answers in the space provided below the problem. If you make a mess, clearly indicate your final answer.
- The exam has a maximum score of 70 points.
- The problems are of varying difficulty. The point value of each problem is indicated. Pile up the easy points quickly and then come back to the harder problems.
- This exam is OPEN BOOK. You may use any books or notes you like. No calculators or other electronic devices are allowed.
- Good luck!

1 (8):
2 (8):
3 (10):
4 (9):
5 (8):
6 (8):
7 (11):
8 (8):
TOTAL (70):

### Problem 1. (8 points):

For this problem, assume the following:

- We are running code on a 6-bit machine using two's complement arithmetic for signed integers.
- `short` integers are encoded using 3 bits.
- Sign extension is performed whenever a `short` is casted to an `int`
- Right shifts of `ints` are arithmetic.

Fill in the empty boxes in the table below. The following definitions are used in the table:

```
int a = -29;
short b = (short)a;
unsigned ua = a;
int x = -21;
short y = (short)x;
unsigned ux = x;
```

Note: You need not fill in entries marked with “—”.

Expression	Decimal Representation	Binary Representation
—	27	
—		100100
x		
y		
ux		
a >> 2		
ua >> 2		
b << 1		
−TMin		

## Problem 2. (8 points):

### Part A

Fill in the blanks in the table below with the number described in the first column of each row. You can give your answers as unexpanded simple arithmetic expressions (such as  $15^{213} + 42$ ); you should not have trouble fitting your answers into the space provided.

Description	Number
<code>int x=1; float *f = (float *)&amp;x; What is the value of *f?</code>	
<code>int x=-1; float *f = (float *)&amp;x; What is the value of *f?</code>	
Smallest positive integer that cannot be represented as a 32-bit float	

## Assignment Project Exam Help

### Part B

Assume we are running code on an IA32 machine, which has a 32-bit word size and uses two's complement arithmetic for signed integers. Consider the following definition:

```
int x = foo();
```

Add WeChat powcoder

Fill in the empty boxes in the table below. For each of the C expressions in the first column, either:

- State that it is true of all argument values, or
- Give an example where it is not true.

Puzzle	True / Counterexample
$x < 0 \Rightarrow -x > 0$	
$x \wedge \sim x < 0$	
$(x \wedge (x \gg 31)) + 1 > 0$	
$(( (!!x) << 31) \gg 31) \& x == x$	

### Problem 3. (10 points):

Consider an 8-bit IEEE floating-point representation with:

- 1 sign bit
- 3 exponent bits (therefore the bias  $B = 2^{3-1} - 1 = 3$ )
- 4 mantissa bits

A. Fill in the blanks in the following table. Express numerical values as fractions (e.g.,  $277/512$ ).

Number	Bit representation
$3/8$	
$9/2$	
	1 000 1000

B. Give the bit representation and numerical value of the largest number representable in this format as a *denormalized* floating-point number.

C. Give the bit representation and numerical value of the largest number representable in this format as a *normalized* floating-point number.

#### Problem 4. (9 points):

Consider the following x86-64 assembly code:

```
# on entry: %rdi = n, %rsi = A
000000000040056e <bar>:
40056e: 41 b8 00 00 00 00    mov     $0x0,%r8d
400574: 41 b9 00 00 00 00    mov     $0x0,%r9d
40057a: 41 39 f9             cmp     %edi,%r9d
40057d: 7d 30              jge     4005af <bar+0x41>
40057f: ba 00 00 00 00    mov     $0x0,%edx
400584: 39 fa             cmp     %edi,%edx
400586: 7d 1f             jge     4005a7 <bar+0x39>
400588: 49 63 c1          movslq  %r9d,%rax
40058b: 48 8b 0c c6        mov     (%rsi,%rax,8),%rcx
40058f: 48 63 c2          movslq  %edx,%rax
400592: 8b 01 81          mov     (%rcx,%rax,4),%eax
400595: 41 0f af c1       imul    %r9d,%eax
400599: 0f af c2          imul    %edx,%eax
# Instruction cltq is equivalent to "movslq %eax,%rax"
40059c: 48 98             cltq
40059e: 49 01 c0          add     %rax,%r8
4005a1: ff c2            inc     %edx
4005a3: 39 fa             cmp     %edi,%edx
4005a5: 7c e8            jl      40058f <bar+0x21>
4005a7: 41 ff c1          inc     %r9d
4005aa: 41 39 f9          cmp     %edi,%r9d
4005ad: 7c d0            jl      40057f <bar+0x11>
4005af: 4c 89 c0          mov     %r8,%rax
4005b2: c3              retq
```

Fill in BOTH of the blanks below for the corresponding C code.

```
long bar(int n, _____ A) {           // Fill in type of A
    long sum = 0;
    int i,j;
    for (i = 0; i < n; i++) {
        for(j = 0; j < n; j++)

            sum += _____;           // Fill in expression
    }
    return sum;
}
```

### Problem 5. (8 points):

Consider the C code below, where H and J are constants declared with #define.

```
int array1[H][J];
int array2[J][H];

int copy_array(int x, int y) {
    array2[y][x] = array1[x][y];

    return 1;
}
```

Suppose the above C code generates the following x86-64 assembly code:

```
# On entry:
#     %edi = x
#     %esi = y
#
copy_array:
    movslq    %edi,%rdi
    movslq    %esi,%rsi
    movq      %rdi,%rax
    leaq      (%rsi,%rsi,8), %rdx
    salq      $5, %rax
    subq      %rdi, %rax
    addq      %rdi, %rdx
    leaq      (%rsi,%rax,2), %rax
    movl      array1(,%rax,4), %eax
    movl      %eax, array2(,%rdx,4)
    movl      $1, %eax
    ret
```

What are the values of H and J?

H =

J =

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

### Problem 6. (8 points):

Consider the following data structure declaration:

```
struct node{
    char x;
    int array[2];
    int idx;
    struct node *next;
};
```

Below are given four C functions and four x86-64 code blocks.

```
char *mon(struct node *ptr){
    return &ptr->x;
}
```

A	movl 8(%rdi),%eax movl %eax,12(%rdi)
---	---

```
int tue(struct node *ptr){
    return ptr->array[ptr->idx];
}
```

B	movq %rdi,%rax
---	----------------

```
void wed(struct node *ptr){
    ptr->idx = ptr->array[1];
    return;
}
```

C	movq 16(%rdi),%rax movsbl (%rax),%eax
---	--

```
char thu(struct node *ptr){
    ptr = ptr->next;
    return ptr->x;
}
```

D	movslq 12(%rdi),%rax movl 4(%rdi,%rax,4), %eax
---	---

In the following table, next to the name of each x86-64 code block, write the name of the C function that it implements.

Code Block	Function Name
A	
B	
C	
D	

### Problem 7. (11 points):

The next problem concerns code generated by GCC for a function involving a switch statement. The code uses a jump to index into the jump table:

```
400518: ff 24 d5 40 06 40 00  jmpq    *0x400640(,%rdx,8)
```

Using GDB, we extract the 8-entry jump table as:

```
0x400640: 0x000000000000400527
0x400648: 0x000000000000400525
0x400650: 0x000000000000400531
0x400658: 0x00000000000040051f
0x400660: 0x000000000000400525
0x400668: 0x000000000000400525
0x400670: 0x000000000000400525
0x400678: 0x000000000000400531
```

The following block of disassembled code implements the branches of the switch statement:

```
# on entry: %rdi = a, %rsi = b, %rdx = c
400510: 31 c0      xor     %eax,%eax
400512: 48 83 fa 01  cmp     $0x7,%rdi
400516: 77 0d      ja     400525 <_Z4testllll+0x15>
400518: ff 24 d5 40 06 40 00  jmpq    *0x400640(,%rdx,8)
40051f: 48 89 f0    mov     %rsi,%rax
400522: 48 29 f8    sub     %rdi,%rax
400525: f3 c3      repz retq # repz is a no-op here
400527: 48 01 f7    add     %rsi,%rdi
40052a: 48 89 f8    mov     %rdi,%rax
40052d: 48 31 f0    xor     %rsi,%rax
400530: c3         retq
400531: 48 8d 46 2a  lea     0x2a(%rsi),%rax
400535: c3         retq
```



Fill in the blank portions of C code below to reproduce the function corresponding to this object code. You can assume that the first entry in the jump table is for the case when c equals 0.

```
long test(long a, long b, long c)
{
    long answer = ____;
    switch(c)
    {
        case ____:
            answer = ____;
            break;
        case ____:
        case ____:
            answer = ____;
            break;
        case ____:
            a = ____;
            /* Fall through */
        case ____:
            answer = ____;
            break;
        default:
            answer = ____;
    }

    return answer;
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Assignment Project Exam Help

<https://powcoder.com>

- # Add WeChat powcoder

B. Rearrange the above fields in `booklist` to conserve the most space in the memory below. Label the bytes that belong to the various fields with their names and clearly mark the end of the struct. Use hatch marks to indicate bytes that are allocated in the struct but are not used.

The figure shows a 3x16 grid of symbols. Each row contains a repeating sequence of four symbols: '+', '-', '|', and 'x'. The first row starts with '+', the second with '-', and the third with '|'. This pattern repeats four times across the sixteen columns.

- Page 10 of 10