Imperial College London – Department of Computing

MSc in Computing Science

580: Algorithms Tutorial 2

- 1. (Part of a 2015 exam question.)
 - (a) Using either Java or pseudocode, write a recursive procedure Pow(x, N) to compute x^N , where N is a positive integer. Use a divide and conquer strategy. *Hint*:

$$x^N = x^{N/2} \times x^{N/2} \qquad \qquad \text{for even } N$$

$$x^N = x^{(N-1)/2} \times x^{(N-1)/2} \times x \qquad \qquad \text{for odd } N.$$

(b) Argest or present as Europie Complex and of yield procedure in the following cases:

$$trye = \begin{cases} f(N) = \begin{cases} f(N) < N \le c \\ f(N) > c \end{cases}$$

What is \overline{c} ?

(c) Solve your expressions for T(N) using the master method. Show each step.

Add WeChat powcoder

(a)

1: **procedure** Pow(x, n)2: if n == 1 then return x3: end if 4: tmp = Pow(x, n/2)5: if $n \mod 2 == 0$ then 6: **return** $tmp \times tmp$ 7: end if 8: **return** $tmp \times tmp \times x$ 9: 10: end procedure

Key feature: Pow should be called recursively ONCE, in line 5. If it is called more than once then the complexity will be $\Theta(N)$.

(b)
$$T(N) = \left\{ \begin{array}{ll} \Theta(1) & \text{, if } N=1 \\ T(\lfloor N/2 \rfloor) + \Theta(1) & \text{, if } N>1 \end{array} \right.$$

- So, c=1. Symbols representing constants would be acceptable in place of the $\Theta(1)$ terms. The second formula must include $\lfloor N/2 \rfloor$, not N/2. The expression is not correct for all N if it uses T(N/2).
- (c) To apply the master method you need to first substitute the recurrence into the expression T(N) = aT(N/b) + f(N), while ignoring any floors or ceilings. This gives us a = 1, b = 2 and $f(N) = \Theta(1)$. Then compute $N^{\log_b a}$, which in this case is $N^0 = 1$. So, $N^{\log_b a} = \Theta(1)$ and $f(N) = \Theta(1) = \Theta(N^{\log_b a} \log_2^0 N)$. Therefore, Case 2 of the master method applies and $T(N) = \Theta(N^{\log_b a} \log_2 N) = \Theta(\log_2 N)$.

Assignment Project Exam Help

https://powcoder.com

Add WeChat powcoder