

The background of the slide features a large, faint, light blue seal of Georgetown University. The seal is circular and contains an eagle with a shield on its chest, holding an olive branch and arrows. Above the eagle is a lyre. The text "DOMACI IN MEXICO" is at the top, "UTRAQUE UNUM" is on a banner across the eagle, and "GEORGIOPOLITANA" is at the bottom.

*ANLY-601*

*Advanced Pattern Recognition*

Assignment Project Exam Help  
*Spring 2018*

<https://powcoder.com>

Add WeChat powcoder

L6 – Bounds on Error Rates

# Bounding the Bayes Error Rate

Recall the likelihood ratio tests, written in terms of the negative log of the likelihood

$$h(x) \equiv -\log \left( \frac{p(x | \omega_1)}{p(x | \omega_2)} \right) \begin{matrix} \omega_1 \\ < \\ \omega_2 \end{matrix} -\log \eta \equiv t$$

Assignment Project Exam Help

Computation of the Bayes error rate for all but the simplest cases (e.g. Gaussian features  $x$  with equal class-conditional covariance matrices) is difficult.

<https://powcoder.com>

Calculating the integrals

Add WeChat powcoder

$$E_2 = \int_{L1} p(x | \omega_2) d^n x = \int_{-\infty}^t p(h | \omega_2) dh$$

is difficult or impossible

$$E_1 = \int_{L2} p(x | \omega_1) d^n x = \int_t^{\infty} p(h | \omega_1) dh$$

# *Bounding the Bayes Error Rate*

Instead, we seek bounds on the error that are

Hopefully tight

Easy to calculate

Assignment Project Exam Help

In practice, we will use empirical error estimates, but the theoretical bounds here provide useful tools to reason with.

<https://powcoder.com>

Add WeChat powcoder

The bounds point out factors entering the error rate. That is, the theoretical framework helps you conceptualize the problem.

# A Calculable Case

Let both class-conditional densities be normal, with the same covariance matrices  $\Sigma_1 = \Sigma_2 = \Sigma$ . The neg. log-likelihood ratio is then

$$h(x) = \frac{1}{2} (M_2 - M_1)^T \Sigma^{-1} x + \frac{1}{2} (M_1^T \Sigma^{-1} M_1 - M_2^T \Sigma^{-1} M_2)$$

since  $x$  is Gaussian, and  $h$  is linear in  $x$ ,  $h$  is Gaussian. Its mean and variance are

$$E[h | \omega_1] = -\frac{1}{2} (M_2 - M_1)^T \Sigma^{-1} (M_2 - M_1) \equiv -\theta$$

$$E[h | \omega_2] = \frac{1}{2} (M_2 - M_1)^T \Sigma^{-1} (M_2 - M_1) \equiv \theta$$

$$\sigma_i^2 = (M_2 - M_1)^T \Sigma^{-1} (M_2 - M_1) = 2\theta$$



# Calculable Case

The error rates become

$$E_2 = \int_{-\infty}^t p(h | \omega_2) dh = \text{erf}\left(\frac{t + \theta}{\sigma}\right)$$

$$E_1 = \int_t^{\infty} p(h | \omega_1) dh = 1 - \text{erf}\left(\frac{t + \theta}{\sigma}\right)$$

$$\text{erf}(z) \equiv \frac{1}{\sqrt{2\pi}} \int_{-\infty}^z e^{-\xi^2/2} d\xi$$



# Back to Bounds

## Chernoff Bound

Classification error rate is

$$\begin{aligned}\mathcal{E} &= P_1 \int_{L2} p(x|\omega_1) d^n x + P_2 \int_{L1} p(x|\omega_2) d^n x \\ &= \int \min \left[ P_1 p(x|\omega_1), P_2 p(x|\omega_2) \right] d^n x\end{aligned}$$

Use inequality  $\min[a, b] \leq a^s b^{1-s}$ ;  $a, b \geq 0, 0 \leq s \leq 1$

to obtain

$$\begin{aligned}\mathcal{E} &\leq \mathcal{E}_U = \min_s \left( P_1^s P_2^{1-s} \int p^s(x|\omega_1) p^{1-s}(x|\omega_2) d^n x \right) \\ &\equiv \min_s \left( P_1^s P_2^{1-s} e^{-\mu(s)} \right)\end{aligned}$$

# Simplification – Bhattacharyya Bound

Don't insist on minimizing with respect to s, but take s=1/2

$$E_U = \frac{1}{\sqrt{P_1 P_2}} \int \sqrt{P(x|\omega_1) P(x|\omega_2)} d^n x$$

<https://powcoder.com>

for x normal, the exponent is

Add WeChat powcoder

$$\mu(1/2) = \frac{1}{8} (M_2 - M_1)^T \left( \frac{\Sigma_1 + \Sigma_2}{2} \right)^{-1} (M_2 - M_1) + \frac{1}{2} \ln \left( \frac{\left| \frac{\Sigma_1 + \Sigma_2}{2} \right|}{\sqrt{|\Sigma_1| |\Sigma_2|}} \right)$$

# *Bhattacharyya Bound – Special Cases*

- Equal Means

$$\mu(1/2) = \frac{1}{2} \ln \left( \frac{|\Sigma_1 + \Sigma_2|}{2 \sqrt{|\Sigma_1| |\Sigma_2|}} \right)$$

Assignment Project Exam Help  
<https://powcoder.com>

Equal Covariances Add WeChat powcoder

$$\mu(1/2) = \frac{1}{8} (M_2 - M_1)^T \Sigma^{-1} (M_2 - M_1)$$





# *Single Hypothesis*

Assignment Project Exam Help  
*Tests*

<https://powcoder.com>

Add WeChat powcoder

# Single Hypothesis

May have data predominantly from one class -- e.g. failure analysis, usually have many examples of “healthy” function and only a few failures; may have many different failure modes.

Assignment Project Exam Help

Given an observation  $x$ , want to know if the corresponds to a healthy, or a failed example. Also called “novelty detection.”

Add WeChat powcoder

May use some kind of distance measure – e.g.

$$d^2 = (x - m)^T \Sigma^{-1} (x - m)$$

where  $\Sigma$  and  $m$  are the covariance and mean of the class  $\omega_1$  that one is able to model well.

# Single Hypothesis

To use this in classification

Given  $x$ , compute  $d^2$  and compare with a threshold

$d^2 \leq c$   
 $d^2 > c$

Assignment Project Exam Help

<https://powcoder.com>

where the threshold  $c$  is chosen based on both in-class, and out-of-class data, or ...

# Single Hypothesis

## Statistics of $d^2$

$d^2$  is a random variable, with mean and variance

$$\begin{aligned} E[d^2] &= E[(x-m)^T \Sigma^{-1} (x-m)] \\ &= \text{Trace} E[\Sigma^{-1} (x-m)(x-m)^T] = \text{Trace}[\Sigma^{-1} \Sigma] = N \end{aligned}$$

$$\text{var}[d^2] = E[d^4] - (E[d^2])^2$$

Note:  $d^2$  is the sum of  $N$  random identically distributed random variables. For large dimension  $N$ , we can invoke the central limit theorem with the result that  $d^2$  becomes normally distributed.

# Single Hypothesis

## Other “distance” measures

- Model the probability distribution for objects in the known class - e.g. as a Gaussian mixture

$$p(x | \omega_1) = \sum_{k=1}^Q a_k \frac{1}{\sqrt{(2\pi)^n |\Sigma_k|}} \exp -\frac{1}{2} (x - m_k)^T \Sigma_k^{-1} (x - m_k)$$

Add WeChat powcoder


where the parameters  $a_k, m_k, \Sigma_k$  are fit by maximum likelihood. Then classify a new datum  $x_0$  using a threshold test

$$-\ln p(x | \omega_1) \begin{matrix} < \\ > \end{matrix} \begin{matrix} \omega_1 \\ not \omega_1 \end{matrix} c$$

# Single Hypothesis

## Other “distance” measures, continued

Model known class by PCA subspace



The hyperplane serves as a geometric model of the known class. See Oja, Subspace methods of Pattern Recognition, Wiley and Sons, for other examples.


# Single Hypothesis

## Other distance measures (cont'd)

Model known class as a curved manifold (constructed e.g. with a neural network). Measure distance between data  $x_0$  and its projection  $F(x_0)$  onto the manifold.

The threshold test is  $d^2 = \|x_0 - F(x_0; \theta)\|^2$

Add WeChat powcoder



# *Problems with Single Hypothesis Tests*

- Usually perform worse than full Bayesian tests. If you have enough data to model both classes, performance should improve.

Assignment Project Exam Help

<https://powcoder.com>

- We turned to the single hypothesis test because one of the two classes is too sparsely sampled to model well. How does one pick the decision threshold  $c$ ?

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



GEORGETOWN UNIVERSITY