

Assignment Project Exam Help

Application of Matlab for Finance

Week 7

<https://powcoder.com>

Shi, Yining

Add WeChat powcoder

October 21, 2017

Today's Class

Assignment Project Exam Help

- ▶ Ordinary Least Squares (OLS)
- ▶ <https://powcoder.com>
- ▶ Rolling Windows Estimation
- ▶ Maximum Likelihood Estimator (MLE)

Add WeChat powcoder

Basic Linear Regression: OLS

Assignment Project Exam Help

- ▶ Y : $T \times 1$ vector of dependent variables
- ▶ X : $T \times M$ matrix of regressors (or $[1, X]$ regression with constant)
- ▶ Coefficient: $\hat{\beta} = (X'X)^{-1}X'Y$, i.e., $\hat{\beta} \rightarrow \min(Y - X\beta)'(Y - X\beta)$
- ▶ Residual: $\hat{\epsilon} = Y - \hat{Y} = Y - X\hat{\beta}$
- ▶ Mean squared error (MSE)/variance of residual: $s^2 = \frac{\hat{\epsilon}'\hat{\epsilon}}{T-M}$
- ▶ Goodness-of-fit against the benchmark: historical average (\bar{Y})

$$\begin{aligned}
 R^2 &= 1 - \frac{\sum_{i=1}^T (Y_i - \hat{Y}_i)^2}{\sum_{i=1}^T (Y_i - \bar{Y})^2} = 1 - \frac{\hat{\epsilon}'\hat{\epsilon}}{(Y - \bar{Y})'(Y - \bar{Y})} \\
 &= 1 - \frac{\text{Sum Squares of Residual}}{\text{Sum Squares of Total}}, \quad \bar{Y} = \frac{\sum_{i=1}^T Y_i}{T}
 \end{aligned}$$

OLS Regression Code

- ▶ `b = regress(y,X)` estimates the M -by-1 β coefficient estimations of regression $y = X\beta$ and stored in output variable `b`.

- ▶ `[b,bint,r,rint,stats] = regress(y,X):`

- ▶ `b`: M -by-1 matrix of the estimations of β
- ▶ `bint`: M -by-2 matrix of the 95% confidence intervals for the coefficient estimates

- ▶ `r`: T -by-1 matrix of the residual

- ▶ `rint`: T -by-2 matrix of intervals that can be used to diagnose outliers (if zero is not inside).

- ▶ `stats`: 1-by-4 vector contains the R^2 statistic, the F statistic and its p -value, and the estimate of the error variance (MSE).

Exercise 1: Basic Linear Regression

Assignment Project Exam Help

- Estimate the coefficients of the Fama-French Three-Factor model

$$r_i = \beta_i^m r_M + \beta_i^s SMB + \beta_i^v HML + \epsilon_i$$

- r_i is the excess return of portfolio
- r_M is the excess return of the market portfolio
- SMB is the size factor
- HML is the value factor
- r_M , SMB, HML are stored in sheet Factors inside excel file FF_Data.xlsx.
- Individual portfolio returns are stored in the IndusPort worksheet.

Exercise 1: Fama French Model

Assignment Project Exam Help

```
1 % Estimate the model by OLS
2 % Alternative code of reading from excel file
3 [ff_fact, ff_txt]= xlsread('FF_Data.xlsx','Factors');
4 [ff_port, ff_port_txt]= xlsread('FF_Data.xlsx','IndusPort');
5
6 % Assign X: Mkt-RF, SMB, HML (last col as rf)
7 x = ff_fact(:,1:3);
8 rf = ff_fact(:,4);
9 % Assign y, Excess returns
10 y = ff_port - rf;
11
12 % Regress with loop for each asset: the coefficients for each asset are
13 % stored in each row of beta
14 [T,K] = size(y);
15 for i = 1: K
16     beta(i,:) = regress(y(:,i),x);
17 end
18
19 % perform the same regression: read beta estimations and the statistics
20 % of the model
21 for i = 1: K
22     [beta(i,:),r,s,stats(i,:)] = regress(y(:,i),x);
23 end
```

<https://powcoder.com>

Add WeChat powcoder

Linear Model Regression

```
res = fitlm(X,y,modelspec)
```

- ▶ `res`: the LinearModel Object for the responses `y` to be fit to data matrix `X`,
- ▶ `modelspec`: model specification for the linear model with 'constant', 'linear', 'interactions', 'quadratic'.
- ▶ Refer relevant items in an objective variable, use the period sign .
 - ▶ `res.Coefficients.Estimate` returns the beta coefficient
 - ▶ `res.Coefficients.pValue` returns the significance of beta estimation
- ▶ The `fitlm` function assumes a constant term, to remove it:
 - ▶ Original model $y \sim 1 + x_1 + x_2 + x_3$
 - ▶ `terms = '1'`
 - ▶ `res = removeTerms(res,terms)`
 - ▶ New model $y \sim x_1 + x_2 + x_3$

Exercise 1: Fama-French Model

Assignment Project Exam Help

```
1 %% Residuals to fit model with nonlinear structure as example
2 y_chsmr = y(-n-1);
3 res = fitlm(x,y_chsmr,'linear');
4 terms = '1';
5 res = removeTerms(res,terms)
6 beta_full = res.Coefficients.Estimate
```

<https://powcoder.com>

Add WeChat powcoder

Rolling and Recursive Regressions

- ▶ Static coefficients may fail to adjust changes in the economy

Assignment Project Exam Help

$$Y = X\beta + e, \quad e \sim N(0, \sigma)$$

- ▶ Time-varying parameters

<https://powcoder.com>

$$Y_t = X_t\beta_t + \epsilon_t, \quad \epsilon_t \sim N(0, \sigma)$$

- ▶ Timely adjusted coefficient shall reflect more updated information;
- ▶ If coefficient change gradually, then similar coefficient in adjacent time periods (seasonal effect)
- ▶ The rolling estimates is a combination of true coefficients and sampling errors
 - ▶ True coefficient is trending: estimates display trend and noise
 - ▶ True coefficient is constant: estimates display random fluctuation and noise

Rolling and Recursive Regressions

Assignment Project Exam Help

- ▶ For a given window width τ , using the τ observations ($t = 1, \dots, \tau$) for estimation
- ▶ Advance one observation at a time ($t = 2, \dots, \tau + 1$), repeat the estimation
- ▶ Plot the estimated coefficient against time to visualize the changes
- ▶ For a sample of observations k , it shall be $k - \tau + 1$ estimates of β

Exercise 2

- ▶ For the same portfolios in the previous exercise, compute rolling β s using 60 consecutive observations
- ▶ Do the coefficient for market exposure appear constant?

Exercise 2: Rolling Estimation

Assignment Project Exam Help

```


1 % Rolling Regression - roll1.m
2 % Read data from file
3 dd = fopen('data.txt');
4 ddnum = datenum(dd, 'dd/mm/yyyy');
5
6 % Read the full sample estimation of beta for Mkt factor
7
8 % Define the Window
9 tau = 60;
10 % Loop from 1 to the end
11 for t=1:length(ddnum)
12     x_roll = x(t-tau:t,:);
13     y_roll = y_cnsmr(t-tau:t);
14     beta_roll(t,:) = regress(y_roll, x_roll);
15 end
16
17 % on plot the exposure to the market risk:
18 plotdd = datenum(tau+1:end,1);
19 plotb_full = beta_full(1)*ones(length(plotdd),1);
20 plotb_roll = beta_roll(tau+1:end,1);
21 % Plot the data
22 plot(plotdd, plotb_full, plotdd, plotb_roll);
23 datetick('x');
24 xlim([plotdd(1), plotdd(end)]);
25 % Add a legend
26 legend('Constant \beta', 'Rolling \beta', 'Location', 'NorthWest');

```

<https://powcoder.com>

Add WeChat powcoder

Estimated Beta



Maximum Likelihood

- Maximum likelihood is a popular method to estimate parameters in econometric models. In many cases, closed form estimators are not available and so non-linear optimizers are required.

- Suppose $\mathbf{X} = (x_1, x_2, \dots, x_n)$ are the samples taken from a random variable \mathbf{X} with probability distribution function (pdf) $f_n(x_n; \theta)$, where $\theta = [\mu, \sigma]'$.

- For example, $X \sim N(\mu, \sigma^2)$, $f(\theta; x) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$
- The joint density function of the sample is, by independence, equal to the product of the marginal densities, which is also known as the likelihood function with respect to the parameter set θ ,

$$L(\theta; X) = \prod_{i=1}^n f_i(x_i; \theta) = f_1(x_1; \theta) f_2(x_2; \theta) \dots f_n(x_n; \theta)$$

- The Maximum Likelihood Estimator (MLE) is the parameter set $\hat{\theta}$ that maximizes the likelihood function $L(\theta; X)$

$$L(\hat{\theta}; X) = \max_{\theta \in \Theta} L(\theta; X)$$

Log Maximum Likelihood

- It is often rather difficult to directly maximise the $L(\theta; X)$. It is much easier to maximise the log-likelihood function since $\ln(\cdot)$ is a monotonic function that maximising $L(\theta; X)$ is equivalent to maximising $\ln L(\theta; X)$

$$L(\theta; X) \rightarrow \max \iff \ln L(\theta; X) \rightarrow \max$$

- The Log-likelihood function

$$\log L(\theta; X) = \sum_{i=1}^n \ln f_i(x_i; \theta)$$

- The crucial is to have explicit pdf function to maximize. MATLAB contains various options for different distribution

$$\begin{aligned} \ln L(\theta; X) &= \sum_{i=1}^n \left(\ln \frac{1}{\sqrt{2\pi}} - \ln \sigma - \frac{(X - \mu)^2}{2\sigma^2} \right) \\ &= n \ln \frac{1}{\sqrt{2\pi}} - n \ln \sigma - \frac{1}{2\sigma^2} \sum_{i=1}^n (X - \mu)^2 \end{aligned}$$

Log Maximum Likelihood: Exercises

Assignment Project Exam Help

- ▶ Use help to find the `mle` function in MATLAB
- ▶ Use the `mle` function to estimate the mean and variance on the monthly FF consumer sector returns
- ▶ Compare the estimated value with the mean and variance of the sample
- ▶ Note: the `mle` function only allows one time series (vector observations) at a time.

<https://powcoder.com>

Add WeChat powcoder

Exercise 3: MLE

Assignment Project Exam Help

```
1 % Maximum Likelihood:
2 % calculate mle of mean and variance of consumer sector excess return
3 ret_cnsmer = y(:,1);
4 parm_est = mle(ret_cnsmer);
5 % calculate the sample statistics
6 parm_data = [mean(ret_cnsmer) std(ret_cnsmer)];
7 % Display
8 disp('Consumption Industry Returns')
9 disp('MLE estimates of mu, sigma')
10 disp(parm_est)
11 disp('sample estimate of mu, sigma')
12 disp(parm_data)
```

<https://powcoder.com>

Add WeChat powcoder

Extra: AR, MA and ARMA code

- ▶ Autoregressive Model: AR(p)

Assignment Project Exam Help

$$Y_t = c + \sum_{i=1}^p \varphi_i Y_{t-i} + \epsilon_t$$

- ▶ Moving-Average Model: MA(q)

<https://powcoder.com>

$$Y_t = \mu + \epsilon_t + \sum_{i=1}^q \theta_i \epsilon_{t-i}$$

- ▶ ARMA(p,q) Model (set $\mu = 0$)

Add WeChat powcoder

$$Y_t = c + \epsilon_t \sum_{i=1}^p \varphi_i Y_{t-i} + \sum_{i=1}^q \theta_i \epsilon_{t-i}$$

- ▶ If Y_t is integrated, use the ARIMA(p,D,q) model, where D is the number of difference order

Extra: AR, MA and ARMA code

- ▶ Code in matlab: `arma(p,D,q)`

AR(1): `arma(1,0,0)`

MA(2): `arma(0,0,2)`

- ▶ ARMA(2,3): `arma(2,0,3)`

- ▶ The presence of AR process violates the assumption of stationary for the linear regression analysis (to apply the central limit theorem)

- ▶ To test whether the underlying time series is stationary, the Augmented Dicky-Fuller test `adftest` is applied to test the presence of unit root in the underlying return sequence.

- ▶ `res = adftest(y)`

- ▶ `res = 0`: fail to reject the null hypothesis of a unit root against the autoregressive alternative.
- ▶ `res = 1`: reject the null hypothesis and conclude that the `y` is stationary.