

# BU CS 332 – Theory of Computation

Lecture 9: Assignment Project Exam Help

Reading:

Sipser Ch 3.1, 3.3

- Turing Machines

<https://powcoder.com>

Add WeChat powcoder

Mark Bun

February 22, 2021

# Turing Machines – Motivation

We've seen finite automata as a restricted model of computation

## Finite Automata / Regular Expressions

- Can do simple pattern matching (e.g., substrings), check parity, addition
- Can't perform unbounded counting
- Can't recognize palindromes

<https://powcoder.com>

Add WeChat powcoder

Somewhat more powerful (not in this course):

## Pushdown Automata / Context-Free Grammars

- Can count and compare, parse math expressions
- Can't recognize  $\{a^n b^n c^n \mid n \geq 0\}$

# Turing Machines – Motivation

## Goal:

Define a model of computation that is

- Assignment Project Exam Help**  
**1) General purpose.** Captures all algorithms that can be implemented in any programming language.  
<https://powcoder.com>
- Add WeChat powcoder**  
**2) Mathematically simple.** We can hope to prove that things are not computable in this model.

# A Brier History

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


# 1900 – Hilbert's Tenth Problem

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

*Given a Diophantine equation with any number of unknown quantities and with rational integral numerical coefficients: To devise a process according to which it can be determined in a finite number of operations whether the equation is solvable in rational integers.*



David Hilbert 1862-1943

# 1928 – The *Entscheidungsproblem*



Wilhelm Ackermann 1896-1962

*The “Decision Problem”*


**Assignment Project Exam Help**  
*Is there an algorithm which  
takes as input a formula (in  
first-order logic) and  
decides whether it’s  
logically valid?*

**<https://powcoder.com>**  
**Add WeChat powcoder**



David Hilbert 1862-1943

# 1936 – Solution to the *Entscheidungsproblem*



"An unsolvable problem of elementary number theory"

Assignment Project Exam Help 2-calculus (CS 320)

<https://powcoder.com>

Alonzo Church 1903-1995



Add WeChat powcoder

"On computable numbers, with an application to the *Entscheidungsproblem*"

Model of computation: Turing Machine

Alan Turing 1912-1954

# Turing Machines


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




# The Basic Turing Machine (TM)




- Input is written on an infinitely long tape
- Head can both read and write, and move in both directions
- Computation halts as soon as control reaches “accept” or “reject” state


# Example



# Example



# Example



What does this TM do on input 000?

- a) Halt and accept
- b) Halt and reject
- c) Halt in state  $q_3$
- d) Loop forever without halting

# Three Levels of Abstraction

## High-Level Description

An algorithm (like CS 330)

## Implementation-Level Description

Describe (in English) the instructions for a TM

- How to move the head
- What to write on the tape

## Low-Level Description

State diagram or formal specification

# Example

Determine if a string  $w \in A = \{0^{2^n} \mid n \geq 0\}$

## High-Level Description

Assignment Project Exam Help

<https://powcoder.com>

Repeat the following forever:

- If there is exactly one 0 in  $w$ , accept
- If there is an odd number of 0s in  $w$  ( $> 1$ ), reject
- Delete half of the 0s in  $w$

# Example

Determine if a string  $w \in A = \{0^{2^n} \mid n \geq 0\}$

## Implementation-Level Description


### Assignment Project Exam Help

1. While moving the tape head left to right:
  - a) Cross off every other 0
  - b) If there is exactly one 0 when we reach the right end of the tape, accept
  - c) If there is an odd number of 0s when we reach the right end of the tape, reject
2. Return the head to the left end of the tape
3. Go back to step 1

# Example

Determine if a string  $w \in A = \{0^{2^n} \mid n \geq 0\}$

## Low-Level Description



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# TMs vs. Finite Automata

Teacher: “zoom breakout rooms are critically important for online learning”

Zoom breakout rooms:



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# Formal Definition of a TM

A TM is a 7-tuple  $M = (Q, \Sigma, \Gamma, \delta, q_0, q_{\text{accept}}, q_{\text{reject}})$

- $Q$  is a finite set of states
  - $\Sigma$  is the input alphabet (does **not** include  $\sqcup$ )
  - $\Gamma$  is the tape alphabet (contains  $\sqcup$  and  $\Sigma$ )
  - $\delta$  is the transition function
- <https://powcoder.com>
- Add WeChat more on this later
- $q_0 \in Q$  is the start state
  - $q_{\text{accept}} \in Q$  is the accept state
  - $q_{\text{reject}} \in Q$  is the reject state ( $q_{\text{reject}} \neq q_{\text{accept}}$ )

# TM Transition Function

$$\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$$

$L$  means “move left” and  $R$  means “move right”

$\delta(p, a) = (q, b, R)$  means:

- Replace  $a$  with  $b$  in current cell
- Transition from state  $p$  to state  $q$
- Move tape head right

Add WeChat powcoder

$\delta(p, a) = (q, b, L)$  means:

- Replace  $a$  with  $b$  in current cell
- Transition from state  $p$  to state  $q$
- Move tape head left UNLESS we are at left end of tape, in which case don't move


# Configuration of a TM

A string with captures the state of a TM together with the contents of the tape

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# Configuration of a TM: Formally


A **configuration** is a string  $uqv$  where  $q \in Q$  and  $u, v \in \Gamma^*$

- Tape contents =  $uv$  (followed by blanks  $\sqcup$ )
- Current state =  $q$
- Tape head on first symbol of  $v$


Assignment Project Exam Help

<https://powcoder.com>

Example: ~~1010111~~ ~~q<sub>5</sub>~~ ~~0111~~ ~~powcoder~~



...



# How a TM Computes

Start configuration:  $q_0 w$



One step of computation:

- $u a q b v$  yields  $u a c q' v$  if  $\delta(q, b) = (q', c, R)$
- $u a q b v$  yields  $u q' a c v$  if  $\delta(q, b) = (q', c, L)$
- If we are at the left end of the tape in configuration  $q b v$ , what configuration do we reach if  $\delta(q, b) = (q', c, L)$ ?

# How a TM Computes

**Start** configuration:  $q_0 w$

One step of computation:

- $u a q b v$  yields  $u a c q' v$  if  $\delta(q, b) = (q', c, R)$
- $u a q b v$  yields  $u q' a c v$  if  $\delta(q, b) = (q', c, L)$
- $q b v$  yields  $q' c v$  if  $\delta(q, b) = (q', c, I)$

**Accepting** configuration:  $q = q_{\text{accept}}$

**Rejecting** configuration:  $q = q_{\text{reject}}$

# How a TM Computes

$M$  **accepts** input  $w$  if there is a sequence of configurations  $C_1, \dots, C_k$  such that:

- $C_1 = q_0 w$
- $C_i$  yields  $C_{i+1}$  **for every  $i$**
- $C_k$  is an accepting configuration

<https://powcoder.com>

$L(M)$  = the set of all strings  $w$  which  $M$  accepts

$A$  is **Turing-recognizable** if  $A = L(M)$  for some TM  $M$ :

- $w \in A \Rightarrow M$  halts on  $w$  in state  $q_{\text{accept}}$
- $w \notin A \Rightarrow M$  halts on  $w$  in state  $q_{\text{reject}}$  **OR**  
 $M$  runs forever



# Recognizers vs. Deciders

$L(M)$  = the set of all strings  $w$  which  $M$  accepts

$A$  is Turing-recognizable if  $A = L(M)$  for some TM  $M$ :

- $w \in A \Rightarrow M$  halts on  $w$  in state  $q_{\text{accept}}$
- $w \notin A \Rightarrow M$  halts on  $w$  in state  $q_{\text{reject}}$  OR  
 $M$  runs forever

Add WeChat powcoder

$A$  is (Turing-)decidable if  $A = L(M)$  for some TM  $M$

which halts on every input

- $w \in A \Rightarrow M$  halts on  $w$  in state  $q_{\text{accept}}$
- $w \notin A \Rightarrow M$  halts on  $w$  in state  $q_{\text{reject}}$

# Back to Hilbert's Tenth Problem

**Computational Problem:** Given a Diophantine equation, does it have a solution over the integers?

$L =$

- $L$  is Turing-recognizable

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- $L$  is **not** decidable (1949-70)

