

BU CS 332 – Theory of Computation

Lecture 4: Assignment Project Exam Help

- More on NFAs

<https://powcoder.com>

- NFAs vs. DFAs

Add WeChat powcoder

- Closure Properties

Reading:

Sipser Ch 1.1-1.2

Mark Bun

February 3, 2021

Last Time


- Deterministic Finite Automata (DFAs)
 - Informal description: State diagram
 - Formal description: What are they?
 - Formal description: How do they compute?
- A language is regular if it is recognized by a DFA
- Intro to Nondeterministic FAs

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Nondeterminism




A **Nondeterministic Finite Automaton** (NFA) accepts if there *exists* a way to make it reach an accept state.

Some special transitions



Example



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$L(N) =$

- a) $\{w \mid w \text{ contains } 00 \text{ or } 01\}$
- b) $\{w \mid \text{the second to last symbol of } w \text{ is } 0\}$
- c) $\{w \mid w \text{ starts with } 00 \text{ or } 01\}$
- d) $\{w \mid w \text{ ends with } 001\}$

Formal Definition of a NFA

An **NFA** is a 5-tuple $M = (Q, \Sigma, \delta, q_0, F)$

Q is the set of states

Σ is the alphabet


$\delta: Q \times \Sigma_\epsilon \rightarrow P(Q)$ is the transition function

$q_0 \in Q$ is the start state

$F \subseteq Q$ is the set of accept states

M **accepts** a string w if **there exists** a path from q_0 to an accept state that can be followed by reading w .

Example



Add WeChat powcoder

$$N = (Q, \Sigma, \delta, q_0, F)$$
$$Q = \{q_0, q_1, q_2, q_3\}$$
$$\Sigma = \{0, 1\}$$
$$F = \{q_3\}$$
$$\delta(q_0, 0) =$$
$$\delta(q_0, 1) =$$
$$\delta(q_1, \epsilon) =$$
$$\delta(q_2, 0) =$$

Nondeterminism

Deterministic Computation



accept or reject


Nondeterministic Computation

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

reject



accept

Ways to think about nondeterminism

- (restricted) parallel computation
- tree of possible computations
- guessing and verifying the “right” choice

Why study NFAs?

- Not really a realistic model of computation: Real computing devices can't really try many possibilities in parallel

Assignment Project Exam Help


But:

<https://powcoder.com>


- Useful tool for understanding power of DFAs/regular languages
- NFAs can be simpler than DFAs
- Lets us study “nondeterminism” as a resource (cf. P vs. NP)

NFAs can be simpler than DFAs

A DFA that recognizes the language
 $\{w \mid w \text{ starts with } 0 \text{ and ends with } 1\}$:



An NFA for this language:



Equivalence of NFAs and DFAs

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Equivalence of NFAs and DFAs

Every DFA *is* an NFA, so NFAs are *at least* as powerful as DFAs

Assignment Project Exam Help

Theorem: For every NFA N , there is a DFA M such that $L(M) = L(N)$


<https://powcoder.com>
Add WeChat powcoder

Corollary: A language is regular if and only if it is recognized by an NFA

Equivalence of NFAs and DFAs (Proof)

Let $N = (Q, \Sigma, \delta, q_0, F)$ be an NFA

Goal: Construct DFA $M = (Q', \Sigma, \delta', q_0', F')$ recognizing $L(N)$



Assignment Project Exam Help

Intuition: Run all threads of N in parallel, maintaining the set of states where all threads are.


<https://pweoder.com>

Add WeChat powcoder

Formally: $Q' = P(Q)$

"The Subset Construction"

NFA -> DFA Example



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Subset Construction (Formally, first attempt)

Input: NFA $N = (Q, \Sigma, \delta, q_0, F)$

Output: DFA $M = (Q', \Sigma, \delta', q_0', F')$

Q' **Assignment Project Exam Help**

$\delta' : Q' \times \Sigma \rightarrow Q'$ **<https://powcoder.com>**

$\delta'(R, \sigma) =$ **Add WeChat powcoder** for all $R \subseteq Q$ and $\sigma \in \Sigma$.

$q_0' =$

$F' =$

Subset Construction (Formally, for real)

Input: NFA $N = (Q, \Sigma, \delta, q_0, F)$

Output: DFA $M = (Q', \Sigma, \delta', q_0', F')$

$Q' = P(Q)$ Assignment Project Exam Help


$\delta' : Q' \times \Sigma \rightarrow Q'$ <https://powcoder.com>

$\delta'(R, \sigma) = \bigcup_{r \in R} \delta(r, \sigma)$ for all $R \subseteq Q$ and $\sigma \in \Sigma$.
Add WeChat powcoder

$q_0' = \{q_0\}$

$F' = \{ R \in Q' \mid R \text{ contains some accept state of } N \}$

NFA -> DFA Example



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Proving the Construction Works

Claim: For every string w , running M on w leads to state

$\{q \in Q \mid \text{There exists a computation path of } M \text{ on input } w \text{ ending at } q\}$

Assignment Project Exam Help

<https://powcoder.com>

Proof idea: By induction on $|w|$

Add WeChat | powcoder

Historical Note

Subset Construction introduced in Rabin & Scott's 1959 paper "Finite Automata and their Decision Problems"




1976 ACM Turing Award citation
Assignment Project Exam Help


For their joint paper "Finite Automata and Their Decision Problem," which introduced the idea of nondeterministic machines, which has proved to be an enormously valuable concept. Their (Scott & Rabin) classic paper has been a continuous source of inspiration for subsequent work in this field.

<https://powcoder.com>

Add WeChat powcoder



NFA \rightarrow DFA: The Catch



If N is an NFA with s states, how many states does the DFA obtained using the subset construction have?

Assignment Project Exam Help

a) s

<https://powcoder.com>

b) s^2

Add WeChat powcoder

c) 2^s

d) None of the above

Is this construction the best we can do?

Subset construction converts an n state NFA into a 2^n -state DFA

Could there be a construction that always produces, say, an n^2 -state DFA?

<https://powcoder.com>

Theorem: For every $n \geq 1$, there is a language L_n such that

1. There is an $(n + 1)$ -state NFA recognizing L_n .
2. There is no DFA recognizing L_n with fewer than 2^n states.

Conclusion: For finite automata, nondeterminism provides an exponential savings over determinism (in the worst case).

Closure Properties

Assignment Project Exam Help
<https://powcoder.com>

Add WeChat powcoder

An Analogy

In algebra, we try to identify operations which are common to many different mathematical structures

Example: The integers $\mathbb{Z} = \{\dots - 2, -1, 0, 1, 2, \dots\}$ are **closed** under

- Addition: $x + y$
- Multiplication: $x \times y$
- Negation: $-x$
- ...but **NOT** Division: x / y

We'd like to investigate similar closure properties of the **class of regular languages**

Regular operations on languages

Let $A, B \subseteq \Sigma^*$ be languages. Define

Union: $A \cup B = \{w \mid w \in A \text{ or } w \in B\}$

Assignment Project Exam Help

Concatenation: $A \circ B = \{xy \mid x \in A, y \in B\}$

Add WeChat powcoder

Star: $A^* =$

Other operations

Let $A, B \subseteq \Sigma^*$ be languages. Define

Complement: $\bar{A} = \{w \mid w \notin A\}$

Assignment Project Exam Help

<https://powcoder.com>

Intersection: $A \cap B = \{w \mid w \in A \text{ and } w \in B\}$

Add WeChat powcoder

Reverse: $A^R = \{w \mid w^R \in A\}$

Closure properties of the regular languages

Theorem: The class of regular languages is **closed** under all three regular operations (union, concatenation, star), as well as under complement, intersection, and reverse.

Assignment Project Exam Help

<https://powcoder.com>

i.e., if A and B are regular, applying any of these operations yields a regular language

Add WeChat powcoder

Assignment Project Exam Help

Proving Closure Properties

<https://powcoder.com>

Add WeChat powcoder

Complement

Complement: $\bar{A} = \{ w \mid w \notin A \}$

Theorem: If A is regular, then \bar{A} is also regular

Proof idea:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Complement, Formally



Let $M = (Q, \Sigma, \delta, q_0, F)$ be a DFA recognizing a language A . Which of the following represents a DFA recognizing \bar{A} ?

- a) $(F, \Sigma, \delta, q_0, Q)$
- b) $(Q, \Sigma, \delta, q_0, Q \setminus F)$, where $Q \setminus F$ is the set of states in Q that are not in F
- c) $(Q, \Sigma, \delta', q_0, F)$ where $\delta'(q, s) = p$ such that $\delta(p, s) = q$
- d) None of the above


Closure under Concatenation

Concatenation: $A \circ B = \{ xy \mid x \in A, y \in B \}$

Theorem. If A and B are regular, $A \circ B$ is also regular.

Proof idea: Given DFAs M_A and M_B , construct NFA by

- Connecting all accept states in M_A to the start state in M_B .
- Make all states in M_A non-accepting.




Closure under Concatenation

Concatenation: $A \circ B = \{ xy \mid x \in A, y \in B \}$


Theorem. If A and B are regular, $A \circ B$ is also regular.

Proof idea: Given DFAs M_A and M_B , construct NFA by


- Connecting all accept states in M_A to the start state in M_B .
- Make all states in M_A non-accepting.



A Mystery Construction



Given DFAs M_A recognizing A and M_B recognizing B , what does the following NFA recognize?



Closure under Star


Star: $A^* = \{ a_1 a_2 \dots a_n \mid n \geq 0 \text{ and } a_i \in A \}$

Theorem. If A is regular, A^* is also regular.

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



Closure under Star

Star: $A^* = \{ a_1 a_2 \dots a_n \mid n \geq 0 \text{ and } a_i \in A \}$

Theorem. If A is regular, A^* is also regular.



On proving your own closure properties

You'll have homework/test problems of the form “show that the regular languages are closed under operation op ”

What would Sipser do? **Assignment Project Exam Help**

- Give the “proof idea”: Explain how to take machine(s) recognizing regular language(s) and create a new machine
https://powcoder.com
Add WeChat powcoder
- Explain in a few sentences why the construction works
- Give a formal description of the construction
- No need to formally prove the construction works