Introduction to AI: Tutorial

Foundation of Logic and Resolution-based Proof Procedures

Alessandra Russo

The aim of this tutorial is to enable you to practise more with fundamental logic-based concepts, introduced in Unit 2, and to gain more practice with SLD and SLDNF derivations from KB expressed using definite clauses and normal clauses.

Question 1

Convert the following first-order sentences into clausal representation:

- i) YXAssignmentupProject Exam Help
- ii) $\forall Y (\exists X P(X, Y) \rightarrow \neg S(Y))$
- iii) \forall X(philosophittps: \forall powcoider) com

Question 2

If possible unify the following pairs and give the punification of the five explain why they do not unify:

- 1) p(f(X), g(Y)) and p(Z, g(f(a))) 2) p(Y, a, b, Y) and p(c, F, G, F)
- 3) p(X, X) and p(E, E)
- 4) p(f(X)) and q(f(X))
- 5) p(V, g(X)) and p(f(X), V)

Question 3

Consider a knowledge base (KB) about the following sentences:

- (a) Lucy is a professor.
- (b) All professor are people.
- (c) John is a dean.
- (d) Deans are professors.
- (e) All professor consider the dean a friend or they don't know him.
 - 1. Formalise each of the above sentence into first-order logic
 - 2. Convert them into clausal form.

- 3. Let KB be the set of clauses that you have given in your answer to part (2) above. Write KB in rule form.
- 4. Assume the only constants to be Lucy and John. Write in full the ground(KB) (i.e. the grounding of KB).
- 5. Give the Herbrand base of KB.
- 6. Give the Least Herbrand model of KB, and an example of an Herbrand interpretation that is not a model of KB.
- 7. Using resolution show that $KB \not\models friendOf(lucy, john)$. Explain also semantically why this is the case.

Question 4

Consider the following KB. Give the SLDNF tree of all derivations of the goal p(X) from KB.

Assignment (Project, Exam Help
$$q(X) \leftarrow not \ r(X)$$
).

https://powcoder.com
 $s(c,b)$.

Add WeChat powcoder

Question 5

Consider the following KB, which formalises the notion that

A student passes the year in which he/she is enrolled if he/she has not failures in any course. John in a student enrolled in his first year, and Logic is a course.

$$KB = \left\{ \begin{array}{l} passedYear(X,Y) \leftarrow year(Y), enrolled(X,Y), not \ failures(X,C) \\ year(firstYear). \\ enrolled(john, firstYear). \\ course(Logic). \end{array} \right\}$$

- 1. Explain why there does not exist an SLDNF derivation of passedYear(X,Y) from KB.
- 2. Modify the KB so that it does accept a derivation of passedYear(X,Y) for some unification of X and Y, and give an example of such an SLDNF derivation.