

COMP 250

INTRODUCTION TO COMPUTER SCIENCE

Assignment Project Exam Help

<https://powcoder.com>

Week 12-2: Heaps
Add WeChat powcoder

Giulia Alberini, Fall 2020

Slides adapted from Michael Langer's

WHAT ARE WE GOING TO DO IN THIS VIDEO?



- **Heaps**

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

HEAPS
<https://powcoder.com>

Add WeChat powcoder

PRIORITY QUEUE

Assume a set of comparable elements or “keys”.

Assignment Project Exam Help

Like a queue, but now we have a more general definition of which element to remove next, namely the one with highest priority.

<https://powcoder.com>
Add WeChat powcoder

e.g. hospital emergency room

PRIORITY QUEUE ADT

- `add(key)`

- `removeMin()`

“highest” priority = “number 1” priority

- `peek()`

- `contains(element)`

- `remove(element)`

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

HOW TO IMPLEMENT A PRIORITY QUEUE ?

- sorted list ?

Assignment Project Exam Help

- binary search tree (last lecture) ?

<https://powcoder.com>


- balanced binary search tree (COMP 251) ?

Add WeChat powcoder

- heap (next 2 lectures)


Not the same “heap” you hear about in COMP 206.

COMPLETE BINARY TREE (DEFINITION)



Binary tree of height h such that every level less than h is full, and all nodes at level h are as far to the left as possible


MIN HEAP (DEFINITION)



Complete binary tree with unique comparable elements, such that each node's element (key) is less than its children's element (key).


ADD()

For example, add (c)




ADD()

For example, add(**c**)



ADD()


For example, add(**c**)



Problem : adding at the next available slot typically destroys the heap property.

ADD()

For example, add(**c**)



Assignment Project Exam Help

What can we do?

<https://powcoder.com>


Let's swap **c** with its parent **f**.

Add WeChat powcoder

Q. Can this create a problem with **c**'s former sibling, who is now **c**'s child?

ADD()

For example, add(**c**)



Assignment Project Exam Help

What can we do?

<https://powcoder.com>

Let's swap **c** with its parent **f**.


Add WeChat powcoder

Q. Can this create a problem with **c**'s former sibling, who is now **c**'s child?

A: No. Why?

ADD()

For example, add(**c**)



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Q: Are we done?

A: Not necessarily. What about **c**'s parent?

ADD()

For example, add(**c**)



Assignment Project Exam Help


We swap **c** with its (new) parent **e**.

<https://powcoder.com>

Now we are done because **c** is greater than its parent **a**

Add WeChat powcoder

ADD() - IMPLEMENTATION




```
add(key) {  
    cur = new node at next available leaf position  
    cur.key = key
```

<https://powcoder.com>

Add WeChat powcoder

```
}
```


ADD() - IMPLEMENTATION



```
add(key) {
```

```
    cur = new node at next available leaf position
```

```
    cur.key = key
```

```
    if (root == null) // empty tree
```

```
        root = cur
```


```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

ADD() - IMPLEMENTATION



```
add(key) {
```

```
    cur = new node at next available leaf position
```

```
    cur.key = key
```

```
    if(root == null) // empty tree
```

```
        root = cur
```

```
    else {
```

```
        while (cur!=root && cur.key<cur.parent.key) {
```

```
            swapKeys(cur, cur.parent)
```

```
            cur = cur.parent
```

```
        }
```

```
    }
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

HOW TO BUILD A HEAP?

add(**k**) Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

HOW TO BUILD A HEAP?

add(**k**)
add(**f**)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

HOW TO BUILD A HEAP?

add(**k**) Assignment Project Exam Help
add(**f**)

<https://powcoder.com>

Add WeChat powcoder

HOW TO BUILD A HEAP?

add(**k**)

add(**f**)

add(**e**)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

HOW TO BUILD A HEAP?

add(**k**)


add(**f**)

add(**e**)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




HOW TO BUILD A HEAP?

add(**k**)
add(**f**)
add(**e**)
add(**a**)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




HOW TO BUILD A HEAP?

```
add( k )  
add( f )  
add( e )  
add( a )
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




HOW TO BUILD A HEAP?

add(**k**)
add(**f**)
add(**e**)
add(**a**)
add(**g**)

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder



HOW TO BUILD A HEAP?

```
add( k )  
add( f )  
add( e )  
add( a )  
add( g )
```




This method of building a heap is slow.

We will see a faster method next video.


REMOVEMIN()

returns root element



REMOVEMIN()

returns root element




REMOVEMIN()

a

Claim: if the root has two children, then the new root *will* be greater than at least one of its children.


Why?

How to solve this problem?



REMOVEDMIN()

Swap keys with the smaller
child!



REMOVEDMIN()


Swap keys with the smaller child!

Keep swapping with keys with the smaller child until it's necessary.

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder




REMOVEDMIN()

Let's removeMin() again!




REMOVEDMIN()

Let's removeMin() again!



REMOVEDMIN()

Let's removeMin() again!




REMOVED MIN()

Now swap with smaller child, if necessary, to preserve heap property.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




REMOVEDMIN()

Now swap with smaller child, if necessary, to preserve heap property.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




REMOVED MIN()

Keep swapping with
smaller child, if necessary.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




REMOVED MIN()

Keep swapping with
smaller child, if necessary.


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




REMOVE_MIN() - IMPLEMENTATION



Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
removeMin () {  
    temp = root.key  
    remove the last leaf node and  
    store its key into the root  
    cur = root  
  
    return temp  
}
```



REMOVE_MIN() - IMPLEMENTATION



Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
removeMin () {  
    temp = root.key  
    remove the last leaf node and  
    store its key into the root  
    cur = root  
    while((cur.left!=null && cur.key > cur.left.key)  
        || (cur.right!=null && cur.key > cur.right.key)) {  
  
    }  
    return temp  
}
```

REMOVEDMIN() - IMPLEMENTATION



Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
removeMin () {  
    temp = root.key  
    remove the last leaf node and  
    store its key into the root  
    cur = root  
    while ((cur.left != null && cur.key > cur.left.key)  
        || (cur.right != null && cur.key > cur.right.key)) {  
        minChild = child with smaller key  
        swapKeys (cur, minChild)  
        cur = minChild  
    }  
    return temp  
}
```

add()

removeMin()



“upHeap”

“downHeap”

REMOVE()

Q: What about remove(key) ?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVE()

Q: What about remove(key) ?


Assignment Project Exam Help

A: Worst case $O(n)$


<https://powcoder.com>

Add WeChat powcoder

HEAP (ARRAY IMPLEMENTATION)




HEAP (ARRAY IMPLEMENTATION)



HEAP INDEX RELATIONS

parent = child / 2
left = 2*parent
right = 2*parent + 1




Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Not used



HEAP INDEX RELATIONS

parent = child / 2
left = 2*parent
right = 2*parent + 1




Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Not used




HEAP INDEX RELATIONS

```
parent = child / 2
left   = 2*parent
right  = 2*parent + 1
```




HEAP INDEX RELATIONS

```
parent = child / 2
left   = 2*parent
right  = 2*parent + 1
```



ASIDE: an array data structure can be used for *any* binary tree. But this is uncommon and often inefficient.



ADD() - IMPLEMENTATION


```
add(key) {  
    size = size + 1 // number of elements in heap  
    // assuming array has room for another element  
    heap[ size ] = key  
  
    i = size  
  
    // the following is sometimes called "upHeap"  
    while ( i > 1 && heap[i] < heap[ i/2 ] ){  
        swapElements( i, i/2 )  
        i = i/2  
    }  
}
```

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder


E.G. add (c)




E.G. add (c)



E.G. add (c)



E.G. add (c)



NEXT VIDEO

- write `removeMin()` using array indices

Assignment Project Exam Help

- discuss best and worst case

<https://powcoder.com>

Add WeChat powcoder

- faster algorithm for building a heap



Coming Soon

Assignment Project Exam Help

In the next video:

- More on <https://powcoder.com>

Add WeChat powcoder