

COMP 250

INTRODUCTION TO COMPUTER SCIENCE

Assignment Project Exam Help

<https://powcoder.com>

Week 1-2 Java syntax Part 2

Giulia Alberini, Fall 2020

WHAT ARE WE GOING TO DO IN THIS VIDEO?



- More on Java syntax **Assignment Project Exam Help**

- Scope of variables **<https://powcoder.com>**

Add WeChat powcoder

Assignment Project Exam Help
MORE OPERATORS

<https://powcoder.com>

Add WeChat powcoder

OPERATION-ASSIGNMENT +=, -=, *=, /=

The following two blocks are equivalent
Assignment Project Exam Help

```
int x = 2;  
x += 5;
```

<https://powcoder.com>

Add WeChat powcoder

```
int x = 2;  
x = x + 5;
```

The same notation can be used for subtraction, multiplication, and division.

POST INCREMENT (DECREMENT)

- Post-increment: $x++$
- Post-decrement: $x--$

<https://powcoder.com>
Add WeChat powcoder

You can use these notations as statements as well as part of a more complex expression.

POST INCREMENT (DECREMENT)

The following statements are equivalent.

`x++;`

`x = x + 1;`

`x--;`

`x = x - 1;`

<https://powcoder.com>

Add WeChat powcoder

POST INCREMENT (DECREMENT)

When used as part of expressions, the increment happens after the statement is executed.

<https://powcoder.com>

The following blocks are equivalent:

```
int x = 5;  
int y = 2*x++;
```

```
int x = 5;  
int y = 2*x;  
x = x + 1;
```

RECOMMENDATION

Use ++ or -- by themselves. Don't write code with pre/post increment/decrement inside other expressions. It makes the code harder to read and more error prone.

<https://powcoder.com>

Add WeChat powcoder

```
int x = 5;  
x = x++ + ++x + x++; // legal, but why??
```


Assignment Project Exam Help

<https://powcoder.com>
MORE SYNTAX

Add WeChat powcoder

IF-ELSE IF-ELSE

- Only one of these blocks will get executed. **Order matters!**
- As soon as one block is executed, the remaining will be skipped
- You can have as many `else ifs` as you want
- The final `else` is not required.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
if (x > 0) {  
    System.out.println("Positive");  
} else if (x < 0) {  
    System.out.println("Negative");  
} else {  
    System.out.println("Zero");  
}
```

COMMON MISTAKE

```
if (x > 0) {  
    System.out.println("Positive");  
} else {  
    System.out.println("Non positive");  
}
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

- Compile-time error!

COMMON MISTAKE

```
if (x > 0) {  
    System.out.println("positive");  
}
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

- The statements inside the block will get executed no matter how the condition evaluates.

WHILE LOOP – SYNTAX

Assignment Project Exam Help

```
while (condition) {  
    https://powcoder.com  
    // some code
```

```
} Add WeChat powcoder
```

The block of code is repeatedly executed as long as the condition evaluates to true.

FOR LOOP – GENERAL STRUCTURE

Assignment Project Exam Help

```
for (statement1; boolean expression; statement2) {  
    // loop body  
}
```

<https://powcoder.com>

Add WeChat powcoder

- Any or all of the above statement/expression can be left out.
- The semicolons always need to be there.

EXAMPLE

Assignment Project Exam Help

```
for (int i = 1; i <= 10; i++) {  
    // some code  
}
```

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE

Assignment Project Exam Help

```
for (int i = 1; i <= 10; i++) {  
    // some code  
}
```

<https://powcoder.com>

Add WeChat powcoder

The ***initializer*** is executed once, before the loop starts.

EXAMPLE

Assignment Project Exam Help

```
for (int i = 1; i <= 10; i++) {  
    // some code  
}
```

<https://powcoder.com>

Add WeChat powcoder

The **condition** is checked at the beginning of each iteration. If it evaluates to false, the loop ends. Otherwise, the body is repeated.

EXAMPLE

Assignment Project Exam Help

```
for (int i = 1; i <= 10; i++) {  
    // some code  
}
```

<https://powcoder.com>

Add WeChat powcoder

The **update** is executed at the end of each iteration.

TO RECAP

1) The initializer is executed

<https://powcoder.com>

2) The condition is checked. If true, the body is executed. Otherwise, the loop ends.

3) The update is executed and we go back to step 2).

VOID METHODS

Assignment Project Exam Help

```
public static void newMethod()
```

<https://powcoder.com>

Add WeChat powcoder

When used as part of a method header, the keyword **void** tells the computer that the method does not return anything.

VALUE METHODS

Compare to void methods, value methods differ in 2 ways:

- They declare the type of the return value
- They use at least one return statement to provide a return value.

Assignment Project Exam Help

<https://powcoder.com>

```
public static double circleArea(double radius) {  
    double area = Math.PI * Math.pow(radius, 2.0);  
    return area;  
}
```

- A call to this method could be: `double a = circleArea(2.5);`

DEAD CODE

- Code that appear after a return statement, or somewhere where it can never be executed, is called **dead code**.

Assignment Project Exam Help

- If your program contains dead code you will receive a **compile-time error: "Unreachable statement"**.

Add WeChat powcoder

```
public static double circleArea(double radius) {  
    double area = Math.PI * Math.pow(radius, 2.0);  
    return area;  
  
    System.out.println("It will never print");  
}
```

OVERLOADING

- Having more than one method with the same name is called **overloading**.

Assignment Project Exam Help

<https://powcoder.com>

- It is legal as long as the methods have different parameters.
- Java will know, based on the inputs, which method has been called.

Add WeChat powcoder

RECAP ON METHODS – GENERAL FORM

- Keywords (e.g., `public static`)
- Return type (e.g., `void, int, boolean`)
- Name of the method
- Parentheses with parameters declarations
- Body of the method (the instructions)

Written between curly brackets and including at least one
`return statement if not void.`

HOW TO READ THE DOCUMENTATION

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

DOCUMENTATION

- The Java Application Programming Interface (API) is a list of all classes that are part of the JDK. You can find the complete list here: <https://docs.oracle.com/javase/8/docs/api/>

<https://powcoder.com>

Add WeChat powcoder

- You can visit the above link if you want to know more about library or methods you'd like to use.

E.g. All about the Math library:

<https://docs.oracle.com/javase/8/docs/api/java/lang/Math.html>

Method Summary

Methods

Modifier and Type	Method and Description
static double	abs (double a) Returns the absolute value of a double value.
static float	abs (float a) Returns the absolute value of a float value.
static int	abs (int a) Returns the absolute value of an int value.
static long	abs (long a) Returns the absolute value of a long value.
static double	acos (double a) Returns the arc cosine of a value; the returned angle is in the range 0.0 through π .
static double	asin (double a) Returns the arc sine of a value; the returned angle is in the range $-\pi/2$ through $\pi/2$.
static double	atan (double a) Returns the arc tangent of a value; the returned angle is in the range $-\pi/2$ through $\pi/2$.
static double	atan2 (double y, double x) Returns the angle θ from the conversion of rectangular coordinates (x, y) to polar coordinates (r, θ).
static double	cbrt (double a) Returns the cube root of a double value.
static double	ceil (double a) Returns the smallest (closest to negative infinity) double value that is greater than or equal to the argument and is e
static double	copySign (double magnitude, double sign) Returns the first floating-point argument with the sign of the second floating-point argument.
static float	copySign (float magnitude, float sign) Returns the first floating-point argument with the sign of the second floating-point argument.
static double	cos (double a) Returns the trigonometric cosine of an angle.
static double	cosh (double x) Returns the hyperbolic cosine of a double value.
static double	exp (double a)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SAMPLE ENTRY

static double

Assignment Project Exam Help

abs(double a)

<https://powcoder.com>

Returns the absolute value of a double value.

Add WeChat powcoder

SAMPLE ENTRY

static double

Assignment Project Exam Help

`abs(double a)`

<https://powcoder.com>

Returns the absolute value of a double value.

Add WeChat powcoder

It specifies the **name** of the method

SAMPLE ENTRY

```
static double
```

Assignment Project Exam Help

```
abs(double a)
```

<https://powcoder.com>

Returns the absolute value of a double value.

Add WeChat powcoder

The number and type of input parameters

SAMPLE ENTRY

static double

Assignment Project Exam Help

abs(double a)

<https://powcoder.com>

Returns the absolute value of a double value.

Add WeChat powcoder

Which together they constitute the **method's signature**

SAMPLE ENTRY

static double

Assignment Project Exam Help

abs(double a)

<https://powcoder.com>

Returns the absolute value of a double value.

Add WeChat powcoder

The **return type** of the method

SAMPLE ENTRY

`static double`

Assignment Project Exam Help

`abs(double a)`

<https://powcoder.com>

Returns the absolute value of a double value.

Add WeChat powcoder

Keyword that tell you how the method can be called.
We'll find out more about this in the following weeks,
so don't worry about it for now.

SAMPLE ENTRY

static double

Assignment Project Exam Help

abs(double a)

<https://powcoder.com>

Returns the absolute value of a double value.

Add WeChat powcoder

And a description of what the method does.

abs

```
public static double abs(double a)
```

Returns the absolute value of a double value. If the argument is not negative, the argument is returned. If the argument is negative, the result is the positive value of the argument.

- If the argument is positive zero or negative zero, the result is positive zero.
- If the argument is infinite, the result is positive infinity.
- If the argument is NaN, the result is NaN.

In other words, the result is the same as the value of the expression:

```
Double.longBitsToDouble((Double.doubleToLongBits(a)<<1)>>>1)
```

Parameters:

a - the argument whose absolute value is to be determined

Returns:

the absolute value of the argument.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE OF OVERLOADING

Note that `Math.abs()` is overloaded

Assignment Project Exam Help

abs(double a)

Returns the absolute value of a double value.

abs(float a)

Returns the absolute value of a float value.

abs(int a)

Returns the absolute value of an int value.

abs(long a)

Returns the absolute value of a long value.

<https://powcoder.com>

Add WeChat powcoder

THE SCOPE OF A VARIABLE

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SCOPE OF A VARIABLE

- A variable **only exists** inside the block in which it is declared.

Assignment Project Exam Help

- It does not exist anywhere else outside that block.

Add WeChat powcoder

- When inside a block,
 - a variable **starts** to exists when it is declared, and
 - it **ends** to exists at the blocks in which it was declared ends.

EXAMPLE 1

```
int x = 5;
if (x > 0) {
    int y = 0;
} else {
    int y = x;
}
System.out.println(y);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
int x = 5;
int y;
if (x > 0) {
    y = 0;
} else {
    y = x;
}
System.out.println(y);
```



EXAMPLE 2

```
int x = 2;
int y = 3;
if (x < y) {
    x = x + y;
    int z = 5;
    y = z*x;
}
System.out.println(x + " " + y + " " + z);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
int x = 2;
int y = 3;
int z = 0;
if (x < y) {
    x = x + y;
    z = 5;
    y = z*x;
}
System.out.println(x + " " + y + " " + z);
```



EXAMPLE 3

```
for (int i = 0; i < 5; i++) {  
    System.out.println(i);  
}  
System.out.println(i);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
int i;  
for (i = 0; i < 5; i++) {  
    System.out.println(i);  
}  
System.out.println(i);
```



EXAMPLE 4

```
int x = 5;
if (x > 0 || isSnowing) {
    System.out.println(x);
}
```

Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder

```
int x = 5;
boolean isSnowing = false;
if (x > 0 || isSnowing) {
    System.out.println(x);
}
```



RECOMMENDED EXERCISES

- Look at code you have previously written in Python (or in any other programming language) which uses numbers (like integers or doubles), variables, conditional statements, loops, and functions. Translate this code into Java.



Coming Soon

Assignment Project Exam Help

In the next video we will be talking about
primitive data types and strings.

<https://powcoder.com>

Add WeChat powcoder