

COMP 250

INTRODUCTION TO COMPUTER SCIENCE

Assignment Project Exam Help

<https://powcoder.com>

Week 2-3: Reference types and Random

Add WeChat powcoder

Giulia Alberini, Fall 2020

WHAT ARE WE GOING TO DO IN THIS VIDEO?



- Reference types

Assignment Project Exam Help

- Random

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help
REFERENCE TYPES

<https://powcoder.com>

Add WeChat powcoder

PRIMITIVE VS REFERENCE TYPES

- Both arrays and Strings are Objects.

Assignment Project Exam Help

- In java, except for the primitive data types (those whose names start with lowercase letters like `int`, `double`, etc.), everything is an Object.

<https://powcoder.com>

Add WeChat powcoder

- Variables of Objects, arrays included, don't store the values of the objects, but a **reference** to the location in memory containing that value. You can think of it as an address which points to where the data is located in memory.

REFERENCE TYPES

```
1 public class Test {  
2  
3     public static void main(String[] args) {  
4         String[] pets = {"cats", "dogs", "ferrets"};  
5         System.out.println(pets);  
6  
7         int[] x = new int[5];  
8         System.out.println(x);  
9     }  
10 }
```

Problems @ Javadoc Declaration Console

<terminated> Test (11) [Java Application] C:\Program Files\Java\jre1.8.0_181\bin\javaw.exe (Jan. 11, 2020, 3:51:49 p.m.)

```
[Ljava.lang.String;@15db9742  
[I@6d06d69c
```

PRIMITIVE VS REFERENCE TYPES – EXAMPLES

```
public static void main(String[] args) {  
    int x = 5;  
    int y = x;  
    x++;  
    System.out.println(x + " " + y);  
}
```

- What does the program print?

6 5

PRIMITIVE VS REFERENCE TYPES – EXAMPLES

```
public static void main(String[] args) {  
    int[] x = {1, 2, 3};  
    int[] y = x;  
    y[0] = 4;  
    System.out.println(x[0] + " " + y[0]);  
}
```

- What does the program print?

4 4

PRIMITIVE VS REFERENCE TYPES – EXAMPLES

```
public static void main(String[] args) {  
    int x = 5;  
    example(x);  
    System.out.println(x);  
}  
public static void example(int x) {  
    x = x*5;  
}
```

- What does the program print?

5

PRIMITIVE VS REFERENCE TYPES – EXAMPLES

```
public static void main(String[] args) {  
    int[] x = {1,2,3};  
    example(x);  
    System.out.println(x[0]);  
}  
public static void example(int[] x) {  
    x[0] = 4;  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- What does the program print?

4

ARRAY VS STRING

- Both arrays and strings are reference types.

Assignment Project Exam Help

- Variables of array-type and String-type both store the address in memory at which the elements of the object begins.

<https://powcoder.com>
Add WeChat powcoder

- Arrays are mutable, Strings are **immutable!!**
 - Once a String has been created it cannot be changed!
 - The elements of an array can be updated anytime we want.


REFERENCE TYPES

```
String[] pets = {"cat", "dog"};
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



REFERENCE TYPES

```
String[] pets = {"cat", "dog"};  
pets[0] = pets[0] + "s";
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

pets



0

1



"cat"



"dog"

"cats"

To note:

- We changed the array. Arrays are **mutable** → the reference stored in pets did not change!
- We changed the first String. Strings are **immutable** → the reference in pets[0] did change!

ARRAY VS STRING – EXAMPLE 1

```
public static void main(String[] args) {  
    int[] x = {1, 2, 3, 4};  
    myMethod(x);  
    System.out.println(Arrays.toString(x));  
}
```

<https://powcoder.com>

```
public static void myMethod(int[] a) {  
    for(int i=0; i<a.length; i++) {  
        a[i] = i;  
    }  
}
```

■ What prints?

➤ [0, 1, 2, 3]

ARRAY VS STRING – EXAMPLE 1

```
public static void main(String[] args) {  
    String s = "word";  
    myMethod(s);  
    System.out.println(s);  
}  
  
public static void myMethod(String t) {  
    t = t + "s";  
}
```

■ What prints?

➤ word

ARRAY VS STRING – EXAMPLE 2

```
char[] letters = {'w', 'o', 'r', 'd'};
for(int i=0; i<letters.length; i++){
    if(letters[i]=='o') {
        letters[i]='a';
    }
}
System.out.println(Arrays.toString(letters));
```

■ What prints?

➤ [w, a, r, d]

ARRAY VS STRING – EXAMPLE 2

```
String s = "word";  
for(int i=0; i<s.length(); i++) {  
    if(s.charAt(i)=='o') {  
        s.charAt(i) = 'a';  
    }  
}  
System.out.println(s);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

■ What prints?

- compile time error: unexpected type.
Required: variable. Found: value.

ARRAY VS STRING – EXAMPLE 2

```
String s = "word";
String t = "";
for(int i=0; i<s.length(); i++) {
    if(s.charAt(i) != 'o') {
        t = t + "a";
    } else {
        t = t + s.charAt(i);
    }
}
System.out.println(t);
```

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

THE NULL KEYWORD

- Any reference type variable can have a `null` value.

Assignment Project Exam Help

- `null` indicates the absence of an address.

<https://powcoder.com>

- We can think of a variable with value `null` as a box with no arrow/pointing nowhere.

```
int[] blank = null;
```

blank



NullPointerException



- If we try to access information through a variable with value `null`, the code will throw a `NullPointerException`.

Assignment Project Exam Help

<https://powcoder.com>

```
int[] blank = null;  
System.out.println(blank.length);  
System.out.println(blank[0]);
```

Add WeChat powcoder

DEFAULT VALUES

- In java, **local variables** (those declared within the body of a method, i.e. all the variables we have seen up to now) are **not** given an initial default value!
 - This is why if we try to use a variable without initializing it, the compiler will throw the following error: "variable ____ might not have been initialized"
<https://powcoder.com>
- On the other hand, **array elements** (and other kind of variables, tbd) are initialized with default values:
 - int/short/byte/long with 0
 - double/float with 0.0
 - boolean with false
 - char with 0
 - **reference types with null.**

EXAMPLES – LOCAL VARIABLES

```
int base;  
int area = squared(base);
```

Assignment Project Exam Help

<https://powcoder.com>

```
String day;  
System.out.println("Today is " + day);
```

Add WeChat powcoder

```
int[] grades;  
int size = grades.length;
```

Compile-time error!
**Variable not
initialized!**

EXAMPLES – ARRAYS' ELEMENTS

```
int[] num = new int[3];  
int sum = num[0] + num[1] + num[2];
```

Assignment Project Exam Help

<https://powcoder.com>

sum has value 0

```
String[] days = new String[7];  
System.out.println("Today is " + days[4]);
```

Add WeChat powcoder

> Today is null

```
String[] days = new String[7];  
int numLettersMonday = days[0].length();
```

NullPointerException

Assignment Project Exam Help

RANDOM

<https://powcoder.com>

Add WeChat powcoder

THE RANDOM CLASS

- Up to now you probably learned how to use `Math.random()` to get random numbers between a minimum value and a maximum value.

Assignment Project Exam Help

- We can also use the `Random` class to generate random numbers.

<https://powcoder.com>

- The `Random` class allows us to seed the random numbers such that we will see ***the same*** sequence of 'random' numbers each time.

Add WeChat powcoder

- Why is it useful?

Easier to debug code that is not working.

Comparing outputs from different codes (for instance your assignments)

HOW TO USE RANDOM

First import the Random class: `add import java.util.Random;`

Then you can create a random number generator using the following statement:

<https://powcoder.com>

```
int seed = 123;  
Random randomGenerator = new Random();  
Random otherGenerator = new Random(seed);
```

HOW TO USE RANDOM

First import the Random class: `add import java.util.Random;`

Then you can create a random number generator using the following statement:

<https://powcoder.com>

```
int seed = 123;  
Random randomGenerator = new Random();  
Random otherGenerator = new Random(seed);
```

**Declaration of two
variables of type Random.**

HOW TO USE RANDOM

First import the Random class: `add import java.util.Random;`

Then you can create a random number generator using the following statement:

<https://powcoder.com>

```
int seed = 123;  
Random randomGenerator = new Random();  
Random otherGenerator = new Random(seed);
```

Declaration of two variables of type Random.

Creation of a Random **object**. Note the **new** keyword! Random is a reference type.

METHODS IN RANDOM

boolean	nextBoolean() Returns the next pseudorandom, uniformly distributed boolean value from this random number generator's sequence.
void	nextBytes(byte[] bytes) Generates random bytes and places them into a user-supplied byte array.
double	nextDouble() Returns the next pseudorandom, uniformly distributed double value between 0.0 and 1.0 from this random number generator's sequence.
float	nextFloat() Returns the next pseudorandom, uniformly distributed float value between 0.0 and 1.0 from this random number generator's sequence.
double	nextGaussian() Returns the next pseudorandom, Gaussian (normal) distributed double value with mean 0.0 and standard deviation 1.0.
int	nextInt() Returns the next pseudorandom, uniformly distributed int value from this random number generator's sequence.
int	nextInt(int n) Returns a pseudorandom, uniformly distributed int value between 0 (inclusive) and the specified value (exclusive), drawn from this random number generator's sequence.
long	nextLong() Returns the next pseudorandom, uniformly distributed long value from this random number generator's sequence.
void	setSeed(long seed) Sets the seed of this random number generator using a single long seed.

DICE ROLL

Here's an example of using Random to simulate a dice roll
Assignment Project Exam Help

<https://powcoder.com>

```
Random randomGenerator = new Random();  
int diceRoll = randomGenerator.nextInt(6) + 1;  
System.out.println("The dice rolled " + diceRoll);
```



Coming Soon

Assignment Project Exam Help

In the next video we will be talking about errors and exceptions, as well as try/catch blocks.

<https://powcoder.com>

Add WeChat powcoder