

COMP 250

INTRODUCTION TO COMPUTER SCIENCE

Assignment Project Exam Help

<https://powcoder.com>

Week 13-1 : Maps

Giulia Alberini, Fall 2020

Slides adapted from Michael Langer's

WHAT ARE WE GOING TO DO IN THIS VIDEO?




- Maps

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

MAP (MATHEMATICS)



A map is a set of pairs $\{ (x, f(x)) \}$.

Each x in domain maps to exactly one $f(x)$ in codomain, but it can happen that $f(x_1) = f(x_2)$ for different x_1, x_2 , i.e. many-to-one.

FAMILIAR EXAMPLES

Calculus 1 and 2 ("functions"):
Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder
Asymptotic complexity in CS:

t : input size \rightarrow number of steps in a algorithm.

MAPS IN EVERYDAY LIFE


The term "map" commonly refers to a 2D spatial representation of a region of the earth's surface.

map(x, y) : position in image \rightarrow position in 2D Montreal



COLOR MAP

The color map representing the USA election results in 2020.



vote_result : US_state \rightarrow {D, R}

RESTAURANT MENU

PLATS

SAUMON POËLÉ
caponata, yogourt, rattes confites,
épinards, citron
27

"THE" POUTINE
canard confit, champignons,
oignons sautés au Jack Daniel's,
Tomme du Haut Richelieu, fromage en grains
19.5

POULET AU BABEURRE
esquites de maïs,
cotija, coriandre, lime, salade verte
27

STEAKS

servis avec deux accompagnements

FILET MIGNON (7 OZ)
BLACK ANGUS "1855"
beurre miso/truffe
38

BAVETTE(8 OZ)
BLACK ANGUS "1855"
sauce au poivre
33

ONGLET(8 OZ)
BLACK ANGUS "1855"
mariné au chimichurri
33

BURGERS

servis avec salade & choix de frites régulières ou de patates douces

LE DOUBLE CHEESE
Classique
2 boulettes de boeuf 4oz, fromage orange,
sauce secrète du H, oignon rouge, pickle, bacon
15

GUÉDILLE DE HOMARD
1/2 HOMARD
céleri, persil, oignons verts, mayo
22

LE BANH MI
haut de cuisse de poulet frits, légumes marinés,
basilic thaï, mayo Sriracha,
18
*aussi offert en version
végétarienne (tofu skin)*

LE MONTIGNAC 2.0
boulette cerf 8oz, oignons caramélisés au Jack Daniel,
bacon, Gruyère suisse, sauce BBQ,
mayo moutarde à l'ancienne, rondelles d'oignons du H
19

ACCOMPAGNEMENTS

POMME DE TERRE ALIGOT
purée, crème, cheddar vieilli

9

**FRITES PATATES DOUCE
& MAYO**
7

FRITES & MAYO
6

POUTINE
sauce et fromage en grain
10

CHAMPIGNONS
9

SALADE VERTE
vinaigrette au gingembre

7

RAPINIS AIL ET CITRON
9

menu : dish_name -> price

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

INDEX IN A BOOK

index : term → list of pages


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


- Exponential inequality 185
- Exponential running time 186, 661, 911
- Extended Church-Turing thesis 910
- Extensible library 101
- External path length 418, 834
- F**
- Factorial function 185
- Fail-fast design 107
- Fail-fast iterator 160, 171
- Farthest pair 240
- Fibonacci heap 628, 682
- Fibonacci numbers 57
- FIFO. *See* First-in first-out policy
- FIFO queue.
 - See* Queue data type
- File system 493
- Filter 60
 - blacklist 491
 - dedup 490
 - whitelist 8, 491
- Final access modifier 105–106
- Fingerprint search 774–778
- Finite state automaton.
 - See also* Maxflow problem
- flow network 888
- inflow and outflow 888
- residual network 895
- st-flow 888
- st-flow network 888
- value 888
- Floyd, R. W. 326
- Floyd's method 327
- for loop 16
- Ford-Fulkerson 891–893
 - analysis of 900
 - maximum-capacity path 901
 - shortest augmenting path 897
- Ford, L. 683
- Foreach loop 138
 - arrays 160
 - strings 160
- Forest
 - graph 520
 - spanning 520
- Forest-of-trees 225
- Formatted output 37
- Fortran language 217
- Fragile base class problem 112
- Frazer, W. 306
- Fredman, M. L. 628
- Function call stack 346, 415
- symbol tables 363
- type parameter 122, 134
- Genomics 492, 498
- Geometric data types 76–77
- Geometric sum 185
- getClass() method 101, 103
- Girth of a graph 559
- Global variable 113
- Gosper, R. W. 759
- Graph data type 522–527
- Graph isomorphism 561, 919
- Graph processing 514–693.
 - See also* Directed graph;
 - See also* Edge-weighted digraph; *See also* Edge-weighted graph; *See also* Undirected graph;
 - See also* Directed acyclic graph
- Bellman-Ford 668–681
- breadth-first search 538–541
- components 543–546
- critical-path method 664–666
- depth-first search 530–537
- Dijkstra's algorithm 652
- Kosaraju's algorithm 586–590
- Kruskal's algorithm 624–627
- longest paths 811, 812

MAP (ADT)




A map is a set of (key, value) pairs.
For each key, there is at most one value.

MAP (ADT)




Note that it is possible for two keys to map to the same value.

MAP (ADT)



It is NOT allowed for one key to map to two different values! The example above is NOT a map.


MAP ENTRIES



The black dots here indicate objects (or potential objects) of type K or V that are *not* in the map.

Each (key, value) pair is called an *entry*. In this example, there are four entries.

EXAMPLE



In COMP 250 this semester, the above mapping has ~650 entries.
Most McGill students are not taking COMP 250 this semester.

Student ID also happens to be part of the student record.

MAP ADT

`put(key, value)` `// Add the entry (key, value) to the map. If the map previously contained an entry with key, the old value is replaced by the specified value.`


Assignment Project Exam Help

<https://powcoder.com>

`get(key)` `// Returns the value to which the specified key is mapped. Why not get(key, value) ?`


`remove(key)` `// Removes the entry with the specified key. Returns true if the entry was removed, false otherwise.`

DATA STRUCTURES FOR MAPS



How to organize a set of (**key**, **value**) pairs, i.e. entries ?

ARRAY LIST



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

How can we implement the following methods?


`put(key, value)`

`get(key)`

`remove(key)`

`put()` would be $O(1)$, while `get()` and `remove()` would be $O(n)$

SINGLY (OR DOUBLY) LINKED LIST



LET'S ADD ASSUMPTIONS


- Special case #1: what if keys are *comparable* ?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

ARRAY LIST (SORTED BY KEY)



How can we implement the following methods?

`put(key, value)`

`get(key)`

`remove(key)`

`put()` and `remove()` would be $O(n)$,
while `get()` could be performs in time
 $O(\log n)$ using binary search

BINARY SEARCH TREE (SORTED BY KEY)

How can we implement the following methods?


`put(key, value)`
`get(key)`
`remove(key)`

The performance of `put()`, `get()` and `remove()` depends on the tree. If we have a balanced tree, then these operations would all take time $O(\log n)$ in worst case. You will learn more about balanced tree in COMP 251.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



MINHEAP (PRIORITY DEFINED BY KEY)

How can we implement the following methods?


```
put( key, value )  
get(key)  
remove(key)
```

The performance of `put()` would be $O(\log n)$. Implementing `get()` would require traversing the tree, so it would be $O(n)$. Implementing `remove()` would be a little weird for heaps...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



LET'S ADD ASSUMPTIONS

- ~~Special case #1: what if keys are comparable?~~
- Special case #2: what if keys are unique positive integers in small range?

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

ARRAYS OF VALUES

Assignment Project Exam Help

Then, we could use an array of
type **V (value)** and have $O(1)$
access.

This would not work well if keys
are 9 digit student IDs.



IN GENERAL

- Keys might not be comparable.

<https://powcoder.com>

- Keys might be not be positive integers.
e.g. Keys might be strings or some other type.

Add WeChat powcoder


STRATEGY IN THE GENERAL CASE

Try to define a map from keys to *small* range of positive integers (array index), and then store the corresponding values in the array.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Recall notation: black dots
are not part of the map.

IN THIS VIDEO


Define a map from keys to *large* range of positive integers
Such map is called *hash code*.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

JAVA'S Object.hashCode ()



1-to-1

Assignment Project Exam Help
(not many-to-1) {0, 1, 2, ..., $2^{24} - 1$ }

<https://powcoder.com>

objects in a Java
program (runtime)

Add WeChat powcoder
object's address in JVM memory
(24 bits)

By default, "obj1 == obj2" means "obj1.hashCode() == obj2.hashCode()"

JAVA'S String.hashCode ()

hashCode

```
public int hashCode()
```

Returns a hash code for this string. The hash code for a String object is computed as

$$s[0]*31^{(n-1)} + s[1]*31^{(n-2)} + \dots + s[n-1]$$

using int arithmetic, where $s[i]$ is the i th character of the string, n is the length of the string, and $^$ indicates exponentiation. (The hash value of the empty string is zero.)

Overrides:

hashCode in class Object

Returns:

a hash code value for this object.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE HASH CODE FOR STRINGS

(not used in Java)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

e.g.

$$h(\text{"eat"}) = h(\text{"ate"}) = h(\text{"tea"})$$

ASCII values of 'a', 'e', 't' are 97, 101, 116.

JAVA'S String.hashCode ()

$$s.hashCode () \equiv \sum_{i=0}^{s.length-1} s[i] * x^{s.length-1-i}$$

Assignment Project Exam Help

<https://powcoder.com>

where $x = 31$.

Add WeChat powcoder

JAVA'S String.hashCode ()

$$s.hashCode() \equiv \sum_{i=0}^{s.length-1} s[i] x^{s.length-1-i}$$

Assignment Project Exam Help

<https://powcoder.com>

where $x = 31$.

Add WeChat powcoder

e.g. $s = \text{"eat"}$ then $s.hashCode() = 101 * 31^2 + 97 * 31 + 116$

'e'

'a'

't'

s[0]

s[1]

s[2]

JAVA'S String.hashCode()

$$s.hashCode() \equiv \sum_{i=0}^{s.length-1} s[i] x^{s.length-1-i}$$

Assignment Project Exam Help

<https://powcoder.com>

where $x = 31$.

Add WeChat powcoder

e.g. $s = \text{"ate"}$ then $s.hashCode() = 97 * 31^2 + 116 * 31 + 101$

'a'

't'

'e'

s[0]

s[1]

s[2]

JAVA'S String.hashCode ()

$$s.hashCode () \equiv \sum_{i=0}^{s.length-1} s[i] * (31)^{s.length-1-i}$$


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

If `s1.hashCode () == s2.hashCode ()` then what can we conclude about `s1.equals (s2)` ?

s1 may or may not be the same string as s2.



JAVA'S String.hashCode ()

$$s.hashCode () \equiv \sum_{i=0}^{s.length-1} s[i] * (31)^{s.length-1-i}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

If `s1.hashCode () != s2.hashCode ()` **then what can we conclude about** `s1.equals (s2)` ?

`s1` is a different string than `s2`.



Coming Soon

Assignment Project Exam Help

In the next video:

■ Hash Maps <https://powcoder.com>

Add WeChat powcoder