

COMP 250

INTRODUCTION TO COMPUTER SCIENCE

Assignment Project Exam Help

<https://powcoder.com>

Week 12-1: Binary Search Trees

Add WeChat: powcoder

Giulia Alberini, Fall 2020

Slides adapted from Michael Langer's

WHAT ARE WE GOING TO DO IN THIS VIDEO?



- Binary Search Trees Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

BINARY SEARCH TREES

<https://powcoder.com>

Add WeChat powcoder

BSTNode

- The keys are “comparable” $<, =, >$
e.g. numbers, strings.

Assignment Project Exam Help

<https://powcoder.com>

```
class BSTNode<K>{  
    K key;  
    BSTNode<K> leftchild;  
    BSTNode<K> rightchild;  
    :  
}
```

Add WeChat powcoder

BINARY SEARCH TREE DEFINITION

- binary tree

Assignment Project Exam Help


- keys are comparable, and unique (no duplicates)

<https://powcoder.com>


Add WeChat powcoder

- for each node, all descendents in left subtree are less than the node, and all descendents in the node's right subtree are greater than the node
(comparison is based on node key)


EXAMPLE



THIS IS NOT A BST. WHY NOT?



BST - TRAVERSALS



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

An in-order traversal on a BST visits the nodes in the natural order defined by the key.

a c d e f g j m

BINARY SEARCH TREE ADT

- find(key)
- findMin()
- findMax()
- add(key)
- remove(key)

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

We can define the operations of a BST without knowing how they are implemented. (ADT)

Let's next look at some recursive algorithms for implementing them.

FIND()



Assignment Project Exam Help


Desired behaviour:

<https://powcoder.com>

- `find(root, g)` returns the `g` node
- `find(root, s)` returns null.

Add WeChat powcoder

FIND() – IMPLEMENTATION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
find(root, key) { // returns a node
    if (root == null)
        return null
    else if (root.key == key)
        return root
}
```

FIND() – IMPLEMENTATION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
find(root, key) { // returns a node
    if (root == null)
        return null
    else if (root.key == key)
        return root
    else if (key < root.key)
        return find(root.left, key)
    else
        return find(root.right, key)
}
```

FINDMIN()




Assignment Project Exam Help

<https://powcoder.com>
findMin() should return the node with the smallest key. So, for example given

Add WeChat [powcoder](https://powcoder.com)
the BST on the left,

- findMin(root) returns ... ?

FINDMIN()




Assignment Project Exam Help

<https://powcoder.com>
findMin() should return the node with the smallest key. So, for example given

Add WeChat [powcoder](https://powcoder.com)
the BST on the left,

- `findMin(root)` returns the **a** node

FINDMIN()




Assignment Project Exam Help

<https://powcoder.com>
findMin() should return the node with the smallest key. So, for example given

Add WeChat [powcoder](https://powcoder.com)
the BST on the left,

- `findMin(root)` returns ... ?

FINDMIN()




Assignment Project Exam Help

<https://powcoder.com>
findMin() should return the node with the smallest key. So, for example given

Add WeChat [powcoder](https://powcoder.com)
the BST on the left,

- `findMin(root)` returns the **c** node

FINDMIN() - IMPLEMENTATION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
findMin(root){ // returns a node
    if (root == null)
        return null
}
```

FINDMIN() - IMPLEMENTATION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
findMin(root){ // returns a node
    if (root == null)
        return null
    else if (root.left == null)
        return root
    else
        return findMin( root.left )
}
```

FINDMAX()




Assignment Project Exam Help

<https://powcoder.com>
findMax() should return the node with the greatest key. So, for example given

Add WeChat [powcoder](https://powcoder.com)
the BST on the left,

- findMax(root) returns ... ?

FINDMAX()




Assignment Project Exam Help

<https://powcoder.com>
findMax() should return the node with the greatest key. So, for example given

Add WeChat [powcoder](https://powcoder.com) the BST on the left,

- `findMax(root)` returns the **m** node.

FINDMAX() – IMPLEMENTATION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
findMax(root) { // returns a node
    if (root == null)
        return null
    else if (root.right == null)
        return root
    else
        return findMax (root.right)
}
```

ADD()



Assignment Project Exam Help

add(key) should add a BSTNode to the tree.


<https://powcoder.com>

- Where?

Add WeChat powcoder

- How?

ADD()



Assignment Project Exam Help

add(key) should add a BSTNode to the tree.

<https://powcoder.com>


- add(j) ?

Add WeChat powcoder

- add(w) ?

A new node is always a leaf.

ADD()



Assignment Project Exam Help


add(key) should add a BSTNode to the
<https://powcoder.com>
tree.

Add WeChat powcoder

- add(**n**) ?

A new node is always a leaf.

ADD() - IMPLEMENTATION



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

```
add(root, key) { // returns root node
```

```
    return root
```

```
}
```

ADD() - IMPLEMENTATION



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

```
add(root, key) { // returns root node
    if (root == null)
        root = new BSTnode(key)

    return root
}
```

ADD() - IMPLEMENTATION



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

```
add(root, key) { // returns root node
    if (root == null)
        root = new BSTnode(key)
    else if (key < root.key) {
        root.left = add(root.left, key)
    }

    return root
}
```

ADD() - IMPLEMENTATION



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


```
add(root, key) { // returns root node
    if (root == null)
        root = new BSTnode(key)
    else if (key < root.key) {
        root.left = add(root.left, key)
    }
    else if (key > root.key) {
        root.right = add(root.right, key)
    }
    return root
}
```

Q: What happens if `root.key == key`?

A: Nothing!

REMOVE()

remove(**c**) →




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVE()


remove(**c**) → this is one way to do it



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder



REMOVE()


remove(**c**) → the following algorithm
does this:




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



REMOVE() - IMPLEMENTATION




```
remove(root, key){ // returns root node
    if( root == null )
        return null
    else if ( key < root.key )
    else if ( key > root.key )
    else
    }
    return root
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVE() - IMPLEMENTATION




```
remove(root, key){ // returns root node
    if( root == null )
        return null
    else if ( key < root.key )
        root.left = remove(root.left, key)
    else if ( key > root.key )
        root.right = remove(root.right, key)
    else
        // Node to be removed is the root
        // Implement the logic to replace the root with its in-order successor or predecessor
    }
    return root
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVE() - IMPLEMENTATION



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

```
remove (root, key) { // returns root node
    if ( root == null )
        return null
    else if ( key < root.key )
        root.left = remove (root.left, key)
    else if ( key > root.key )
        root.right = remove (root.right, key)
    else if (root.left == null)
        root = root.right
    else if (root.right == null)
        root = root.left

    }
    return root
}
```

REMOVE() - IMPLEMENTATION




Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
remove (root, key) { // returns root node
    if ( root == null )
        return null
    else if ( key < root.key )
        root.left = remove (root.left, key)
    else if ( key > root.key )
        root.right = remove (root.right, key)
    else if (root.left == null)
        root = root.right
    else if (root.right == null)
        root = root.left

    }
    return root
}
```

REMOVE() - IMPLEMENTATION




Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

```
remove(root, key){ // returns root node
    if( root == null )
        return null
    else if ( key < root.key )
        root.left = remove(root.left, key)
    else if ( key > root.key )
        root.right = remove(root.right, key)
    else if (root.left == null)
        root = root.right
    else if (root.right == null)
        root = root.left
    else {
        root.key = findMin(root.right).key
        root.right = remove(root.right, root.key)
    }
    return root
}
```

REMOVE() - EXAMPLE

remove(**k**) →




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVE() - EXAMPLE

remove(**k**) →




BALANCED VS UNBALANCED

balanced


$$\text{height} = \log(n + 1) - 1$$

$$n = 2^{h+1} - 1$$



maximally
unbalanced

$$\text{height} = n - 1$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

BEST VS WORST CASE SCENARIO

best case

worst case

findMin() Assignment Project Exam Help

findMax()

<https://powcoder.com>

Add WeChat powcoder

find(key)

add(key)


remove(key)

BEST VS WORST CASE SCENARIO

best case

worst case

findMin() $O(1)$ findMax() $O(n)$



findMax()

<https://powcoder.com>

Add WeChat powcoder

find(key)

add(key)

remove(key)

BEST VS WORST CASE SCENARIO

best case

worst case

findMin() $O(1)$ $O(n)$

findMax() $O(1)$ $O(n)$

find(key)


add(key)

remove(key)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



BEST VS WORST CASE SCENARIO

best case

worst case

findMin() $O(1)$ $O(n)$

findMax() $O(1)$ $O(n)$


find(key) $O(1)$ $O(n)$

add(key)

remove(key)


<https://powcoder.com>

Add WeChat powcoder



could be zigzag

BEST VS WORST CASE SCENARIO

	best case	worst case	
findMin()	$O(1)$	$O(n)$	
findMax()	$O(1)$	$O(n)$	
find(key)	$O(1)$	$O(n)$	} Could be zigzag
add(key)	$O(1)$	$O(n)$	
remove(key)	$O(1)$	$O(n)$	

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


BINARY SEARCH (TREES)

When a binary search tree is balanced, then finding a key is very similar to a binary search.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



BALANCED BINARY SEARCH TREES

(COMP 251: AVL TREES, RED-BLACK TREES)

	best case	worst case
findMin()	$O(\log n)$	$O(\log n)$
findMax()	$O(\log n)$	$O(\log n)$
find(key)	$O(1)$	$O(\log n)$
add(key)	$O(\log n)$	$O(\log n)$
remove(key)	$O(\log n)$	$O(\log n)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Coming Soon

Assignment Project Exam Help

In the next videos:

■ Heaps <https://powcoder.com>

Add WeChat powcoder