

COMP 250

INTRODUCTION TO COMPUTER SCIENCE

Assignment Project Exam Help

<https://powcoder.com>

Week 5-3 : Doubly Linked Lists

Add WeChat powcoder

Giulia Alberini, Fall 2020

WHAT ARE WE GOING TO DO IN THIS VIDEO?



- Doubly Linked Lists Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

LINKED LISTS
<https://powcoder.com>

Add WeChat powcoder

IMPLEMENTATIONS

There are different implementations of a list:

- Array list
 - Singly linked list
 - Doubly linked list
- Assignment Project Exam Help**
- <https://powcoder.com>**
- Idea: the elements in the list are linked using pointers**
- Add WeChat powcoder**


DOUBLY LINKED LIST

Each node has a reference to the next node *and* to the previous node.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



DOUBLY LINKED LIST NODE

```
class DNode {  
    Shape element;  
    DNode next;  
    DNode prev;  
}
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
DNode myNode = new DNode();  
n.element = new Shape(▲);
```

myNode



DOUBLY LINKED LIST


```
public class DLinkedList {  
    private DNode head;  
    private DNode tail;  
    private int size;  
    :  
    private class DNode {  
        Shape element;  
        DNode next;  
        DNode prev;  
    }  
}
```

```
DLinkedList list = new DLinkedList();  
:
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



DOUBLY LINKED LIST – removeLast()

```
tail = tail.prev;  
tail.next.prev = null; // not necessary  
tail.next = null;  
size = size - 1;  
// to return the element,  
// you need to do a bit more work  
// edge cases for size = 0 and 1 to be added
```

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

list

head

tail

size



DOUBLY LINKED LIST – removeLast()


```
tail = tail.prev;  
tail.next.prev = null; // not necessary  
tail.next = null;  
size = size - 1;  
// to return the element,  
// you need to do a bit more work  
// edge cases for size = 0 and 1 to be added
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

For a doubly linked list, removing the last element is much faster.



WORSE CASE TIME COMPLEXITY (N = LIST SIZE)

	array list	SLinkedList	DLinkedList
addFirst()	$O(N)$	$O(1)$	$O(1)$
removeFirst()	$O(N)$	$O(1)$	$O(1)$
addLast()	$O(1)$	$O(1)$	$O(1)$
removeLast()	$O(1)$	$O(N)$	$O(1)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OTHER LIST OPERATIONS

Many list operations require access to a specific node i

Assignment Project Exam Help

get(i)

set(i, e)

add(i, e)

remove(i)

:

<https://powcoder.com>

Add WeChat powcoder

LINKED LISTS

Suppose we want to access general node i in a linked list.

Two issues arise: Assignment Project Exam Help

<https://powcoder.com>

- Edge cases ($i = 0, i = \text{size} - 1$) require extra code.
This is a pain and can lead to coding errors.
- How long does it take to access node i ?

AVOID EDGE CASES WITH "DUMMY NODES"


```
public class DLinkedList {  
    private DNode dummyHead;  
    private DNode dummyTail;  
    private int size;  
    :  
    public DLinkedList() {  
        dummyHead = new DNode();  
        dummyTail = new DNode();  
        dummyHead.next = dummyTail;  
        dummyTail.prev = dummyHead;  
        size = 0;  
    }  
}
```

```
// empty list  
DLinkedList list = new DLinkedList();
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



AVOID EDGE CASES WITH "DUMMY NODES"


```
public class DLinkedList {  
    private DNode dummyHead;  
    private DNode dummyTail;  
    private int size;  
    :  
    public DLinkedList() {  
        dummyHead = new DNode();  
        dummyTail = new DNode();  
        dummyHead.next = dummyTail;  
        dummyTail.prev = dummyHead;  
        size = 0;  
    }  
}
```

```
DLinkedList list = new DLinkedList();  
// add 2 elements...
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



HOW DO WE ACCESS A NODE? – get()


```
public Shape get(int i) {  
    DNode node = getNode(i);  
    return node.element;  
}
```

Assignment Project Exam Help

<https://powcoder.com>

```
private DNode getNode(int i) {  
    // verify that 0<=i<size omitted  
    DNode node = dummyHead.next;  
    for(int k=0; k<i; k++)  
        node = node.next;  
    return node;  
}
```

Add WeChat powcoder




CAN WE SPEED THIS UP? – getNode()

```
private DNode getNode(int i) {  
    // verify that 0<=i<size omitted  
    DNode node;  
    if (i < size/2) {  
        node = dummyHead.next;  
        for(int k=0; k<i; k++)  
            node = node.next;  
    }  
    else {  
        node = dummyTail.prev;  
        for(int k=size -1; k>i; k--)  
            node = node.prev;  
    }  
    return node;  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



JAVA LINKEDLIST CLASS

<https://docs.oracle.com/javase/8/docs/api/java/util/LinkedList.html>

It uses a *doubly linked list* as the underlying data structure.

Assignment Project Exam Help

It has some methods that ArrayList doesn't have e.g.:

- `addFirst()`
- `removeFirst()`
- `addLast()`
- `removeLast()`

Why ?

<https://powcoder.com>

Add WeChat powcoder

Q: What is the time complexity of the following ?

```
DLinkedList list = new DLinkedList( ) ;
```

```
for (k = 0; k < N; k++) // N is some constant  
list.addFirst(10);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Q: What is the time complexity of the following ?

```
DLinkedList list = new DLinkedList( ) ;
```

```
for (k = 0; k < N; k++) // N is some constant  
list.addFirst(1);
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

A: $1 + 1 + 1 + \dots 1 = N \quad \Rightarrow \quad O(N)$

where '1' means constant.

Q: What is the time complexity of the following ?

```
for (k = 0; k < list.size(); k++) // size == N
```

Assignment Project Exam Help

<https://powcoder.com>

Assuming here that `getNode(1)` always starts at the head.

Q: What is the time complexity of the following ?

```
for (k = 0; k < list.size(); k++) // size == N
```

Assignment Project Exam Help

<https://powcoder.com>


Assuming here that `getNode(1)` always starts at the head.

A: 1 + 2 + 3 + N

$$= \frac{N(N+1)}{2} \Rightarrow O(N^2)$$

In 3 weeks we'll talk about a more efficient way to iterate through elements in a (Java) LinkedList!

WHAT ABOUT "SPACE COMPLEXITY" ?



All three data structures use space $O(N)$ for a list of size N .
But linked lists use 2x (single) or 3x (double).

ARRAY LIST VERSUS LINKED LIST ?

Array lists and linked lists both take $O(N)$ time to add or remove from an arbitrary position in the list.

<https://powcoder.com>

In practice and when N is large, array lists are faster. But the reasons are subtle and have to do with how computer memory works, in particular, how caches exploit contiguous memory allocation. You will learn about that topic in COMP 273.

Add WeChat powcoder

DO YOU EVER NEED LINKED LISTS ?

Yes. Even if you prefer ArrayLists, you still need to understand LinkedLists. Linked lists are special cases of a general and widely used data structure called a *tree* which we will be discussing extensively.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Coming Soon

Assignment Project Exam Help

In the next videos:

- <https://powcoder.com>
Quadratic sorting algorithms
- [Add WeChat powcoder](#)
Asymptotic notations