

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

Distributed

<https://powcoder.com>

Connections

Add WeChat powcoder

<https://powcoder.com>

## Outline

### Assignment Project Exam Help

- Trees

Add WeChat powcoder

- Canonical Form

- Distributed Views

- Broadcast Assignment Project Exam Help

- BFS/DFS

<https://powcoder.com>

- Flooding

Add WeChat powcoder

- Convergecast

- Applications

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Trees

Add WeChat powcoder

<https://powcoder.com>

## Trees and Communication

### Assignment Project Exam Help

- Trees are everywhere: saplings, rivers, chemical compounds.
  - There is something about their efficiency and economy.


Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




- Trees form a natural communication structure in distributed computing.

<https://powcoder.com>

## Main Concepts on Trees

### Assignment Project Exam Help

- A tree is a connected graph that has no cycles.
- Start with the tree of one vertex: we can build up any tree we wish by successively adding a new edge and a new vertex.
  - At each stage, the # of vertices exceeds the number of edges by 1, so every tree with  $n$  vertices has exactly  $n - 1$  edges



<https://powcoder.com>

## Characterization of Trees

### Assignment Project Exam Help

- Let  $T$  be a graph with  $n$  vertices. Then the following statements are equivalent.
  - 1.  $T$  is connected and has no cycles.
  - 2.  $T$  has  $n - 1$  edges and has no cycles.
  - 3.  $T$  is connected and has  $n - 1$  edges.
  - 4.  $T$  is connected and the removal of any edge disconnects  $T$ .
  - 5. Any two vertices of  $T$  are connected by exactly one path.
  - 6.  $T$  contains no cycles, but the addition of any new edge creates a cycle.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

<https://powcoder.com>

## Spanning Trees


### Assignment Project Exam Help

- Let  $G$  be a connected graph. Then a spanning tree in  $G$  is a subgraph of  $G$  that includes every vertex and is also a tree.
- A graph ...



Add WeChat powcoder

- ... and possible spanning trees



- Spanning trees emerge naturally in communication.

<https://powcoder.com>

## Forests

### Assignment Project Exam Help

- A Forest is a collection of vertex disjoint trees.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Forests arise naturally in clustering.
- A Spanning Forest is a collection of vertex disjoint spanning trees.



<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>  
**Canonical Form**

Add WeChat powcoder


<https://powcoder.com>

## How Do Nodes Build their Knowledge?

### Assignment Project Exam Help

- They learn by exchanging messages in rounds.

Add WeChat powcoder



### Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- At the same time, different nodes learn different things!

<https://powcoder.com>

## Information Growth and Knowledge Discovery

### Assignment Project Exam Help


- Start from node  $u$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- When does the growth stop?

<https://powcoder.com>

### In a Line Graph

## Assignment Project Exam Help

- In a typical synchronous distributed algorithm each node executes the following atomic actions

send  $\rightarrow$  receive  $\rightarrow$  process

in synchronous rounds.

## Assignment Project Exam Help


- Node  $v$ , by exchanging messages in rounds...

<https://powcoder.com>



Add WeChat powcoder

- ...receives information about distance 1, 2, 3, ... nodes.



<https://powcoder.com>

### Canonical Form

## Assignment Project Exam Help

- Assume that initially, all nodes only know their own identifier and potentially some additional input.
- Information needs at least  $r$  rounds to travel  $r$  hops.
- After  $r$  rounds, a node  $v$  can only learn about other nodes at distance at most  $r$ .
- If message size and local computations are not restricted, it is in fact not hard to see, that
  - in  $r$  rounds, a node  $v$  can learn exactly all the node labels and inputs up to distance  $r$  from  $v$ .
- This allows us to transform every deterministic  $r$ -round synchronous algorithm into a simple canonical form.

<https://powcoder.com>

## Cumulative Messages

### Assignment Project Exam Help

- The idea is to “simplify communication” with cumulative messages

Add WeChat powcoder

- A typical synchronous distributed algorithm at each node consists of a sequence of executions

### Assignment Project Exam Help

send  $\rightarrow$  receive  $\rightarrow$  process

<https://powcoder.com>

in synchronous rounds.

Add WeChat powcoder

- Often what matters is the source and the destination.
- Can we first do a sequence of  $r$  executions “send  $\rightarrow$  receive” followed by a single “process” at the end?
- In other words, can we send “cumulative” messages for  $r$  rounds and finally do the processing?

<https://powcoder.com>

### Example: Computing the Sum in a Ring

Assignment Project Exam Help

- Consider a ring of  $n$  nodes with identifiers  $ID_i$  and weights  $w_i$  at each node, for  $i = 1, 2, \dots, n$ .
- In a typical distributed computation for a node  $i$ :  
for  $r$  rounds do
  1.  $i$  sends pair  $(ID_i, w_i)$  to  $i + 1$ , and receives pair  $(ID_{i-1}, w_{i-1})$  from  $i - 1$ .
  2. process by adding  $w_i + w_{i-1}$ .
- This can be done in a cumulative manner at  $i$  as follows:
  1.  $i$  sends  $(ID_i, w_i), (ID_{i-1}, w_{i-1}), \dots, (ID_{i-1}, w_{i-r})$  to  $i + 1$ , receives  $(ID_{i-1}, w_{i-1}), (ID_{i-2}, w_{i-2}), \dots, (ID_{i-r-1}, w_{i-r-1})$  from  $i - 1$
  2. process by adding  $w_{i-1} + w_{i-2} + \dots + w_{i-r-1}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


<https://powcoder.com>

## Synchronous Algorithm: Canonical Form

### Assignment Project Exam Help

- Synchronous Algorithm Canonical Form**

1. In  $r$  rounds, send complete initial state to nodes at distance at most  $r$  /\* all the communication first \*/
  2. Compute output based on complete information about  $r$ -neighborhood /\* do all the computation in the end \*/
- Example: information “moves” in waves!





<https://powcoder.com>

### Main Claim on Canonical Form

## Assignment Project Exam Help

- **Theorem 1** *If message size and local computations are not bounded, every deterministic, synchronous  $r$ -round algorithm can be transformed into an algorithm having the canonical form (i.e., it is possible to first communicate for  $r$  rounds and then do all the computations in the end).*
- Notice the importance of being able to transmit messages of arbitrary size:
  - this size will depend on the number of  $r$  rounds, and
  - it can be exponential in  $r$
- To handle “large size messages” you need “large memory”

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### Main Argument (1/2)

## Assignment Project Exam Help

- Consider an  $r$ -round algorithm  $\mathcal{A}$ . We want to show that  $\mathcal{A}$  can be brought to a canonical form.
- First, let the nodes communicate for  $r$  rounds.
- Assume that in every round, every node sends its complete state to all of its neighbors.
- By induction, after  $i$  rounds, every node knows the initial state of all other nodes at distance at most  $i$ .
- Hence, after  $r$  rounds, a node  $v$  has the combined initial knowledge of all the nodes in its  $r$ -neighborhood.
- We want to show that this suffices to simulate locally (at node  $v$ ) enough of Algorithm  $\mathcal{A}$  to compute all the messages that  $v$  receives in the  $r$  communication rounds of a regular execution of Algorithm  $\mathcal{A}$ .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### Main Argument (2/2)

## Assignment Project Exam Help

- We prove the following statement by induction on  $i$ .

**Claim.** For all nodes at distance at most  $r - i + 1$  from  $v$ , node  $v$  can compute all messages of the first  $i$  rounds of a regular execution of  $\mathcal{A}$ .

- $i = 1$ :  $v$  knows the initial state of all nodes in the  $r$ -neighborhood and can compute all messages of first round.
- Induction Step: from  $i$  to  $i + 1$ .
  - By the induction hypothesis,  $v$  can compute the messages of the first  $i$  rounds of all nodes in its  $(r - i + 1)$ -neighborhood.
  - It can therefore compute all messages that are received by nodes in the  $(r - i)$ -neighborhood in the first  $i$  rounds.
  - This is exactly what is needed to compute the messages of round  $i + 1$  of nodes in the  $(r - i)$ -neighborhood.

<https://powcoder.com>

### Issues

## Assignment Project Exam Help

- It is straightforward to generalize the canonical form to randomized algorithms.
  - Every node first computes all the random bits it needs throughout the algorithm.
- The random bits are then part of the initial state of a node.

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>  
**Distributed Views**

Add WeChat powcoder

<https://powcoder.com>

## Views: Undirected Networks


### Assignment Project Exam Help

- Each node has port labels and can build a view accumulating its knowledge.
- The view of depth  $k$  of a node is a tree containing information on all the walks of length  $k$  leaving that node.
- Views contain all the information that nodes could obtain by exchanging messages with their neighbors.

Add WeChat powcoder

### Assignment Project Exam Help

<https://powcoder.com>



<https://powcoder.com>

## **$r$ -View (or $r$ -Hop View or $r$ -Neighborhood)**

Assignment Project Exam Help

- Collection of initial states of all nodes in the  $r$ -neighborhood of a node  $v$ , is called  $r$ -hop view (or neighborhood) of  $v$ .
  - For a given graph  $G$ , it is denoted by

$V_r^G(v)$  or  $N_r^G(v)$

Assignment Project Exam Help

- We usually omit mention of  $G$  (when clear from the context) and denote it by

$V_r(v)$  or  $N_r(v)$ .

Add WeChat powcoder


- A view can be enriched as needed by including information:
  - on node states,
  - node topology  $r$  hops away from the source  $v$ ,
  - etc

<https://powcoder.com>

Example:  $r$ -Hop Views for  $r = 0, 1, 2, 3$

Assignment Project Exam Help

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

### Issues

## Assignment Project Exam Help

- Assume that initially, every node knows its degree, its label (identifier) and potentially some additional input.
- The  $r$ -hop view of a node  $v$  then includes
  - the complete topology of the  $r$ -neighborhood,
  - possibly edges between nodes at distance  $r$  in the subgraph, and
  - the labels and additional inputs of all nodes in the  $r$ -neighborhood.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### The View as a Function

## Assignment Project Exam Help

- **Theorem 2** *A deterministic  $r$ -round algorithm  $A$  is a function that maps every possible  $r$ -hop view to the set of possible outputs.*
- By Theorem 1, we know that we can transform Algorithm  $A$  to the canonical form.
- After  $r$  communication rounds, every node  $v$  knows exactly its  $r$ -hop view.
- This information suffices to compute the output of node  $v$ .

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### Issues

## Assignment Project Exam Help

- Two nodes with equal  $r$ -hop views
  - have to compute the same output in every  $r$ -round algorithm.
- For coloring algorithms, the only input of a node  $v$  is its label.
  - The  $r$ -hop view of a node therefore is its labeled  $r$ -neighborhood.

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

<https://powcoder.com>

## Power of Views<sup>a</sup>

### Assignment Project Exam Help

- For a graph of  $n$  nodes, Norris (1995) proved that if two nodes have the same view of depth  $n - 1$ , then they have the same views for all depths.



- Taking the diameter  $\delta$  of a graph into account, can improve  $n - 1$  to

$$O(\delta + \delta \log(n/\delta))$$

for bidirectional graphs with port numberings

---


<sup>a</sup>We won't discuss details for these claims.

<https://powcoder.com>

## Views: Directed Networks

### Assignment Project Exam Help

- A view can be computed by a node on a network using a distributed deterministic algorithm



- In directed networks we have “in” and “out” views at a node.

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>  
**Broadcasting**


Add WeChat powcoder

<https://powcoder.com>

## Broadcasting

### Assignment Project Exam Help

- Broadcasting refers to a method of transferring a message to all recipients “at once” in a network.



- It is initiated by a single processor, the source.
- The source sends a message to all other nodes in the system.
- In a typical network it may not be possible to send a message “at once” since there might be multiple hops from the source to the rest of the nodes.

<https://powcoder.com>

## Graph Concepts in Broadcasting

### Assignment Project Exam Help

- The distance  $d(u, v)$  between nodes  $u$  and  $v$  in an undirected graph  $G$  is the number of hops of a minimum length path between  $u$  and  $v$ .

Add WeChat powcoder

- The radius
  - of a node  $u$  is the maximum distance between  $u$  and any other node in the graph

### Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$R(u) = \max_v d(u, v)$$

- of a graph is the minimum radius of any node in the graph.

$$R = \min_u R(u)$$

- The radius and diameter of a graph are called graph eccentricities.




<https://powcoder.com>

## Examples: Graph Eccentricities

### Assignment Project Exam Help

- Distance

Add WeChat [powcoder](https://powcoder.com)



- Radius
- Diameter


<https://powcoder.com>

### Examples: Graph Eccentricities

#### Assignment Project Exam Help

- Radius, Diameter

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- There is a close relationship between the radius  $R$  and the diameter  $D$  of a graph
  - $R \leq D \leq 2R$ .

<https://powcoder.com>

### Examples: Graph Eccentricities

## Assignment Project Exam Help


- What are the Radius and Diameter?

Add WeChat powcoder

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>  
**BFS/DFS**


Add WeChat powcoder

<https://powcoder.com>

## BFS Spanning Trees

### Assignment Project Exam Help

- Traversal of a graph is performed by visiting all of its vertices in some predefined order.
- **Breadth-First-Search Tree.** A breadth-first-search tree  $T$  of a graph  $G$  is a spanning tree of  $G$  such that for every node of  $G$ , the tree path is a minimum hop path to the root.



- Of course a root must be specified!

<https://powcoder.com>

### BFS Algorithm<sup>a</sup>

## Assignment Project Exam Help

- **BFS Algorithm:** Input a graph  $G = (V, E)$

Proceed by layers,

Add WeChat powcoder

1. mark the root  $r$ ;
2. mark all neighbor vertices that are one hop away from  $r$ ;
3. mark new vertices that are one hop away from these neighbors (these are two hops away from  $r$ );
4. and so on.

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- It uses a FIFO queue
- It checks whether a vertex has been discovered before enqueueing the vertex rather than delaying this check until the vertex is dequeued from the queue

---

<sup>a</sup>Invented in 1945 by Konrad Zuse


<https://powcoder.com>

## BFS Algorithm

### Assignment Project Exam Help

- How do you construct a BFS tree from a given graph?

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## BFS (Distance Computation (1/2))

### Assignment Project Exam Help

- It starts by placing the source node  $s$  at distance  $d(s) = 0$ ; the distance of all other nodes starts as  $d(i) = \infty$ .
- At the  $k$ th step (starting at  $k = 0$ ), all nodes  $i$  at distance  $d(i) = k$  are examined, and any neighbors  $j$  with  $d(j) = \infty$  (i.e., not yet discovered) have their distance  $d(j)$  set to  $k + 1$ .
- The process halts when step  $k$  finds no such neighbors;  $d(j)$  is then the length of the shortest path from  $s$  to  $j$ , or  $d(j) = \infty$  if there is no such path.



<https://powcoder.com>


## BFS (Distance Computation (2/2))

### Assignment Project Exam Help

- BFS is the simplest way to search a graph.
- It is suited only for unweighted graphs: ignores edge weights.
- **Example 1:**

Assignment Project Exam Help

<https://powcoder.com>



- **Example 2:** In a social network, your friends are at level one and your friends of friends are at level two in a BFS starting at your node.

<https://powcoder.com>

### What is BFS Tree Used for?

#### Assignment Project Exam Help

- Finding all nodes within one connected component
  - BFS by itself is not enough: some message passing is needed!
- Finding the shortest path between two nodes  $u$  and  $v$  (with path length measured by number of edges)
  - $u$  and  $v$  could be the nodes initiating BFS trees, respectively.
- Testing a graph for bipartiteness
  - Construct a BFS tree from a vertex  $v$  and look at all other vertices at odd or even distance from  $v$ .
- Doing efficient broadcast
  - from any any node.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## DFS Spanning Trees

### Assignment Project Exam Help

- For a rooted spanning tree  $T$  of a graph  $G$ ,

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

let us denote by

- $S(u)$  all the nodes in the subtree of  $u$ , and
- $P(u)$  denote all the vertices that exist in a path between  $u$  and the root.

<https://powcoder.com>

## DFS Spanning Trees

### Assignment Project Exam Help

- **DFS Algorithm:** Input a graph  $G = (V, E)$

1. Start from a vertex  $r$ ;
2. visit all possible vertices as far as you can reach;
3. when all vertices are visited, return to the current parent node.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


<https://powcoder.com>

## DFS (Depth-First Search) (1/2)

Assignment Project Exam Help

- DFS visits the same nodes as BFS but in a different order.
- If it sees an unvisited node  $j$  while examining node  $i$ , it fully discovers all unvisited nodes reachable from  $j$  and then backtracks to node  $i$  to consider the remainder of the nodes adjacent to  $i$ .

Assignment Project Exam Help



- It is best described recursively.

<https://powcoder.com>

## DFS (Depth-First Search) (2/2)

### Assignment Project Exam Help

- All nodes start out unvisited.
- DFS( $i$ ):


Add WeChat powcoder

1. mark  $i$  as visited
2. for all nodes  $j$  adjacent to  $i$  do:
3. if node  $j$  is not visited  $DFS(j)$

Assignment Project Exam Help

- Example <https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

What is DFS Tree Used for?

Assignment Project Exam Help

- Finds all of the vertices reachable from a source vertex  $r$  in a graph  
Add WeChat powcoder
  - unlike BFS it does not need to search the whole graph.
- Topological sorting.  
Assignment Project Exam Help
  - this is because of the way it traverses a directed graph.
- Finding the bridges of a graph.  
<https://powcoder.com>  
Add WeChat powcoder
  - these are edges whose removal disconnects the graph.
- Finding connected components.
  - like BFS.
- Finding strongly connected components.
  - these are maximal “strongly connected components” of a directed graph.

<https://powcoder.com>

### Lower Bounds

## Assignment Project Exam Help

- The message complexity of broadcast in an  $n$  node graph is at least  $n - 1$ .

[Add WeChat powcoder](#)

- This is because every node must receive the message.

- Which graphs require  $n - 1$  message complexity?

## Assignment Project Exam Help

- The source's radius is a lower bound for the time complexity.

- This is because it needs that many hops from a source.

<https://powcoder.com>

- You can use a pre-computed spanning tree to do broadcast with tight message complexity.

[Add WeChat powcoder](#)

- If the spanning tree is a BFS spanning tree (for a given source), then the time complexity is tight as well.




<https://powcoder.com>

## More on BFS and DFS

### Assignment Project Exam Help

- Both BFS and DFS describe a tree;  $i$  is the parent of  $j$  if the unvisited node  $j$  is discovered while examining node  $i$ .
- The DFS tree has a rich set of mathematical properties.
  - For example, if “( $i$ ” is printed at the start of  $DFS(i)$  and “ $i$ )” when it finishes (after traversing all its neighbors  $j$ ), then the result is an expression with properly nested and matching parentheses.
  - The parentheses of two nodes  $i$  and  $j$  are either nested one within the other, or they are disjoint.



(1 (2 (3 (4 (5 5) (6 6) 4) 3) 2) 1)

<https://powcoder.com>

## Impact of Knowledge: Clean Graphs

### Assignment Project Exam Help

- If the graph is stored in adjacency list form, both BFS and DFS take an amount of time that is linear in the size of the graph:  $O(|V| + |E|)$ , where  $|V|$  and  $|E|$  are the number of nodes and edges, respectively.
- Knowledge can affect the message complexity!
- Call a graph (network) *clean* if the nodes do not know the topology of the graph.
- If the nodes do not know the topology of the graph (i.e., for a clean network) then the number of edges is a lower bound for the broadcast message complexity.
  - If you do not try every edge, you might miss a whole part of the graph behind it.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>  
**Flooding**

Add WeChat powcoder

<https://powcoder.com>

## Outline

### Assignment Project Exam Help

- Flooding
- FloodMaxID
- OptFloodMax

Add WeChat powcoder

### Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Flooding

### Assignment Project Exam Help

- Used by nodes to identify themselves

[Add WeChat powcoder](#)

- **Flooding Algorithm**

1. The source (root) sends the message to all neighbors.
2. Each other node  $v$  upon receiving the message the first time forwards the message to all (other) neighbors.
3. Upon later receiving the message again (over other edges), a node can discard the message.


[https://powcoder.com](#)  
[Add WeChat powcoder](#)

<https://powcoder.com>

### Flooding Example

## Assignment Project Exam Help

- Let  $A$  be the initiating node:



- Note that node  $D$  receives two messages.

<https://powcoder.com>

## Flooding and Trees

### Assignment Project Exam Help

- If node  $v$  receives the message first from node  $u$ , then node  $v$  calls node  $u$  parent.
  - Parent relation defines a spanning tree  $T$  (nodes receiving more than one message keep message only from one initiator).
  - If flooding algorithm is executed in a synchronous system, then  $T$  is a BFS spanning tree (with respect to the root).
- Let  $R(s)$  be the radius of the source  $s$  in the network.
  - In asynchronous systems the flooding algorithm terminates after  $R(s)$  time units.
  - However, the spanning tree constructed may not be a BFS spanning tree.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## FloodMaxID

### Assignment Project Exam Help

- We give a simple algorithm that causes both leaders and non-leaders to identify themselves.
- The algorithm
  - requires that the processes know the diameter of the network;
  - floods the maximum ID throughout the network,
    - \* so we call it the FloodMaxID algorithm.
- The algorithm makes leader election possible in a general network.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

## Flood MaxID

### Assignment Project Exam Help

- **FloodMaxID Algorithm**

1. Every process maintains a record of the maximum ID it has seen so far (initially its own).
  2. At each round, each process propagates this maximum on all of its outgoing edges.
  3. After  $D$  (diameter) rounds, if the maximum value seen is the process's own ID, the process elects itself the leader; otherwise, it is a non-leader.
- FloodMax elects the process with the maximum ID.

<https://powcoder.com>

## Analysis of FloodMax

### Assignment Project Exam Help

- Define  $i_{\max}$  to be the index of the process with the maximum ID, and  $u_{\max}$  to be that user ID.
- **Theorem 3** *In the FloodMax algorithm, process  $i_{\max}$  outputs leader and each other process outputs non-leader, within diameter rounds.*
- **Main Claim** *After diameter rounds,*
  - $status_{i_{\max}} = leader$  and
  - $status_j = non-leader$ , for every  $j \neq i_{\max}$ .
- The key to the proof of this Claim is the fact that
  - after  $r$  rounds, the maximum ID has reached every process that is within distance  $r$  of  $i_{\max}$ , as measured along directed paths in  $G$ .

<https://powcoder.com>

## FloodMax

### Assignment Project Exam Help

- The FloodMax algorithm does not extend directly to the asynchronous setting, because there are no rounds in the asynchronous model.
- However, it is possible to simulate the rounds asynchronously.
  - We simply require each process that sends a round  $r$  message to tag that message with its round number  $r$ .
  - The recipient waits to receive round  $r$  messages from all its neighbors before performing its round  $r$  transition.
- By simulating diameter rounds, the algorithm can terminate correctly.

<https://powcoder.com>

### OptFloodMax Algorithm

#### Assignment Project Exam Help

- There is a simple improvement that can be used to decrease the communication complexity in many cases, although it does not decrease the order of magnitude in the worst case.
- Namely, processes can send their current max user ID values only when they first learn about them, not at every round.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>  
Convergecast


Add WeChat powcoder

<https://powcoder.com>

## Convergecast

### Assignment Project Exam Help

- Convergecast is reversed broadcast:
  - Instead of a root sending a message to all other nodes, all other nodes send information to a root.



- Convergecast is useful for input collection.

<https://powcoder.com>

## Echo Algorithm

### Assignment Project Exam Help

#### Echo Algorithm

Add WeChat powcoder

- **Requirement:** This algorithm is initiated at the leaves.
  1. A leaf sends a message to its parent.
  2. If an inner node has received a message from each child, it sends a message to the parent.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Complexity Issues: Broadcast and Convergecast (1/2)

Assignment Project Exam Help

- The echo algorithm is paired with the flooding algorithm, which is used to let the leaves know that they should start the echo process; this is known as flooding/echo.
- One can use convergecast for termination detection.
  - If a root wants to know whether all nodes in the system have finished some task, it initiates a flooding/echo;
    - \* the message in the echo algorithm then means “This subtree has finished the task.”
- Message complexity of the echo algorithm is  $n - 1$ ,
  - but together with flooding it is  $O(m)$ , where  $m = |E|$  is the number of edges in the graph.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

## Complexity Issues: Broadcast and Convergecast (2/2)

Assignment Project Exam Help

- The time complexity of the echo algorithm is determined by the depth of the spanning tree (i.e., the radius of the root within the tree) generated by the flooding algorithm.
- The flooding/echo algorithm can do much more than collecting acknowledgements from subtrees.
  - For instance, one can use it to compute the number of nodes in the system, or the maximum ID (for leader election), or the sum of all values stored in the system.
- By combining results one can compute even fancier aggregations, e.g., with the number of nodes and the sum one can compute the average. With the average one can compute the standard deviation. And so on . . .

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Application to Leader Election

### Assignment Project Exam Help

- Asynchronous broadcast and convergecast can be used to solve the leader election problem in arbitrary graphs
  - without any distinguished source node and
  - without the processes having any knowledge of the number of nodes or the diameter of the network.
- The processes need to have unique IDs.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Basic Leader Election Algorithm

### Assignment Project Exam Help

- Every node can initiate
  - first a broadcast, and
  - next a convergecast

Add WeChat powcoder

in order to discover the maximum user ID in the network.

### Assignment Project Exam Help

- The node that finds that the maximum is equal to its own ID elects itself as leader.
- This algorithm uses  $O(n|E|)$  messages.

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

(Directed Graph) BFS  
Assignment Project Exam Help  
<https://powcoder.com>  
Add WeChat powcoder  
and Applications

<https://powcoder.com>

## Construction of BFS

### Assignment Project Exam Help

- How do we perform breadth-first search (BFS) in a network based on an arbitrary strongly connected directed graph having a distinguished source node?
- We consider how to establish a breadth-first spanning tree for the (di)-graph.
- Motivation for constructing such a tree comes from the desire to have a convenient structure to use as a basis for broadcast communication.
- The BFS tree minimizes the maximum communication time from the process at the distinguished node to all other processes in the network
  - To do this run BFS from each node of the graph and compare values obtained at each node.

<https://powcoder.com>

## Construction of BFS

### Assignment Project Exam Help

- We suppose that the network is strongly connected and that there is a distinguished source node  $i_0$ .
- The algorithm is supposed to output the structure of a breadth-first directed spanning tree of the network graph, rooted at  $i_0$ .
- The output should appear in a distributed fashion: each process other than  $i_0$  should have a parent component that gets set to indicate the node that is its parent in the tree.
- As usual, processes only communicate over directed edges.
- Processes are assumed to have user IDs but to have no knowledge of the size or diameter of the network.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## SynchBFS

### Assignment Project Exam Help

- The basic idea for this algorithm is the same as for the standard sequential breadth-first search algorithm.

Add WeChat powcoder

- **SynchBFS Algorithm**

1. At any point during execution, there is some set of processes that is *marked*: initially just  $i_0$ .
2. Process  $i_0$  sends out a search message at round 1, to all of its outgoing neighbors.
3. At any round, if an unmarked process receives a search message, it marks itself and chooses one of the processes from which the search has arrived as its parent.
4. At the first round after a process gets marked, it sends a search message to all of its outgoing neighbors.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Analysis of SynchBFS

### Assignment Project Exam Help

- We can prove the invariant that
  - after  $r$  rounds, every process at distance  $d$  from  $i_0$  in the graph,  $1 \leq d \leq r$ , has its parent pointer defined; moreover, each such pointer points to a node at distance  $d - 1$  from  $i_0$ .

Add WeChat powcoder

This invariant can, as usual, be proved by induction on the number of rounds.

Assignment Project Exam Help

<https://powcoder.com>

- The time complexity is at most diameter rounds.
- The number of messages is just  $|E|$ 
  - a search message is transmitted exactly once on each directed edge.

Add WeChat powcoder



<https://powcoder.com>

## Applications of BFS

### Assignment Project Exam Help

- Message Broadcast

Add WeChat powcoder

- Global computation

- Electing a leader

- Computing the diameter

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### Message Broadcast: Piggybacking

## Assignment Project Exam Help

- The SynchBFS algorithm can easily be augmented to implement message broadcast.
- If a process has a message  $M$  that it wants to communicate to all of the processes in the network,
  - it can simply initiate an execution of SynchBFS with itself as the root, piggybacking message  $M$  on the search message it sends in round 1.
- Other processes continue to piggyback  $M$  on all their search messages as well.
  - Since the tree eventually spans all the nodes, message  $M$  is eventually delivered to all the processes.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Global Computation

### Assignment Project Exam Help

- This means
  - Collection of information from throughout the network or,
  - more generally, the computation of a function based on distributed inputs.
- For example,
  - consider the problem in which each process has a nonnegative integer input value and we want to find the sum of all the inputs in the network.
  - Using a BFS tree, this can be done easily (and efficiently) as follows.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Global Computation

### Assignment Project Exam Help

- Starting from the leaves, “fan in” the results in a convergecast procedure, as follows.

Add WeChat powcoder

1. Each leaf sends its value to its parent;
2. each parent waits until it gets the values from all its children, adds them to its own input value, and then sends the sum to its own parent.

Assignment Project Exam Help

<https://powcoder.com>

- The sum calculated by the root of the BFS tree is the final answer.

Add WeChat powcoder

<https://powcoder.com>

### Electing a Leader

## Assignment Project Exam Help

- Using SynchBFS, an algorithm can be designed to elect a leader in a network with IDs, even when the processes have no knowledge of  $n$  or diameter.  
<https://powcoder.com>  
Add WeChat powcoder
- 1. Namely, all the processes can initiate breadth-first searches in parallel.  
Assignment Project Exam Help
- 2. Each process  $i$  uses the tree thereby constructed and the global computation procedure just described to determine the maximum ID of any process in the network.  
<https://powcoder.com>  
Add WeChat powcoder
- 3. The process with the maximum ID then declares itself to be the leader, and all others announce that they are not the leader.
- If the graph is undirected, the time is  $O(\text{diameter})$  and the number of messages is  $O(n|E|)$ .

<https://powcoder.com>

## Computing the Diameter

### Assignment Project Exam Help

- The diameter of the network can be computed by having all processes initiate breadth-first searches in parallel.

Add WeChat powcoder

1. Each process  $i$  uses the tree thereby constructed to determine  $\max\text{-dist}$ , defined to be the maximum distance from  $i$  to any other process in the network.

Assignment Project Exam Help

2. Each process  $i$  then reuses its breadth-first tree for a global computation to discover the maximum of the  $\max\text{-dist}$  values.

Add WeChat powcoder

- If the graph is undirected, the time is  $O(\text{diam})$  and the number of messages is  $O(n|E|)$ , where  $\text{diam}$  is the diameter of the graph.
- The diameter thus computed could be used, for example, in the leader-election algorithm FloodMax.

<https://powcoder.com>

### Exercises<sup>a</sup>

## Assignment Project Exam Help

1. Explain why every tree is a bipartite graph.
2. Let  $T$  be a graph with  $n$  vertices. Then the following statements are equivalent.
  - (a)  $T$  is connected and has no cycles.
  - (b)  $T$  has  $n - 1$  edges and has no cycles.
  - (c)  $T$  is connected and has  $n - 1$  edges.
  - (d)  $T$  is connected and the removal of any edge disconnects  $T$ .
  - (e) Any two vertices of  $T$  are connected by exactly one path.
  - (f)  $T$  contains no cycles, but the addition of any new edge creates a cycle.
3. Give an algorithm to compute the diameter and radius of a tree.
4. Determine the size of a message which propagates for  $r$  hops in

---

<sup>a</sup>Not to hand in!

<https://powcoder.com>

## Assignment Project Exam Help

“Synchronous Algorithm Canonical Form”. More specifically, consider a complete binary rooted tree with height  $n$ . Label the ports at an interior node as  $L, R$  (for the Left and Right siblings at a node), and  $P$  for its parent. Do the same in an analogous manner for the root and the leaves. For each  $r \leq n$  and each node  $v$  construct the  $r$ -view at this node.

## Assignment Project Exam Help

<https://powcoder.com>



5. A connected graph is Hamiltonian if there is a cycle, that includes every vertex exactly once (such a cycle is called Hamiltonian). A connected graph is semi-Hamiltonian if there is a path (but not a cycle) that includes every vertex exactly once (such a path is called semi-Hamiltonian). Determine which of the following graphs are semi-Hamiltonian, and write down a corresponding semi-Hamiltonian path where possible:



<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder




6. A forest is a graph (not necessarily connected) each of whose components is a tree.
- (a) Let  $G$  be a forest with 11 vertices and  $k$  components. How many edges does  $G$  have?
- (b) Construct a forest with 12 vertices and 9 edges.
- (c) Is it true that every forest with  $k$  components has at least  $2k$  vertices of degree 1?
7. A spanning forest in a graph  $G$  (not necessarily connected) is obtained by constructing a spanning tree for each component of  $G$ .

<https://powcoder.com>

- (a) Find a spanning forest for the following graph.

Assignment Project Exam Help

Add WeChat powcoder




- (b) Let  $G$  be a graph, and let  $F$  be a subgraph of  $G$ . If  $F$  is a forest which includes all vertices of  $G$ , is  $F$  necessarily a spanning forest of  $G$ ?

Assignment Project Exam Help

<https://powcoder.com>

8. Find three spanning trees in the Petersen graph (depicted below):

Add WeChat powcoder



9. Prove that trees and forests are bipartite graphs.

<https://powcoder.com>

10. Prove that, in a bipartite graph, every cycle has an even number of edges. Conversely, prove that, if every cycle of a graph has an even number of edges, then the graph is bipartite.

**Hint:** Consider a connected graph  $G$ . Choose a vertex  $v$  in  $G$  and consider those vertices whose minimum distance from  $v$  is even and those whose minimum distance from  $v$  is odd. To which vertices are the “odd” vertices adjacent? To which vertices are the “even” vertices adjacent?

Add WeChat powcoder