

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

# Leader Election in the Ring

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder  
(Part 2)

<https://powcoder.com>

## Outline

### Assignment Project Exam Help

- Non-Comparison Based Algorithms

- Time Slice
- Variable Speeds

- Lower Bounds

- Randomized

- identity selection
- Leader election

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Comparison of Leader Election Algorithms

### Assignment Project Exam Help

- Resulting Tradeoffs

Add WeChat powcoder

Algorithm	Rounds	Time	# Messages
TimeSlice	$O(u_{\min} n)$	$O(u_{\min} n)$	$O(n)$
VariableSpeed	$O(2^{u_{\min}} n)$	$O(2^{u_{\min}} n)$	$O(n)$
Randomized	$O(\log n)$	$O(n)$	$O(n \log n)$

Assignment Project Exam Help

<https://powcoder.com>  
 where  $u_i$  denotes the  $i$ -th node's identifier and  $u_{\min}$  the minimum identifier among the node identifiers.

Add WeChat powcoder

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help  
**Non-Comparison**  
<https://powcoder.com>  
**Based**  
Add WeChat powcoder

<https://powcoder.com>

### Time Slice Algorithm

## Assignment Project Exam Help

- Uses the *strong* assumption that
  - the ring size  $n$  is known to all the processes (non-uniform).
- It assumes unidirectional communication.
- It elects the process with the minimum user ID.
- Assumes processor IDs are natural numbers.
  - Each process  $i$  has the ID  $u_i$  (unknown to the rest of the processors).
- Employs synchrony in a deeper way in that
  - it uses a token to convey information.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


<https://powcoder.com>

## Time Slice Algorithm: Searching for IDs!

### Assignment Project Exam Help

- Employs a *circulating token*, carrying an ID around the ring.

Add WeChat powcoder



### Assignment Project Exam Help

<https://powcoder.com>

- Let  $v$  denote the phase. Starting from  $v = 1$  and each phase incrementing by 1, it attempts to elect  $v$  as leader.
- For  $v = 1, 2, \dots$ : in phase  $v$  only a token carrying ID  $v$  is permitted to circulate.
- Processor IDs are unknown to other processors (and can be large numbers).

<https://powcoder.com>

## Time Slice Algorithm

### Assignment Project Exam Help

1. Computation proceeds in phases  $1, 2, \dots$  and each phase consists of  $n$  consecutive rounds (we use  $n$  is known).
2. Each phase devoted to the possible circulation, all the way around the ring, of a token carrying a particular value. Nodes check if their ID is equal to the value of the token.
3. In phase  $v$ , which consists of rounds  $(v-1)n + 1, \dots, vn$ , only a token carrying value  $v$  is permitted to circulate.
4. If a process  $i$  with ID equal to  $v$  exists, and round  $(v-1)n + 1$  is reached then process  $i$  elects itself the leader and sends a token carrying its ID around the ring.
5. As this token travels, all the other processes note that they have received it, which prevents them from electing themselves as leader or initiating the sending of a token at any later phase.



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

i.e., you assume the nodes have  
MAC addresses : in the Network Card

**Assignment Project Exam Help**

**<https://powcoder.com>**

**Add WeChat powcoder**




<https://powcoder.com>

### Example of Time Slice Algorithm

Assignment Project Exam Help

- A token carrying a certain value circulates around the ring.

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

1. Phase  $v = 1$ : Token carrying ID equal to 1 circulating around the ring; nodes check if their ID is equal to 1;
  2. Phase  $v = 2$ : Token carrying ID equal to 1 circulating around the ring; nodes check if their ID is equal to 1;
  3. etc.
- Note that in each phase, it takes  $n$  steps for the token to go around the ring.

Add WeChat powcoder


<https://powcoder.com>

## Correctness of Time Slice Algorithm

### Assignment Project Exam Help

- The minimum ID  $u_{\min}$  eventually gets all the way around, which causes its originating process to become elected.
  - No messages are sent before round  $(u_{\min} - 1)n + 1$ , and
  - no messages are sent after round  $u_{\min}n$ .
- The total number of messages sent is just  $n$ .
  - These are the non-null messages of the node with minimum ID  $u_{\min}$  claiming to be the leader.
- If we prefer to elect the process with the maximum ID rather than the process with the minimum, we can simply let the minimum send a special message around after it is discovered in order to determine the maximum.
- The communication complexity is still  $O(n)$ .

$$u_{\min} \cdot n$$



<https://powcoder.com>

### Correctness of Time Slice Algorithm

#### Assignment Project Exam Help

- The good property of the TimeSlice algorithm is that the total number of messages is  $n$ .
- Unfortunately, the time complexity is about  $nu_{\min}$ , which is an unbounded number, even in a fixed-size ring.
- This time complexity limits the practicality of the algorithm.
- It is only useful in practice for small ring networks in which IDs are assigned from among the small positive integers.

#### Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


<https://powcoder.com>

### Variable Speed Algorithm

#### Assignment Project Exam Help

- Employs *circulating tokens* (as many tokens as nodes) carrying certain IDs.

Add WeChat powcoder



#### Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

- Each process  $i$  has the ID  $u_i$  (unknown to the rest of the processors).
- Process  $i$  initiates a token, which travels around the ring, carrying the ID  $u_i$  of the originating process  $i$ .
- Different tokens travel at different speeds.

<https://powcoder.com>

### Variable Speed Algorithm

#### Assignment Project Exam Help

1. Each process  $i$  initiates a token, which travels around the ring, carrying the value  $u_i$  of the ID originating process  $i$ .
2. Different tokens travel at different speeds.
  - A token with value  $v$  travels at the speed of one message transmission per  $2^v$  rounds, that is, each process along its path waits  $2^v$  rounds after receiving the token before sending it out. /\* a token with value  $v$  takes time  $n2^v$  to circulate around the ring (if it does) \*/
3. Each process keeps track of the smallest value it has seen so far and simply discards any token carrying an identifier that is larger than this smallest one.
4. If a token returns to its originator the originator is elected leader.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Correctness of Variable Speed Algorithm

### Assignment Project Exam Help

- Algorithm guarantees that
  - by the time the token carrying the smallest identifier  $u_{\min}$  gets all the way around the ring,
  - the second smallest identifier could only get at most halfway around, the third smallest could only get at most a quarter of the way around, and in general,
  - the  $k$ th smallest could only get at most  $1/2^{k-1}$  of the way around.
- Therefore, up to the time of election, the token carrying  $u_{\min}$  uses more messages than all the others combined.
- Since  $u_{\min}$  uses exactly  $n$  messages, the total number of messages sent, up to the time of election, is less than  $2n$ .

<https://powcoder.com>

## Correctness of Variable Speed Algorithm

### Assignment Project Exam Help

- By the time  $u_{\min}$  gets all the way around the ring, all nodes know about this value, and so will refuse to send out any other tokens.
- It follows that  $2n$  is an upper bound on the total number of messages that are ever sent by the algorithm (including the time after the leader output).
- The time complexity, as mentioned above, is  $n2^{u_{\min}}$ , since each node delays the token carrying ID  $u_{\min}$  for  $2^{u_{\min}}$  time units.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help  
**Leader Election**  
<https://powcoder.com>  
**Lower Bound**  
Add WeChat powcoder

<https://powcoder.com>

## Comparison Based Algorithms

### Assignment Project Exam Help

- An algorithm is comparison based if it behaves the same on rings that have the same order pattern of the identifiers.
  - in two rings with corresponding processors  $p_1, p_2, \dots, p_n$  and  $q_1, q_2, \dots, q_n$  the actions of the algorithm depend only on the order of the identifiers  $ID(p_1), ID(p_2), \dots, ID(p_n)$  and  $ID(q_1), ID(q_2), \dots, ID(q_n)$ , respectively.
- We have seen that the best comparison based algorithm achieves the following bounds:
  - communication complexity of  $O(n \log n)$  messages, and
  - time of  $O(n)$ .

<https://powcoder.com>

Add WeChat powcoder

Radius  
Growth

<https://powcoder.com>

## Non-Comparison Based Algorithms

### Assignment Project Exam Help

- Non-comparison based algorithms, on the other hand, use  $O(n)$  messages, but (can) have a huge running time.
- A lower bound of  $\Omega(n \log n)$  messages can be shown for
  1. *comparison based* algorithms; lower bound holds even if we assume that communication is bidirectional and the ring size  $n$  is known to the processes.
  2. *non-comparison based* algorithms: with bounded time complexity (i.e., bounded number of rounds).<sup>a</sup>
- In the sequel we discuss only the first bound for comparison based algorithms.<sup>b</sup>

---

<sup>a</sup>This can be proved using Ramsey Theory.

<sup>b</sup>Greg N. Frederickson and Nancy A. Lynch. Electing a leader in a synchronous ring. Journal of the ACM, 34(1):98-115, January 1987.

<https://powcoder.com>

## The Plan: What Are We Going to Do?

### Assignment Project Exam Help

- Assume we are given a uniform ( $n$  is unknown) algorithm  $\mathcal{A}$  that solves the above comparison based variant of the leader election problem.
- We will show that there exists an admissible execution (i.e., an execution that conforms to the model being considered) of  $\mathcal{A}$  in which  $\Omega(n \log n)$  messages are being sent.
  - So not all executions will satisfy this  $\Omega(n \log n)$  lower bound condition!
- **Theorem 1** *For any comparison based leader election algorithm on a ring of size  $n$  there is an execution of the algorithm in which  $\Omega(n \log n)$  messages are being sent.*

Rad Gro.       $O(n \log n)$

<https://powcoder.com>

## How Do You Prove a $\Omega(n \log n)$ Lower Bound?

Assignment Project Exam Help

- The quantity being considered is the following:  $M(n)$  = “the number of messages required to elect a leader in an  $n$ -node ring”.
- This means that we must find a constant  $c > 0$  independent of  $n$  such that

$$M(n) \geq cn \log n,$$

for all  $n$ .

Add WeChat powcoder

- But how do we accomplish this task?
  - Using a recurrence!

*we do not really care about  $c > 0$  independent of  $n$*

<https://powcoder.com>

## A Simple Recurrence

### Assignment Project Exam Help

- We will show that

Add WeChat powcoder

$$M(n) \geq 2M(n/2) + n/4$$

(1)

This is what we have to prove

- What does this mean?

### Assignment Project Exam Help

- Let's denote our problem  $LE(n)$ :

– Leader Election is a ring of size  $n$ .

<https://powcoder.com>

- One way to interpret Inequality (1) is the following:

Add WeChat powcoder


1. Split  $LE(n)$  into two subproblems  $LE(n/2)$ .
2. Show that the number of messages required to solve  $LE(n)$  is at least the number of messages required to solve two  $LE(n/2)$  problems plus  $n/4$ .

<https://powcoder.com>

### What Does it Mean to Split?

#### Assignment Project Exam Help

- From our definition  $M(n/2) =$  “the number of messages required to elect a leader in an  $n/2$  node ring”.
- So we need to split the ring of size  $n$  into two subrings each of size  $n/2$ :





Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




<https://powcoder.com>

Glueing!

## Assignment Project Exam Help

- How do you glue two subrings into a bigger ring?

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

- You must find two respective schedules in the subrings of size  $n/2$  which send at least  $M(n/2)$  messages in each subring and also leave at least one edge unused!

Add WeChat powcoder

- You need this so that you can do the glueing!
- We will call such schedules which leave an edge of the ring unused *open*
  - *open* because they leave an edge unused.

<https://powcoder.com>

Inequality (1) Implies  $M(n) \geq \frac{n}{4}(\log n + 1)$

Assignment Project Exam Help

- For simplicity, assume  $n$  is a power of 2.

Add WeChat powcoder

- Assume that  $M(n) \geq 2M(n/2) + n/4$  has been proved<sup>a</sup>

- By induction: we will prove

- Base case:

$$M(2) \geq \frac{2}{4}(\log 2 + 1) = 1$$

<https://powcoder.com>

- Inductive Case:


Assuming the inductive assumption

$$M(n/2) \geq \frac{n}{8}(\log \frac{n}{2} + 1)$$

we'll prove

$$M(n) \geq \frac{n}{4}(\log n + 1)$$

<sup>a</sup>We have not proved this yet! This is our goal in this lecture!



$$S(n) \leq 2S\left(\frac{n}{2}\right) + \frac{n}{4}$$

$S(n) \stackrel{!}{=} \# \text{ of steps}$

You do not know what the explicit formula for  $S(n)$  is

Example: Radix Growth satisfies this inequality

what is  $S(n)$ ?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$n$

$n/2$

$n/2$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$S(n) \leq 2 S(n/2) + \frac{n}{4}$$

$$S(n) \leq 2 S(n/2) + n/4$$

$$\leq 2 \left( 2 S(n/4) + n/8 \right) + n/4$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$= 2^3 \cdot S(n/2^3) + 3 \cdot \frac{n}{4}$$

$$= n \cdot S(1) + \log n \cdot \frac{n}{4}$$

$$S(1) = 1$$

$$S(2) \leq 2 \cdot S(1) + \frac{1}{4}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$S(4) \leq 2 \cdot S(2) + \frac{4}{4}$$

$$S(8) \leq 2 \cdot S(4) + \frac{8}{4}$$

⋮

⋮

<https://powcoder.com>

Base Case

## Assignment Project Exam Help

- Here we must show that

Add WeChat powcoder

$$M(2) \geq \frac{2}{4}(\log 2 + 1) = 1$$

- Somehow this seems like a simple statement about rings of just 2 nodes.

Assignment Project Exam Help

- Lets postpone it for a moment!

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### Inductive Step

## Assignment Project Exam Help

- Assume the inductive assumption

Add WeChat powcoder

$$M(n/2) \geq \frac{n}{8} (\log \frac{n}{2} + 1)$$

- Therefore

## Assignment Project Exam Help

$$M(n) \geq 2M(n/2) + n/4 \quad (\text{By Inequality (1)})$$

$$\geq 2 \left( \frac{n}{8} (\log \frac{n}{2} + 1) \right) + \frac{n}{4} \quad (\text{Inductive Assumption})$$

$$= \frac{n}{4} \log n + \frac{n}{4}$$

$$= \frac{n}{4} (\log n + 1)$$

$\log n - 1$

- Lets move now to the details! We are missing the proofs of
  - the base case, and
  - Inequality (1).



<https://powcoder.com>

## Basic Concepts/Assumptions

### Assignment Project Exam Help

- We prove the lower bound for a special variant of the leader election problem, where the elected leader must be the processor with the maximum identifier in the ring;

– in addition, all the processors must know the identifier of the elected leader.<sup>a</sup>

Assignment Project Exam Help

$$\Omega(n) \geq 2 \Omega\left(\frac{n}{2}\right) + \frac{n}{4}$$

- We only accept uniform algorithms where the node with the maximum identifier can be the leader.
- Additionally, every node that is not the leader must know the identity of the leader.
- Ring is asynchronous: nodes may wake up at arbitrary times (but at the latest when receiving the first message).

<sup>a</sup>Unless this is done, no leader has been elected.

<https://powcoder.com>

## Rules of the Game

### Assignment Project Exam Help

- Recall execution model
- Nodes wake up at the latest when receiving first message
- Algorithms must be uniform
- We assume we have an algorithm and show it cannot complete faster than  $O(n \log n)$  time
- Algorithm needs to do this regardless of how messages are scheduled
  - And when nodes wake up
  - Otherwise it is not a solution
- But communication links must be FIFO

[Add WeChat powcoder](https://powcoder.com)

[Assignment Project Exam Help](https://powcoder.com)

<https://powcoder.com>

[Add WeChat powcoder](https://powcoder.com)

<https://powcoder.com>

## Schedules

### Assignment Project Exam Help

- An execution of a distributed algorithm is a list of events, sorted by time.  
– An event is a record (time, node, type, message) where type is “send” or “receive”.
- A schedule  $\sigma$  of  $\mathcal{A}$  for a particular ring is open if there exists an edge  $e$  of the ring such that in  $\sigma$  no message is delivered over the edge  $e$  in either direction;  
– **Edge is open** if no message which is traversing the edge has been received so far.  
– **Schedule is open** if there is an open edge in the ring.

We need to “cut” the ring into two subrings

A schedule in which edges are "left open".

Assignment Project Exam Help

<https://powcoder.com>

Open means unused.

Add WeChat powcoder

We need to ensure that an execution will take place that will transmit "enough" messages and still leave an edge used!



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$n/2$

attach

$n/2$

<https://powcoder.com>

### Scheduler

## Assignment Project Exam Help

- We assume no two events happen at exactly the same time.
- During the proof we can “play god” and specify which message in transmission arrives next in the execution.
- If more than one message is in transit, the scheduler can choose which one arrives first.
- If two messages are transmitted over the same directed edge, then it is sometimes required that the message transmitted first will also be received first.
  - We respect the FIFO conditions for links.

<https://powcoder.com>

### Open Schedules


## Assignment Project Exam Help

- Schedule: Execution chosen by the scheduler
- Open schedule:
  - Schedule with an open edge / communication link

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



- Open edge:
  - Edge along which no message has yet been scheduled

<https://powcoder.com>

**Main Idea: Ring of  $n$  nodes**

**Assignment Project Exam Help**

- We want to count how many messages we need to send to elect a leader and at the same time maintain an open schedule, i.e. there is an edge for which no message has been received so far.
  - We prove it by induction on  $n$
  - Will assume  $n$  is a power of 2.
- The proof is by induction on  $n$ :
  - The base case is for  $n = 2^1$ ;
  - The inductive step is for  $n = 2^i$ , where  $i > 1$ .

**Add WeChat powcoder**

**Assignment Project Exam Help**

<https://powcoder.com>

**Add WeChat powcoder**

$$\underbrace{M(n)}_{\checkmark\checkmark} \geq \underbrace{M\left(\frac{n}{2}\right)}_{\checkmark} + \underbrace{M\left(\frac{n}{2}\right)}_{\checkmark} + \frac{n}{4}$$



<https://powcoder.com>

**Base Case: Starting the recursion in a 2-node Ring**

**Assignment Project Exam Help**

- **Lemma 1** *Given a ring  $R$  with two nodes, we can construct an open schedule in which at least one message is received.*

**Add WeChat powcoder**

- *The nodes cannot distinguish this schedule from one on a larger ring with all other nodes being where the open edge is.*

**Assignment Project Exam Help**

<https://powcoder.com>

**Add WeChat powcoder**


<https://powcoder.com>

## 2-node Ring

### Assignment Project Exam Help

- Two processors  $p_0, p_1$  have identifiers  $u$  and  $v$  s.t.  $u > v$ .

Add WeChat powcoder



- Processor  $p_1$  must learn the identity of node  $v$ , thus receive at least one message.
- We stop the execution of the algorithm as soon as the first message is received.


<https://powcoder.com>

### Induction Step

## Assignment Project Exam Help

- Assume two rings of size  $n/2$  with open schedules

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### Induction Step

#### Assignment Project Exam Help

- Assume two rings of size  $n/2$  with open schedules

Add WeChat powcoder


leader in  $R_1$

#### Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

leader in  $R_2$



Def. of  
LE problem  
is crucial

We can construct an open schedule on a ring of size  $n$

- If  $M(n/2)$  is number of messages can construct schedule with  $2M(n/2)$  without scheduling either of the two open edges
- Remember: We decide when edges are scheduled and when nodes wake up

<https://powcoder.com>

### Induction Step


## Assignment Project Exam Help

- Each node in, say  $R_1$ , must learn of at least one node in  $R_2$
- At least  $n/2$  messages must be passed from  $R_1$  to  $R_2$ <sup>a</sup>
- But some messages use  $e_1$  and others use  $e_2$  is not good enough as an argument!
- Closing one of the edges will cause at least  $n/4$  messages to be passed (not necessarily over the closed edge though)
- Schedule this edge and leave the other open

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



$\frac{n}{2}$   
At least  $n/4$  messages must pass through  $e_1$  or  $e_2$

<sup>a</sup>This is crucial to the leader election process!

<https://powcoder.com>

## Gluings Together

### Assignment Project Exam Help

- We can show that


Add WeChat powcoder

**Lemma 2** *Gluings together  $R_1$  and  $R_2$ , at least  $2M(n/2) + n/4$  messages must be exchanged to solve leader election on the ring of size  $n$ . Moreover, at least one edge of the ring will be left open.<sup>a</sup>*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<sup>a</sup>This is crucial to the validity of the induction step.


<https://powcoder.com>

### Recursive Step: Stitching

## Assignment Project Exam Help

- Take two size  $n/2$  subrings  $R_1$  and  $R_2$  with open schedules.

Add WeChat powcoder



## Assignment Project Exam Help

- Take the open edges in each sub-schedule and use these edges to glue the subrings into a ring of size  $n$ .
- Electing a leader in the resulting 'glued' ring involves messages that
  1. stay within each subring, plus
  2. move from one ring to the other.

<https://powcoder.com>

Add WeChat powcoder


<https://powcoder.com>

### Stitching

## Assignment Project Exam Help

- Glue two rings of size  $n/2$ :


Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





<https://powcoder.com>

## **$n$ -node Ring: Idea of Inductive Hypothesis**


### Assignment Project Exam Help

- **Lemma 3** *By glueing together two rings of size  $n/2$  for which we have open schedules, we can construct a new open schedule on a ring of size  $n$ .*
  - *If  $M(n/2)$  denotes the number of messages already received in each of these schedules, at least  $n/4$  additional messages have to be exchanged in order to solve leader election.*
- Divide the ring into two subrings  $R_1$  and  $R_2$  of size  $n/2$ .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




- These subrings cannot be distinguished from rings with  $n/2$  nodes if no messages are received from “outsiders”.
- Can ensure this by not scheduling such messages until we want.

<https://powcoder.com>

## $n$ -node Ring: Idea of Inductive Hypothesis Assignment Project Exam Help

- Executing both given open schedules on  $R_1$  and  $R_2$  “in parallel” is possible because we control not only the scheduling of the messages, but also when nodes wake up.
- This ensures that  $2M(n/2)$  messages are sent before the nodes in  $R_1$  and  $R_2$  learn anything of each other!



Without loss of generality,  $R_1$  contains the maximum identifier.


- Each node in  $R_2$  must learn the identity of the max identifier, thus at least  $n/2$  additional messages must be received.

<https://powcoder.com>

## Close One and Open the Other

### Assignment Project Exam Help

- The only problem is that we cannot connect the two subrings with both edges since the new ring needs to remain open.




- Thus, only messages over one of the edges can be received.
- We look into the future: we check what happens when we close only one of these connecting edges.

<https://powcoder.com>

### Count Messages

## Assignment Project Exam Help

- Since we know that  $n/2$  nodes have to be informed in  $R_2$ , there must be at least  $n/2$  messages that must be received by  $R_2$ .
- Closing both edges must inform  $n/2$  nodes, thus for one of the two edges there must be a node in distance  $n/4$  which will be informed upon creating that edge.



- This results in  $n/4$  additional messages. Thus, we pick this edge and leave the other one open which yields the claim.

We know that  $n/2$  messages must pass through either via  $e_1$  or via  $e_2$   
why isn't the overhead  $n/2$


Assignment Project Exam Help

<https://powcoder.com>

In the "plus" from  $R_1, R_2$   
Add WeChat powcoder  
ring

~~we~~ we need to leave an edge  
open!

$$M(n) \geq M(n/2) + M(n/2) + \left(\frac{n}{4}\right)$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Assignment Project Exam Help

- So we have proved.
- **Theorem 2** *Any comparison based leader election algorithm on a ring of size  $n$  needs at least  $\Omega(n \log n)$  messages.*

## Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

Randomized

<https://powcoder.com>

Leader Election

{ Deferm. lead. El.  
Def. LE with random labels



<https://powcoder.com>

## A Simple Way to Break Symmetry

### Assignment Project Exam Help

- Assume that each node is equipped with a generator of random bits. Add WeChat powcoder
- Each node  $i$  can flip a fair coin  $X_i$ , for  $i = 0, 1, \dots, n - 1$ .
  - Warning: we are not using  $i$  as an identity!
  - $X_i$  is a “fair coin” means we assume that
 
$$\Pr[X_i = 0] = \Pr[X_i = 1] = \frac{1}{2}$$
- The coins are independent of each other. Add WeChat powcoder
- Observe that for  $i \neq j$ ,

$$\Pr[X_i = X_j] = \frac{1}{2}$$

$$\underbrace{X_i = X_j = 0}_{1/4}$$

or

$$\underbrace{X_i = X_j = 1}_{1/4}$$

<https://powcoder.com>

## Randomized Identity Selection (1/2)


### Assignment Project Exam Help

- For simplicity assume the ring is unidirectional.
  1. Each node “flips a coin” and chooses a random bit 0 or 1; the selection of each node is independent of the others.
  2. For  $c \log n$  rounds each node sends and receives bits from its neighbour.<sup>a</sup> We must specify now the hidden constant  $c$  in  $c \log n$  is selected <sup>\*/</sup>  $c > 4$
  3. Each node uses as identity the number whose binary representation is the sequence of  $c \log n$  bits it has collected, in the order received.
- **NB:** The input collection phase is  $c \log n$  rounds.

---

<sup>a</sup> $c > 0$  is a constant that will be determined later.

## Add WeChat powcoder



- Evangelos Kranakis, Carleton University, SCS (October 3, 2020)

<https://powcoder.com>

## Randomized Identity Selection: Example for 4 Steps

Assignment Project Exam Help

Add WeChat powcoder

Node 1                      1100    12

Node 2                      1001    9

Node 3                      0011    3

Node 4                      0111    7

Assignment Project Exam Help

Node 5                      1110    14

<https://powcoder.com>

Node 6                      1101    13

Node 7                      1010    10

Add WeChat powcoder

Node 8                      0100    4

Node 9                      1001    9

Node 10                     0011    6

Node 11                     0111    7

Node 12                     1110    14

<https://powcoder.com>

## Correctness of Randomized Identity Selection

### Assignment Project Exam Help

- **Theorem 3** For  $c \geq 3$ , w.h.p. (i.e., with probability  $\geq 1 - 1/n$ )

Algorithm Randomized ID Selection ensures that the identities selected are pairwise distinct. Moreover, the algorithm

1. uses a total of  $n$  random bits,
2. terminates in  $c \log n$  rounds,
3. the total number of bits transmitted is  $cn \log n$ .

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Correctness of Randomized Identity Selection Assignment Project Exam Help

- Consider the  $i$ -th node. Lets use the notation  $k = c \log n$ .
- After  $c \log n$  rounds node  $i$  will have received the following sequence of bits

$$X_i, X_{(i+1) \bmod n}, X_{(i+2) \bmod n}, \dots, X_{(i+k) \bmod n}$$

and form its identity

$$ID_i := X_i X_{(i+1) \bmod n} X_{(i+2) \bmod n} \dots X_{(i+k) \bmod n}$$

- We now ask the question.

How likely is it that two different nodes  $i \neq j$  of the ring will obtain the same identity?

<https://powcoder.com>

## Correctness of Randomized Identity Selection

Assignment Project Exam Help

- Assume  $i \neq j$ .

- Observe that

$$ID_i = ID_j \text{ iff } X_i X_{(i+1) \bmod n} \cdots X_{(i+k) \bmod n}$$

$$= X_j X_{(j+1) \bmod n} \cdots X_{(j+k) \bmod n}$$

Assignment Project Exam Help

$$\text{iff } X_{i+l} = X_{j+l}, \text{ for all } 1 \leq l \leq k.$$

<https://powcoder.com>

- Therefore

Add WeChat powcoder

$$\begin{aligned} \Pr[ID_i = ID_j] &= \Pr[\forall l \leq k (X_{i+l} = X_{j+l})] \\ &= \prod_{l=1}^k \Pr[X_{i+l} = X_{j+l}] \\ &= 2^{-k} = \frac{1}{n^c} \text{ (since } k = c \log n) \end{aligned}$$

$(1/2)^k$

<https://powcoder.com>

## Correctness of Randomized Identity Selection

### Assignment Project Exam Help

- However since there are at most  $\binom{n}{2}$  pairs  $i \neq j$  we get

Add WeChat powcoder

$$\Pr[\exists i \neq j (ID_i = ID_j)] \leq \sum_{i \neq j} \Pr[ID_i = ID_j]$$

Boole's Rule

Union Rule

$$\leq \frac{\binom{n}{2}}{n^c}$$

### Assignment Project Exam Help

$$\leq \frac{1}{n^{c-2}}$$

<https://powcoder.com>

- Hence,

Add WeChat powcoder

$$\Pr[\forall i \neq j (ID_i \neq ID_j)] \geq 1 - \frac{1}{n^{c-2}}$$

$C = 4$

$$1 - \frac{1}{100^2}$$



<https://powcoder.com>

## Randomized Leader Election (2/2)

### Assignment Project Exam Help

- A leader election algorithm in a ring of size  $n$  has to run for  $n$  rounds so as to ensure that every node is informed of the leader.

Add WeChat powcoder

- **Algorithm Randomized Leader Election**

1. Each node chooses a random bit 0 or 1 independently of each other.
2. **For**  $n$  rounds each node sends and receives bits from its neighbour.
3. Each node computes its identity as the sequence of  $n$  bits it receives /\* in the order received \*/
4. A node becomes a leader if its identity is the largest among everybody else's identities.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

## Randomized Identity Selection: Example

### Assignment Project Exam Help

- Lets run the algorithm for 4 steps:

Add WeChat powcoder

Node 1	1100	12
--------	------	----

Node 2	1001	9
--------	------	---

Node 3	0011	3
--------	------	---

### Assignment Project Exam Help

Node 4	0111	7
--------	------	---

<https://powcoder.com>

Node 5	1110	14
--------	------	----

Node 6	1101	13
--------	------	----

Add WeChat powcoder

Node 7	1010	10
--------	------	----

Node 8	0100	4
--------	------	---

Node 9	1001	9
--------	------	---

...	...	...
-----	-----	-----

- Which one of the 12 nodes receives the largest identifier?

<https://powcoder.com>

## Correctness of Randomized Leader Election Assignment Project Exam Help

- **Theorem 4** *With probability at least  $\geq 1 - n^2/2^n$  Algorithm Randomized Leader Election ensures that a unique leader is elected. The algorithm uses a total of  $n$  random bits, terminates in  $n$  rounds and the total number of bits transmitted is  $n^2$ .<sup>a</sup>*
- The algorithm terminates in  $n$  rounds, because Step 2 of the algorithm runs for  $n$  rounds (not  $c \log n$  as in identity selection).
- In Step 4, how does each node compute the identity of every other node without additional communication?

---

<sup>a</sup>Notice that the IDs constructed by this algorithm can be as large as  $2^n$ .

<https://powcoder.com>

## Correctness of Randomized Leader Election Assignment Project Exam Help

- For the sake of simplicity, assume addition below is mod  $n$
- If

Add WeChat powcoder

$$ID_i = X_i X_{i+1} \cdots X_{i+n-1}$$

is  $i$ 's identity as computed by the algorithm then  $i$  can compute  $ID_{i+k \bmod n}$  by simply rotating it  $k$  positions.

Assignment Project Exam Help

- Indeed

<https://powcoder.com>

$$ID_i = X_i X_{i+1} X_{i+2} X_{i+3} \cdots X_{i+n-2} X_{i+n-1}$$

Add WeChat powcoder

$$ID_{i+1} = X_{i+1} X_{i+2} X_{i+3} \cdots X_{i+n-2} X_{i+n-1} X_i$$

$$ID_{i+2} = X_{i+2} X_{i+3} \cdots X_{i+n-2} X_{i+n-1} X_i X_{i+1}$$

$$\vdots = \vdots$$

- No additional communication round is needed.

<https://powcoder.com>

## Correctness of Randomized Identity Selection

Assignment Project Exam Help

- Finally, the claim on the probability.
- Just repeating the previous argument with  $k = n$  we see that

$$\Pr[ID_i = ID_j] = \Pr[\forall l \leq k (X_{i+l} = X_{j+l})]$$

$$= \prod_{l=1}^k \Pr[X_{i+l} = X_{j+l}]$$

Assignment Project Exam Help

<https://powcoder.com>

- Therefore since there are at most  $\binom{n}{2}$  pairs  $i \neq j$  we get

$$\begin{aligned} \Pr[\exists i \neq j (ID_i = ID_j)] &\leq \sum_{i \neq j} \Pr[ID_i = ID_j] \\ &\leq \binom{n}{2} / 2^n \\ &\leq n^2 / 2^n. \end{aligned}$$

<https://powcoder.com>

### Sources

## Assignment Project Exam Help

- H. Attiya, J. Welch, Distributed Computing, John Wiley and Sons, 2E, 2004.

Add WeChat powcoder

- R. Wattenhofer, Lecture Notes on Principles of Distributed Computing, ETH Spring 2012.

## Assignment Project Exam Help

- N. Lynch, Distributed Algorithms, Morgan-Kaufmann, 1996.

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

### Exercises<sup>a</sup>

## Assignment Project Exam Help

1. Can pairwise distinct identifiers be selected if the nodes have independent random generators?
2. Why are we allowed to interpret an event  $E$  that is valid “with probability at least  $\geq 1 - n^2/2^n$ ” as “it is valid with high probability”?
3. Justify the validity of the approximation  $e^{-1} \approx 1 - x$ , for  $|x|$  sufficiently small. (Use the Taylor series expansion of the function  $e^u$ , where  $u$  is a real number.)
4. Consider the following variant of randomized ID selection: Each node selects  $k$  random bits  $b_1, b_2, \dots, b_k$  and makes the sequence  $b_1 b_2 \dots b_k$  its identifier. Show that by choosing  $k$  appropriately with high probability the identifiers chosen by the nodes are pairwise distinct. **NB.** This algorithm differs

---

<sup>a</sup>Do not submit!



<https://powcoder.com>

from the one discussed in class in that it does not require any message exchanges.

Assignment Project Exam Help

5. How do “Timeslice” and “VariableSpeed” differ from the traditional “Clock-wise” and “RadiusGrowth” algorithms?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder