

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Locality

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>
Locality Everywhere

Add WeChat powcoder

<https://powcoder.com>

Outline

Assignment Project Exam Help

- Locality everywhere.

- Locality in Computing

- Local Coloring

- Coloring Trees

- Lower Bounds

Add WeChat powcoder

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>
Locality Everywhere

Add WeChat powcoder

<https://powcoder.com>

Locality Everywhere!

Assignment Project Exam Help

- Locality is everywhere:

- Physics

- Biology

- Social Sciences

- Mathematics

Assignment Project Exam Help

- They have differences and similarities.

Add WeChat powcoder

<https://powcoder.com>

Locality in Physics

Assignment Project Exam Help


- An object is only directly influenced by its immediate surroundings.
- A theory using the principle of locality is said to be a “local theory”.
- Relativity is a local theory
 - It limits the speed at which such influences can travel to the speed of light c .
- Quantum mechanics is not a local theory.
 - A measurement made on one of a pair of separated but entangled particles causes a simultaneous effect, the collapse of the wave function, in the remote particle (i.e. an effect exceeding the speed of light).

Add WeChat powcoder

Theory
Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

Locality in Biology

Assignment Project Exam Help

- Phenotypes might be influenced by local variations and effects.

Add WeChat powcoder

- Shape

- Size

- Color

Assignment Project Exam Help

- Nature

- Other environmental factors

<https://powcoder.com>

- In turn, this affects the genotype.

Add WeChat powcoder

- Quantum Biology is a newly developing field for the study of non-local biological phenomena.

- Bird navigation

Salmon, Turtle

<https://powcoder.com>

Locality in Social Sciences

Assignment Project Exam Help

- Local Characteristics

- Language

- Behaviour

- Culture

- Food

Assignment Project Exam Help

- Global Phenomena

- Cascades

- Rumors

- How do certain events cascade?

Social

o o

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Locality in Mathematics

Assignment Project Exam Help


- It has a proximity interpretation.
- Related somehow to distance. (geometric distance)
- Concerns phenomena that are geometrically close to each other.
- Locality is influenced by distance but is not the same thing as location!

<https://powcoder.com>

Add WeChat powcoder

paths between nodes
paths of a certain length

u sends messages to
all nodes three hops away



<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

Locality in Computing

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Locality

Assignment Project Exam Help


- Usually it means:
 - the execution of a process depends on nearby processes.
 - there is no dependency between events that occur far away.
- It has a special role in computing and communication.
 - What can be computed globally if there is a restriction on how far information can propagate?
- Can you elect a leader?
 - making use only of local information?

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

Locality

Assignment Project Exam Help


- Decision made at node u not affected by nodes far away from u .

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



locality
is somehow
hop-distance


- How do we quantify “far away” from u ?

<https://powcoder.com>

How far is local?

Assignment Project Exam Help

- Given that locality is influenced by distance “how far is far away”? **Add WeChat powcoder**
- May depend on the topology



- How do you parametrize locality?
- Best to study specific problems!

<https://powcoder.com>

Coloring

Assignment Project Exam Help

- Global vs Local Algorithms

Add WeChat powcoder

- On a Line

- On a Tree

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Local Algorithms in DC

Assignment Project Exam Help

- An algorithm is local if messages initiated by the nodes do not propagate too far from their originator.

[Add WeChat powcoder](https://powcoder.com)

- How can you ensure correctness of the algorithm?
- Which problems can you solve this way?
- How far is too far?


Assignment Project Exam Help

- Local approach is important for wireless communication!

<https://powcoder.com>

- Lets go back to coloring

[Add WeChat powcoder](https://powcoder.com)



<https://powcoder.com>

Coloring

Assignment Project Exam Help

- A vertex coloring is an assignment of colors to vertices of a graph so that any two adjacent vertices are assigned different colors.

<https://powcoder.com>

- How do you color a set of points on a line?

Assignment Project Exam Help



- If nodes have identities $1, 2, \dots, n$ then color nodes with even identities blue, and with odd identities red.



<https://powcoder.com>

Add WeChat powcoder

– Is the algorithm correct?

– Is this a local algorithm?

– Is there a local colouring algorithm?



<https://powcoder.com>

Global vs Local Coloring

Assignment Project Exam Help

- Before a node decides on its colour it must collect information about its neighboring nodes.

Add WeChat powcoder

- There are two ways to do this depending on how far this information collection can spread

Assignment Project Exam Help

1. Globally

2. Locally

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Globally/Locally

Assignment Project Exam Help


- Globally?



- You are not constrained by # of hops.

- Locally?

Assignment Project Exam Help



- Constrained by # of hops.
- In a distributed setting, the difficulty lies in keeping the assignment of colors consistent throughout the graph despite the fact that propagation is limited!

Why do you want a local coloring algorithm

Assignment Project Exam Help

<https://powcoder.com>

If algorithm is global, then it is not fault tolerant


Local algorithms are more robust to failures (node or link)

<https://powcoder.com>

Coloring with Restricted Number of Hops

Assignment Project Exam Help

- Consider nodes “independently” initiating coloring.



- If the number of hops a message can propagate is restricted you may not be able to complete the coloring!

Assignment Project Exam Help


- If a given set of nodes start coloring at the same time how do you ensure consistent coloring?

<https://powcoder.com>

- Nodes will start with their own identifiers.



Add WeChat powcoder

- More than that, you may have to use more than the minimum required number of colors so as to achieve a correct coloring!
- Regardless of the number of colors you use
 - can you achieve a proper coloring, and
 - at the same time restrict the number of hops?



Assignment Project Exam Help

<https://powcoder.com>



Limit on the # of hops, will affect the # of colors used!

<https://powcoder.com>

Quantifying Locality: Network Assignment Project Exam Help

- Consider a class \mathcal{N} of networks.
- A typical network $G = (V, E)$ in \mathcal{N} is a graph with n vertices.
 - Line,
 - Ring,
 - Tree,
 - etc.
- The concept should be applicable to all classes of graphs (networks).

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Quantifying Locality: Distance

Assignment Project Exam Help

- Locality should depend on distance.
- Let $n \rightarrow h(n)$ be an integer valued function:
 - $h(n)$ is the number of hops allowed in a network of size n .

Add WeChat powcoder

- Examples:

- $n \rightarrow h(n) = 1,$
- $n \rightarrow h(n) = c, c$ is some constant,
- $n \rightarrow h(n) = \log n,$
- $n \rightarrow h(n) = \sqrt{n},$
- $n \rightarrow h(n) = n,$
- $n \rightarrow h(n) = \log^* n, \text{ etc}$

<https://powcoder.com>

Add WeChat powcoder

Local is an algorithm which for every node in a graph of size n nodes messages are propagated at most $h(n)$ hops

<https://powcoder.com>

Quantifying Locality: Problems

Assignment Project Exam Help

- Consider a problem \mathcal{P} (e.g., colouring), and a class \mathcal{A} of synchronous, distributed algorithms solving \mathcal{P} for \mathcal{N} .
 - The class \mathcal{A} of distributed algorithms is h -local if during the execution of an algorithm $A \in \mathcal{A}$ on a network $G \in \mathcal{N}$ (on n vertices), a message emanating from a node will never propagate more than $h(n)$ hops from its originator.

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Propagation distance (hop-distance) is determined by the function h .

<https://powcoder.com>

Which Problems in DC are Local?

Assignment Project Exam Help

- Not all problems are going to be h -local, for a given function h .

Add WeChat powcoder

- Which ones are h -local, for a function $n \rightarrow h(n) = c$, where c a constant?

– Leader Election

Assignment Project Exam Help

– Spanning Tree

– Maximum Independent Set

– Coloring

– Minimum Dominating Set

- For which topologies?

<https://powcoder.com>

Add WeChat powcoder

100
 $\log^* 10 \leq 5$

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>
Local Coloring


Add WeChat powcoder

<https://powcoder.com>

Coloring a Line Graph: Assumptions

Assignment Project Exam Help

- Assume you are on a line of n nodes.



- To start, assume that each node v has a distinct identity id_v (for example, either their location or the network interface card would do).

Assignment Project Exam Help

- Identity selection is much easier than the coloring problem...besides we also know several ways to solve this problem!


<https://powcoder.com>

Add WeChat powcoder

$\log^*(11) \leq 3$

All students

1 1 1



<https://powcoder.com>

Local Coloring Algorithm

Assignment Project Exam Help

- Our main goal is to show
- **Theorem 1** *There is a coloring algorithm which can 3-color any line in $O(\log^* n)$ time, where*

- $\log^* n$ is the iterated logarithm of n
- in the algorithm all nodes start with their identifiers.

$$\log(\log(\dots \log n)) \leq 2$$

- This result is important in certain types of networks (like wireless) where messages should not propagate too far!
- **NB:** Note the important parameters taken into account:
 - Final number of colors in the graph.
 - Termination time of the coloring algorithm.

<https://powcoder.com>

Assumptions for Coloring

Assignment Project Exam Help

- Let $v \rightarrow c_v$ be an arbitrary coloring of the vertices.
 - Observe that $c_v := id_v$ is a legal coloring!
- For example,
 - the identity assignment below is a colouring using n colors,



- and so is any permutation of the identities.

<https://powcoder.com>

line of n vertices

L_n : can be colored with
 n colors :
 $2^0 = 1, 2^1, 2^2, \dots, 2^n$

$$1^2, 2^2, 3^2, \dots, n^2$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Assumptions for Coloring

Assignment Project Exam Help

Every vertex v is initially colored c_v

- Represent each c_v as a sequence of bits.
 - Let $|c_v|$ be the number of bits in c_v , and
 - $c_v(i)$ the i -th bit of c_v .

- **Example:**

– $c_u = 594 = 512 + 64 + 16 + 2 = 2^9 + 2^6 + 2^4 + 2^1$.

– In binary $c_u = 1001010010$

– $c_u(i)$ is the i th bit where counting starts from $i = 0$ from left to right: $c_u(0) = 1, c_u(2) = 0$.

- The **concatenation**

– of two sequences s, s' of bits is the sequence ss' .

– **Example:** if $s = 1010$ and $s' = 110$ then $ss' = 1010110$

$10110 \quad 1011011$

<https://powcoder.com>

Idea for an Algorithm on a Line

Assignment Project Exam Help

- Assume an ordering of the vertices (left to right would do).

Add WeChat powcoder



- Starting Rule:

- Start with any legal coloring,

- * for example $c_v := id_v$, for all v .

<https://powcoder.com>

- Color “leftmost vertex” with the bit 0.^a

Add WeChat powcoder

- Any other starting coloring would do.


^aThis is a starting condition and we will need to justify it: will do this later!

<https://powcoder.com>

Recoloring Rule

Assignment Project Exam Help

- Since nodes $u \rightarrow v$ are neighbors (with u preceding v), their current colors must be different: $c_u \neq c_v$.
- Produce a new “legal” coloring for a vertex v from the current one, say c_v , as follows:
 - Find the first index $1 \leq i \leq |c_v|$ such that v 's color differs from the colour of its predecessor.
 - Set new color to “ i concatenated with $c_v(i)$ ”: $c_v \rightarrow \underbrace{ic_v(i)}$;
- Recoloring rule guarantees that neighbors will get new **different** colors.
- **NB:** Bit representation of each new color is of length logarithmic of the length of the previous color!



$$\begin{array}{l}
 \sim \\
 \text{color} : c_v \quad 1 \leq i \leq |c_v| \\
 i \in c_v(i) \quad (\log c_v) + 1
 \end{array}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Coloring Algorithm for Vertex v

Assignment Project Exam Help

- Assume an ordering of the vertices (left to right would do).

Add WeChat powcoder



- Coloring Algorithm:

1. $c_v \leftarrow id_v$;

2. Repeat: <https://powcoder.com>

(a) $\ell \leftarrow |c_v|$;

(b) if v is “leftmost vertex” then set $I \leftarrow 0$

else set $I \leftarrow \min\{i : c_v(i) \neq c_{pre(v)}(i)\}$;

(c) Set $c_v \leftarrow Ic_v(I)$; /* concatenation */

(d) Inform the successor $suc(v)$ of v of this choice;

3. Until $|c_v| = \ell$; /*Until length does not change */

Assignment Project Exam Help

Add WeChat powcoder

<https://powcoder.com>

Example (1/2)

Assignment Project Exam Help

- Given two nodes $u \rightarrow v$.
- Lets show how the color of node v changes from the old color c_v to a new color c_v .

Add WeChat powcoder

- A similar change occurs to the color of u , but this is influenced from the predecessor of u .

Assignment Project Exam Help

- Let their current colors be $c_u = 554$ and $c_v = 631$.

<https://powcoder.com>

- Convert to binary.

Add WeChat powcoder

$$c_u = 512 + 64 + 16 + 2 = 2^9 + 2^6 + 2^4 + 2^1$$

$$c_v = 512 + 64 + 32 + 16 + 4 + 2 + 1 = 2^9 + 2^6 + 2^5 + 2^4 + 2^2 + 2^1 + 2^0$$

- $c_u = 1001010010$ and $c_v = 1001110111$

<https://powcoder.com>

Example (2/2)

Assignment Project Exam Help

- Consider the two nodes with colors

Add WeChat powcoder

$$c_u = 1001010010 \text{ and } c_v = 1001110111$$

- What is the smallest i such that $c_u(i) \neq c_v(i)$?

Assignment Project Exam Help

- Line up the bits

<https://powcoder.com>

1001010010

Add WeChat powcoder

1001110111

- So $i = 4$ (counting starts from 0); in binary 4 is 100 and the new colour of v in binary representation is

$$ic_v(i) = 1001 = 9$$


<https://powcoder.com>

Execution of Coloring Algorithm

Assignment Project Exam Help

- A node receives input from its predecessor...

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

- ...and provides input to its successor.

Add WeChat powcoder


$\log^* n$

<https://powcoder.com>

Correctness: Legal Coloring (1/2)

Assignment Project Exam Help

- Consider three consecutive neighboring nodes u, v, w at some iteration of the algorithm with $u = \text{prev}(v)$, $v = \text{pre}(w)$.



Assignment Project Exam Help

- Let I, J be the indices picked by v, w in Step 2(b), respectively.
 - $I := \min\{i : c_u(i) \neq c_v(i)\}$ and $J := \min\{j : c_v(j) \neq c_w(j)\}$
 - v, w receive the new colours:

$$c_v \leftarrow Ic_v(I)$$

and

$$c_w \leftarrow Jc_w(J)$$

<https://powcoder.com>

Correctness: Legal Coloring (2/2)

Assignment Project Exam Help

- We need to show that $Ic_v(I) \neq Jc_w(J)$.
- There are two cases to consider:
 1. If $I \neq J$ then rule 2(b) ensures that the new labels $Ic_v(I), Jc_w(J)$ as defined in 2(c) differ in a bit
 - because I, J do
 2. If $I = J$ then rule 2(b) ensures that the new labels as defined in 2(c) differ in the last bit
 - Recall that $c_u(I) \neq c_v(I)$ and $c_v(J) \neq c_w(J)$
 - Since $I = J$ we have that $c_u(I) \neq c_v(I)$ and $c_v(I) \neq c_w(I)$
 - The new labels for v, w will be $Ic_v(I)$ and $Ic_w(I)$ and by choice of I we have that $c_v(I) \neq c_w(I)$.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Number of Rounds

5

Assignment Project Exam Help

- At the start, $K_0 = K = O(\log n)$ is the max number of bits of a node in the original ID coloring.

Add WeChat powcoder

$5 \log n$:

n^5

- Let K_r denote the number of bits in the color representation after the r th iteration.

Assignment Project Exam Help

- Observe that $K_{r+1} = \lceil \log K_r \rceil + 1$.

r -th iteration c_v
 $\lceil \log K_r \rceil + 1$

- Therefore the second coloring will be of roughly $\log \log n$ bits, the third of roughly $\log \log \log n$ bits, etc.

Add WeChat powcoder

- As a matter of fact the “sizes of the colours” shrink very rapidly!
 - The size of the colour (measured in bits) in the new step is the logarithm of the size of the colour in the previous step!

<https://powcoder.com>

Iterated Logarithm: \log^*

Assignment Project Exam Help

- $\log^* n$ is not really a logarithm:
 - it is rather the number of iterations of the log function on a number n until it stops having an effect!
- **Log-Star** (in base 2) of n :
 - Is the number of logarithms in base 2 needed so that starting from n you get down to ≤ 1
- Can be defined in any base! Here we look only on base 2

<https://powcoder.com>

Add WeChat powcoder

$$\log_2 4 = 2$$

$$\lceil \log_2 3 \rceil + 1 = 3$$

$$\lceil \log_2 15 \rceil + 1 = 5$$

$$\lceil \log_2 5 \rceil + 1 = 4$$

$$\lceil \log_2 4 \rceil + 1 = 3$$

<https://powcoder.com>

Definition of \log^*

Assignment Project Exam Help

- **Iterated Definition of $\log^* n$:** Let

– $\log^{(1)} n = \log n$, and

– $\log^{(x+1)} n = \log(\log^{(x)} n)$, for $x \geq 1$.

Then $\log^* n =$ first integer x such that $\log^{(x)} n \leq 2$.^a

- **Recursive definition of $\log^* n$:**

<https://powcoder.com>

$$\log^* x = \begin{cases} 1 & \text{if } x \leq 2 \\ 1 + \log^*(\log x) & \text{if } x > 2 \end{cases}$$

^a $\log^{(x)} n$ should not be confused with $\log^x n$: the logarithm to the power x .

<https://powcoder.com>

Example

Assignment Project Exam Help

- Log-star is a very slowly growing function.

Add WeChat powcoder

- Consider the number $n = 2^{2^5}$.

$$\log(2^{2^5}) = 2^5$$

Assignment Project Exam Help

$$\log(2^{2^5}) = 5$$

<https://powcoder.com>

$$\log(5) \approx 2.32192809489$$

$$\log(2.32) < 2.$$

Add WeChat powcoder

Hence, $\log^*(2^{2^5}) = 4$.

- Log-star of all the atoms in the observable universe (estimated to be 10^{80}) is 5.

<https://powcoder.com>

The Starting Nodes: Something Wrong?

Assignment Project Exam Help

- Recall the leftmost node was given the color 0.
- It is not clear from the description of the algorithm why the identities of the nodes “located” at the beginning of the line are reduced to constant size.

Add WeChat powcoder

- By beginning we mean the first $O(\log^* n)$ nodes.

- Observe that the identities of the nodes after location $O(\log^* n)$ are indeed reduced to constant size.

Add WeChat powcoder

- Can remedy this by adding an additional step at the end of the algorithm:

- The first $O(\log^* n)$ nodes run a recoloring algorithm to reduce their colors to constant size.

- Note that this step takes additional time $O(\log^* n)$.

<https://powcoder.com>

Six Coloring in $\log^* n$ Iterations

Assignment Project Exam Help

- If K_i = number of bits in the coloring after i iterations then

– $K_{r+1} = \lceil \log K_r \rceil + 1$.

– $K_{r+1} < K_r$ as long as $K_r \geq 4$.

- In the final iteration r we have that $K_r = K_{r-1} \leq 3$.

- Therefore in the final coloring you have

- at most three choices for an index to a bit in the $(r-1)$ st coloring, and

- two choices for the value of the bit,

which gives a total of six colors.

- It turns out,

- we can improve on # of colors from six to three, but we promised
- cannot improve on the $\log^* n$.

If $x \geq 4$
 $1 + \lceil \log x \rceil < x$

$K_r \leq 3$

Can color the line in 6 colors. But

can do it in 3!

<https://powcoder.com>

Three Colors Suffice

Assignment Project Exam Help

- How do we reduce the number of colors from six to three?

Add WeChat powcoder

- Suppose that the algorithm we discussed before has colored a line with the six colors 0, 1, 2, 3, 4, 5 as follows

0 5 4 2 5 3 0 3 1 5 4 2 3 0 1 4 3 2 4 0 1 0 2 4 5

Assignment Project Exam Help

- How do you color it using only the colors 0, 1, 2?

<https://powcoder.com>

Add WeChat powcoder

0, 1, 2, 3, 4, 5

<https://powcoder.com>

Three Colors Suffice Assignment Project Exam Help

- Start with the sequence

Add WeChat powcoder

0 5 4 2 5 3 0 3 1 5 4 2 3 0 1 4 3 2 4 0 1 0 2 4 5 2

- Eliminate 5: by choosing a color from 0, 1, 2

Assignment Project Exam Help

0 1 4 2 0 3 0 3 1 0 4 2 3 0 1 4 3 2 4 0 1 0 2 4 0 2

- Eliminate 4: by choosing a color from 0, 1, 2

<https://powcoder.com>

Add WeChat powcoder

0 1 0 2 0 (3) 0 (3) 1 0 1 2 (3) 0 1 0 3 2 1 0 1 0 2 1 0

- Eliminate 3: by choosing a color from 0, 1, 2

0 1 0 2 0 1 0 1 0 1 2 1 0 1 0 1 2 1 0 1 0 2 1 0


2

<https://powcoder.com>

Coloring Rings

Assignment Project Exam Help

- **Theorem 2** *There is an algorithm which can 3-color any ring of size n in $\log^* n$ time.*
- Same algorithm.



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Can you reduce the number of rounds any further

$$\Omega(\log^* n)$$


e.g. inverse Ackerman function

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

3-coloring



<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>
Coloring Trees

Add WeChat powcoder

<https://powcoder.com>

From Lines to Trees


Assignment Project Exam Help

- The line colouring algorithm also works on trees!
- Add WeChat powcoder
- The basic assumption is that you must have a node of the tree designated as the root!
- Further, other nodes must have a parent (i.e., a predecessor)!
- The main theorem is the following.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



<https://powcoder.com>

6-Coloring Theorem

Assignment Project Exam Help

- **Theorem 3** *There is an algorithm which can 6-color any tree in $\log^* n$ time.*

Add WeChat powcoder



Assignments
of

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1
3-color

<https://powcoder.com>

6-Coloring Algorithm for Trees: Vertex v

Assignment Project Exam Help

Algorithm: 6-Color

1. $c_v \leftarrow id_v$,

2. Repeat:

(a) $\ell \leftarrow |c_v|$;

(b) if v is "the root" then set $I \leftarrow 0$


else set $I \leftarrow \min\{i : c_v(i) \neq c_{parent(v)}(i)\}$;

(c) Set $c_v \leftarrow Ic_v(I)$; /* concatenation */

(d) Inform all children of v of this choice;

3. Until $|c_v| = \ell$;

- Why is the algorithm correct?



<https://powcoder.com>

3-Coloring Theorem for Trees

Assignment Project Exam Help

- **Theorem 4** *There is an algorithm which can 3-color any tree in $O(\log^4 n)$ time.*
- The reason is that the coloring on the descendants of a given node is independent when done on disjoint paths.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

<https://powcoder.com>

Shift-Down Algorithm

Assignment Project Exam Help


- The color reduction method is called “shift-down”.

- **Algorithm Shift-Down**

1. Concurrently at all vertices:
2. Recolor each non-root vertex by the color of its parent.
3. Recolor root by a new color, different from its current one.

Assignment Project Exam Help

<https://powcoder.com>



- Why is “shift-down” correct?
- Colors (of the original coloring) are shifted down.



<https://powcoder.com>

Analysis of Shift-Down Algorithm

Assignment Project Exam Help

- **Lemma 1 (Analysis of Algorithm Shift Down)**

Algorithm Shift Down preserves coloring legality; also siblings are monochromatic.



- Two vertices $v = \text{parent}(w)$, w are recolored by $c_{\text{parent}(v)}$ and c_v , which are different since c was a legal colouring.
- If $v = \text{root}$, then the new colors are x and c_v , where x is some color different from c_v .
- Also, all children of some vertex v get the same new color c_v .

<https://powcoder.com>

Final Color Reduction

Assignment Project Exam Help

- Now assume the six colors employed in the tree are

Add WeChat powcoder

0, 1, 2, 3, 4, 5

Cancellation procedure:

- The final three reduction steps involve cancelling colors

Assignment Project Exam Help

3, 4, 5

<https://powcoder.com>

one at a time.

- In the end, there will be three colors left 0, 1, 2.
 - This is done by Algorithm Six2Three

Add WeChat powcoder

<https://powcoder.com>

Six2Three Algorithm

Assignment Project Exam Help

- Algorithm Six2Three

1. for $x = 5, 4, 3$ do /* Cancel color x */
2. Perform subroutine **Shift-Down** on the current colouring;
3. if $c_v = x$ then
4. v chooses new color $c_v \in \{0, 1, 2\}$ not used by any of the neighbors.
5. endif
6. endfor

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


<https://powcoder.com>

Example of Six2Three

Assignment Project Exam Help

- Recolouring method

Add WeChat powcoder



Assignment Project Exam Help

<https://powcoder.com>

- Example discarding color 4:


Add WeChat powcoder

Each reduction of color 5

	Round	#Round
5	2	3
4	2	3
3	2	3
colored with {0, 1, 2}	6	

$\log^* n + \underbrace{6}_{\log^* n}$

4
cannot
choose
any of
0, 1, 2




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

If requires one
map shift
before you
can remove 4.



<https://powcoder.com>

Analysis of Six2Three


Assignment Project Exam Help

- **Theorem 5 (Analysis of Algorithm Six to Three)**

Algorithm Six2Three colors a tree with three colors in time $O(\log^ n)$.*

- Each vertex colored x will find an available color from the set $\{1, 2, 3\}$,
 - since by the Shift-Down Lemma at most two of these colors are occupied, one by its parent and one by its children.
- Now note that recoloring the x colored vertices simultaneously creates no problem since they are all mutually nonadjacent.

It is important
we have a tree.



<https://powcoder.com>

Optimality

Assignment Project Exam Help

- Fast tree-coloring with only 2 colors is more than exponentially more expensive than coloring with 3 colors.

– In a tree degenerated to a line, nodes far away need to figure out whether they are an even or odd number of hops away from each other in order to get a 2-coloring.

– To do that one has to send a message to these nodes. This costs time linear in the number of nodes.

<https://powcoder.com>
Add WeChat powcoder

↓ We use the # of rounds to signify "speed".

$\log^* n$ rounds

to get 2-coloring
you need n rounds
 $\Omega(\log^* n)$

<https://powcoder.com>

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>
Lower Bounds

Add WeChat powcoder

<https://powcoder.com>

Can anything be better than $\log^* n$?

Assignment Project Exam Help

- The only thing better than $O(\log^* n)$ running time is $O(1)$ running time!

Add WeChat powcoder

- A 2-coloring is possible with $O(1)$ running time in a distributed system with GPS!

← global algorithm

Assignment Project Exam Help

- It turns out that we can prove a lower bound of $\Omega(\log^* n)$ on the time required to color the n -vertex line (ring) by three colors.

<https://powcoder.com>

- This implies a tight bound of $\Theta(\log^* n)$ on the time required for 3-coloring the line (ring).

$$O(\log^* n) \cap \Omega(\log^* n)$$

$\log^* n$ is not a constant

<https://powcoder.com>

$\Omega(\log^* n)$ Lower Bound

Assignment Project Exam Help

- **Theorem 6** Every deterministic, distributed algorithm to color a directed ring with 3 or less colors needs at least $(\log^* n)/2 - 1$ rounds.

- The proof uses a theorem of Frank P. Ramsey.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



(22 February 1903 19 January 1930).

- We will not prove Theorem 6 here.

<https://powcoder.com>


Generalizations and Additional Results

Assignment Project Exam Help

- Linial (1992) proves that
 - in rooted d -regular tree $T_{d,r}$ of radius r , any synchronous distributed algorithm running in time $\leq \frac{2}{3}r$ cannot color $T_{d,r}$ by fewer than $\frac{1}{2}\sqrt{d}$ colors. (4) = 64
 - an arbitrary graph G of order n and max degree Δ , can be colored with $5\Delta^2 \log n$ colors in one time unit distributively.
 - for G labeled, in time $O(\log^* n)$ it is possible to color G with $O(\Delta^2)$ colors in a distributive synchronous algorithm.
- There exists a deterministic distributed algorithm for coloring arbitrary graphs with max degree Δ ;
 - can be colored with $\Delta + 1$ colors in $O(\Delta \log^* n)$ time.

d-regular tree

$$d = 4$$



When you have a distributed algorithm

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Terminates

r
rounds

round:

receive, process, send



<https://powcoder.com>

Exercises^a

Assignment Project Exam Help

1. For any graph $G = (V, E)$ define the chromatic numbers

Add WeChat powcoder

$\chi_{centralized}(G), \chi_{distributed}(G), \chi_{local}(G)$

for centralized, distributed, and local computation.

- (a) How do they differ?

Assignment Project Exam Help

- (b) Is there a natural order of these three quantities?

<https://powcoder.com>

2. Define the concepts of centralized, distributed and local for any algorithmic computation and make a comparison.

Add WeChat powcoder

3. Let $n \rightarrow h(n)$ be an integer valued function, where $h(n)$ is the number of hops allowed in a network of size n to complete the computation. Formulate the various types of computation discussed above in terms of the function $h(n)$.

4. (★★) Consider Exercise 3. If $h(n) = n$ then the number of

^aDo not submit!

<https://powcoder.com>

colors is 2. If $h(n) = 1$ then the number of colors is 3. For which threshold value of $h(n)$ does the number of colors jumps from 2 to 3?

Add WeChat powcoder

5. Compute $\log^*(10^{1000})$.

6. Compute $\log^*(2^{2^{2^{16}}})$.

Assignment Project Exam Help

7. Explain in more detail (than the slide presented in class) that the local coloring algorithm (before the six \rightarrow three reductions) reduces to a six coloring.

<https://powcoder.com>
Add WeChat powcoder

8. Show in detail that on the line graph three colors suffice.

9. Prove that a \log^* coloring algorithm is possible on a ring. How many colors does it require?

10. Prove in detail the correctness of the \log^* tree coloring algorithm.

<https://powcoder.com>

Sources

Assignment Project Exam Help

- L. Barenboim, and M. Elkin. Distributed graph coloring: Fundamentals and recent developments. Synthesis Lectures on Distributed Computing Theory 4.1 (2013): 1-171.
- N. Linial. Locality in distributed graph algorithms. SIAM Journal on Computing 21.1 (1992): 193-201.
- D. Peleg, Distributed Computing: A Locality Sensitive Approach, SIAM, 2000.

<https://powcoder.com>

Add WeChat powcoder