

Advanced Network Technologies

Queueing Theory

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Dr. Wei Bao | Lecturer
School of Computer Science



THE UNIVERSITY OF
SYDNEY

- › Markov Chain
- › Queueing System and Little's Theorem
- › M/M/1 Queue foundations **Assignment Project Exam Help**
- › M/M/1 Queue **<https://powcoder.com>**

Add WeChat powcoder



› Markov Chain

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

› A stochastic process

- $X_1, X_2, X_3, X_4 \dots$
- $\{X_n, n = 1, 2, \dots\}$
- X_n takes on a finite or countable number of possible values.
- $X_n \in \{1, 2, \dots, S\}$
- i : i th state
- **Markov Property**: The state of the system at time $n+1$ depends only on the state of the system at time n

$$\Pr[X_{n+1} = x_{n+1} / X_n = x_n, \dots, X_2 = x_2, X_1 = x_1] = \Pr[X_{n+1} = x_{n+1} / X_n = x_n]$$







<https://powcoder.com>

Add WeChat powcoder

- Stationary Assumption: Transition probabilities are independent of time (n)

$$\Pr[X_{n+1} = b \mid X_n = a] = p_{ab}$$

Weather:


- raining today  40% rain tomorrow
 60% no rain tomorrow
- not raining today  20% rain tomorrow
 80% no rain tomorrow

Assignment Project Exam Help





<https://powcoder.com>

Add WeChat powcoder

Stochastic FSM:



Weather:

- raining today  40% rain tomorrow
 60% no rain tomorrow
- not raining today  20% rain tomorrow
 80% no rain tomorrow

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Matrix:

$$P = \begin{pmatrix} 0.4 & 0.6 \\ 0.2 & 0.8 \end{pmatrix}$$


- Stochastic matrix:
Rows sum up to 1



$$P = \begin{pmatrix} p_{11} & p_{12} & \cdots & p_{1S} \\ p_{21} & p_{22} & \cdots & p_{2S} \\ \vdots & \vdots & \ddots & \vdots \\ p_{S1} & p_{S2} & \cdots & p_{SS} \end{pmatrix}$$

Assignment Project Exam Help
<https://powcoder.com>
Add WeChat powcoder

- Gambler starts with \$10
- At each play we have one of the following:
 - Gambler wins \$1 with probability p
 - Gambler loses \$1 with probability $1-p$
- Game ends when gambler goes broke, or gains a fortune of \$100
(Both 0 and 100 are absorbing states)





Gambler's Example

- transient state

if, given that we start in state i , there is a non-zero probability that we will never return to i

Assignment Project Exam Help

<https://powcoder.com>

- recurrent state

Non-transient

Add WeChat powcoder

- absorbing state

impossible to leave this state.

Coke vs. Pepsi Example

- Given that a person's last cola purchase was **Coke**, there is a **90%** chance that his next cola purchase will also be **Coke**.

- If a person's last cola purchase was **Pepsi**, there is an **80%** chance that his next cola purchase will also be **Pepsi**.


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat to transition diagram:

transition matrix:

$$P = \begin{bmatrix} 0.9 & 0.1 \\ 0.2 & 0.8 \end{bmatrix}$$





Coke vs. Pepsi Example

Given that a person is currently a **Pepsi** purchaser, what is the probability that he will purchase **Coke** two purchases from now?

Assignment Project Exam Help

$$\Pr[\text{Pepsi} \rightarrow ? \rightarrow \text{Coke}] =$$

$$\Pr[\text{Pepsi} \rightarrow \text{Coke} \rightarrow \text{Coke}] + \Pr[\text{Pepsi} \rightarrow \text{Pepsi} \rightarrow \text{Coke}] =$$

$$0.2 * 0.9 + 0.8 * 0.2 = 0.34$$

$$P = \begin{bmatrix} 0.9 & 0.1 \\ 0.2 & 0.8 \end{bmatrix} \begin{bmatrix} 0.9 & 0.1 \\ 0.2 & 0.8 \end{bmatrix} = \begin{bmatrix} 0.83 & 0.17 \\ 0.34 & 0.66 \end{bmatrix}$$

Pepsi \rightarrow ? ? \rightarrow Coke

Coke vs. Pepsi Example

Given that a person is currently a **Coke** purchaser, what is the probability that he will purchase **Pepsi** **three** purchases from now?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$P^3 = \begin{bmatrix} 0.9 & 0.1 \\ 0.2 & 0.8 \end{bmatrix} \begin{bmatrix} 0.83 & 0.17 \\ 0.34 & 0.66 \end{bmatrix} = \begin{bmatrix} 0.781 & 0.219 \\ 0.438 & 0.562 \end{bmatrix}$$

Coke vs. Pepsi Example

- Assume each person makes one cola purchase per week
- Suppose 60% of all people now drink Coke, and 40% drink Pepsi
- What fraction of people will be drinking Coke three weeks from now?

$$P = \begin{bmatrix} 0.9 & 0.1 \\ 0.2 & 0.8 \end{bmatrix} \quad P^3 = \begin{bmatrix} 0.781 & 0.219 \\ 0.438 & 0.562 \end{bmatrix}$$

$$\Pr[X_3 = \text{Coke}] = 0.6 * 0.781 + 0.4 * 0.438 = 0.6438$$

Q_i - the distribution in week i


$Q_0 = (0.6, 0.4)$ - initial distribution

$$Q_3 = Q_0 * P^3 = (0.6438, 0.3562)$$



Coke vs. Pepsi Example

Simulation:





Steady State and Stationary distribution

$$\lim_{n \rightarrow \infty} P(X_n = i) = \pi_i$$

Assignment Project Exam Help

<https://powcoder.com>

$$\lim_{n \rightarrow \infty} P^n = \mathbf{1}\pi$$

Add WeChat powcoder

$$\pi = \pi \cdot P$$



Steady State and Stationary distribution

$$P = \begin{bmatrix} 0.9 & 0.1 \\ 0.2 & 0.8 \end{bmatrix}$$

$$\pi = \begin{bmatrix} \frac{2}{3} & \frac{1}{3} \end{bmatrix}$$

Assignment Project Exam Help

<https://powcoder.com>

$$P^{10} = \begin{bmatrix} 0.6761 & 0.3239 \\ 0.6478 & 0.3522 \end{bmatrix}$$


Add WeChat powcoder

$$P^{100} = \begin{bmatrix} 0.6667 & 0.3333 \\ 0.6667 & 0.3333 \end{bmatrix}$$

$$\begin{bmatrix} \frac{2}{3} & \frac{1}{3} \end{bmatrix} \begin{bmatrix} 0.9 & 0.1 \\ 0.2 & 0.8 \end{bmatrix} = \begin{bmatrix} \frac{2}{3} & \frac{1}{3} \end{bmatrix}$$

Steady State and Stationary distribution

PageRank: A Web surfer browses pages in a five-page Web universe shown in figure. The surfer selects the next page to view by selecting with equal probability from the pages pointed to by the current page. If a page has no outgoing link (e.g., page 2), then the surfer selects any of the pages in the universe with equal probability. Find the probability that the surfer views page 1.






Steady State and Stationary distribution

Transition matrix P

$$P = \begin{bmatrix} 0 & 1/2 & 1/2 & 0 & 0 \\ 1/5 & 1/5 & 1/5 & 1/5 & 1/5 \\ 1/3 & 1/3 & 0 & 1/3 & 0 \\ 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 1/2 & 0 & 1/2 \end{bmatrix}$$



Steady State and Stationary distribution

Stationary Distribution:
Solve the following equations:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\pi = \pi \cdot P$$
$$\sum_{i=1}^5 \pi_i = 1$$

$$\pi = (0.12195, 0.18293, 0.25610, 0.12195, 0.317072)$$


Search engineer. page rank: 5, 3, 2, 1, 4

› Queueing System and Little's Theorem


Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



- Customers = Data packets
- Service Time = Packet Transmission Time (function of packet length and transmission speed)
- Queueing delay = time spent in buffer before transmission
- Average number of customers in systems
 - Typical number of customers either waiting in queue or undergoing service
- Average delay per customer
 - Typical time a customer spends waiting in queue + service time



- W : average waiting time in queue
- X : average service time
- T : average time spent in system ($T = W + X$)
- N_Q = average number of customers in queue
- ρ = utilization = average number of customers in service
- N = average number of customer in system ($N = N_Q + \rho$)
- Want to show later: $N = \lambda T$ (Little's theorem)
- λ Average arrival rate




$\alpha(t)$ = Number of customers who arrived in the interval $[0, t]$

$\beta(t)$ = Number of customers who departed in the interval $[0, t]$

$N(t)$ = Number of customers in the system at time t , $N(t) = \alpha(t) - \beta(t)$

T_i = Time spent in the system by the i -th arriving customer




Average # of customers until t

$$N_t = \frac{1}{t} \int_0^t N(\tau) d\tau$$

Average # of customers in long-term

$$N = \lim_{t \rightarrow \infty} \frac{1}{t} \int_0^t N(\tau) d\tau$$




Average # arrival rate until t

$$\lambda_t = \frac{\alpha(t)}{t}$$

Average # arrival rate in long-term

$$\lambda = \lim_{t \rightarrow \infty} \frac{\alpha(t)}{t}$$




Average customer delay till t

$$T_t = \frac{\sum_{i=1}^{\alpha(t)} T_i}{\alpha(t)}$$

Average customer delay in long-term

$$T = \lim_{t \rightarrow \infty} \frac{\sum_{i=1}^{\alpha(t)} T_i}{\alpha(t)}$$




Shaded area when the queue is empty: two ways to compute

$$\int_0^t N(\tau) d\tau$$

=

$$\sum_{i=1}^{\alpha(t)} T_i$$




Shaded area when the queue is empty: two ways to compute

$$\frac{1}{t} \int_0^t N(\tau) d\tau$$


=

$$\frac{1}{t} \sum_{i=1}^{\alpha(t)} T_i$$



Shaded area when the queue is empty: two ways to compute

$$N_t = \frac{1}{t} \int_0^t N(\tau) d\tau = \lambda_t \frac{\sum_{i=1}^{\alpha(t)} T_i}{\alpha(t)} T_t$$



Shaded area when the queue is empty: two ways to compute

$$N_t = \lambda_t T_t$$

$$N = \lambda T$$

Note that the above Little's Theorem is valid for any service disciplines (e.g., first-in-first-out, last-in-first-out), interarrival time distributions, and service time distributions.


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Little's Theorem



- $N = \lambda T$
- $N_Q = \lambda W$
- $\rho = \text{proportion of time that the server is busy} = \lambda X$
- $T = W + X$
- $N = N_Q + \rho$

› M/M/1 Queue foundations

Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder

- › Exponential Distribution
- › • The cumulative distribution function $F(x)$ and probability density function $f(x)$ are:
- › $F(x) = 1 - e^{-\lambda x}$ $f(x) = \lambda e^{-\lambda x}$ $x \geq 0, \lambda > 0$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



The mean is equal to its standard deviation: $E[X] = \sigma_X = 1/\lambda$

- › $P(X > s + t / X > t) = P(X > s)$ for all $s, t \geq 0$
- › The only continuous distribution with this property
- › Practice Q2 in Tutorial Week 4

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Other Properties of Exponential Distribution

- › Let X_1, \dots, X_n be i.i.d. exponential r.v.s with mean $1/\lambda$,
- › then $X_1 + X_2 + \dots + X_n$ (Practice Q2 in Tutorial Week 4)

Assignment Project Exam Help
<https://powcoder.com>

$$f_{X_1 + \dots + X_n}(t) = \lambda e^{-\lambda t} \frac{(\lambda t)^{n-1}}{(n-1)!}$$

Add WeChat powcoder

- › gamma distribution with parameters n and λ .
- › Suppose X_1 and X_2 are independent exponential r.v.s with means $1/\lambda_1$ and $1/\lambda_2$, respectively then

$$P(X_1 < X_2) = \frac{\lambda_1}{\lambda_1 + \lambda_2}$$

- › A stochastic process $\{N(t), t \geq 0\}$ is a counting process if $N(t)$ represents the total # of events that have occurred up to time t .
- › 1. $N(t) \geq 0$ and $N(t)$ is integer valued.
- › 2. If $s < t$, then $N(s) \leq N(t)$.
- › 3. For $s < t$, $N(t) - N(s) =$ # of events that have occurred in (s, t)
- › • Examples:
 - › – # of people who have entered a particular store by time t
 - › – # of packets sent by a mobile phone
- › • A counting process is said to be independent increment if # of events which occur in disjoint time intervals are independent.
- › • A counting process is said to be stationary increment if the distribution of # of events which occur in any interval of time depends only on the length of the time interval.

- › The counting process $\{N(t), t \geq 0\}$ is said to be a Poisson process having rate $\lambda > 0$, if
- › 1. $N(0) = 0$
- › 2. The process has independent increments (i.e., # of events which occur in disjoint time intervals are independent)
 - › – for $0 < t_1 < t_2 < t_3 < t_4$, for all $n, j \geq 0$
 - › – $P\{N(t_4) - N(t_3) = n \mid N(t_2) - N(t_1) = j\} = P\{N(t_4) - N(t_3) = n\}$
- › 3. Number of events in any interval of length t is Poisson distributed with mean λt . That is, for all $s, t \geq 0$

$$E(N(t + s) - N(s)) = \lambda t$$


$$P(N(t + s) - N(s) = n) = \frac{(\lambda t)^n}{n!} e^{-\lambda t}$$



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





Poisson Process: Inter arrival time distribution

Exponential distribution with parameter λ
(mean $1/\lambda$)


Assignment Project Exam Help

$$P(T_2 > t) = P\{T_2 > t \mid T_1 = t_1\} = e^{-\lambda t}$$

<https://powcoder.com>

$$P(T_1 > t) = P(N(t) = 0) = e^{-\lambda t}$$

Add WeChat powcoder



Poisson Process: Inter arrival time distribution

Given that an event arrives now, what is the distribution of T , where T is the time duration between now and next arrival event?

Assignment Project Exam Help
Exponentially distributed with parameter λ

<https://powcoder.com>




Poisson Process: Inter arrival time distribution

Given that an packet event arrives at t_0 time ago, what is the distribution of T , where T is the time duration between now and next arrival event?

Assignment Project Exam Help
Exponentially distributed with parameter λ

<https://powcoder.com>



Reason: Memoryless!

Number of arrivals in a short period of time

Number of arrival events in a very short period

$$P\{N(t+h) - N(t) = 1\} = \lambda h + o(h); \text{ and}$$
$$P\{N(t+h) - N(t) \geq 2\} = o(h).$$

<https://powcoder.com>

$o()$. Small o notation. The function $f(.)$ is said to be $o(h)$ if

Add WeChat powcoder

$$\lim_{h \rightarrow 0} \frac{f(h)}{h} = 0$$

Poisson process:

Independent increments

of arrivals: Poisson distributed

of arrivals in a small period of time h . 1 arrival, probability λh

Inter-arrival time distribution: exponential distribution

Add WeChat powcoder



› M/M/1 Queue

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

› Notations Used in Queueing Systems

- › $X/Y/Z$
 - › – X refers to the distribution of the interarrival times
 - › – Y refers to the distribution of service times
 - › – Z refers to the number of servers
- › Common distributions:
 - › – M = Memoryless = exponential distribution
 - › – D = Deterministic arrivals or fixed-length service
 - › – G = General distribution of interarrival times or service times
- › $M/M/1$ refers to a single-server queueing model with exponential interarrival times (i.e., Poisson arrivals) and exponential service times.
- › In all cases, successive interarrival times and service times are assumed to be statistically independent of each other.

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

- › Arrival:
 - › Poisson arrival with rate λ
 - › Service: Assignment Project Exam Help
 - › Service time: <https://powcoder.com> exponential distribution with mean $1/\mu$
 - › μ : service rate, Add WeChat powcoder
 - › $\lambda < \mu$: Incoming rate < outgoing rate
-



Markov Chain Formulation



Assignment Project Exam Help
 δ : a small value


<https://powcoder.com>

N_k = Number of customers in the system at time $k\delta$
 $N_0 N_1 N_2 \dots$ is a Markov Chain!

Q: How to compute the transition probability?



Markov Chain Formulation




Assignment Project Exam Help

$$P(0 \text{ customer arrives}) = 1 - \lambda\delta + o(\delta)$$

$$P(1 \text{ customer arrives}) = \lambda\delta + o(\delta)$$

$$P(\geq 2 \text{ customer arrives}) = o(\delta)$$



Assignment Project Exam Help

<https://powcoder.com>

$$P(0 \text{ customer leaves}) = 1 - \mu\delta + o(\delta)$$

$$P(i \text{ customer leaves}) = \begin{cases} \mu\delta + o(\delta) & i \geq 1 \\ 0 & i = 0 \end{cases}$$

$$P(\geq 2 \text{ customer leaves}) = o(\delta)$$

No one in the system

Aim to compute $P_{ij} = P\{N_{k+1} = j / N_k = i\}$

For example, $P\{N_{k+1} = i / N_k = i\}, i \geq 0$

Assignment Project Exam Help

<https://powcoder.com>

$P(0 \text{ customer arrives})P(0 \text{ customer departs})$
 $+ P(1 \text{ customer arrives})P(1 \text{ customer departs})$
 $+ P(\text{other})$

Add WeChat powcoder


Result : $1 - \lambda\delta - \mu\delta + o(\delta)$

$$[1 - \lambda\delta + o(\delta)][1 - \mu\delta + o(\delta)] = 1 - \lambda\delta - \mu\delta + o(\delta)$$

$$[\lambda\delta + o(\delta)][\mu\delta + o(\delta)] = o(\delta)$$

$$o(\delta)o(\delta) = o(\delta)$$


Result:



π_i Stationary distribution of state i


The probability that there are i units in the system

How to derive π_i balance equation satisfied



$$\lambda\delta\pi_2 + \mu\delta\pi_2 = \lambda\delta\pi_1 + \mu\delta\pi_3$$

How to derive π_i



balance equation is performed at each state


$$\lambda\delta\pi_0 = \mu\delta\pi_1$$



$$\lambda\delta\pi_1 + \mu\delta\pi_1 = \lambda\delta\pi_0 + \mu\delta\pi_2$$

$$\lambda\delta\pi_1 = \mu\delta\pi_2$$

How to derive π_i




balance equation is performed at each state

$$\lambda\delta\pi_0 = \mu\delta\pi_1$$

$$\lambda\delta\pi_1 = \mu\delta\pi_2$$

$$\lambda\delta\pi_2 + \mu\delta\pi_2 = \lambda\delta\pi_1 + \mu\delta\pi_3 \quad \longrightarrow \quad \lambda\delta\pi_2 = \mu\delta\pi_3$$

How to derive π_i



balance equation is performed at each state

$$\lambda\delta\pi_0 = \mu\delta\pi_1$$

$$\lambda\delta\pi_1 = \mu\delta\pi_2$$




$$\lambda\delta\pi_i = \mu\delta\pi_{i+1}$$

For any i

$$\lambda\delta\pi_2 = \mu\delta\pi_3$$

How to derive π_i



balance equation is performed at each state

$$\pi_1 = \frac{\lambda}{\mu} \pi_0$$

$$\pi_2 = \left(\frac{\lambda}{\mu} \right)^2 \pi_0$$


...

$$\pi_i = \left(\frac{\lambda}{\mu} \right)^i \pi_0$$

$$\sum_{i=0}^{\infty} \pi_i = 1$$

Sum of geometric sequence

How to derive π_i



balance equation is performed at each state

$$\pi_1 = \rho \pi_0$$

$$\pi_2 = (\rho)^2 \pi_0$$

...


$$\pi_i = (\rho)^i \pi_0$$

$$\rho = \frac{\lambda}{\mu} < 1$$

$$\sum_{i=0}^{\infty} \pi_i = 1$$

Sum of geometric sequence

How to derive π_i



balance equation is performed at each state

$$\lim_{N \rightarrow \infty} \frac{\pi_0(1 - \rho^N)}{1 - \rho} = \frac{\pi_0}{1 - \rho} = 1$$

$$\pi_0 = 1 - \rho$$

$$\pi_i = (1 - \rho)\rho^i$$

Sum of geometric sequence

Average number of users in the system

$$\begin{aligned} E(N) &= \sum_{n=0}^{\infty} n(1-\rho)\rho^n \\ &= \rho(1-\rho) \sum_{n=0}^{\infty} n\rho^{n-1} \\ &= \rho(1-\rho) \frac{\partial \left[\sum_{n=0}^{\infty} \rho^n \right]}{\partial \rho} \\ &= \rho(1-\rho) \frac{\partial \left[\frac{\rho}{1-\rho} \right]}{\partial \rho} = \frac{\rho}{1-\rho} \end{aligned}$$



Average waiting time

Little's Theorem


Assignment Project Exam Help

$$E(T) = \frac{E(N)}{\lambda} = \frac{1}{\mu - \lambda}$$

<https://powcoder.com>
Add WeChat powcoder




Stationary Distribution Derivation




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



Stationary Distribution Derivation



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

balance equation is performed at each state

$$\lambda\pi_0 = \mu\pi_1$$

$$\lambda\pi_1 + \mu\pi_1 = \lambda\pi_0 + \mu\pi_2$$

...



<https://powcoder.com>


Add WeChat powcoder


balance equation is performed at each state

Following the same step, derive the same result


Stationary Distribution Derivation

Queueing delay goes to infinity when arrival rate approaches service rate!





- › Arrival:
 - › Poisson arrival with rate λ
 - › Service: Assignment Project Exam Help
 - › Service time for one server: exponential distribution with mean $1/\mu$ <https://powcoder.com> Add WeChat powcoder
 - › service rate is $i\mu$, if there are $i < m$ users in the system
 - › service rate is $m\mu$, if there are $i \geq m$ users in the system
-



Add WeChat powcoder

$$\lambda \pi_{i-1} = i \mu \pi_i \quad i \leq m$$

$$\lambda \pi_{i-1} = m \mu \pi_i \quad i > m$$


$$\pi_n = \begin{cases} \pi_0 \frac{(m\rho)^n}{n!} & n \leq m \\ \pi_0 \frac{m^m \rho^n}{m!} & n > m \end{cases}$$

$$\rho = \frac{\lambda}{m\mu} < 1$$

Then, π_0 can be solved



Assignment Project Exam Help






Assignment Project Exam Help

Arrivals <https://powcoder.com> Departures

An arrival is dropped
if all the servers are busy


Add WeChat powcoder



Arrivals will dropped if there are n users in the system.

Assignment Project Exam Help

<https://powcoder.com>



How do you derive its stationary distribution?

› Analyze M/M/ ∞ , M/M/m/n queues

- Draw the state transition diagrams
- Derive their stationary distributions
- For M/M/m/n queue, calculate the probability that an incoming user is dropped. Calculate the probability that the queue is empty (i.e., all users are served in the servers or there are no users at all.)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder