

COMP2022: Formal Languages and Logic

2018 Semester 2, Week 5

Assignment Project Exam Help

Joseph Godbehere

<https://powcoder.com>

30th August, 2018

Add WeChat powcoder



THE UNIVERSITY OF
SYDNEY

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Assignment Project Exam Help

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be subject of copyright protect under the Act.

Do not remove this notice.

OUTLINE

► Non-Deterministic Finite Automata (NFA)

- Non-determinism
- ϵ -transitions

► <https://powcoder.com>

► Minimal DFA

► Add WeChat powcoder

► Regular Languages and Closure properties

► Regular Expressions (introduction)

NON DETERMINISTIC FINITE AUTOMATA (NFA)

Assignment Project Exam Help

DFA

- ▶ has exactly one transition per input from each state
- ▶ no choice in the computation \Rightarrow *deterministic*

<https://powcoder.com>

NFA

- ▶ can have any number of transitions per input from each state
- ▶ so some steps of the computation might be *non-deterministic*
- ▶ can also have ε -transitions
 - ▶ i.e. transitions which the automaton can follow without scanning any input

Add WeChat powcoder

NON-DETERMINISM

Assignment Project Exam Help


- ▶ As we scan through a string, the NFA can be in many states at the same time
- ▶ Transitions from a state given an input symbol is to a set of states (0, 1, 2 or more states)
- ▶ The string is accepted if at least one sequence of states leads to a final state
 - ▶ i.e. if we are in at least one accept state, after reading all the input
- ▶ Parallel computation

<https://powcoder.com>


Add WeChat powcoder

EXAMPLE

NFA accepting strings over $\{0, 1\}$ containing substring "000"



The corresponding DFA would be




NFA WITH ε -TRANSITIONS

Assignment Project Exam Help

- ▶ <https://powcoder.com>
- ▶ Remember that ε is the empty string

Add WeChat powcoder

EXAMPLE




- ▶ From A, with a 0:
- ▶ From A, with a 1:
- ▶ From B, with ϵ :
- ▶ From E, with ϵ :

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE




- ▶ From A, with a 0: B
- ▶ From A, with a 1: E
- ▶ From B, with ε : C
- ▶ From E, with ε : C

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE




- ▶ From A, with a 0: B
- ▶ From A, with a 1: E
- ▶ From B, with ϵ :
- ▶ From E, with ϵ :

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE




- ▶ From A, with a 0: B
- ▶ From A, with a 1: E
- ▶ From B, with ε : D
- ▶ From E, with ε :

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE




- ▶ From A, with a 0: B
- ▶ From A, with a 1: E
- ▶ From B, with ϵ : D
- ▶ From E, with ϵ : B and C

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE




- ▶ From A, with a 0: B
- ▶ From A, with a 1: E
- ▶ From B, with ϵ : D
- ▶ From E, with ϵ : B and C

So from A with 0, we can potentially also reach D without needing to scan more input.

(Epsilon closure (*later in the lecture*))

EXAMPLE



► From A, with a 0: B
 ► From A, with a 1: E

► From B, with ϵ : D

► From E, with ϵ : B and C

	0	1	ϵ
A	{E}	{B}	\emptyset
B	\emptyset	{C}	{D}
C	\emptyset	{D}	\emptyset
D	\emptyset	\emptyset	\emptyset
E	{F}	\emptyset	{B, C}
F	{D}	\emptyset	\emptyset

So from A with 0, we can potentially also reach D without needing to scan more input.

(Epsilon closure (later in the lecture))

FORMAL DEFINITION OF NFA

Definition: A non-deterministic finite automaton is a 5-tuple

- $(Q, \Sigma, \delta, q_0, F)$, where:
- Q is a finite set called the states,
 - Σ is a finite set called the alphabet,
 - $\delta: Q \times \Sigma \rightarrow \mathcal{P}(Q)$ is the transition function*,
 - q_0 is the start state, and
 - $F \subseteq Q$ is the set of accept states.

*Recall:

- if $A = \{a, b, c\}$ then
 $\mathcal{P}(A) = \{\emptyset, \{a\}, \{b\}, \{c\}, \{a, b\}, \{a, c\}, \{b, c\}, \{a, b, c\}\}$
- $ab\varepsilon = a\varepsilon b = \varepsilon ab = ab$
- $\Sigma_\varepsilon = \Sigma \cup \{\varepsilon\}$

TRANSITION FUNCTION FOR NFA


Assignment Project Exam Help

- $\delta(q, a)$ is a set of states which is the union of all the states which can be reached from q on a .
- This could be the empty set \emptyset

Add WeChat powcoder

- Note: when following epsilon transitions, you can also remain in the same state (as if $q \in \delta(q, \epsilon)$ for all $q \in Q$)

EXAMPLE



<https://powcoder.com>


$\delta : Q \times \Sigma_{\epsilon} \rightarrow \mathcal{P}(Q)$ is given by:

	0	1	ϵ
q_1	$\{q_1, q_2\}$	$\{q_1\}$	\emptyset
q_2	$\{q_1, q_3\}$	\emptyset	$\{q_1\}$
q_3	\emptyset	$\{q_4\}$	\emptyset
q_4	$\{q_4\}$	$\{q_4\}$	\emptyset

- $Q = \{q_1, q_2, q_3, q_4\}$
- $\Sigma = ?$
- The start state is q_1
- The set of accept states is $\{q_4\}$

Some strings where N reaches the accept state: 01, 0000001

EXAMPLE



<https://powcoder.com>


$\delta : Q \times \Sigma_{\varepsilon} \rightarrow \mathcal{P}(Q)$ is given by:

	0	1	ε
q_1	$\{q_1, q_2\}$	$\{q_1\}$	\emptyset
q_2	$\{q_1, q_3\}$	\emptyset	$\{q_1\}$
q_3	\emptyset	$\{q_4\}$	\emptyset
q_4	$\{q_4\}$	$\{q_4\}$	\emptyset

- ▶ $Q = \{q_1, q_2, q_3, q_4\}$
- ▶ $\Sigma = \{0, 1\}$
- ▶ The start state is q_1
- ▶ The set of accept states is $\{q_4\}$

Some strings where N reaches the accept state: 01, 0000001

NFA COMPUTATION : PARALLELISM



Several choices that exist can be seen as parallel computation or as a tree of possibilities


<https://powcoder.com>

Read 1 - - - -

Read 0 - - - -

Read 0 - - - -

Read 1 - - - -



LANGUAGE OF AN NFA

Assignment Project Exam Help

- ▶ A string w is accepted by an NFA if at least one sequence of transitions starting from q_0 on input w leads to an accept state

<https://powcoder.com>

- ▶ i.e. if we are in at least one accept state, after reading all the input
- ▶ The language recognised by an NFA (i.e. the set of strings it accepts) is called regular

Add WeChat powcoder


EXAMPLES OF NFA (1)

Assignment Project Exam Help

L_1 : Strings over $\{a, b, c\}$ ending with an a

<https://powcoder.com>

a, b, c




Add WeChat powcoder

EXAMPLES OF NFA (2)

Assignment Project Exam Help

L_2 : Strings over $\{a, b, c\}$ composed of at least one repetition of the substring ab

<https://powcoder.com>



Add WeChat powcoder

EXAMPLES OF NFA (3)

Assignment Project Exam Help

L_3 : Strings over $\{0, 1\}$ with a 1 in the third last position

<https://powcoder.com>



OUTLINE

- ▶ Non-Deterministic Finite Automata (NFA)
 - ▶ Non-determinism
 - ▶ ϵ -transitions

- ▶ <https://powcoder.com>

- ▶ Minimal DFA

- ▶ Regular Languages and Closure properties
- ▶ Regular Expressions (introduction)

EQUIVALENCE OF NFAS AND DFAS

Assignment Project Exam Help

- ▶ DFA: exactly one transition per input from each state
- ▶ NFA: zero, one or several possible transitions, ϵ -transitions
- ▶ \Rightarrow any DFA is a NFA (NFA more general)

<https://powcoder.com>

But are there languages that are recognised by some NFA but not by a DFA?

Add WeChat powcoder

No. If a language is recognised by a NFA then we can always devise a DFA which recognises it.

Theorem: Every NFA has an equivalent DFA

REGULAR LANGUAGES AND FINITE AUTOMATA

Theorem (Kleene 56):

The class of regular languages is exactly the same as the class of languages accepted by DFAs

Theorem (Rabin & Scott 59):

The class of regular languages is exactly the same as the class of languages accepted by NFAs

\Rightarrow Any regular language must be accepted by at least one DFA and at least one NFA

Can we transform NFAs into DFAs?

TRANSFORMING A NFA INTO A DFA: INTRO

Key idea: Read the NFA as if it was a DFA and keep in memory the possible set of states it could be in for each given input (i.e. similar to the levels of the decision tree example.)

Each state of the new DFA is a subset of the NFA states (subset construction)

When we transition from a state X , with a given input symbol i , we must also consider all the ways in which we could follow epsilon transitions before and after reading i

- i.e. We transition to the set of states reachable via paths using any number of ϵ transitions before and/or after i

EPSILON-CLOSURE

The *Epsilon-closure* of a state q , denoted $E(q)$, is the set of all states which can be reached from q by 0 or more ε -transitions

- $q \in E(q)$
- If $p \in E(q)$ and there is an ε -transition from p to r , then $r \in E(q)$

<https://powcoder.com>

Add WeChat powcoder


EPSILON-CLOSURE

The *Epsilon-closure* of a state q , denoted $E(q)$, is the set of all states which can be reached from q by 0 or more ε -transitions.

- $q \in E(q)$
- If $p \in E(q)$ and there is an ε -transition from p to r , then $r \in E(q)$

<https://powcoder.com>

Example:



► $E(A) =$

► $E(B) =$

► $E(E) =$

Add WeChat powcoder


EPSILON-CLOSURE

The *Epsilon-closure* of a state q , denoted $E(q)$, is the set of all states which can be reached from q by 0 or more ε -transitions.

- $q \in E(q)$
- If $p \in E(q)$ and there is an ε -transition from p to r , then $r \in E(q)$

<https://powcoder.com>

Example:



► $E(A) = \{A\}$

► $E(B) = \{B, C, D\}$

► $E(E) = \{A, B, C, D, E, F\}$

Add WeChat powcoder


EPSILON-CLOSURE

The *Epsilon-closure* of a state q , denoted $E(q)$, is the set of all states which can be reached from q by 0 or more ϵ -transitions

- $q \in E(q)$
- If $p \in E(q)$ and there is an ϵ -transition from p to r , then $r \in E(q)$

<https://powcoder.com>

Example:



- $E(A) = \{A\}$
- $E(B) = \{B, D\}$
- $E(E) =$


EPSILON-CLOSURE

The *Epsilon-closure* of a state q , denoted $E(q)$, is the set of all states which can be reached from q by 0 or more ε -transitions

- $q \in E(q)$
- If $p \in E(q)$ and there is an ε -transition from p to r , then $r \in E(q)$

<https://powcoder.com>

Example:



- $E(A) = \{A\}$
- $E(B) = \{B, C\}$
- $E(E) = \{B, C, D, E\}$

EPSILON-CLOSURE FOR SETS

Assignment Project Exam Help


The Epsilon-closure of a set of states S , denoted $E(S)$, is the union of the Epsilon-closure of each state

<https://powcoder.com>

$$E(S \cup T) = E(S) \cup E(T)$$

Add WeChat powcoder

CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	$\{q_4\}$	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$E(\{q_1\}) =$$

$$E(\{q_2\}) =$$


$$E(\{q_3\}) =$$

$$E(\{q_4\}) =$$

$$E(\{q_5\}) =$$

$$E(\{q_1, q_3, q_5\}) =$$


CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	q_4	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$\begin{aligned}
 E(\{q_1\}) &= \{q_1, q_2\} \\
 E(\{q_2\}) &= \\
 E(\{q_3\}) &= \\
 E(\{q_4\}) &= \\
 E(\{q_5\}) &= \\
 E(\{q_1, q_3, q_5\}) &=
 \end{aligned}$$

CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	$\{q_4\}$	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$E(\{q_1\}) = \{q_1, q_2\}$$

$$E(\{q_2\}) = \{q_2\}$$


$$E(\{q_3\}) =$$

$$E(\{q_4\}) =$$

$$E(\{q_5\}) =$$

$$E(\{q_1, q_3, q_5\}) =$$


CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	q_4	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$\begin{aligned}
 E(\{q_1\}) &= \{q_1, q_2\} \\
 E(\{q_2\}) &= \{q_2\} \\
 E(\{q_3\}) &= \{q_2, q_3\} \\
 E(\{q_4\}) &= \{q_4, q_5\} \\
 E(\{q_5\}) &= \{q_5\} \\
 E(\{q_1, q_3, q_5\}) &=
 \end{aligned}$$


CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	$\{q_4\}$	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$\begin{aligned}
 E(\{q_1\}) &= \{q_1, q_2\} \\
 E(\{q_2\}) &= \{q_2\} \\
 E(\{q_3\}) &= \{q_2, q_3\} \\
 E(\{q_4\}) &= \{q_2, q_3, q_4, q_5\} \\
 E(\{q_5\}) &= \{q_4, q_5\} \\
 E(\{q_1, q_3, q_5\}) &=
 \end{aligned}$$


CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	q_4	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$\begin{aligned}
 E(\{q_1\}) &= \{q_1, q_2\} \\
 E(\{q_2\}) &= \{q_2\} \\
 E(\{q_3\}) &= \{q_2, q_3\} \\
 E(\{q_4\}) &= \{q_3, q_4, q_5\} \\
 E(\{q_5\}) &= \{q_5\} \\
 E(\{q_1, q_3, q_5\}) &=
 \end{aligned}$$

CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	q_4	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$E(\{q_1\}) = \{q_1, q_2\}$$

$$E(\{q_2\}) = \{q_2\}$$


$$E(\{q_3\}) = \{q_2, q_3\}$$

$$E(\{q_4\}) = \{q_2, q_3, q_4, q_5\}$$

$$E(\{q_5\}) = \{q_5\}$$

$$\begin{aligned}
 &E(\{q_1, q_3, q_5\}) \\
 &= E(\{q_1\}) \cup E(\{q_3\}) \cup E(\{q_5\}) \\
 &=
 \end{aligned}$$

CONSTRUCTING EPSILON-CLOSURES



	a	b	ϵ
q_1	\emptyset	\emptyset	$\{q_2\}$
q_2	$\{q_3, q_4\}$	\emptyset	\emptyset
q_3	\emptyset	$\{q_4\}$	$\{q_2\}$
q_4	$\{q_5\}$	\emptyset	$\{q_3, q_5\}$
q_5	\emptyset	\emptyset	\emptyset

$$E(\{q_1\}) = \{q_1, q_2\}$$

$$E(\{q_2\}) = \{q_2\}$$

$$E(\{q_3\}) = \{q_2, q_3\}$$

$$E(\{q_4\}) = \{q_2, q_3, q_4, q_5\}$$

$$E(\{q_5\}) = \{q_5\}$$

$$\begin{aligned}
 &E(\{q_1, q_3, q_5\}) \\
 &= E(\{q_1\}) \cup E(\{q_3\}) \cup E(\{q_5\}) \\
 &= \{q_1, q_2, q_3, q_5\}
 \end{aligned}$$

NFA TO DFA ALGORITHM

Assignment Project Exam Help

We want to convert a NFA $M = (Q, \Sigma, \delta, q_0, F)$ into an equivalent DFA $M' = (Q', \Sigma, \delta', q'_0, F')$ which recognises $L(N)$

- <https://powcoder.com>
- ▶ $Q' \subseteq 2^Q$
 - ▶ Σ does not change
 - ▶ $\delta'(R, a) = \bigcup_{r \in R} E(\delta(r, a))$
 - ▶ $q'_0 = E(q_0)$
 - ▶ $F' = \{R \in Q' \mid R \text{ contains an accept state of } N\}$
- Add WeChat powcoder


NFA TO DFA ALGORITHM

We want to convert a NFA $N = (Q, \Sigma, \delta, q_0, F)$ into an equivalent DFA $M = (Q', \Sigma, \delta', q_0', F')$ which recognises $L(N)$

Algorithm

1. DFA start state is $E(q)$, where q is the NFA start state
2. If $R \subseteq \mathcal{P}(Q)$ is a DFA state and $a \in \Sigma$ then construct the following DFA state as a DFA table entry in either 2 ways:
 - $\delta'(R, a) = E(\cup_{r \in R} \delta(r, a))$ closure of union
 - $\delta'(R, a) = \cup_{r \in R} E(\delta(r, a))$ union of closures
3. A DFA state is accepting if any of its elements are an NFA accept state.

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) =$		

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$		

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	
$\{q_2, q_3, q_4, q_5\}$		

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	\emptyset
$\{q_2, q_3, q_4, q_5\}$		

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	\emptyset
$\frac{\{q_2, q_3, q_4, q_5\}}{\emptyset}$		

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	\emptyset
$\{q_2, q_3, q_4, q_5\}$	$\{q_2, q_3, q_4, q_5\}$	\emptyset
\emptyset		

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	\emptyset
$\{q_2, q_3, q_4, q_5\}$	$\{q_2, q_3, q_4, q_5\}$	$\{q_2, q_3, q_4, q_5\}$
\emptyset		

Resulting DFA:

FROM NFA TO DFA: EXAMPLE




Transition table:

	a	b
$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	\emptyset
$\{q_2, q_3, q_4, q_5\}$	$\{q_2, q_3, q_4, q_5\}$	$\{q_2, q_3, q_4, q_5\}$
\emptyset	\emptyset	\emptyset

Resulting DFA:


FROM NFA TO DFA: EXAMPLE




Transition table:

		a	b
A	$E(start) = \{q_1, q_2\}$	$\{q_2, q_3, q_4, q_5\}$	\emptyset
B	$\{q_2, q_3, q_4, q_5\}$	$\{q_2, q_3, q_4, q_5\}$	$\{q_2, q_3, q_4, q_5\}$
C	\emptyset	\emptyset	\emptyset

Resulting DFA:



FROM NFA TO DFA: EXAMPLE




<https://powcoder.com>

Transition table:

Add WeChat powcod ^a ^b		

FROM NFA TO DFA: EXAMPLE




<https://powcoder.com>

Transition table:

$E(struct) =$	a	b

FROM NFA TO DFA: EXAMPLE

Assignment Project Exam Help




<https://powcoder.com>

Transition table:

	a	b
$\delta(q_1, a) = \{q_1, q_2\}$		

FROM NFA TO DFA: EXAMPLE




<https://powcoder.com>

Transition table:

$E(struct) = \{q_1, q_2\}$	$\overset{a}{\{q_1, q_2, q_3\}}$	$\overset{b}{\text{powcod}}$
----------------------------	----------------------------------	------------------------------

FROM NFA TO DFA: EXAMPLE




<https://powcoder.com>

Transition table:

	a	b
$\delta(q_1, a) = \{q_1, q_2\}$	$\{q_1, q_2, q_3\}$	
$\{q_1, q_2, q_3\}$		

FROM NFA TO DFA: EXAMPLE




<https://powcoder.com>

Transition table:

$E(stu, tu) = \{q_1, q_2\}$	$\overset{a}{\{q_1, q_2, q_3\}}$	$\overset{b}{\{q_1, q_2\}}$
$\{q_1, q_2, q_3\}$		

FROM NFA TO DFA: EXAMPLE

Assignment Project Exam Help




<https://powcoder.com>

Transition table:

	a	b
$\delta(q_1, a) = \{q_1, q_2\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2\}$
$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_3\}$	

FROM NFA TO DFA: EXAMPLE

Assignment Project Exam Help




<https://powcoder.com>

Transition table:

	a	b
$\delta(q_1, a) = \{q_1, q_2\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2\}$
$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_4\}$

FROM NFA TO DFA: EXAMPLE

Assignment Project Exam Help




<https://powcoder.com>

Transition table:

	a	b
$\delta(q_1, a) = \{q_1, q_2\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2\}$
$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_4\}$
<u>$\{q_1, q_2, q_4\}$</u>		

FROM NFA TO DFA: EXAMPLE

Assignment Project Exam Help




<https://powcoder.com>

Transition table:

	a	b
$\delta(q_1, a) = \{q_1, q_2\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2\}$
$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_4\}$
<u>$\{q_1, q_2, q_4\}$</u>	$\{q_1, q_2, q_3, q_4\}$	

FROM NFA TO DFA: EXAMPLE

Assignment Project Exam Help




<https://powcoder.com>

Transition table:

	a	b
$\overline{E}(st, rt) = \{q_1, q_2\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2\}$
$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_4\}$
$\{q_1, q_2, q_4\}$	$\{q_1, q_2, q_3, q_4\}$	
$\{q_1, q_2, q_3, q_4\}$		

FROM NFA TO DFA: EXAMPLE

Assignment Project Exam Help




<https://powcoder.com>

Transition table:

	a	b
$\overline{E}(st, rt) = \{q_1, q_2\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2\}$
$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_4\}$
$\{q_1, q_2, q_4\}$	$\{q_1, q_2, q_3, q_4\}$	$\{q_1, q_2, q_4\}$
$\{q_1, q_2, q_3, q_4\}$		

FROM NFA TO DFA: EXAMPLE




<https://powcoder.com>

Transition table:

Add WeChat powered		
$E(struct) = \{q_1, q_2\}$	$\overset{a}{\{q_1, q_2, q_3\}}$	$\overset{b}{\{q_1, q_2\}}$
$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_4\}$
$\{q_1, q_2, q_4\}$	$\{q_1, q_2, q_3, q_4\}$	$\{q_1, q_2, q_4\}$
$\{q_1, q_2, q_3, q_4\}$	$\{q_1, q_2, q_3, q_4\}$	$\{q_1, q_2, q_4\}$

FROM NFA TO DFA: EXAMPLE



<https://powcoder.com>

Transition table:

	a	b
A	$\{q_1, q_2\}$	$\{q_1, q_2\}$
B	$\{q_1, q_2, q_3\}$	$\{q_1, q_2, q_4\}$
C	$\{q_1, q_2, q_4\}$	$\{q_1, q_2, q_4\}$
D	$\{q_1, q_2, q_3, q_4\}$	$\{q_1, q_2, q_4\}$

OUTLINE

Assignment Project Exam Help

- ▶ Non-Deterministic Finite Automata (NFA)
 - ▶ Non-determinism
 - ▶ ϵ -transitions

- ▶ <https://powcoder.com>

- ▶ **Minimal DFA**

Add WeChat powcoder

- ▶ Regular Languages and Closure properties
- ▶ Regular Expressions (introduction)

MINIMISATION OF DFA (IDEA)

Every DFA has a unique equivalent *minimal DFA*

Assignment Project Exam Help

Definition: Two states s and t are *equivalent* if: for any string, the path from s leads to an accepting state if and only if the path from t does.

<https://powcoder.com>

To reduce an automaton, find all non-equivalent states:

1. If s is accepting and t non accepting, then they are not equivalent
2. If, with input x , there is a transition from s to s' and from t to t' and we know that s' and t' are not equivalent, then s and t are not equivalent

Then merge equivalent states.

MINIMISATION OF DFA: TABLE-FILLING ALGORITHM


1. Examine all pairs of states and find all pairs s, t that are NOT equivalent, i.e. satisfying either of:
 - 1.1 s is accepting and t is not or vice versa
 - 1.2 with the same input x , s goes to a state s' and t to a state t' and you have already proven that s' and t' are NOT equivalent
2. When no further non-equivalence can be proven, then the remaining pairs can be merged respectively into one state.

Theorems

1. If two states are not distinguished by the table-filling algorithm, then the states are equivalent
2. The equivalence of states is transitive

EXAMPLE

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder

THE TABLE OF STATE NON-EQUIVALENCES

<i>A</i>	-	-	-	-	-
<i>B</i>		-	-	-	-
<i>C</i>					
<i>D</i>				-	-
<i>E</i>					-
	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>

Assignment Project Exam Help

<https://powcoder.com>

1. Cross out all the pairs of accept/non-accept states. *A*, *E* are non-accepting and all the others are.

Add WeChat powcoder

THE TABLE OF STATE NON-EQUIVALENCES

<i>A</i>	-	-	-	-	-
<i>B</i>	x	-	-	-	-
<i>C</i>	x	-	-	-	-
<i>D</i>	x			-	-
<i>E</i>		x	x	x	-
	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>

<https://powcoder.com>

1. Cross out all the pairs of accept/non-accept states. *A*, *E* are non-accepting and all the others are.
2. Look at each remaining pair.

Add WeChat powcoder

THE TABLE OF STATE NON-EQUIVALENCES

<i>A</i>	-	-	-	-	-
<i>B</i>	x	-	-	-	-
<i>C</i>	x	-	-	-	-
<i>D</i>	x			-	-
<i>E</i>	x	x	x	x	-
	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>

Assignment Project Exam Help

<https://powcoder.com>

1. Cross out all the pairs of accept/non-accept states. *A*, *E* are non-accepting and all the others are.

2. Look at each remaining pair.

► $\delta(A, 0) = A$ and $\delta(E, 0) = C$, but $A \neq C$, therefore $A \not\equiv E$

Add WeChat powcoder

THE TABLE OF STATE NON-EQUIVALENCES

<i>A</i>	-	-	-	-	-
<i>B</i>	x	-	-	-	-
<i>C</i>	x	x	-	-	-
<i>D</i>	x			-	-
<i>E</i>	x	x	x	x	-
	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>

Assignment Project Exam Help

<https://powcoder.com>

1. Cross out all the pairs of accept/non-accept states. *A*, *E* are non-accepting and all the others are.

2. Look at each remaining pair.

- ▶ $\delta(A, 0) = A$ and $\delta(E, 0) = C$, but $A \neq C$, therefore $A \not\equiv E$
- ▶ $\delta(B, 0) = D$ and $\delta(C, 0) = E$, but $D \neq E$, therefore $B \not\equiv C$

Add WeChat powcoder

THE TABLE OF STATE NON-EQUIVALENCES

A	-	-	-	-	-
B	x	-	-	-	-
C	x	x	-	-	-
D	x			-	-
E	x	x	x	x	-
	A	B	C	D	E

1. Cross out all the pairs of accept/non-accept states. A , E are non-accepting and all the others are.
2. Look at each remaining pair.

- $\delta(A, 0) = A$ and $\delta(E, 0) = C$, but $A \not\equiv C$, therefore $A \not\equiv E$
- $\delta(B, 0) = D$ and $\delta(C, 0) = E$, but $D \not\equiv E$, therefore $B \not\equiv C$
- We can't find a reason to claim $B \not\equiv D$ yet

THE TABLE OF STATE NON-EQUIVALENCES

<i>A</i>	-	-	-	-	-
<i>B</i>	x	-	-	-	-
<i>C</i>	x	x	-	-	-
<i>D</i>	x		x	-	-
<i>E</i>	x	x	x	x	-
	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>

<https://powcoder.com>

1. Cross out all the pairs of accept/non-accept states. *A*, *E* are non-accepting and all the others are.

2. Look at each remaining pair

- ▶ $\delta(A, 0) = A$ and $\delta(E, 0) = C$, but $A \neq C$, therefore $A \not\equiv E$
- ▶ $\delta(B, 0) = D$ and $\delta(C, 0) = E$, but $D \neq E$, therefore $B \not\equiv C$
- ▶ We can't find a reason to claim $B \not\equiv D$ yet
- ▶ $\delta(C, 0) = E$ and $\delta(D, 0) = B$, and $E \neq B$, therefore $C \not\equiv D$

THE TABLE OF STATE NON-EQUIVALENCES

<i>A</i>	-	-	-	-	-
<i>B</i>	x	-	-	-	-
<i>C</i>	x	x	-	-	-
<i>D</i>	x		x	-	-
<i>E</i>	x	x	x	x	-
	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>

<https://powcoder.com>


1. Cross out all the pairs of accept/non-accept states. *A*, *E* are non-accepting and all the others are.
2. Look at each remaining pair
 - ▶ $\delta(A, 0) = A$ and $\delta(E, 0) = C$, but $A \neq C$, therefore $A \not\equiv E$
 - ▶ $\delta(B, 0) = D$ and $\delta(C, 0) = E$, but $D \neq E$, therefore $B \not\equiv C$
 - ▶ We can't find a reason to claim $B \not\equiv D$ yet
 - ▶ $\delta(C, 0) = E$ and $\delta(D, 0) = B$, and $E \neq B$, therefore $C \not\equiv D$
3. Repeat step 2 until no changes are found

Add WeChat powcoder

MERGING EQUIVALENT STATES

Theorem: If two states are not distinguished by the table-filling algorithm, then that pair of states are equivalent.

We can merge together equivalent states. The minimal DFA for the example becomes:



RESULTING DFA

Assignment Project Exam Help

- ▶ <https://powcoder.com> is minimal
- ▶ is unique

Add WeChat powcoder

OUTLINE

Assignment Project Exam Help

- ▶ Non-Deterministic Finite Automata (NFA)
 - ▶ Non-determinism
 - ▶ ϵ -transitions

- ▶ <https://powcoder.com>

- ▶ Minimal DFA

Add WeChat powcoder

- ▶ Regular Languages and Closure properties
- ▶ Regular Expressions (introduction)

REVISION

Definition:

A language is *regular* if and only if there exists a finite automaton which recognises it.

Minimal examples:

- ▶ \emptyset is a regular language
- ▶ $\{\epsilon\}$ is a regular language
- ▶ For all $a \in \Sigma$, the set $\{a\}$ is a regular language

Think about how to make a DFA for each of these languages

CLOSURE PROPERTIES OF REGULAR LANGUAGES

Let L_1 and L_2 be regular languages.

Assignment Project Exam Help

The *regular operations* are defined as follows:

- ▶ Union: $L_1 \cup L_2 = \{w | w \in L_1 \text{ or } w \in L_2\}$
- ▶ Concatenation: $L_1 L_2 = \{w_1 w_2 | w_1 \in L_1 \text{ and } w_2 \in L_2\}$
- ▶ Star: $L^* = \{w_1 w_2 \dots w_k | k \geq 0 \text{ and } w_i \in L \text{ for } i = 1, \dots, k\}$


Theorems

Add WeChat powcoder

- ▶ The union of two regular languages is regular
- ▶ The concatenation of two regular languages is regular
- ▶ The star closure of a regular language is regular

UNION OF TWO REGULAR LANGUAGES

If L_1 and L_2 are regular, then finite automata M_1 and M_2 exist which recognise them. we can construct an automaton M which recognises $L_1 \cup L_2 = \{w \mid w \in L_1 \text{ or } w \in L_2\}$



UNION OF TWO REGULAR LANGUAGES

Let $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$, $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$

Let $M = (Q, \Sigma, \delta, q_0, F)$ where:

- $Q = \{q_0\} \cup Q_1 \cup Q_2$
- q_0 is the new start state
- Transition function δ defined for any $q \in Q$ and any $a \in \Sigma_\epsilon$

<https://powcoder.com>

Add WeChat powcoder

$$\delta(q, a) = \begin{cases} \delta_1(q, a) & \text{if } q \in Q_1 \\ \delta_2(q, a) & \text{if } q \in Q_2 \\ \{q_1, q_2\} & \text{if } q = q_0 \text{ and } a = \epsilon \\ \emptyset & \text{if } q = q_0 \text{ and } a \neq \epsilon \end{cases}$$

- Accepting set $F = F_1 \cup F_2$

M accepts if and only if M_1 or M_2 does

i.e. $L(M) = \{w | w \in L_1 \text{ or } w \in L_2\} = L_1 \cup L_2$

CONCATENATION OF TWO REGULAR LANGUAGES


If L_1 and L_2 are regular, then finite automata M_1 and M_2 exist which recognise them.

Assignment Project Exam Help

we can construct an automaton M which recognises

$L_1 L_2 = \{w_1 w_2 \mid w_1 \in L_1 \text{ and } w_2 \in L_2\}$:

<https://powcoder.com>



Note that the accept states of M_1 are *not* accept states in M

CONCATENATION OF TWO REGULAR LANGUAGES

Let $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$, $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$

Let $M = (Q, \Sigma, \delta, q, F)$ where:

- $Q = Q_1 \cup Q_2$
- q_1 is start state (same as M_1)
- Transition function δ defined for any $q \in Q$ and any $a \in \Sigma_\epsilon$

$$\delta(q, a) = \begin{cases} \delta_1(q, a) & \text{if } q \in Q_1 \text{ and } q \notin F_1 \\ \delta_1(q, a) & \text{if } q \in F_1 \text{ and } a \neq \epsilon \\ \delta_1(q, a) \cup \{q_2\} & \text{if } q \in F_1 \text{ and } a = \epsilon \\ \delta_2(q, a) & \text{if } q \in Q_2 \end{cases}$$

- Accepting set $F = F_2$ (same as M_2)

$$L(M) = \{w_1 w_2 \mid w_1 \in L_1 \text{ and } w_2 \in L_2\} = L_1 L_2$$

STAR CLOSURE OF A REGULAR LANGUAGE


If L is regular, then a finite automaton M_1 exists which recognises

Assignment Project Exam Help

we can construct an automaton M which recognises

$L^* = \{w_1 w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in L \text{ for } i = 1, \dots, k\}$:

<https://powcoder.com>



e.g. if $L = \{a, b\}$ then this automaton recognises

$\{\epsilon, a, b, aa, ab, bb, aaa, \dots\} = L^*$

STAR CLOSURE OF A REGULAR LANGUAGE

Let $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$

Let $M = (Q, \Sigma, \delta, q_0, F)$ where:

- $Q = Q_1 \cup \{q_0\}$
- q_0 is the new start state
- Transition function δ defined for any $q \in Q$ and any $a \in \Sigma_\epsilon$

<https://powcoder.com>

Add WeChat powcoder

$$\delta(q, a) = \begin{cases} \delta_1(q, a) & \text{if } q \in Q_1 \text{ and } q \notin F_1 \\ \delta_1(q, a) & \text{if } q \in F_1 \text{ and } a \neq \epsilon \\ \delta_1(q, a) \cup \{q_0\} & \text{if } q \in F_1 \text{ and } a = \epsilon \\ \{q_0\} & \text{if } q = q_0 \text{ and } a = \epsilon \\ \emptyset & \text{if } q = q_0 \text{ and } a \neq \epsilon \end{cases}$$

- Accepting set $F = F_1 \cup \{q_0\}$

$$L(M) = \{w_1 w_2 \dots w_k \mid k \geq 0 \text{ and } w_i \in L \text{ for } i = 1, \dots, k\} = L^*$$

EXAMPLE

Assignment Project Exam Help

Construct an NFA recognising the set of strings containing the pattern *aaa* or the strings composed of 0 or more sequences of *ab*

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE FROM CONSTRUCTION TO MINIMAL DFA

Assignment Project Exam Help

Let $\Sigma = \{0, 1\}$

Let L_1 be the language of strings which do not contain consecutive 0's

Let L_2 be the language of strings ending with 0

<https://powcoder.com>

Add WeChat powcoder

COMPLEMENT OF A REGULAR LANGUAGE

Assignment Project Exam Help

The complement of a regular language is regular.
 The complement of a language L is $\{x|x \notin L\}$

Example

Let $L_1 = \{x|x \text{ contains an odd number of } a\text{'s}\}$

Then the complement of L_1 is $L_2 = \{x|x \notin L_1\} = \{x|x \text{ contains an even number of } a\text{'s}\}$

Add WeChat powcoder

You will explore how to construct a suitable automata in this week's tutorial

INTERSECTION OF A REGULAR LANGUAGE


If L_1 and L_2 are regular, then $L_1 \cap L_2$ is regular.

We can use the cross product technique to build the DFA.

Example:

$L_1 = \{x \mid x \in \{a, b\}^* \text{ and } x \text{ contains an odd number of } a\text{'s}\}$

$L_2 = \{x \mid x \in \{a, b\}^* \text{ and } x \text{ contains an odd number of } b\text{'s}\}$



CROSS-PRODUCT OF DFAs

Let $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$, $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$ be two DFA

Let $M = (Q, \Sigma, \delta, q_0, F)$ where:

- ▶ $Q = Q_1 \times Q_2$ (i.e. all ordered pairs (u, v) such that $u \in Q_1$ and $v \in Q_2$)
- ▶ The start state (q_1, q_2) is the pair of start states from Q_1 and Q_2
- ▶ The transition function δ is defined as:

$$\delta((u, v), x) = (\delta_1(u, x), \delta_2(v, x))$$


- ▶ Accepting set $F = \{(u, v) | u \in F_1 \text{ and } v \in F_2\}$

Note that M is also deterministic

EXAMPLE CROSS-PRODUCT FOR INTERSECTION

Example:


$L_1 = \{x \mid x \in \{a, b\}^* \text{ and } x \text{ contains an odd number of } a\text{'s}\}$
 $L_2 = \{x \mid x \in \{a, b\}^* \text{ and } x \text{ contains an odd number of } b\text{'s}\}$



CROSS-PRODUCT CAN BE USED FOR UNION

Example:

$L_1 = \{x \mid x \in \{a, b\}^* \text{ and } x \text{ contains an odd number of } a\text{'s}\}$
 $L_2 = \{x \mid x \in \{a, b\}^* \text{ and } x \text{ contains an odd number of } b\text{'s}\}$



OUTLINE

Assignment Project Exam Help

- ▶ Non-Deterministic Finite Automata (NFA)
 - ▶ Non-determinism
 - ▶ ϵ -transitions

- ▶ <https://powcoder.com>

- ▶ Minimal DFA

Add WeChat powcoder

- ▶ Regular Languages and Closure properties
- ▶ Regular Expressions (introduction)

REGULAR EXPRESSIONS

In arithmetic we use operations to build up expressions, describing numbers such as

$$(5 + 3) \times 4 \text{ (value is 32)}$$

$$4/2 - 1 \text{ (value is 1)}$$

<https://powcoder.com>

With regular languages, we use regular operations to build up expressions describing languages such as

Add WeChat powcoder

$(0 \mid 1)0^*$ (strings starting with 0 or 1, then any number of 0's)

$(ab)^*a$ (any number of ab 's, followed by a)

REGULAR EXPRESSIONS VS FINITE AUTOMATA

- ▶ RegEx: algebraic description of the strings in a language
- ▶ FA: a machine-like description

- ▶ RegEx serve as the input language for many systems which process strings

- ▶ Search commands

- ▶ UNIX grep

- ▶ Web browsers

- ▶ Text editors

- ▶ Text formatting systems

- ▶ ...

- ▶ Lexical-analyser generators (Lex, Flex, etc.)

- ▶ Like FA, RegEx define exactly the class of *regular languages*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

DEFINITION OF A REGULAR EXPRESSION (REGEX)

- Basic expressions and the language they describe

- If a is any symbol of the input alphabet, then a is a RegEx and its language $L(a) = \{a\}$

- ε is a RegEx and $L(\varepsilon) = \{\varepsilon\}$

- \emptyset is a RegEx and $L(\emptyset) = \emptyset$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

DEFINITION OF A REGULAR EXPRESSION (REGEX)

- ▶ Basic expressions and the language they describe
 - ▶ If a is any symbol of the input alphabet, then a is a RegEx and its language $L(a) = \{a\}$
 - ▶ ε is a RegEx and $L(\varepsilon) = \{\varepsilon\}$
 - ▶ \emptyset is a RegEx and $L(\emptyset) = \emptyset$
- ▶ Operators on RegEx. If R and S are RegEx, then
 - ▶ Union: $R \mid S$ (sometimes denoted $R + S$) is a RegEx
 - ▶ Concatenation: RS (sometimes denoted $R \circ S$) is a RegEx
 - ▶ Star Closure: R^* is a RegEx

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

DEFINITION OF A REGULAR EXPRESSION (REGEX)

- ▶ Basic expressions and the language they describe
 - ▶ If a is any symbol of the input alphabet, then a is a RegEx and its language $L(a) = \{a\}$
 - ▶ ε is a RegEx and $L(\varepsilon) = \{\varepsilon\}$
 - ▶ \emptyset is a RegEx and $L(\emptyset) = \emptyset$
- ▶ Operators on RegEx. If R and S are RegEx, then
 - ▶ Union: $R \mid S$ (sometimes denoted $R + S$) is a RegEx
 - ▶ Concatenation: RS (sometimes denoted $R \circ S$) is a RegEx
 - ▶ Star Closure: R^* is a RegEx
- ▶ Precedence of operators: $^*, \circ, \mid$ to avoid excessive parentheses
 - ▶ e.g. $R \mid ST^* = (R \mid (S(T^*)))$, similar to how $8 + 21/3^2 = (8 + (21/(3^2)))$
 - ▶ Use parentheses to change the order of operations

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

LANGUAGE OF A REGULAR EXPRESSION

Assignment Project Exam Help

Let x, y be symbols from the input alphabet.

$$L(x) = \{x\}$$

$$L(\epsilon) = \{\epsilon\}$$

$$L(\emptyset) = \{\emptyset\}$$

Add WeChat powcoder

$$L(x \mid y) = \{x, y\}$$

$$L(x^*) = \{\epsilon, x, xx, xxx, \dots\}$$

$$L(xy) = \{xy\}$$

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

Assignment Project Exam Help

$L(a \mid b) =$

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

Assignment Project Exam Help

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) =$$

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

Assignment Project Exam Help

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$L((a \mid b) \mid c) =$$

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$L((a \mid b) \mid c) = L(a \mid b) \cup L(c)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$\begin{aligned} L((a \mid b) \mid c) &= L(a \mid b) \cup L(c) \\ &= \{a, b\} \cup \{c\} \\ &= \end{aligned}$$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$\begin{aligned} L((a \mid b) \mid c) &= L(a \mid b) \cup L(c) \\ &= \{a, b\} \cup \{c\} \\ &= \{a, b, c\} \end{aligned}$$

$$L(a \mid (b \mid c)) = L(a) \cup L(b \mid c)$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$\begin{aligned} L((a \mid b) \mid c) &= L(a \mid b) \cup L(c) \\ &= \{a, b\} \cup \{c\} \\ &= \{a, b, c\} \end{aligned}$$

$$\begin{aligned} L(a \mid (b \mid c)) &= L(a) \cup L(b \mid c) \\ &= \{a\} \cup \{b, c\} \\ &= \{a, b, c\} \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$\begin{aligned} L((a \mid b) \mid c) &= L(a \mid b) \cup L(c) \\ &= \{a, b\} \cup \{c\} \\ &= \{a, b, c\} \end{aligned}$$

$$\begin{aligned} L(a \mid (b \mid c)) &= L(a) \cup L(b \mid c) \\ &= \{a\} \cup \{b, c\} \\ &= \{a, b, c\} \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$\begin{aligned} L((a \mid b) \mid c) &= L(a \mid b) \cup L(c) \\ &= \{a, b\} \cup \{c\} \\ &= \{a, b, c\} \end{aligned}$$

$$\begin{aligned} L(a \mid (b \mid c)) &= L(a) \cup L(b \mid c) \\ &= \{a\} \cup \{b, c\} \\ &= \{a, b, c\} \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: UNION $R \mid S$

Definition: $L(R \mid S) = L(R) \cup L(S)$

$$L(a \mid b) = L(a) \cup L(b) = \{a\} \cup \{b\} = \{a, b\}$$

$$L(b \mid a) = L(b) \cup L(a) = \{b\} \cup \{a\} = \{a, b\} = L(a \mid b)$$

$$\begin{aligned} L((a \mid b) \mid c) &= L(a \mid b) \cup L(c) \\ &= \{a, b\} \cup \{c\} \\ &= \{a, b, c\} \end{aligned}$$

$$\begin{aligned} L(a \mid (b \mid c)) &= L(a) \cup L(b \mid c) \\ &= \{a\} \cup \{b, c\} \\ &= \{a, b, c\} \end{aligned}$$

Because it is associative we can write $L(a \mid b \mid c)$

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$L(ab) =$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) =$$

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$L((ab)\epsilon) = L(ab) = \{ab\}$$

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$L((ab)c) = \{rs \mid r \in L(ab) \text{ and } s \in L(c)\} \\ =$$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$\begin{aligned} L((ab)c) &= \{rs \mid r \in L(ab) \text{ and } s \in L(c)\} \\ &= \{rs \mid r \in \{ab\} \text{ and } s \in \{c\}\} \end{aligned}$$

=

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$\begin{aligned} L((ab)c) &= \{rs \mid r \in L(ab) \text{ and } s \in L(c)\} \\ &= \{rs \mid r \in \{ab\} \text{ and } s \in \{c\}\} \\ &= \{abc\} \end{aligned}$$

$$L(b(Lc)) =$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$\begin{aligned} L((ab)c) &= \{rs \mid r \in L(ab) \text{ and } s \in L(c)\} \\ &= \{rs \mid r \in \{ab\} \text{ and } s \in \{c\}\} \\ &= \{abc\} \end{aligned}$$

$$\begin{aligned} L(a(bc)) &= \{rs \mid r \in L(a) \text{ and } s \in L(bc)\} \\ &= \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$\begin{aligned} L((ab)c) &= \{rs \mid r \in L(ab) \text{ and } s \in L(c)\} \\ &= \{rs \mid r \in \{ab\} \text{ and } s \in \{c\}\} \\ &= \{abc\} \end{aligned}$$

$$\begin{aligned} L(a(bc)) &= \{rs \mid r \in L(a) \text{ and } s \in L(bc)\} \\ &= \{rs \mid r \in \{a\} \text{ and } s \in \{bc\}\} \\ &= \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$\begin{aligned} L((ab)c) &= \{rs \mid r \in L(ab) \text{ and } s \in L(c)\} \\ &= \{rs \mid r \in \{ab\} \text{ and } s \in \{c\}\} \\ &= \{abc\} \end{aligned}$$

$$\begin{aligned} L(a(bc)) &= \{rs \mid r \in L(a) \text{ and } s \in L(bc)\} \\ &= \{rs \mid r \in \{a\} \text{ and } s \in \{bc\}\} \\ &= \{abc\} \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

OPERATORS ON REGEX: CONCATENATION RS

Definition: $L(RS) = \{rs \mid r \in L(R) \text{ and } s \in L(S)\}$

$$L(ab) = \{rs \mid r \in L(a) \text{ and } s \in L(b)\} = \{ab\}$$

$$L(ba) = \{rs \mid r \in L(b) \text{ and } s \in L(a)\} = \{ba\}$$

$$\begin{aligned} L((ab)c) &= \{rs \mid r \in L(ab) \text{ and } s \in L(c)\} \\ &= \{rs \mid r \in \{ab\} \text{ and } s \in \{c\}\} \\ &= \{abc\} \end{aligned}$$

$$\begin{aligned} L(a(bc)) &= \{rs \mid r \in L(a) \text{ and } s \in L(bc)\} \\ &= \{rs \mid r \in \{a\} \text{ and } s \in \{bc\}\} \\ &= \{abc\} \end{aligned}$$

Because it is associative we can write $L(abc)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

$$L((a|b)c) = \{r \mid r \in L(a|b) \text{ and } g \in L(c)\}$$

$$=$$

<https://powcoder.com>

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

$$L((a|b)c) = \{rs \mid r \in L(a|b) \text{ and } s \in L(c)\}$$

$$= \{rs \mid r \in (\{a\} \cup \{b\}) \text{ and } s \in \{c\}\}$$

=

<https://powcoder.com>

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

$$\begin{aligned}
 L((a|b)c) &= \{rs \mid r \in L(a|b) \text{ and } s \in L(c)\} \\
 &= \{rs \mid r \in (\{a\} \cup \{b\}) \text{ and } s \in \{c\}\} \\
 &= \{rs \mid r \in \{a, b\} \text{ and } s \in \{c\}\}
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

$$\begin{aligned}
 L((a|b)c) &= \{rs \mid r \in L(a|b) \text{ and } s \in L(c)\} \\
 &= \{rs \mid r \in (\{a\} \cup \{b\}) \text{ and } s \in \{c\}\} \\
 &= \{rs \mid r \in \{a, b\} \text{ and } s \in \{c\}\}
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

$$\begin{aligned}
 L((a|b)c) &= \{rs \mid r \in L(a|b) \text{ and } s \in L(c)\} \\
 &= \{rs \mid r \in (\{a\} \cup \{b\}) \text{ and } s \in \{c\}\} \\
 &= \{rs \mid r \in \{a, b\} \text{ and } s \in \{c\}\} \\
 &= \{ac, bc\}
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

$$\begin{aligned}
 L((a|b)c) &= \{rs \mid r \in L(a|b) \text{ and } s \in L(c)\} \\
 &= \{rs \mid r \in (\{a\} \cup \{b\}) \text{ and } s \in \{c\}\} \\
 &= \{rs \mid r \in \{a, b\} \text{ and } s \in \{c\}\} \\
 &= \{ac, bc\}
 \end{aligned}$$

<https://powcoder.com>

$$\begin{aligned}
 L((ab|c)) &= L(ab) \cup L(c) \\
 &= \{rs \mid r \in L(a) \text{ and } s \in L(b)\} \cup L(c) \\
 &=
 \end{aligned}$$

Add WeChat powcoder

UNION AND CONCATENATION

Assignment Project Exam Help

$$\begin{aligned}
 L((a|b)c) &= \{rs \mid r \in L(a|b) \text{ and } s \in L(c)\} \\
 &= \{rs \mid r \in (\{a\} \cup \{b\}) \text{ and } s \in \{c\}\} \\
 &= \{rs \mid r \in \{a, b\} \text{ and } s \in \{c\}\}
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}
 L((ab)|c) &= L(ab) \cup L(c) \\
 &= \{rs \mid r \in L(a) \text{ and } s \in L(b)\} \cup L(c) \\
 &= \{rs \mid r \in \{a\} \text{ and } s \in \{b\}\} \cup \{c\} \\
 &=
 \end{aligned}$$

UNION AND CONCATENATION

Assignment Project Exam Help

$$\begin{aligned}
 L((a|b)c) &= \{rs \mid r \in L(a|b) \text{ and } s \in L(c)\} \\
 &= \{rs \mid r \in (\{a\} \cup \{b\}) \text{ and } s \in \{c\}\} \\
 &= \{rs \mid r \in \{a, b\} \text{ and } s \in \{c\}\}
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}
 L((ab)|c) &= L(ab) \cup L(c) \\
 &= \{rs \mid r \in L(a) \text{ and } s \in L(b)\} \cup L(c) \\
 &= \{rs \mid r \in \{a\} \text{ and } s \in \{b\}\} \cup \{c\} \\
 &= \{ab\} \cup \{c\} \\
 &= \{ab, c\}
 \end{aligned}$$

OPERATORS ON REGEX: STAR CLOSURE R^*

R^* means 0 or more occurrences of R
 $L(R^*) = \{\epsilon\} \cup L(R) \cup L(RR) \cup L(RRR) \cup \dots$

$L(0^*) = \{\epsilon, 0, 00, 000, \dots\}$
 $L((01)^*) = \{\epsilon, 01, 0101, 010101, \dots\}$

$L(\emptyset^*) =$

Add WeChat powcoder

OPERATORS ON REGEX: STAR CLOSURE R^*

R^* means 0 or more occurrences of R
 $L(R^*) = \{\varepsilon\} \cup L(R) \cup L(RR) \cup L(RRR) \cup \dots$

$L(0^*) = \{\varepsilon, 0, 00, 000, \dots\}$
 $L((01)^*) = \{\varepsilon, 01, 0101, 010101, \dots\}$

$$L(\emptyset^*) = \{\varepsilon\} \cup L(\emptyset) \cup \dots = \{\varepsilon\}$$

$L(a|b)^* =$

OPERATORS ON REGEX: STAR CLOSURE R^*

R^* means 0 or more occurrences of R
 $L(R^*) = \{\epsilon\} \cup L(R) \cup L(RR) \cup L(RRR) \cup \dots$

$L(0^*) = \{\epsilon, 0, 00, 000, \dots\}$
 $L((01)^*) = \{\epsilon, 01, 0101, 010101, \dots\}$

$L(\emptyset^*) = \{\epsilon\} \cup L(\emptyset) \cup \dots = \{\epsilon\}$

$L(a | bc^*) = \{a, b, bc, bcc, bcce, \dots\}$
 $L(a | (bc)^*) =$

OPERATORS ON REGEX: STAR CLOSURE R^*

R^* means 0 or more occurrences of R
 $L(R^*) = \{\varepsilon\} \cup L(R) \cup L(RR) \cup L(RRR) \cup \dots$

$L(0^*) = \{\varepsilon, 0, 00, 000, \dots\}$
 $L((01)^*) = \{\varepsilon, 01, 0101, 010101, \dots\}$

$$L(\emptyset^*) = \{\varepsilon\} \cup L(\emptyset) \cup \dots = \{\varepsilon\}$$

$L(a | bc^*) = \{a, b, bc, bcbc, bc^2c, \dots\}$
 $L(a | (bc)^*) = \{a, \varepsilon, bc, bcbc, bc^2c, \dots\}$
 $L((a | b)c^*) =$

OPERATORS ON REGEX: STAR CLOSURE R^*

R^* means 0 or more occurrences of R
 $L(R^*) = \{\epsilon\} \cup L(R) \cup L(RR) \cup L(RRR) \cup \dots$

$L(0^*) = \{\epsilon, 0, 00, 000, \dots\}$
 $L((01)^*) = \{\epsilon, 01, 0101, 010101, \dots\}$

$$L(\emptyset^*) = \{\epsilon\} \cup L(\emptyset) \cup \dots = \{\epsilon\}$$

$L(a | bc^*) = \{a, b, bc, bcc, bccc, \dots\}$
 $L(a | (bc)^*) = \{a, \epsilon, bc, bcbc, bc bcbc, \dots\}$
 $L((a | b)c^*) = \{a, b, ac, bc, acc, bcc, accc, bccc, \dots\}$

SOME PROPERTIES OF REGEX

Let R, S, T be regular expressions

► Union properties:

► $R \mid S = S \mid R$ (commutative)

► $R \mid \emptyset = \emptyset \mid R = R$

► $R \mid R = R$

► $(R \mid S) \mid T = R \mid (S \mid T)$ (associative)

► Concatenation properties:

Add WeChat powcoder

► Union and concatenation are *distributive* when combined:

Assignment Project Exam Help

<https://powcoder.com>

SOME PROPERTIES OF REGEX

Let R, S, T be regular expressions

► Union properties:

► $R \mid S = S \mid R$ (commutative)

► $R \mid \emptyset = \emptyset \mid R = R$

► $R \mid R = R$

► $(R \mid S) \mid T = R \mid (S \mid T)$ (associative)

► Concatenation properties:

► $R\emptyset = \emptyset R = \emptyset$

► $R\epsilon = \epsilon R = R$

► $(RS)T = R(ST)$ (associative)

► Union and concatenation are *distributive* when combined:

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SOME PROPERTIES OF REGEX

Let R, S, T be regular expressions

► Union properties:

- $R \mid S = S \mid R$ (commutative)
- $R \mid \emptyset = \emptyset \mid R = R$
- $R \mid R = R$
- $(R \mid S) \mid T = R \mid (S \mid T)$ (associative)

► Concatenation properties:

- $R\emptyset = \emptyset R = \emptyset$
- $R\epsilon = \epsilon R = R$
- $(RS)T = R(ST)$ (associative)

► Union and concatenation are *distributive* when combined:

- $R(S \mid T) = RS \mid RT$
- $(S \mid T)R = SR \mid TR$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SOME PROPERTIES OF REGEX

Let R, S, T be regular expressions

Assignment Project Exam Help

- ▶ Star Closure properties:

▶ $(R^*)^* = R^* = \epsilon$

<https://powcoder.com>

Add WeChat powcoder

SOME PROPERTIES OF REGEX

Let R, S, T be regular expressions

Assignment Project Exam Help

- ▶ Star Closure properties:

$$\begin{aligned} \text{▶ } \emptyset^* &= \varepsilon^* = \varepsilon \\ \text{▶ } R^* &= R^* R^* = (R^*)^* = R \mid R^* \end{aligned}$$

Add WeChat powcoder

SOME PROPERTIES OF REGEX

Assignment Project Exam Help

Let R, S, T be regular expressions

- ▶ Star Closure properties:

<https://powcoder.com>

▶ $R^* = R^*R^* = (R^*)^* = R \mid R^*$

▶ $R^* = \varepsilon \mid R^* = (\varepsilon \mid R)^* = (\varepsilon \mid R)R^* = \varepsilon \mid RR^*$

Add WeChat powcoder

SOME PROPERTIES OF REGEX

Assignment Project Exam Help

Let R, S, T be regular expressions

- ▶ Star Closure properties:

<https://powcoder.com>

- ▶ $\epsilon^* = \epsilon^* = \epsilon$
- ▶ $R^* = R^* R^* = (R^*)^* = R \mid R^*$

- ▶ $R^* = \epsilon \mid R^* = (\epsilon \mid R)^* = (\epsilon \mid R) R^* = \epsilon \mid R R^*$

- ▶ $RR^* = R^* R$

Add WeChat powcoder

SOME PROPERTIES OF REGEX

Assignment Project Exam Help

Let R, S, T be regular expressions

- ▶ Star Closure properties:

$$\epsilon^* = \epsilon^+ = \epsilon$$

$$R^* = R^*R^* = (R^*)^* = R \mid R^*$$

$$R^* = \epsilon \mid R^* = (\epsilon \mid R)^* = (\epsilon \mid R)R^* = \epsilon \mid RR^*$$

$$RR^* = R^*R$$

$$(R \mid S)^* = (R^* \mid S^*)^* = (R^*S^*)^* = (R^*S)^*R^* = R^*(S^*)^*$$

Add WeChat powcoder

SOME PROPERTIES OF REGEX

Assignment Project Exam Help

Let R, S, T be regular expressions

- ▶ Star Closure properties:

$$\epsilon^* = \epsilon^* = \epsilon$$

$$R^* = R^* R^* = (R^*)^* = R \mid R^*$$

$$R^* = \epsilon \mid R^* = (\epsilon \mid R)^* = (\epsilon \mid R) R^* = \epsilon \mid R R^*$$

$$R R^* = R^* R$$

$$(R \mid S)^* = (R^* \mid S^*)^* = (R^* S^*)^* = (R^* S)^* R^* = R^* (S R^*)^*$$

$$R(SR)^* = (RS)^* R$$

SOME PROPERTIES OF REGEX

Assignment Project Exam Help

Let R, S, T be regular expressions

- ▶ Star Closure properties:

<https://powcoder.com>

- ▶ $\epsilon^* = \epsilon$
- ▶ $R^* = R^*R^* = (R^*)^* = R \mid R^*$

- ▶ $R^* = \epsilon \mid R^* = (\epsilon \mid R)^* = (\epsilon \mid R)R^* = \epsilon \mid RR^*$

- ▶ $RR^* = R^*R$

Add WeChat powcoder

- ▶ $(R \mid S)^* = (R^* \mid S^*)^* = (R^*S^*)^* = (R^*S)^*R^* = R^*(ST^*)^*$

- ▶ $R(SR)^* = (RS)^*R$

- ▶ $(R^*S)^* = \epsilon \mid (R \mid S)^*S$

SOME PROPERTIES OF REGEX

Assignment Project Exam Help

Let R, S, T be regular expressions

- ▶ Star Closure properties:

<https://powcoder.com>

- ▶ $\emptyset^* = \varepsilon^* = \varepsilon$
- ▶ $R^* = R^*R^* = (R^*)^* = R \mid R^*$

- ▶ $R^* = \varepsilon \mid R^* = (\varepsilon \mid R)^* = (\varepsilon \mid R)R^* = \varepsilon \mid RR^*$

- ▶ $RR^* = R^*R$

Add WeChat powcoder

- ▶ $(R \mid S)^* = (R^* \mid S^*)^* = (R^*S^*)^* = (R^*S)^*R^* = R^*(S^*)^*$

- ▶ $R(SR)^* = (RS)^*R$

- ▶ $(R^*S)^* = \varepsilon \mid (R \mid S)^*S$

- ▶ $(RS^*)^* = \varepsilon \mid R(R \mid S)^*$

EXAMPLES OF REGEX

- All possible strings which can be formed with a , b , or c

Assignment Project Exam Help

- Strings over $\{0, 1\}$ which end with 01

<https://powcoder.com>

- Traffic lights?

Add WeChat powcoder

- Identifiers for Java programs?

EXAMPLES OF REGEX

Assignment Project Exam Help

- ▶ All possible strings which can be formed with a , b , or c
 $(a|b|c)^*$

- ▶ Strings over $\{0, 1\}$ which end with 01

<https://powcoder.com>

- ▶ Traffic lights?

Add WeChat powcoder

- ▶ Identifiers for Java programs?

EXAMPLES OF REGEX

Assignment Project Exam Help

- ▶ All possible strings which can be formed with a , b , or c
 $(a|b|c)^*$

- ▶ Strings over $\{0, 1\}$ which end with 01
 $(0|1)^*01$

- ▶ Traffic lights?

Add WeChat powcoder

- ▶ Identifiers for Java programs?

EXAMPLES OF REGEX

► All possible strings which can be formed with a , b , or c
 $(a|b|c)^*$

- Strings over $\{0, 1\}$ which end with 01
 $(0|1)^*01$

- Traffic lights?
 $(red|red \circ amber|amber|green)$

- Identifiers for Java programs?

EXAMPLES OF REGEX

► All possible strings which can be formed with a , b , or c
 $(a|b|c)^*$

- Strings over $\{0, 1\}$ which end with 01
 $(0|1)^*01$

- Traffic lights?
 $(red|red\ o\ amber|amber|green)$

- Identifiers for Java programs?
 $(letter|\$|_)(letter|digit|\$|_)^*$

EXAMPLES OF REGEX

▶ a^*ba^* represents
Assignment Project Exam Help

▶ $((a \mid b)(a \mid b))^*$ represents

<https://powcoder.com>

▶ $ab^*a \mid ba^*b \mid a \mid b$ represents

Add WeChat powcoder

▶ $a^*\emptyset$ represents

EXAMPLES OF REGEX

► a^*ba^* represents
Strings over $\{a, b\}$ with exactly one b

► $((a | b)(a | b))^*$ represents

<https://powcoder.com>

► $ab^*a | ba^*b | a | b$ represents

Add WeChat powcoder

► $a^*\emptyset$ represents

EXAMPLES OF REGEX

- ▶ a^*ba^* represents
Strings over $\{a, b\}$ with exactly one b

- ▶ $((a \mid b)(a \mid b))^*$ represents
Strings over $\{a, b\}$ with even length

- ▶ $ab^*a \mid ba^*b \mid a \mid b$ represents

- ▶ $a^*\emptyset$ represents

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

EXAMPLES OF REGEX

- ▶ a^*ba^* represents
Strings over $\{a, b\}$ with exactly one b

- ▶ $((a \mid b)(a \mid b))^*$ represents
Strings over $\{a, b\}$ with even length

- ▶ $ab^*a \mid ba^*b \mid a \mid b$ represents
Strings of a 's starting and ending with b , or strings of b 's starting and ending with a , or a single a or b

- ▶ $a^*\emptyset$ represents

EXAMPLES OF REGEX

- ▶ a^*ba^* represents
Strings over $\{a, b\}$ with exactly one b

- ▶ $((a | b)(a | b))^*$ represents
Strings over $\{a, b\}$ with even length

- ▶ $ab^*a | ba^*b | a | b$ represents
Strings of a 's starting and ending with b , or strings of b 's starting and ending with a , or a single a or b

- ▶ $a^*\emptyset$ represents
The empty language, \emptyset

EQUIVALENCE OF REGEX AND FA

Theorem:

A language is regular if and only if a regular expression describes it.

Proof:

Show the equivalence of RegEx and FA ($\text{RegEx} \Leftrightarrow \text{FA}$)

1. $\text{RegEx} \Rightarrow \text{FA}$:

Show that for each RegEx, there exists an NFA which recognises the same language

2. $\text{FA} \Rightarrow \text{RegEx}$:

Show that for each NFA, there exists a RegEx which recognises the same language

EQUIVALENCE OF REGEX AND FA

Theorem:

A language is regular if and only if a regular expression describes it.

Proof:

Show the equivalence of RegEx and FA ($\text{RegEx} \Leftrightarrow \text{FA}$)

1. $\text{RegEx} \Rightarrow \text{FA}$:

Show that for each RegEx, there exists an NFA which recognises the same language

2. $\text{FA} \Rightarrow \text{RegEx}$:

Show that for each NFA, there exists a RegEx which recognises the same language

Next week: proof

APPLICATION: PATTERN MATCHING

Assignment Project Exam Help

- Provides a technique for finding occurrences of patterns in text (e.g. web/document searching)
- Some of the best known algorithms are based on Finite Automata.
- Constructing a NFA to recognise the strings containing the pattern is trivial.
- Then we convert the NFA to DFA, then minimal DFA, so the pattern can be matched efficiently

<https://powcoder.com>

Add WeChat powcoder

DFAs AND NFAs

Assignment Project Exam Help

- ▶ NFAs and DFAs define the class of regular languages
 - ▶ Each NFA can be transformed into a unique minimal DFA
 - ▶ NFAs are often more intuitive to build and easier to understand
 - ▶ DFA - *especially minimal DFA* - are more efficient to compute
 - ▶ despite the fact they often have far more states than the NFA
 - ▶ Regular languages are closed under the union, concatenation, star closure, intersection, and complement operations
 - ▶ We use these to build the NFA, before converting to a minimal DFA

<https://powcoder.com>

Add WeChat powcoder

REGULAR EXPRESSIONS

Assignment Project Exam Help

- ▶ What they are and how to use them
- ▶ Regular operations
- ▶ Equivalence with DFA/NFA

<https://powcoder.com>

Add WeChat powcoder