

COMP2022: Formal Languages and Logic

2018 Semester 2, Week 7

Assignment Project Exam Help

Kalina Yacef, Joseph Godbehere

<https://powcoder.com>

13th September, 2018

Add WeChat powcoder



THE UNIVERSITY OF
SYDNEY

COMMONWEALTH OF AUSTRALIA

Copyright Regulations 1969

Assignment Project Exam Help

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be subject of copyright protect under the Act.

Do not remove this notice.

OUTLINE

Assignment Project Exam Help

- ▶ Grammars
- ▶ Context-Free Grammars (CFG)
- ▶ Context-Free Languages (CFL)
- ▶ Parsing (Introduction)
- ▶ Ambiguity
- ▶ Recursive Grammars
- ▶ Clean Grammars
- ▶ Types of Grammar

<https://powcoder.com>

Add WeChat powcoder

INTRODUCTION

Assignment Project Exam Help

So far, we have seen two different, but equivalent, methods of describing languages: finite automata and regular expressions, which describe *regular languages*

<https://powcoder.com>

We have already proven that some languages, such as $\{0^n 1^n \mid n \geq 0\}$, cannot be described using FA or RE.

Add WeChat powcoder

Today we will introduce *context-free grammars (CFG)*, which describe the next category of languages, the *context-free languages*

GRAMMARS

Assignment Project Exam Help

Grammars are another way to describe a language

A *grammar* is a set of rules which can be used to generate a language

Add WeChat powcoder

The language generated is the set of all strings which can be *derived* from the grammar

INTRODUCTORY EXAMPLE (G_1)

Assignment Project Exam Help

$S \rightarrow 01$

Base case: $01 \in L$

$S \rightarrow 0S1$

Recursive case: if $S \in L$ then $0S1 \in L$

G_1 generates the language $L = \{0^n 1^n \mid n \geq 0\}$, which we already know is not regular

How does it derive 000111?

Add WeChat powcoder

INTRODUCTORY EXAMPLE (G_1)

Assignment Project Exam Help

 $S \rightarrow 01$

Base case: $01 \in L$

 $S \rightarrow 0S1$

Recursive case: if $S \in L$ then $0S1 \in L$

G_1 generates the language $L = \{0^n 1^n \mid n \geq 0\}$, which we already know is not regular

How does it derive 000111?

Add WeChat powcoder

S

INTRODUCTORY EXAMPLE (G_1)

Assignment Project Exam Help

 $S \rightarrow 01$

Base case: $01 \in L$

 $S \rightarrow 0S1$

Recursive case: if $S \in L$ then $0S1 \in L$

G_1 generates the language $L = \{0^n 1^n \mid n \geq 0\}$, which we already know is not regular

How does it derive 000111?

 $S \Rightarrow 0S1$

using rule $S \rightarrow 0S1$

Add WeChat powcoder

INTRODUCTORY EXAMPLE (G_1)

Assignment Project Exam Help

$$S \rightarrow 01$$

Base case: $01 \in L$

$$S \rightarrow 0S1$$

Recursive case: if $S \in L$ then $0S1 \in L$

G_1 generates the language $L = \{0^n 1^n \mid n \geq 0\}$, which we already know is not regular

How does it derive 000111?

$$S \Rightarrow 0S1$$

using rule $S \rightarrow 0S1$

$$\Rightarrow 00S11$$

using rule $S \rightarrow 0S1$

Add WeChat powcoder

INTRODUCTORY EXAMPLE (G_1)

Assignment Project Exam Help

$$S \rightarrow 01$$

Base case: $01 \in L$

$$S \rightarrow 0S1$$

Recursive case: if $S \in L$ then $0S1 \in L$

G_1 generates the language $L = \{0^n 1^n \mid n \geq 0\}$, which we already know is not regular

How does it derive 000111?

$$S \Rightarrow 0S1$$

using rule $S \rightarrow 0S1$

$$\Rightarrow 00S11$$

using rule $S \rightarrow 0S1$

$$\Rightarrow 000111$$

using rule $S \rightarrow 01$

Add WeChat powcoder

INTRODUCTORY EXAMPLE (G_2)

Assignment Project Exam Help

$S \rightarrow NounPhrase VerbPhrase$

$NounPhrase \rightarrow \text{the } Noun$

$VerbPhrase \rightarrow Verb NounPhrase$

$Noun \rightarrow \text{girl} \mid \text{ball}$

$Verb \rightarrow \text{likes} \mid \text{sees}$

<https://powcoder.com>

What language does G_2 generate?

Add WeChat powcoder

INTRODUCTORY EXAMPLE (G_2)

Assignment Project Exam Help

$S \rightarrow NounPhrase VerbPhrase$

$NounPhrase \rightarrow the\ Noun$

$VerbPhrase \rightarrow Verb\ NounPhrase$

$Noun \rightarrow girl\ | \ ball$

$Verb \rightarrow likes\ | \ sees$

<https://powcoder.com>

What language does G_2 generate?

{ the girl likes the girl, the girl likes the ball,
the girl sees the girl, the girl sees the ball,
the ball likes the girl, the ball likes the ball,
the ball sees the girl, the ball sees the ball }

Add WeChat powcoder

DEFINITIONS

Terminals

- The finite set of symbols which make up strings of the language

Non-terminals / Variables

- A finite set of symbols used to generate the strings.
- They never appear in the language.

Start symbol

- The variable used to start every derivation

DEFINITIONS

Production rules

- Sometimes called substitution or derivation rules
- Define strings of *variables* and *terminals* which can be substituted for a *variable*:

Variables \rightarrow \langle string of *Var* α \rangle e. and *Terminals* \rangle

Add WeChat powcoder

DEFINITIONS

Production rules

- Sometimes called substitution or derivation rules
- Define strings of *variables* and *terminals* which can be substituted for a *variable*:

Variables \rightarrow < string of Var a (e.g. and *Terminals* >

A variable can have many rules:

Noun \rightarrow girl

Noun \rightarrow ball

Noun \rightarrow quokka

DEFINITIONS

Production rules

- Sometimes called substitution or derivation rules
- Define strings of *variables* and *terminals* which can be substituted for a *variable*:

Variables \rightarrow \langle string of *Var a* \rangle e. and *Terminals* \rangle

A variable can have many rules:

They can be written together:

Noun \rightarrow girl

Noun \rightarrow girl | ball | quokka

Noun \rightarrow ball

Noun \rightarrow quokka

ANOTHER EXAMPLE

Assignment Project Exam Help

$$S \rightarrow T \mid (S \cdot S) \mid (\lambda T.S)$$

$$T \rightarrow a \mid b \mid \dots$$

<https://powcoder.com>

This is a grammar for lambda calculus expressions

- ▶ The variables are S, T
- ▶ S is the start variable
- ▶ The terminals are $a, b, \dots, (,), \lambda, \cdot, \cdot$ (i.e. atoms and operators)

Add WeChat powcoder

SOME COMMON NOTATIONAL CONVENTIONS

Assignment Project Exam Help

If not stated otherwise:

- ▶ A, B, C, \dots and S are variables
- ▶ S is the start variable
- ▶ a, b, c, \dots are terminals
- ▶ \dots, X, Y, Z are either terminals or variables
- ▶ $\dots w, x, y, z$ are strings of terminals only
- ▶ $\alpha, \beta, \gamma, \dots$ are strings of terminals and/or variables

<https://powcoder.com>

Add WeChat powcoder

CONTEXT-FREE GRAMMAR (CFG)

A *context-free grammar* is a grammar where every production rule

has the form $A \rightarrow \alpha$

- ▶ A is a variable
- ▶ α is a string of terminals and/or variables (possibly ϵ)

<https://powcoder.com>

Add WeChat powcoder

CONTEXT-FREE GRAMMAR (CFG)

A *context-free grammar* is a grammar where every production rule has the form $A \rightarrow \alpha$

- ▶ A is a variable
- ▶ α is a string of terminals and/or variables (possibly ϵ)

Context-free grammars describe *context-free languages*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

CONTEXT-FREE GRAMMAR (CFG)

A *context-free grammar* is a grammar where every production rule has the form $A \rightarrow \alpha$

- ▶ A is a variable
- ▶ α is a string of terminals and/or variables (possibly ϵ)

Context-free grammars describe *context-free languages*

Example:

$\{a^n b^n \mid n \in \mathbb{N}\}$ is not a regular language (no finite automata exists recognising it) but we can prove that it is a context-free language, because the following grammar generates it:

$$S \rightarrow aSb \mid \epsilon$$

CFG: FORMAL DEFINITION

A context-free grammar G is a 4-tuple (V, T, P, S) where:

- ▶ V is a finite set of *variables*
- ▶ T is a finite set of *terminals*
- ▶ P is a finite set of *production rules* in the form $\alpha \rightarrow \beta$ where $\alpha \in V$ and $\beta \in \{V \cup T \cup \{\epsilon\}\}^*$
- ▶ $S \in V$ is a special variable called the *Start Symbol*

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

EXAMPLE G_1

Assignment Project Exam Help

$$\begin{aligned} S &\rightarrow 01 \\ S &\rightarrow 0S1 \end{aligned}$$

More formally, $G_1 = (T, V, S, P)$ where

<https://powcoder.com>

$$T =$$

$$V =$$

Add WeChat powcoder

$$\begin{aligned} S &= \\ P &= \end{aligned}$$

EXAMPLE G_1

Assignment Project Exam Help

$$\begin{aligned} S &\rightarrow 01 \\ S &\rightarrow 0S1 \end{aligned}$$

More formally, $G_1 = (T, V, S, P)$, where

<https://powcoder.com>

$$T = \{0, 1\}$$

$$V =$$

Add WeChat powcoder

$$\begin{aligned} S &= \\ P &= \end{aligned}$$

EXAMPLE G_1

Assignment Project Exam Help

$$\begin{aligned} S &\rightarrow 01 \\ S &\rightarrow 0S1 \end{aligned}$$

More formally, $G_1 = (T, V, S, P)$ where

<https://powcoder.com>

$$T = \{0, 1\}$$

$$V = \{S\}$$

Add WeChat powcoder

$$P =$$

EXAMPLE G_1

Assignment Project Exam Help

$$\begin{aligned} S &\rightarrow 01 \\ S &\rightarrow 0S1 \end{aligned}$$

More formally, $G_1 = (T, V, S, P)$, where

<https://powcoder.com>

$$T = \{0, 1\}$$

$$V = \{S\}$$

Add WeChat powcoder

$$\begin{aligned} S &= S \\ P &= \end{aligned}$$

EXAMPLE G_1

Assignment Project Exam Help

$$\begin{aligned} S &\rightarrow 01 \\ S &\rightarrow 0S1 \end{aligned}$$

More formally, $G_1 = (T, V, S, P)$ where

$$T = \{0, 1\}$$

$$V = \{S\}$$

$$S = S$$

$$P = \{$$

$$S \rightarrow 01$$

$$S \rightarrow 0S1$$

$$\}$$

EXAMPLE G_2

Assignment Project Exam Help

$S \rightarrow NounPhrase VerbPhrase$
 $NounPhrase \rightarrow the Noun$

$VerbPhrase \rightarrow Verb NounPhrase$

$Noun \rightarrow girl \mid ball$
 $Verb \rightarrow likes \mid sees$

<https://powcoder.com>

More formally, $G_2 = (T, V, S, P)$ where:

Add WeChat powcoder

$T =$

$V =$

$S =$

$P =$

EXAMPLE G_2

Assignment Project Exam Help

$S \rightarrow NounPhrase\ VerbPhrase$
 $NounPhrase \rightarrow the\ Noun$

$VerbPhrase \rightarrow Verb\ NounPhrase$

$Noun \rightarrow girl \mid ball$
 $Verb \rightarrow likes \mid sees$
<https://powcoder.com>

More formally, $G_2 = (T, V, S, P)$ where:

$T = \{the, girl, ball, likes, sees\}$

$V =$

$S =$

$P =$

Add WeChat powcoder

EXAMPLE G_2

Assignment Project Exam Help

$S \rightarrow NounPhrase\ VerbPhrase$
 $NounPhrase \rightarrow the\ Noun$

$VerbPhrase \rightarrow Verb\ NounPhrase$

$Noun \rightarrow girl \mid ball$
 $Verb \rightarrow likes \mid sees$
<https://powcoder.com>

More formally, $G_2 = (T, V, S, P)$ where:

Add WeChat powcoder

$T = \{the, girl, ball, likes, sees\}$

$V = \{S, NounPhrase, VerbPhrase, Noun, Verb\}$

$S =$

$P =$

EXAMPLE G_2

Assignment Project Exam Help

$S \rightarrow NounPhrase\ VerbPhrase$
 $NounPhrase \rightarrow the\ Noun$

$VerbPhrase \rightarrow Verb\ NounPhrase$

$Noun \rightarrow girl \mid ball$
 $Verb \rightarrow likes \mid sees$
<https://powcoder.com>

More formally, $G_2 = (T, V, S, P)$ where:

Add WeChat powcoder

$T = \{the, girl, ball, likes, sees\}$

$V = \{S, NounPhrase, VerbPhrase, Noun, Verb\}$

$S = S$

$P =$

EXAMPLE G_2

Assignment Project Exam Help

$S \rightarrow NounPhrase\ VerbPhrase$
 $NounPhrase \rightarrow the\ Noun$

$VerbPhrase \rightarrow Verb\ NounPhrase$

$Noun \rightarrow girl \mid ball$
 $Verb \rightarrow likes \mid sees$
<https://powcoder.com>

More formally, $G_2 = (T, V, S, P)$ where:

Add WeChat powcoder

$T = \{the, girl, ball, likes, sees\}$

$V = \{S, NounPhrase, VerbPhrase, Noun, Verb\}$

$S = S$

$P = (\text{set of seven rules above})$

LANGUAGE OF A GRAMMAR

Let w be a string over T .
 $w \in L(G)$ if and only if it is possible to derive w from \bar{S} .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

LANGUAGE OF A GRAMMAR

Let w be a string over T .
 $w \in L(G)$ if and only if it is possible to derive w from \bar{S} .

Notation:

$\alpha \Rightarrow \beta$ denotes that α derives β in one step.

$\alpha \Rightarrow^+ \beta$ means it derives it in one or more steps.

Add WeChat powcoder

LANGUAGE OF A GRAMMAR

Let w be a string over T .
 $w \in L(G)$ if and only if it is possible to derive w from S .

Notation:

$\alpha \Rightarrow \beta$ denotes that α derives β in one step.

$\alpha \Rightarrow^+ \beta$ means it derives it in one or more steps

The language of a grammar $G = (V, T, P, S)$ is the set

$L(G) = \{w \mid w \in T^* \text{ and } S \Rightarrow^+ w\}$

LANGUAGE OF A GRAMMAR

Let w be a string over T .
 $w \in L(G)$ if and only if it is possible to derive w from S .

Notation:

$\alpha \Rightarrow \beta$ denotes that α derives β in one step.

$\alpha \Rightarrow^+ \beta$ means it derives it in one or more steps

The language of a grammar $G = (V, T, P, S)$ is the set

$L(G) = \{w \mid w \in T^* \text{ and } S \Rightarrow^+ w\}$

If two grammars generate the same language, then they are *equivalent*.

DERIVATION OF A STRING

Assignment Project Exam Help

- ▶ Begin with the start symbol
- ▶ Repeatedly replace one variable with the right hand side of one of its productions

- ▶ ... until the string is composed only of terminal symbols

<https://powcoder.com>

Add WeChat powcoder

DERIVATION OF A STRING

- ▶ Begin with the start symbol
- ▶ Repeatedly replace one variable with the right hand side of one of its productions

- ▶ ... until the string is composed only of terminal symbols

<https://powcoder.com>

Example, derivation of 000111 from this grammar:

Add WeChat powcoder

$S \rightarrow 0S1 \mid \epsilon \quad A \Rightarrow$

DERIVATION OF A STRING

Assignment Project Exam Help

- ▶ Begin with the start symbol
- ▶ Repeatedly replace one variable with the right hand side of one of its productions
- ▶ ... until the string is composed only of terminal symbols

<https://powcoder.com>

Example, derivation of 000111 from this grammar:

Add WeChat powcoder

$S \rightarrow 0S1 \mid \epsilon \quad A \Rightarrow 0S1$

\Rightarrow

DERIVATION OF A STRING

- ▶ Begin with the start symbol
- ▶ Repeatedly replace one variable with the right hand side of one of its productions
- ▶ ... until the string is composed only of terminal symbols

<https://powcoder.com>

Example, derivation of 000111 from this grammar:

Add WeChat powcoder

$S \rightarrow 0S1 \mid \epsilon \quad S \Rightarrow 0S1$

$\Rightarrow 00S11$

$\Rightarrow 000S111$

\Rightarrow

DERIVATION OF A STRING

- ▶ Begin with the start symbol
- ▶ Repeatedly replace one variable with the right hand side of one of its productions
- ▶ ... until the string is composed only of terminal symbols

<https://powcoder.com>

Example, derivation of 000111 from this grammar:

Add WeChat powcoder

$S \rightarrow 0S1 \mid \epsilon \quad S \Rightarrow 0011$

$\Rightarrow 00S11$

$\Rightarrow 000S111$

$\Rightarrow 000111$

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

<https://powcoder.com>

Add WeChat powcoder

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

Add WeChat powcoder

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

Add WeChat powcoder

<https://powcoder.com>

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

<https://powcoder.com>

Add WeChat powcoder

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

$\Rightarrow \text{the girl sees NounPhrase}$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

$\Rightarrow \text{the girl sees NounPhrase}$

$\Rightarrow \text{the girl sees the Noun}$

<https://powcoder.com>

Add WeChat powcoder

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$ $S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

$\Rightarrow \text{the girl sees NounPhrase}$

$\Rightarrow \text{the girl sees the Noun}$

$\Rightarrow \text{the girl sees the ball}$

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

$\Rightarrow \text{the girl sees NounPhrase}$

$\Rightarrow \text{the girl sees the Noun}$

$\Rightarrow \text{the girl sees the ball}$

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{NounPhrase Verb NounPhrase}$

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow NounPhrase VerbPhrase$
 $\Rightarrow the Noun VerbPhrase$
 $\Rightarrow the girl VerbPhrase$
 $\Rightarrow the girl Verb NounPhrase$
 $\Rightarrow the girl sees NounPhrase$
 $\Rightarrow the girl sees the Noun$
 $\Rightarrow the girl sees the ball$

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$
 $\Rightarrow \text{the Noun VerbPhrase}$
 $\Rightarrow \text{the girl VerbPhrase}$
 $\Rightarrow \text{the girl Verb NounPhrase}$
 $\Rightarrow \text{the girl sees NounPhrase}$
 $\Rightarrow \text{the girl sees the Noun}$
 $\Rightarrow \text{the girl sees the ball}$

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

$\Rightarrow \text{the girl sees NounPhrase}$

$\Rightarrow \text{the girl sees the Noun}$

$\Rightarrow \text{the girl sees the ball}$

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{NounPhrase Verb NounPhrase}$

$\Rightarrow \text{NounPhrase Verb the Noun}$

$\Rightarrow \text{NounPhrase Verb the ball}$

$\Rightarrow \text{NounPhrase sees the ball}$

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

$\Rightarrow \text{the girl sees NounPhrase}$

$\Rightarrow \text{the girl sees the Noun}$

$\Rightarrow \text{the girl sees the ball}$

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{NounPhrase Verb NounPhrase}$

$\Rightarrow \text{NounPhrase Verb the Noun}$

$\Rightarrow \text{NounPhrase Verb the ball}$

$\Rightarrow \text{NounPhrase sees the ball}$

$\Rightarrow \text{the Noun sees the ball}$

LEFTMOST AND RIGHTMOST DERIVATIONS

Leftmost derivation: always derive the leftmost variable first

Rightmost derivation: always derive the rightmost variable first

Example: "the girl sees the ball"

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{the Noun VerbPhrase}$

$\Rightarrow \text{the girl VerbPhrase}$

$\Rightarrow \text{the girl Verb NounPhrase}$

$\Rightarrow \text{the girl sees NounPhrase}$

$\Rightarrow \text{the girl sees the Noun}$

$\Rightarrow \text{the girl sees the ball}$

$S \Rightarrow \text{NounPhrase VerbPhrase}$

$\Rightarrow \text{NounPhrase Verb NounPhrase}$

$\Rightarrow \text{NounPhrase Verb the Noun}$

$\Rightarrow \text{NounPhrase Verb the ball}$

$\Rightarrow \text{NounPhrase sees the ball}$

$\Rightarrow \text{the Noun sees the ball}$

$\Rightarrow \text{the girl sees the ball}$

CONTEXT-FREE LANGUAGES

A language is *context-free* if it is generated by a CFG

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

CONTEXT-FREE LANGUAGES

A language is *context-free* if it is generated by a CFG

Assignment Project Exam Help
 The syntax of most programming languages are context-free.

$S \rightarrow \text{while } E \text{ do } S$

$S \rightarrow \text{if } E \text{ then } S \text{ else } S$

$S \rightarrow I := E$

$S \rightarrow \{SL\}$

$L \rightarrow ; SL \mid \epsilon$

$E \rightarrow \dots$ (description of an expression)

$I \rightarrow \dots$ (description of an identifier)

<https://powcoder.com>

Add WeChat powcoder

CONTEXT-FREE LANGUAGES

Assignment Project Exam Help

A language is *context-free* if it is generated by a CFG

$\{\text{Regular Languages}\} \subset \{\text{Context-Free Languages}\}$

<https://powcoder.com>

- ▶ The *union* of two CFL is also context-free
- ▶ The *concatenation* of two CFL is also context-free
- ▶ The *star closure* of a CFL is also context-free

Add WeChat powcoder

EXAMPLE

Consider the grammar G :

$$S \rightarrow AB$$

$$S \Rightarrow AB$$

$$A \rightarrow \varepsilon \mid aA$$

$$B \rightarrow \varepsilon \mid bB$$

<https://powcoder.com>

What is $L(G)$?

Add WeChat powcoder

EXAMPLE

Consider the grammar G :

$$S \rightarrow AB$$

$$A \rightarrow \varepsilon \mid aA$$

$$B \rightarrow \varepsilon \mid bB$$

$$S \Rightarrow AB$$

$$\Rightarrow aAB$$

$$\Rightarrow^+ aaaaAB$$

$$\Rightarrow aaaaB$$

What is $L(G)$?

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

EXAMPLE

Consider the grammar G :

$$S \rightarrow AB$$

$$A \rightarrow \varepsilon \mid aA$$

$$B \rightarrow \varepsilon \mid bB$$

$$S \Rightarrow AB$$

$$\Rightarrow aAB$$

$$\Rightarrow^+ aaaaAB$$

$$\Rightarrow aaaaB$$

$$\Rightarrow aaaaabB$$

$$\Rightarrow^+ aaaaabbbbbbB$$

$$\Rightarrow aaaaabbbbbbb$$

What is $L(G)$?

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

EXAMPLE

Consider the grammar G :

$$S \rightarrow AB$$

$$A \rightarrow \varepsilon \mid aA$$

$$B \rightarrow \varepsilon \mid bB$$

$$S \Rightarrow AB$$

$$\Rightarrow aAB$$

$$\Rightarrow^+ aaaaAB$$

$$\Rightarrow aaaaB$$

$$\Rightarrow aaaaabB$$

$$\Rightarrow^+ aaaaabbbbB$$

$$\Rightarrow aaaaabbbbb$$

What is $L(G)$?

Add WeChat powcoder

$$\text{i.e. } L(G) = L(a^*b^*) = \{a^n b^m \mid n \geq 0, m \geq 0\}$$

MORE EXAMPLES

Describe the language generated

Assignment Project Exam Help

$$1. S \rightarrow aSa \mid bSb \mid \varepsilon$$

$$2. S \rightarrow aS \mid bS \mid a$$

$$3. S \rightarrow SS \mid bS \mid a$$

$$4. S \rightarrow aT \mid bT \mid \varepsilon$$

$$T \rightarrow aS \mid bS$$

$$5. S \rightarrow aSa \mid bSb \mid a \mid b$$

MORE EXAMPLES

Give grammars generating these languages

Assignment Project Exam Help

1. $\{ba^{n+1}b \mid n \geq 0\}$

2. <https://powcoder.com>
Odd-length strings in $\{a, b\}^*$ with middle symbol a

3. Even-length strings in $\{a, b\}^*$ with matching middle symbols

Add WeChat powcoder

4. Binary strings containing more 0's than 1's

5. Strings over $\{a, b\}$ with at least three a 's

CONSTRUCTING GRAMMARS

Let M and N be two languages whose grammars have disjoint sets of non-terminals (rename them if necessary). Let S_M and S_N be their start symbols.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

CONSTRUCTING GRAMMARS

Let M and N be two languages whose grammars have disjoint sets of non-terminals (rename them if necessary). Let S_M and S_N be their start symbols.

Then we can construct a grammar recognising the following languages, with a new start symbol S :

Add WeChat powcoder

CONSTRUCTING GRAMMARS

Let M and N be two languages whose grammars have disjoint sets of non-terminals (rename them if necessary). Let S_M and S_N be their start symbols.

Then we can construct a grammar recognising the following languages, with a new start symbol S :

- Union: the grammar for $M \cup N$ starts with $S \rightarrow S_M \mid S_N$

Add WeChat powcoder

All other productions remain unchanged (aside for renaming of variables as needed)

CONSTRUCTING GRAMMARS

Let M and N be two languages whose grammars have disjoint sets of non-terminals (rename them if necessary). Let S_M and S_N be their start symbols.

Then we can construct a grammar recognising the following languages, with a new start symbol S :

- ▶ Union: the grammar for $M \cup N$ starts with $S \rightarrow S_M \mid S_N$
- ▶ Concatenation: the grammar for MN starts with $S \rightarrow S_M S_N$

All other productions remain unchanged (aside for renaming of variables as needed)

CONSTRUCTING GRAMMARS

Let M and N be two languages whose grammars have disjoint sets of non-terminals (rename them if necessary). Let S_M and S_N be their start symbols.

Then we can construct a grammar recognising the following languages, with a new start symbol S :

- ▶ Union: the grammar for $M \cup N$ starts with $S \rightarrow S_M \mid S_N$
- ▶ Concatenation: the grammar for MN starts with $S \rightarrow S_M S_N$
- ▶ Star closure: the grammar for M^* starts with $S \rightarrow S_M S \mid \epsilon$

All other productions remain unchanged (aside for renaming of variables as needed)

USING THE UNION RULE

Let $L = \{\varepsilon, a, b, aa, bb, \dots, a^n b^n, \dots\}$

Then $L = M \cup N$ where $M = \{a^n \mid n \geq 0\}$, $N = \{b^n \mid n \geq 0\}$

So a grammar G_M of M is
and a grammar G_N of N is

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

USING THE UNION RULE

Let $L = \{\varepsilon, a, b, aa, bb, \dots, a^n b^n, \dots\}$

Then $L = M \cup N$ where $M = \{a^n \mid n \geq 0\}$, $N = \{b^n \mid n \geq 0\}$

So a grammar G_M of M is $S_M \rightarrow \varepsilon \mid aS_M$
and a grammar G_N of N is

Add WeChat powcoder

USING THE UNION RULE

Let $L = \{\varepsilon, a, b, aa, bb, \dots, a^n, b^n, \dots\}$

Then $L = M \cup N$ where $M = \{a^n \mid n \geq 0\}$, $N = \{b^n \mid n \geq 0\}$

So a grammar G_M of M is $S_M \rightarrow \varepsilon \mid aS_M$
 and a grammar G_N of N is $S_N \rightarrow \varepsilon \mid bS_N$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

USING THE UNION RULE

Let $L = \{\varepsilon, a, b, aa, bb, \dots, a^n b^n, \dots\}$

Assignment Project Exam Help

Then $L = M \cup N$ where $M = \{a^n \mid n \geq 0\}$, $N = \{b^n \mid n \geq 0\}$

<https://powcoder.com>

So a grammar G_M of M is $S_M \rightarrow \varepsilon \mid aS_M$
and a grammar G_N of N is $S_N \rightarrow \varepsilon \mid bS_N$

Add WeChat powcoder

Using the union rule we get:

$$S \rightarrow S_M \mid S_N$$

$$S_M \rightarrow \varepsilon \mid aS_M$$

$$S_N \rightarrow \varepsilon \mid bS_N$$

USING THE CONCATENATION RULE

Let $L = \{a^m b^n \mid m \geq 0, n \geq 0\}$

Then $L = MN$ where $M = \{a^m \mid m \geq 0\}$, $N = \{b^n \mid n \geq 0\}$

So a grammar G_M of M is $S_M \rightarrow \varepsilon \mid aS_M$
 and a grammar G_N of N is $S_N \rightarrow \varepsilon \mid bS_N$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

USING THE CONCATENATION RULE

Let $L = \{a^m b^n \mid m \geq 0, n \geq 0\}$

Then $L = MN$ where $M = \{a^m \mid m \geq 0\}$, $N = \{b^n \mid n \geq 0\}$

So a grammar G_M of M is $S_M \rightarrow \varepsilon \mid aS_M$
 and a grammar G_N of N is $S_N \rightarrow \varepsilon \mid bS_N$

Using the concatenation rule we get

$$S \rightarrow S_M S_N$$

$$S_M \rightarrow \varepsilon \mid aS_M$$

$$S_N \rightarrow \varepsilon \mid bS_N$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

USING THE STAR CLOSURE RULE

Let L be strings consisting of 0 or more occurrences of aa or bb
 i.e. $(aa | bb)^*$

Then $L = M^*$ where $M = \{aa, bb\}$

So a grammar G_M of M is

Add WeChat powcoder

USING THE STAR CLOSURE RULE

Let L be strings consisting of 0 or more occurrences of aa or bb
 i.e. $(aa | bb)^*$

Then $L = M^*$ where $M = \{aa, bb\}$

So a grammar G_M of M is $S_M \rightarrow aa | bb$

Add WeChat powcoder

USING THE STAR CLOSURE RULE

Let L be strings consisting of 0 or more occurrences of aa or bb
 i.e. $(aa | bb)^*$

Then $L = M^*$ where $M = \{aa, bb\}$

So a grammar G_M of M is $S_M \rightarrow aa | bb$

Using the star closure rule we get:

$$S \rightarrow S_M S \mid \varepsilon$$

$$S_M \rightarrow aa \mid bb$$

PARSING

Assignment Project Exam Help

Given a sentence, the problem of *parsing* is determining *how* the grammar generates it.

<https://powcoder.com>

i.e. To discover the *correct* derivation of the sentence, or the correct parse tree

Add WeChat powcoder

PARSE TREE

A *parse tree* is a tree labelled by symbols from the CFG

- ▶ root = the start symbol
- ▶ interior node = a variable
- ▶ leaf node = a terminal or ε
- ▶ children of X = the right hand side of a production rule for X , in order

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

PARSE TREE

A *parse tree* is a tree labelled by symbols from the CFG

- ▶ root = the start symbol
- ▶ interior node = a variable
- ▶ leaf node = a terminal or ε
- ▶ children of X = the right hand side of a production rule for X , in order


<https://powcoder.com>

Add WeChat powcoder

Example parse tree for "0011" in

$S \rightarrow 0S1 \mid 01$

An in-order traversal of the leaf nodes retrieves the string



PARSE TREE OR DERIVATION TREE

The parse tree defines the (syntactic) *meaning* of a string in the grammar's language


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

PARSE TREE OR DERIVATION TREE

The parse tree defines the (syntactic) *meaning* of a string in the grammar's language



$$S \rightarrow S \cdot S$$

$$S \rightarrow x \mid y \mid z$$

This parse tree implies
that the expression
means $x \cdot (y \cdot z)$

NATURAL LANGUAGE PROCESSING (NLP) EXAMPLE

Assignment Project Exam Help

NounPhrase → *ComplexNoun* | *ComplexNoun PrepPhrase*

VerbPhrase → *ComplexVerb* | *ComplexVerb PrepPhrase*

PrepPhrase → *Prep ComplexNoun*

ComplexNoun → *Article Noun*

ComplexVerb → *Verb* | *Verb NounPhrase*

Article → *a* | *the*

Noun → *girl* | *dog* | *stick* | *ball*

Verb → *chases* | *sees*

Prep → *with*

<https://powcoder.com>

Add WeChat powcoder

SIMPLE EXAMPLE

Is the string "a ball" accepted by this grammar?

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SIMPLE EXAMPLE

Is the string "a ball" accepted by this grammar?

Assignment Project Exam Help

We have no choice but start by deriving

$S \Rightarrow \text{NounPhrase VerbPhrase}$

<https://powcoder.com>

Add WeChat powcoder

SIMPLE EXAMPLE

Is the string "a ball" accepted by this grammar?

Assignment Project Exam Help

We have no choice but start by deriving

$S \Rightarrow \text{NounPhrase VerbPhrase}$

<https://powcoder.com>

All the production rules for *VerbPhrase* produce a *ComplexVerb*, which in turn must produce a *Verb*.

Add WeChat powcoder

SIMPLE EXAMPLE

Is the string “a ball” accepted by this grammar?

Assignment Project Exam Help

We have no choice but start by deriving

$S \Rightarrow \text{NounPhrase VerbPhrase}$

All the production rules for *VerbPhrase* produce a *ComplexVerb*, which in turn must produce a *Verb*.

Add WeChat powcoder

Therefore all strings in the language contain a verb. “a ball” does not contain a verb, so it cannot be accepted by the grammar.

AMBIGUITY: EXAMPLE

Ambiguity: several meanings for the same sentence.

"The girl chases the dog with a stick" has *two leftmost derivations*

Sentence ⇒ NounPhrase VerbPhrase

⇒ *ComplexNoun VerbPhrase*

⇒ *Article Noun VerbPhrase*

⇒ *the Noun VerbPhrase*

⇒ *the girl VerbPhrase*

⇒ *the girl ComplexVerb*

⇒ *the girl Verb NounPhrase*

⇒ *the girl chases NounPhrase*

⇒ *the girl chases ComplexNoun PrepPhrase*

⇒ *the girl chases Article Noun PrepPhrase*

⇒ *the girl chases the Noun PrepPhrase*

⇒ *the girl chases the dog PrepPhrase*

⇒ *the girl chases the dog Prep ComplexNoun*

⇒ *the girl chases the dog with ComplexNoun*

⇒ *the girl chases the dog with Article Noun*

⇒ *the girl chases the dog with a Noun*

⇒ *the girl chases the dog with a stick*

Sentence ⇒ NounPhrase VerbPhrase

⇒ *ComplexNoun VerbPhrase*

⇒ *Article Noun VerbPhrase*

⇒ *the Noun VerbPhrase*

⇒ *the girl VerbPhrase*

⇒ *the girl ComplexVerb PrepPhrase*

⇒ *the girl Verb NounPhrase PrepPhrase*

⇒ *the girl chases NounPhrase PrepPhrase*

⇒ *the girl chases Article Noun PrepPhrase*

⇒ *the girl chases the Noun PrepPhrase*

⇒ *the girl chases the dog PrepPhrase*

⇒ *the girl chases the dog Prep ComplexNoun*

⇒ *the girl chases the dog with ComplexNoun*

⇒ *the girl chases the dog with Article Noun*

⇒ *the girl chases the dog with a Noun*

⇒ *the girl chases the dog with a stick*

<https://powcoder.com>

Add WeChat powcoder

AMBIGUITY: EXAMPLE

Ambiguity: several meanings for the same sentence.


“The girl chases the dog with a stick” has *two leftmost derivations*

$Sentence \Rightarrow^+ the\ girl\ VerbPhrase$
 $\Rightarrow the\ girl\ ComplexVerb$
 $\Rightarrow^+ the\ girl\ chases\ \underline{the\ dog\ with\ a\ stick}$


$Sentence \Rightarrow^+ the\ girl\ VerbPhrase$
 $\Rightarrow the\ girl\ ComplexVerb\ PrepPhrase$
 $\Rightarrow^+ the\ girl\ chases\ \underline{the\ dog}\ with\ a\ stick$

Who has the stick?

FIRST LEFTMOST DERIVATION TREE



SECOND LEFTMOST DERIVATION TREE



AMBIGUOUS GRAMMARS

Definition:

A string is *ambiguous* on a given grammar if it has two different parse trees. Otherwise, it is unambiguous.

Definition:

A grammar is *ambiguous* if it contains an ambiguous string.

<https://powcoder.com>

Add WeChat powcoder

AMBIGUOUS GRAMMARS

Definition:

A string is *ambiguous* on a given grammar if it has two different parse trees. Otherwise, it is unambiguous.

Definition:

A grammar is *ambiguous* if it contains an ambiguous string.

Each parse tree has only one leftmost derivation, so this is equivalent to saying that the string has two distinct leftmost derivations.

AMBIGUOUS GRAMMARS

Definition:

A string is *ambiguous* on a given grammar if it has two different parse trees. Otherwise, it is unambiguous.

Definition:

A grammar is *ambiguous* if it contains an ambiguous string.

Each parse tree has only one leftmost derivation, so this is equivalent to saying that the string has two distinct leftmost derivations.

Similarly for rightmost derivations.

IS THIS GRAMMAR AMBIGUOUS?

Assignment Project Exam Help

$$\begin{array}{c} E \rightarrow E - E \\ E \rightarrow a \mid b \mid c \end{array}$$

Rightmost derivations of $a - b - c$:

<https://powcoder.com>

Add WeChat powcoder

IS THIS GRAMMAR AMBIGUOUS?

Assignment Project Exam Help

$$E \rightarrow E - E$$

$$E \rightarrow a \mid b \mid c$$

Rightmost derivations of $a - b - c$:

<https://powcoder.com>

$$E \Rightarrow E - E$$

$$\Rightarrow E - c$$

$$\Rightarrow E - E - c$$

$$\Rightarrow E - b - c$$

$$\Rightarrow a - b - c$$

Add WeChat powcoder

i.e. $(a - b) - c$

IS THIS GRAMMAR AMBIGUOUS?

Assignment Project Exam Help

$$E \rightarrow a \mid b \mid c$$

Rightmost derivations of $a - b - c$:

<https://powcoder.com>

$$E \Rightarrow E - E$$

$$E \Rightarrow E - E$$

$$\Rightarrow E - c$$

$$\Rightarrow E - E - E$$

$$\Rightarrow E - E - c$$

$$\Rightarrow E - E - c$$

$$\Rightarrow E - b - c$$

$$\Rightarrow E - b - c$$

$$\Rightarrow a - b - c$$

$$\Rightarrow a - b - c$$

Add WeChat powcoder

i.e. $(a - b) - c$


i.e. $a - (b - c)$

IS THIS GRAMMAR AMBIGUOUS?

Assignment Project Exam Help

$$E \rightarrow a \mid b \mid c$$

Rightmost derivations of $a - b - c$:



REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

Assignment Project Exam Help

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

<https://powcoder.com>

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

Assignment Project Exam Help

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

Now the only rightmost derivation is:

<https://powcoder.com>

$$E \Rightarrow E - T$$

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

Assignment Project Exam Help

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

Now the only rightmost derivation is:

<https://powcoder.com>

$$E \Rightarrow E - T$$

$$\Rightarrow E - c$$

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

Now the only rightmost derivation is:

$$E \Rightarrow E - T$$

$$\Rightarrow E - c$$

$$\Rightarrow E - T - c$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

Now the only rightmost derivation is:

$$E \Rightarrow E - T$$

$$\Rightarrow E - c$$

$$\Rightarrow E - T - c$$

$$\Rightarrow E - b - c$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

Now the only rightmost derivation is:

$$E \Rightarrow E - T$$

$$\Rightarrow E - c$$

$$\Rightarrow E - T - c$$

$$\Rightarrow E - b - c$$

$$\Rightarrow T - b - c$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

Now the only rightmost derivation is:

$$E \Rightarrow E - T$$

$$\Rightarrow E - c$$

$$\Rightarrow E - T - c$$

$$\Rightarrow E - b - c$$

$$\Rightarrow T - b - c$$

$$\Rightarrow a - b - c$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

REMOVING AMBIGUITY (EXAMPLE)

Suppose we want $a - b - c$ to always mean $(a - b) - c$?

Introduce a new nonterminal symbol T :

$$E \rightarrow E - T \mid T$$

$$T \rightarrow a \mid b \mid c$$

Now the only rightmost derivation is:

$$E \Rightarrow E - T$$


$$\Rightarrow E - c$$

$$\Rightarrow E - T - c$$

$$\Rightarrow E - b - c$$

$$\Rightarrow T - b - c$$

$$\Rightarrow a - b - c$$



RECURSION

If a variable X can generate a string containing X itself, then it is recursive

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

RECURSION

Assignment Project Exam Help

If a variable X can generate a string containing X itself, then it is recursive

- ▶ left-recursive: it occurs at the start of the string $X \Rightarrow^+ X\beta$

<https://powcoder.com>

Add WeChat powcoder

RECURSION

If a variable X can generate a string containing X itself, then it is recursive

Assignment Project Exam Help

- ▶ left-recursive: it occurs at the start of the string $X \Rightarrow^+ X\beta$
- ▶ right-recursive: it occurs at the end of the string $X \Rightarrow^+ \alpha X$

<https://powcoder.com>

Add WeChat powcoder

RECURSION

Assignment Project Exam Help

If a variable X can generate a string containing X itself, then it is recursive

- ▶ left-recursive: it occurs at the start of the string $X \Rightarrow^+ X\beta$
- ▶ right-recursive: it occurs at the end of the string $X \Rightarrow^+ \alpha X$
- ▶ self-embedding: it occurs in between: $X \Rightarrow^+ \alpha X\beta$

<https://powcoder.com>

Add WeChat powcoder

RECURSION

If a variable X can generate a string containing X itself, then it is recursive

Assignment Project Exam Help

- ▶ left-recursive: it occurs at the start of the string $X \Rightarrow^+ X\beta$
- ▶ right-recursive: it occurs at the end of the string $X \Rightarrow^+ \alpha X$
- ▶ self-embedding: it occurs in between: $X \Rightarrow^+ \alpha X \beta$

<https://powcoder.com>

A grammar is recursive if any of its variables is recursive

Add WeChat powcoder

RECURSION

Assignment Project Exam Help

If a variable X can generate a string containing X itself, then it is recursive

- ▶ left-recursive: it occurs at the start of the string $X \Rightarrow^+ X\beta$
- ▶ right-recursive: it occurs at the end of the string $X \Rightarrow^+ \alpha X$
- ▶ self-embedding: it occurs in between: $X \Rightarrow^+ \alpha X\beta$

<https://powcoder.com>

A grammar is recursive if any of its variables is recursive

Add WeChat powcoder

A grammar for an infinite language must contain at least one recursive variable

BALANCED PARENTHESES

Assignment Project Exam Help

This grammar generates the language of balanced parentheses:

<https://powcoder.com>

$B \rightarrow (B) \mid BB \mid \epsilon$

Show that it is ambiguous.

Add WeChat powcoder

REMOVE LEFT RECURSION

Original grammar is left-recursive: $B \rightarrow (B) \mid BB \mid \varepsilon$

An equivalent grammar without left-recursion: $B \rightarrow (B)B \mid \varepsilon$

Left parsing of $()()()$ is now deterministic:

Remaining input	Derivation steps	
$()()()$	B	start symbol
$()()()$	$(B)B$	$B \rightarrow (B)B$
$)()()$	$B)B$	matching terminals
$)()()$	$)B$	$B \rightarrow \varepsilon$
$()()$	B	matching terminals
...

CLEAN GRAMMARS

- ▶ No circular definitions: $A_1 \Rightarrow A_2 \Rightarrow \dots \Rightarrow A_n \Rightarrow A_1$
 All the A 's can generate the same set of strings, therefore there is no reason to distinguish between them. They should be reduced to a single variable.

<https://powcoder.com>

Add WeChat powcoder

CLEAN GRAMMARS

- ▶ No circular definitions: $A_1 \Rightarrow A_2 \Rightarrow \dots \Rightarrow A_n \Rightarrow A_1$
 All the A 's can generate the same set of strings, therefore there is no reason to distinguish between them. They should be reduced to a single variable.

<https://powcoder.com>

- ▶ No useless variables:
 A variable is useless if it cannot appear in the derivation of any string, i.e. there is no derivation $S \Rightarrow^+ \alpha X \beta \Rightarrow^+ \sigma$ where σ is a string of terminals. Useless variables can be removed without affecting the language generated by the grammar.

CLEAN GRAMMARS

- ▶ No circular definitions: $A_1 \Rightarrow A_2 \Rightarrow \dots \Rightarrow A_n \Rightarrow A_1$
 All the A 's can generate the same set of strings, therefore there is no reason to distinguish between them. They should be reduced to a single variable.

<https://powcoder.com>

- ▶ No useless variables:
 A variable is useless if it cannot appear in the derivation of any string, i.e. there is no derivation $S \Rightarrow^+ \alpha X \beta \Rightarrow^+ \sigma$ where σ is a string of terminals. Useless variables can be removed without affecting the language generated by the grammar.
- ▶ No null productions (except for the start symbol)

TYPES OF GRAMMARS

We are interested in 4 classes of grammars, depending on the type

of production rules that they allow:

Type 0 (unrestricted) $\chi \rightarrow \alpha$

Type 1 (context-sensitive) $\chi \rightarrow \alpha$ where $1 \leq |\chi| \leq |\alpha|$

Type 2 (context-free) $A \rightarrow \alpha$

Type 3 (regular) $A \rightarrow \omega B$ and $A \rightarrow \omega$

χ	arbitrary string of one or more symbols
α	arbitrary string of symbols, possibly null
A, B	non-terminal symbols
ω	arbitrary string of terminal symbols

Recall the Chomsky Hierarchy from week 1!

CONTEXT-FREE GRAMMARS

- ▶ Generate Context-Free Languages
 - ▶ Very important class of languages in CS (compilers, NLP, etc)
 - ▶ All rules are in the form $A \rightarrow \alpha$
 - ▶ Closed under Union, Concatenation and Star Closure
 - ▶ String derivation (left-most, right-most)
 - ▶ Ambiguous grammars
 - ▶ Clean grammars

<https://powcoder.com>

Add WeChat powcoder

Next lecture:

- ▶ Push-Down Automata
- ▶ Parsing