

COMP2022: Formal Languages and Logic

2018 Semester 2, Week 3


# Assignment Project Exam Help

Joseph Godbehere

<https://powcoder.com>

16th August, 2018

Add WeChat powcoder



THE UNIVERSITY OF  
SYDNEY

# COMMONWEALTH OF AUSTRALIA

## Copyright Regulations 1969

# Assignment Project Exam Help

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be subject of copyright protect under the Act.

**Do not remove this notice.**

## OUTLINE

# Assignment Project Exam Help

- ▶ Revision - Lambda Calculus

- ▶ Y Combinator

<https://powcoder.com>

- ▶ Encodings

- ▶ numbers (a different way)

- ▶ pars

- ▶ iss

Add WeChat powcoder

- ▶ Functional Programming

WHEN ARE  $\alpha$ -REDUCTIONS REQUIRED?

# Assignment Project Exam Help

If they never change the meaning, why bother?

- ▶ Readability
- ▶  $\beta$ -reduction assumes all variables have different labels
  - ▶ Usually it doesn't matter...
  - ▶ ... except when it does!
  - ▶ ... even worse - it's not enough to only look at the subformula being reduced

<https://powcoder.com>

Add WeChat powcoder

WRONG

# Assignment Project Exam Help

$$\lambda x. (\lambda y. x. y) x$$

$$= \lambda x. (\lambda x. x)$$

$$= \lambda x. (\lambda y. y)$$

$$= \lambda x. y. y$$

$$= FALSE$$

<https://powcoder.com>

## Add WeChat powcoder

- Where is the error?

WRONG

# Assignment Project Exam Help

$$\begin{aligned} & \lambda x. (\lambda y. x. y) x \\ &= \lambda x. (\lambda x. x) \quad \text{(mistake!)} \end{aligned}$$

$$\begin{aligned} &= \lambda x. (\lambda y. y) \\ &= \lambda x y. y \\ &= FALSE \end{aligned}$$

<https://powcoder.com>

## Add WeChat powcoder

- Where is the error?
- Why is it a mistake?

WRONG

# Assignment Project Exam Help

$$\begin{aligned} & \lambda x. (\lambda y. x. y) x \\ &= \lambda x. (\lambda x. x) \quad \text{(mistake!)} \end{aligned}$$

<https://powcoder.com>

$$\begin{aligned} &= \lambda x. (\lambda y. y) \\ &= \lambda x y. y \\ &= FALSE \end{aligned}$$

## Add WeChat powcoder

- ▶ Where is the error?
- ▶ Why is it a mistake?
- ▶  $x$  was bound to the *first*  $\lambda$ , but on line 2 it is not! Free variables in  $N$  should not become bound in  $M[x := N]$

CORRECT

# Assignment Project Exam Help

$$\begin{aligned} & \lambda x.(\lambda yx.y)x \\ &= \lambda x.(\lambda yz.y)x & (\alpha) \\ &= \lambda x.(\lambda z.x) & (\beta) \\ &= \lambda xz.x \\ &= TRUE \end{aligned}$$

## https://powcoder.com

## Add WeChat powcoder

Rule of thumb: always perform  $\alpha$  reductions before  $\beta$  reductions.

- ▶ sometimes it's necessary
- ▶ usually makes the formula easier to read too



## $\eta$ -REDUCTION (ETA)

If  $x$  is not free in  $M$ , then we can write:

Assignment Project Exam Help

Idea: any input applied to this will simply be applied to  $M$

<https://powcoder.com>

Add WeChat powcoder

## $\eta$ -REDUCTION (ETA)

If  $x$  is not free in  $M$ , then we can write:

# Assignment Project Exam Help

$$\lambda x. Mx \equiv M$$

Idea: any input applied to this will simply be applied to  $M$

- ▶ If  $x$  is not free in  $M$ , then  $(\lambda x. Mx)N \equiv Mx[x := N] \equiv MN$ 
  - ▶ Identical to applying  $N$  to  $M$  directly.

# Add WeChat powcoder

# η-REDUCTION (ETA)

If  $x$  is not free in  $M$ , then we can write:

# Assignment Project Exam Help

$$\lambda x. Mx \equiv M$$

Idea: any input applied to this will simply be applied to  $M$

- ▶ If  $x$  is not free in  $M$ , then  $(\lambda x. Mx)N \equiv Mx[x := N] \equiv MN$ 
  - ▶ Identical to applying  $N$  to  $M$  directly.

Uses:

- ▶ It can simplify some arguments a little
  - ▶ e.g.  $\lambda x. (\lambda y. y)x \equiv \lambda y. y$
- ▶ It can help to convert expressions to 'point free' form (where they do not label their variables).
  - ▶ Point-free programs can be easier to reason about, but are often difficult to read.

## OUTLINE

# Assignment Project Exam Help

- ▶ Revision - Lambda Calculus

- ▶ **Y Combinator**

<https://powcoder.com>

- ▶ Encodings

- ▶ numbers (a different way)

- ▶ pars
  - ▶ iss

Add WeChat powcoder

- ▶ Functional Programming

# NECESSARY LOGICAL NOTATION: QUANTIFIERS

Assignment Project Exam Help

- ▶ “for all possible values of  $X$ ...” denoted  $\forall X$
- ▶ “there exists a value of  $X$  such that ...” denoted  $\exists X$

Examples (for all positive rational numbers)

- ▶ “ $\forall x (x * 1 = x)$ ” is true
- ▶ “ $\exists x (x + 1 = 4)$ ” is true (choose  $x = 3$ )
- ▶ “ $\forall x (x + 1 = 4)$ ” is false (e.g. false on  $x = 1$ )
- ▶ “ $\exists x \forall y (xy = 0)$ ” is true (choose  $x = 0$ )
- ▶ “ $\exists x \forall y (xy = 1)$ ” is false (whatever we choose for  $x$ , we’ll be able to find a  $y$  that doesn’t work)
- ▶ “ $\forall x \exists y (xy = 1)$ ” is true (for any  $x$ , we can choose  $y = \frac{1}{x}$ )

## COMBINATORS

**Assignment Project Exam Help**

A *combinator* is any expression  $M$  which contains no free variables.

<https://powcoder.com>

Add WeChat powcoder

# COMBINATORS

Assignment Project Exam Help

A *combinator* is any expression  $M$  which contains no free variables.

Example:

- $\lambda xy.xyz$  is not a combinator ( $z$  is free)

<https://powcoder.com>

Add WeChat powcoder

# COMBINATORS

## Assignment Project Exam Help

A *combinator* is any expression  $M$  which contains no free variables.

Example:

- ▶  $\lambda xy.xyz$  is not a combinator ( $z$  is free)
- ▶  $\lambda xy.xyy$  is a combinator (all variables bound)

Add WeChat powcoder



# COMBINATORS

## Assignment Project Exam Help

A *combinator* is any expression  $M$  which contains no free variables.

Example:

- ▶  $\lambda xy.xyz$  is not a combinator ( $z$  is free)
- ▶  $\lambda xy.xyy$  is a combinator (all variables bound)

## Add WeChat powcoder

Combinators combine values into expressions without relying on quantifiers or explicitly defining variables.

## COMBINATOR EXAMPLES

Standard combinators:

- ▶  $I = \lambda x.x$  (identity)
- ▶  $K = \lambda x y.x$  (true)
- ▶  $K_* = \lambda x y.y$  (false)
- ▶  $S = \lambda x y z.xz(yz)$  (generalisation of application)

<https://powcoder.com>

Add WeChat powcoder

## COMBINATOR EXAMPLES

Standard combinators:

- ▶  $I = \lambda x.x$  (identity)
- ▶  $K = \lambda x y.x$  (true)
- ▶  $K_* = \lambda x y.y$  (false)
- ▶  $S = \lambda x y z.xz(yz)$  (generalisation of application)

We can easily deduce (by using  $\beta$  reduction):

- ▶  $IM = M$
- ▶  $KMN = M$
- ▶  $K_*MN = N$
- ▶  $SMNL = ML(NL)$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## COMBINATOR EXAMPLES

Standard combinators:

- ▶  $I = \lambda x.x$  (identity)
- ▶  $K = \lambda x y.x$  (true)
- ▶  $K_* = \lambda x y.y$  (false)
- ▶  $S = \lambda x y z.xz(yz)$  (generalisation of application)

We can easily deduce (by using  $\beta$  reduction):

- ▶  $IM = M$
- ▶  $KMN = M$
- ▶  $K_*MN = N$
- ▶  $SMNL = ML(NL)$

Interestingly, these  $\lambda$ -free combinators are sufficient to make expressions equal to any  $\lambda$  term. We will not talk about that further today though.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## SOLVING SIMPLE EQUATIONS

Assignment  $\exists C \forall X. C X = X X$  Project Exam Help  
(Where  $X, F$  are expressions in the lambda calculus)

<https://powcoder.com>

Add WeChat powcoder

# SOLVING SIMPLE EQUATIONS

## Assignment $\exists C \forall X. GCX = XXX$ Exam Help

(Where  $X, F$  are expressions in the lambda calculus)

"There exists some  $G$  such that for all  $X$  it's true that  
 $GC = XXX$ "

Proof:

Add WeChat powcoder

## SOLVING SIMPLE EQUATIONS

# Assignment Project Exam Help

(Where  $X, F$  are expressions in the lambda calculus)

"There exists some  $G$  such that for all  $X$  it's true that

$GC = XXX$ "

Proof:

► Let  $G = \lambda x.xxX$

Add WeChat powcoder

## SOLVING SIMPLE EQUATIONS

# Assignment $\exists C \forall X. CX = XXX$ Project Exam Help

(Where  $X, F$  are expressions in the lambda calculus)

"There exists some  $G$  such that for all  $X$  it's true that

$GX = XXX$ "

Proof:

- ▶ Let  $G = \lambda x. xxx$
- ▶ Then  $GX = (\lambda x. xxx)X = XXX$

<https://powcoder.com>  
Add WeChat powcoder



## SOLVING SIMPLE EQUATIONS

# Assignment Exam Help

(Where  $X, F$  are expressions in the lambda calculus)

"There exists some  $G$  such that for all  $X$  it's true that

$GX = XXX$ "

Proof:

- ▶ Let  $G = \lambda x. xxx$
- ▶ Then  $GX = (\lambda x. xxx)X = XXX$

That was easy... But what if we need to reason about a recursive function?

## FIXED POINT COMBINATORS

# Assignment Project Exam Help

A *fixed point combinator* is a combinator which has a fixed point.

<https://powcoder.com>

We say  $F$  has a fixed point if  $\exists X (FX = X)$

Add WeChat powcoder

i.e. some input  $X$  exists which, when applied to  $F$ , outputs  $X$  again.

# FIXED POINT THEOREM (I)

Theorem:

$$\forall F \exists X. FX = X$$

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# FIXED POINT THEOREM (I)

Theorem:

$$\forall F \exists X. FX = X$$

Assignment Project Exam Help

"For all  $F$ , there exists some  $X$  such that  $FX = X$ "

- i.e. all functions have a fixed point

<https://powcoder.com>

Add WeChat powcoder

# FIXED POINT THEOREM (I)

Theorem:

$$\forall F \exists X. FX = X$$

Assignment Project Exam Help

"For all  $F$ , there exists some  $X$  such that  $FX = X$ "

► i.e. all functions have a fixed point

Proof

<https://powcoder.com>

Let  $W = \lambda x. F(xx)$  and  $X = WW$ . Then:

Add WeChat powcoder

## FIXED POINT THEOREM (I)

Theorem:

$$\forall F \exists X. FX = X$$

"For all  $F$ , there exists some  $X$  such that  $FX = X$ "

- i.e. all functions have a fixed point

Proof

Let  $W = \lambda x. F(xx)$  and  $X = WW$ . Then:

$$X = WW$$

(def. of  $X$ )

Add WeChat powcoder

<https://powcoder.com>

# FIXED POINT THEOREM (I)

Theorem:

$$\forall F \exists X. FX = X$$

"For all  $F$ , there exists some  $X$  such that  $FX = X$ "

► i.e. all functions have a fixed point

Proof

Let  $W = \lambda x. F(xx)$  and  $X = WW$ . Then:

$$\begin{aligned}
 X &= WW && \text{(def. of } X\text{)} \\
 &= (\lambda x. F(xx)) W && \text{(def. of } W\text{)} \\
 &=
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# FIXED POINT THEOREM (I)

Theorem:

$$\forall F \exists X. FX = X$$

"For all  $F$ , there exists some  $X$  such that  $FX = X$ "

► i.e. all functions have a fixed point

Proof

Let  $W = \lambda x. F(xx)$  and  $X = WW$ . Then:

$$\begin{aligned}
 X &= WW && \text{(def. of } X\text{)} \\
 &= (\lambda x. F(xx)) W && \text{(def. of } W\text{)} \\
 &= F(WW) && (\beta\text{-reduction)} \\
 &=
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# FIXED POINT THEOREM (I)

Theorem:

$$\forall F \exists X. FX = X$$

"For all  $F$ , there exists some  $X$  such that  $FX = X$ "

► i.e. all functions have a fixed point

Proof

Let  $W = \lambda x. F(xx)$  and  $X = WW$ . Then:

$$\begin{aligned}
 X &= WW && \text{(def. of } X\text{)} \\
 &= (\lambda x. F(xx)) W && \text{(def. of } W\text{)} \\
 &= F(WW) && (\beta\text{-reduction)} \\
 &= FX && \text{(def. of } X\text{)}
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## FIXED POINT THEOREM (II)

There is a fixed point combinator (the “Y Combinator”)

Assignment Project Exam Help

such that

$$\forall F \ F(YF) = YF$$

Proof.

<https://powcoder.com>

$YF =$

Add WeChat powcoder

## FIXED POINT THEOREM (II)

There is a fixed point combinator (the “Y Combinator”)

Assignment Project Exam Help

such that

$$\forall F \ F(YF) = YF$$

Proof.

<https://powcoder.com>

$$YF = \left( \lambda f. (\lambda x. f(xx)) (\lambda x. f(xx)) \right) F \quad (\text{defn. of } Y)$$

Add WeChat powcoder

## FIXED POINT THEOREM (II)

There is a fixed point combinator (the “Y Combinator”)

Assignment Project Exam Help

such that

$$\forall F \ F(YF) = YF$$

Proof.

$$YF = \left( \lambda f. (\lambda x. f(xx)) (\lambda x. f(xx)) \right) F \quad (\text{defn. of } Y)$$

$$= \left( \lambda x. F(xx) \right) \left( \lambda x. F(xx) \right) \quad (\beta\text{-reduction})$$

=

Add WeChat powcoder

<https://powcoder.com>

## FIXED POINT THEOREM (II)

There is a fixed point combinator (the “Y Combinator”)

Assignment Project Exam Help

such that

$$\forall F \ F(YF) = YF$$

Proof.

$$YF = \left( \lambda f. (\lambda x. f(xx)) (\lambda x. f(xx)) \right) F \quad (\text{defn. of } Y)$$

$$= \left( \lambda x. F(xx) \right) \left( \lambda x. F(xx) \right) \quad (\beta\text{-reduction})$$

$$= F \left( (\lambda x. F(xx)) (\lambda x. F(xx)) \right) \quad (\text{by pf. of theorem (i)})$$

=

Add WeChat powcoder

<https://powcoder.com>

## FIXED POINT THEOREM (II)

There is a fixed point combinator (the “Y Combinator”)

Assignment Project Exam Help

such that

$$\forall F \ F(YF) = YF$$

Proof.

<https://powcoder.com>

$$YF = \left( \lambda f. (\lambda x. f(xx)) (\lambda x. f(xx)) \right) F \quad (\text{defn. of } Y)$$

$$= \left( \lambda x. F(xx) \right) \left( \lambda x. F(xx) \right) \quad (\beta\text{-reduction})$$

$$= F \left( (\lambda x. F(xx)) (\lambda x. F(xx)) \right) \quad (\text{by pf. of theorem (i)})$$

$$= F(YF) \quad (\text{by equality above})$$

## Y COMBINATOR

So, uh... Why is this interesting?

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Y COMBINATOR

So, uh... Why is this interesting?

# Assignment Project Exam Help

1. Good news: it allows us to write self recursive functions

► it effectively lets us define variables

<https://powcoder.com>

Add WeChat powcoder



# Y COMBINATOR

So, uh... Why is this interesting?

## Assignment Project Exam Help

1. Good news: it allows us to write self recursive functions

► it effectively lets us define variables

<https://powcoder.com>

2. Bad news: it leads to Curry's Paradox, and the incompleteness of lambda calculus

► not all valid expressions can be proved / computed

Add WeChat powcoder

## RECURSION EXAMPLE

Suppose we want to compute factorials:

**Assignment Project Exam Help**

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n - 1)$$

<https://powcoder.com>

Add WeChat powcoder

## RECURSION EXAMPLE

Suppose we want to compute factorials:

**Assignment Project Exam Help**

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n - 1)$$

We'll need some helper functions / encodings:

- Church numerals:  $c_n = \lambda f x. f^n(x)$

**<https://powcoder.com>**

**Add WeChat powcoder**

## RECURSION EXAMPLE

Suppose we want to compute factorials:

*$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n - 1)$*

We'll need some helper functions / encodings:

- Church numerals:  $c_n = \lambda f x. f^n(x)$

- This notation, indicating  $n$  repetitions of  $f(\dots)$  is a little dangerous (but convenient).

- Be aware that Church numerals have the form:

$$\lambda fz. f(f(f(f(fz)))) \neq \lambda fz. fffffz$$

## RECURSION EXAMPLE

Suppose we want to compute factorials:

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n - 1)$$

We'll need some helper functions / encodings:

► Church numerals:  $c_n = \lambda f x. f^n(x)$

► ISZERO :=  $\lambda n n (\lambda x. FALSE) TRUE$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## RECURSION EXAMPLE

Suppose we want to compute factorials:

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n - 1)$$

We'll need some helper functions / encodings:

- ▶ Church numerals:  $c_n = \lambda f x. f^n(x)$
- ▶  $\text{ISZERO} := \lambda n n (\lambda x. \text{FALSE}) \text{ TRUE}$ 
  - ▶ Returns TRUE if the argument is a Church zero, FALSE if it's any other Church numeral



ISZERO ZERO

# Assignment Project Exam Help

*ISZERO ZERO*

$= (\lambda n.n (\lambda x.FALSE) TRUE) ZERO$  (def. ISZERO)

<https://powcoder.com>

=

Add WeChat powcoder



ISZERO ZERO

# Assignment Project Exam Help

*ISZERO ZERO*

$$= (\lambda n. n (\lambda x. FALSE) TRUE) ZERO \quad (\text{def. ISZERO})$$

$$= TRUE (\lambda x. FALSE) TRUE \quad (\beta)$$

$$=$$

Add WeChat powcoder

ISZERO ZERO

# Assignment Project Exam Help

*ISZERO ZERO*

$$= (\lambda n. n (\lambda x. FALSE) TRUE) ZERO \quad (\text{def. ISZERO})$$

$$= TRUE (\lambda x. FALSE) TRUE \quad (\beta)$$

$$= (\lambda fz. z) (\lambda x. FALSE) TRUE \quad (\text{def. ZERO})$$

Add WeChat powcoder

ISZERO ZERO

# Assignment Project Exam Help

*ISZERO ZERO*

$$= (\lambda n.n (\lambda x.FALSE) TRUE) ZERO \quad (\text{def. ISZERO})$$

$$= TRUE (\lambda x.FALSE) TRUE \quad (\beta)$$

$$= (\lambda fz.z) (\lambda x.FALSE) TRUE \quad (\text{def. ZERO})$$

$$= (\lambda z.z) TRUE \quad (\beta)$$

Add WeChat powcoder

ISZERO ZERO

# Assignment Project Exam Help

*ISZERO ZERO*

$$= (\lambda n.n (\lambda x.FALSE) TRUE) ZERO \quad (\text{def. ISZERO})$$

$$= TRUE (\lambda x.FALSE) TRUE \quad (\beta)$$

$$= (\lambda fz.z) (\lambda x.FALSE) TRUE \quad (\text{def. ZERO})$$

$$= (\lambda z.z) TRUE \quad (\beta)$$

$$= TRUE \quad (\beta)$$

<https://powcoder.com>

Add WeChat powcoder

ISZERO ONE

# Assignment Project Exam Help

*ISZERO ONE*

=  
=  
=  
=  
<https://powcoder.com>

=  
=  
=  
=  
Add WeChat powcoder  
=

ISZERO ONE

# Assignment Project Exam Help

*ISZERO ONE*

$= (\lambda n.n (\lambda x.FALSE) TRUE) ONE$  (def. ISZERO)

<https://powcoder.com>

Add WeChat powcoder

ISZERO ONE

# Assignment Project Exam Help

*ISZERO ONE*

$= (\lambda n.n (\lambda x.FALSE) TRUE) ONE$  (def. ISZERO)

$= ONE (\lambda x.FALSE) TRUE$  ( $\beta$ )

=

=

Add WeChat powcoder

=

ISZERO ONE

# Assignment Project Exam Help

*ISZERO ONE*

$= (\lambda n.n (\lambda x.FALSE) TRUE) ONE$  (def. ISZERO)

$= ONE (\lambda x.FALSE) TRUE$  ( $\beta$ )

$= (\lambda fz.fz) (\lambda x.FALSE) TRUE$  (def. ONE)

=

Add WeChat powcoder

=



ISZERO ONE

# Assignment Project Exam Help

*ISZERO ONE*

$= (\lambda n.n (\lambda x.FALSE) TRUE) ONE$  (def. ISZERO)

$= ONE (\lambda x.FALSE) TRUE$  ( $\beta$ )

$= (\lambda fz.fz) (\lambda x.FALSE) TRUE$  (def. ONE)

$= (\lambda z.(\lambda x.FALSE)z) TRUE$  ( $\beta$ )

Add WeChat powcoder

=

# ISZERO ONE

## Assignment Project Exam Help

*ISZERO ONE*

$= (\lambda n.n (\lambda x.FALSE) TRUE) ONE$  (def. ISZERO)

$= ONE (\lambda x.FALSE) TRUE$  ( $\beta$ )

$= (\lambda fz.fz) (\lambda x.FALSE) TRUE$  (def. ONE)

$= (\lambda z.(\lambda x.FALSE)z) TRUE$  ( $\beta$ )

$= (\lambda x.FALSE) TRUE$  ( $\beta$ )

$=$

Add WeChat powcoder

# ISZERO ONE

## Assignment Project Exam Help

*ISZERO ONE*

$= (\lambda n.n (\lambda x.FALSE) TRUE) ONE$  (def. ISZERO)

$= ONE (\lambda x.FALSE) TRUE$  ( $\beta$ )

$= (\lambda fz.fz) (\lambda x.FALSE) TRUE$  (def. ONE)

$= (\lambda z.(\lambda x.FALSE)z) TRUE$  ( $\beta$ )

$= (\lambda x.FALSE) TRUE$  ( $\beta$ )

$= FALSE$  ( $\beta$ )

<https://powcoder.com>  
Add WeChat powcoder

## RECURSION EXAMPLE

Suppose we want to compute factorials:

**Assignment Project Exam Help**

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n-1)$$

We'll need some helper functions / encodings:

- Church numerals:  $c_n := \lambda f x. f^n(x)$
- $\text{ISZERO} := \lambda n. n(\lambda x. \text{FALSE}) \text{ TRUE}$
- $\text{MULT} := \lambda xyz. x(yz)$  (seen previously)

**Add WeChat powcoder**

## RECURSION EXAMPLE

Suppose we want to compute factorials:

**Assignment Project Exam Help**

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n-1)$$

We'll need some helper functions / encodings:

- ▶ Church numerals:  $0 := \lambda f x. f^0(x)$
- ▶  $\text{ISZERO} := \lambda n. n (\lambda x. \text{FALSE}) \text{ TRUE}$
- ▶  $\text{MULT} := \lambda xyz. x(yz)$  (seen previously)
- ▶  $\text{PRED} := \lambda n f x y. n (\lambda g h. h (g f)) (\lambda y. x) (\lambda u. u)$ 
  - ▶ This gives the predecessor of a number
  - ▶  $\text{PRED } 1 = 0$ ,  $\text{PRED } 2 = 1$ , ...,  $\text{PRED } n = (n-1)$
  - ▶ The derivation of this is *much* longer than for the operations which increase numbers

# RECURSION EXAMPLE

Suppose we want to compute factorials:

**Assignment Project Exam Help**

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n-1)$$

We'll need some helper functions / encodings:

- ▶ Church numerals:  $c_n := \lambda f x. f^n(x)$
- ▶ ISZERO :=  $\lambda n. n (\lambda x. FALSE) TRUE$
- ▶ MULT :=  $\lambda xyz. x(yz)$  (seen previously)
- ▶ PRED :=  $\lambda n f g n (\lambda g h. h(fg)) (\lambda y. x) (\lambda u. u)$ 
  - ▶ This gives the predecessor of a number
  - ▶ PRED 1 = 0, PRED 2 = 1, ..., PRED n = (n-1)
  - ▶ The derivation of this is *much* longer than for the operations which increase numbers
    - ▶ Subtraction and division are also difficult!

# PRED TWO... IS A MONSTER

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}
 \text{PRED TWO} &= \lambda nfx. n(\lambda ygh.h(gf))(\lambda y.x)(\lambda u.u) \quad \text{PRED TWO} \\
 &= \lambda fx. \text{PRED TWO} (\lambda gh.h(gf))(\lambda y.x)(\lambda u.u) \\
 &= \lambda fx. (\lambda ab.a(ab))(\lambda gh.h(gf))(\lambda y.x)(\lambda u.u) \\
 &= \lambda fx. ((\lambda b. (\lambda gh.h(gf)) ((\lambda gh.h(gf)) b)))(\lambda y.x)(\lambda u.u) \\
 &= \lambda fx. (\lambda gh.h(gf)) ((\lambda gh.h(gf))(\lambda y.x))(\lambda u.u) \\
 &= \lambda fx. (\lambda gh.h(gf)) ((\lambda h.h((\lambda y.x)f)))(\lambda u.u) \\
 &= \lambda fx. (\lambda gh.h(gf))(\lambda h.hx)(\lambda u.u) \\
 &= \lambda fx. (\lambda gh.h(gf))(\lambda i.ix)(\lambda u.u) \\
 &= \lambda fx. (\lambda h.h((\lambda i.ix)f))(\lambda u.u) \\
 &= \lambda fx. (\lambda h.h(fx))(\lambda u.u) \\
 &= \lambda fx. (\lambda u.u)(fx)) = \lambda fx.fx = \text{ONE}
 \end{aligned}$$

## RECURSION EXAMPLE

# Assignment Project Exam Help

Suppose we want to compute factorials:

$$f(n) = \text{if } (n == 0) \text{ then } 1 \text{ else } n * f(n - 1)$$

We'll need some helper functions / encodings:

- ▶ Church numerals:  $c_n = \lambda f x. f^n(x)$
- ▶ ISZERO :=  $\lambda n. n(\lambda x. FALSE) TRUE$
- ▶ MULT :=  $\lambda x y z. x(yz)$
- ▶ PRED :=  $\lambda n f x. n(\lambda g h. h(gf))(\lambda y. x)(\lambda u. u)$

<https://powcoder.com>  
Add WeChat powcoder



## RECURSION EXAMPLE

We want to write something like:

"FACT n := (ISZERO n) - (MULT a (FACT (PREP n)))"

We can't directly define functions self referentially, so we use the Y Combinator:

<https://powcoder.com>

Add WeChat powcoder

## RECURSION EXAMPLE

We want to write something like:

"FACT  $n := (ISZERO\ n) \ 1 \ (MULT\ n \ (FACT\ (PRED\ n)))$ "

We can't directly define functions self referentially, so we use the Y Combinator:

►  $H = \lambda f n. (ISZERO\ n) \ 1 \ (MULT\ n \ (f\ (PRED\ n)))$

►  $H$  takes a function and a number. If the number is zero, it returns 1, otherwise it returns the product of  $n$  and  $(n-1)$ .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## RECURSION EXAMPLE

We want to write something like:

"`FACT n := (ISZERO n) 1 (MULT n (FACT (PRED n)))`"

We can't directly define functions self referentially, so we use the Y Combinator:

►  $H = \lambda f n. (ISZERO\ n)\ 1\ (MULT\ n\ (f\ (PRED\ n)))$

►  $H$  takes a function and a number. If the number is zero, it returns 1, otherwise it returns the product of  $n$  and  $(n-1)$ .

►  $FACTORIAL = Y\ H$

► Because  $YH = H(YH)$ , the Y Combinator helps us to apply the  $H$  function to itself

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## FACTORIAL 5(OVERVIEW)

►  $H = \lambda f n. (ISZERO\ n)\ 1\ (MULT\ n\ (f\ (PRED\ n)))$

►  $FACTORIAL = Y\ H$

$H$  takes a function  $f$  and a number  $n$ . It returns 1 if the number is 0, otherwise the product of  $n$  and  $f(n - 1)$

<https://powcoder.com>  
FACTORIAL5

Add WeChat powcoder

## FACTORIAL 5(OVERVIEW)

►  $H = \lambda f n. (ISZERO\ n)\ 1\ (MULT\ n\ (f\ (PRED\ n)))$

►  $FACTORIAL = Y\ H$

$H$  takes a function  $f$  and a number  $n$ . It returns 1 if the number is 0, otherwise the product of  $n$  and  $f(n - 1)$

<https://powcoder.com>  
 $FACTORIAL\ 5 = (Y\ H)\ 5$

Add WeChat powcoder

## FACTORIAL 5(OVERVIEW)

►  $H = \lambda f n. (ISZERO\ n)\ 1\ (MULT\ n\ (f\ (PRED\ n)))$

►  $FACTORIAL = Y\ H$

$H$  takes a function  $f$  and a number  $n$ . It returns 1 if the number is 0, otherwise the product of  $n$  and  $f(n - 1)$

<https://powcoder.com>

$FACTORIAL\ 5 = (Y\ H)\ 5$

$= H\ (Y\ H)\ 5$  (Y Combinator!)

Add WeChat powcoder

## FACTORIAL 5(OVERVIEW)

►  $H = \lambda f n. (ISZERO\ n)\ 1\ (MULT\ n\ (f\ (PRED\ n)))$

►  $FACTORIAL = Y\ H$

$H$  takes a function  $f$  and a number  $n$ . It returns 1 if the number is 0, otherwise the product of  $n$  and  $f(n - 1)$

<https://powcoder.com>

$FACTORIAL\ 5 = (Y\ H)\ 5$

$= H\ (Y\ H)\ 5$  (Y Combinator!)

$= 5 * ((Y\ H)\ 4)$  (because  $5 \neq 0$ )

Add WeChat powcoder

## FACTORIAL 5(OVERVIEW)

►  $H = \lambda f n. (ISZERO\ n)\ 1\ (MULT\ n\ (f\ (PRED\ n)))$

►  $FACTORIAL = Y\ H$

$H$  takes a function  $f$  and a number  $n$ . It returns 1 if the number is 0, otherwise the product of  $n$  and  $f(n - 1)$

<https://powcoder.com>

$FACTORIAL\ 5 = (Y\ H)\ 5$

$= H\ (Y\ H)\ 5$  (Y Combinator!)

$= 5 * ((Y\ H)\ 4)$  (because  $5 \neq 0$ )

$= \dots$

$= 120 * ((Y\ H)\ 0)$

Assignment Project Exam Help

Add WeChat powcoder



## FACTORIAL 5(OVERVIEW)

►  $H = \lambda f n. (ISZERO\ n)\ 1\ (MULT\ n\ (f\ (PRED\ n)))$

►  $FACTORIAL = Y\ H$

$H$  takes a function  $f$  and a number  $n$ . It returns 1 if the number is 0, otherwise the product of  $n$  and  $f(n - 1)$

<https://powcoder.com>

$FACTORIAL\ 5 = (Y\ H)\ 5$

$= H\ (Y\ H)\ 5$  (Y Combinator!)

$= 5 * ((Y\ H)\ 4)$  (because  $5 \neq 0$ )

$= \dots$

$= 120 * ((Y\ H)\ 0)$

$= 120 * 1 = 120$

Add WeChat powcoder

## FACTORIAL 3 (DETAILED 1)

*FACTORIAL 3*  
Assignment Project Exam Help

=

= <https://powcoder.com>

=

= Add WeChat powcoder

=

=

=

## FACTORIAL 3 (DETAILED 1)

*FACTORIAL 3*  
Assignment Project Exam Help

=

= <https://powcoder.com>

=

= Add WeChat powcoder

=

=

=

## FACTORIAL 3 (DETAILED 1)

*FACTORIAL 3*  
 ~~$= Y H\ 3$~~  Assignment Project Exam Help

$= H\ (Y\ H)\ 3$

(Y Combinator)

$= \text{https://powcoder.com}$

$=$

$= \text{Add WeChat powcoder}$

$=$

$=$

$=$

## FACTORIAL 3 (DETAILED 1)

*FACTORIAL 3*  
 $= Y H 3$

$= H (Y H) 3$  (Y Combinator)

$= \left( \lambda n. (ISZERO\ n) 1 (MULT\ n\ (f(PRED\ n))) \right) (YH) 3$  (H)

$=$

$=$  Add WeChat powcoder

$=$

$=$

$=$

## FACTORIAL 3 (DETAILED 1)

*FACTORIAL 3*  
 $= Y H 3$   
 Assignment Project Exam Help

$= H (Y H) 3$  (Y Combinator)

$= \left( \lambda n. (ISZERO\ n) 1 \left( MULT\ n \left( f(PRED\ n) \right) \right) \right) (YH) 3$  (H)

$= \left( \lambda n. (ISZERO\ n) 1 \left( MULT\ n (YH(PRED\ n)) \right) \right) 3$  ( $\beta$ )

$=$  Add WeChat powcoder

$=$

$=$

$=$

## FACTORIAL 3 (DETAILED 1)

*FACTORIAL 3*  
 $= Y H 3$   
 Assignment Project Exam Help

$= H (Y H) 3$  (Y Combinator)

$= (\lambda n. (ISZERO\ n) 1 (MULT\ n\ (f(PRED\ n)))) (YH) 3$  (H)

$= (\lambda n. (ISZERO\ n) 1 (MULT\ n\ (YH(PRED\ n)))) 3$  ( $\beta$ )

$= (ISZERO\ 3) 1 (MULT\ 3\ (Y H (PRED\ 3)))$  ( $\beta$ )

$=$

$=$

$=$

Add WeChat powcoder

# FACTORIAL 3 (DETAILED 1)

Assignment Project Exam Help

$$\begin{aligned}
 & \text{FACTORIAL 3} \\
 &= Y H 3 \\
 &= H (Y H) 3 \quad (\text{Y Combinator}) \\
 &= (\lambda n. (ISZERO n) 1 (MULT n (f (PRED n)))) (YH) 3 \quad (H) \\
 &= (\lambda n. (ISZERO n) 1 (MULT n (YH (PRED n)))) 3 \quad (\beta) \\
 &= (ISZERO 3) 1 (MULT 3 (Y H (PRED 3))) \quad (\beta) \\
 &= \dots = FALSE 1 (MULT 3 (Y H (PRED 3))) \quad (3 \neq 0) \\
 &= \\
 &=
 \end{aligned}$$



# FACTORIAL 3 (DETAILED 1)

Assignment Project Exam Help

$$\begin{aligned}
 & \text{FACT} 3 \\
 &= Y H 3 \\
 &= H (Y H) 3 \quad (\text{Y Combinator}) \\
 &= (\lambda n. (ISZERO n) 1 (MULT n (f (PRED n)))) (YH) 3 \quad (H) \\
 &= (\lambda n. (ISZERO n) 1 (MULT n (YH (PRED n)))) 3 \quad (\beta) \\
 &= (ISZERO 3) 1 (MULT 3 (Y H (PRED 3))) \quad (\beta) \\
 &= \dots = FALSE 1 (MULT 3 (Y H (PRED 3))) \quad (3 \neq 0) \\
 &= \dots = MULT 3 (Y H (PRED 3)) \quad (\text{def. FALSE}) \\
 &=
 \end{aligned}$$

## FACTORIAL 3 (DETAILED 1)

*FACTORIAL 3*  
 $= Y H 3$   
 Assignment Project Exam Help

$= H (Y H) 3$  (Y Combinator)

$= (\lambda n. (ISZERO\ n) 1 (MULT\ n\ (f(PRED\ n)))) (YH) 3$  (H)

$= (\lambda n. (ISZERO\ n) 1 (MULT\ n\ (YH(PRED\ n)))) 3$  ( $\beta$ )

$= (ISZERO\ 3) 1 (MULT\ 3\ (Y H (PRED\ 3)))$  ( $\beta$ )

$= \dots = FALSE\ 1 (MULT\ 3\ (Y H (PRED\ 3)))$  ( $3 \neq 0$ )

$= \dots = MULT\ 3\ (Y H (PRED\ 3))$  (def. *FALSE*)

$= \dots = MULT\ 3\ (Y H\ 2)$  ( $PRED\ 3 = 2$ )

<https://powcoder.com>  
 Add WeChat powcoder

## FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

*= ... = MULT 3 (Y H 2)*

<https://powcoder.com>

Add WeChat powcoder

## FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

$= \dots = \text{MULT } 3 (Y \ H \ 2)$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (Y \ H \ 1))$

<https://powcoder.com>

=

=

Add WeChat powcoder

=

=

## FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

$= \dots = \text{MULT } 3 (Y \ H \ 2)$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (Y \ H \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 (Y \ H \ 0)))$

$=$

$=$

Add WeChat powcoder

$=$

$=$

## FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

$= \dots = \text{MULT } 3 (Y \ H \ 2)$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (Y \ H \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 (Y \ H \ 0)))$

$= \dots = \dots (\text{ISZERO } 0) \ 1 \dots$

Add WeChat powcoder

=

=

# FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

$= \dots = \text{MULT } 3 \text{ (Y H 2)}$

$= \dots = \text{MULT } 3 \text{ (MULT } 2 \text{ (Y H 1))}$

<https://powcoder.com>

$= \dots = \text{MULT } 3 \text{ (MULT } 2 \text{ (MULT } 1 \text{ (Y H 0))})}$

$= \dots = \dots (\text{ISZERO } 0) \text{ 1} \dots$

$= \dots = \text{MULT } 3 \text{ (MULT } 2 \text{ (MULT } 1 \text{ 1))}$

Add WeChat powcoder

$=$

$=$

## FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

$= \dots = \text{MULT } 3 (Y \ H \ 2)$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (Y \ H \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 (Y \ H \ 0)))$

$= \dots = \dots (\text{ISZERO } 0) \ 1 \dots$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 \ 1)$

$=$

$=$

Add WeChat powcoder



## FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

$= \dots = \text{MULT } 3 (Y \ H \ 2)$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (Y \ H \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 (Y \ H \ 0)))$

$= \dots = \dots (\text{ISZERO } 0) \ 1 \dots$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 \ 1)$

$= \dots = \text{MULT } 3 \ 2$

$=$

Add WeChat powcoder

## FACTORIAL 3 (DETAILED 2)

Assignment Project Exam Help

$= \dots = \text{MULT } 3 (Y \ H \ 2)$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (Y \ H \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 (Y \ H \ 0)))$

$= \dots = \dots(\text{ISZERO } 0) \ 1 \dots$

$= \dots = \text{MULT } 3 (\text{MULT } 2 (\text{MULT } 1 \ 1))$

$= \dots = \text{MULT } 3 (\text{MULT } 2 \ 1)$

$= \dots = \text{MULT } 3 \ 2$

$= \dots = 6$

Add WeChat powcoder

## Y COMBINATOR REMINDER

# Assignment Project Exam Help

This worked because the Y Combinator

$$Y = \lambda f. (\lambda x. f(xx)) (\lambda x. f(xx))$$

Has the property that  $F(YF) = YF$  for all  $F$ .

Important:

- ▶ When performing the reductions, use that property
- ▶ *Don't*  $\beta$ -reduce the Y Combinator directly.

<https://powcoder.com>

Add WeChat powcoder

## OUTLINE

# Assignment Project Exam Help

- ▶ Revision - Lambda Calculus

- ▶ Y Combinator

<https://powcoder.com>

- ▶ **Encodings**

- ▶ numbers (a different way)

- ▶ pars
- ▶ iss

Add WeChat powcoder

- ▶ Functional Programming

# BOOLEANS

## Assignment Project Exam Help

Reminder: our definition of Church Booleans lets us write:

*if B then P else Q*

simply as:

*B P Q*

where *B* is some boolean, i.e. anything which reduces to

- ▶ *TRUE* =  $\lambda xy.x$ , or
- ▶ *FALSE* =  $\lambda xy.y$

<https://powcoder.com>

Add WeChat powcoder

## PAIRS (BARENDREGT STYLE)

Let  $P, Q$  be expressions in the lambda calculus.

If we write:

$$[M, N] = \lambda z. (if\ z\ then\ M\ else\ N)$$

<https://powcoder.com>

Then:

- ▶  $[M, N]\ TRUE = M$
- ▶  $[M, N]\ FALSE = N$

We can use  $[M, N]$  to denote an ordered pair.

Add WeChat powcoder

## PAIRS (BARENDREGT)

Assignment Project Exam Help

$$\begin{aligned}
 [M, N] \text{ TRUE} &= (\lambda z. z \ M \ N) \text{ TRUE} \\
 &= \text{TRUE} \ M \ N \\
 &= (\lambda xy. x) \ M \ N \\
 &= (\lambda y. M) \ N \\
 &= M
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

# PAIRS (BARENDREGT)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}
 [M, N] \text{ TRUE} &= (\lambda z. z \ M \ N) \text{ TRUE} \\
 &= \text{TRUE } M \ N \\
 &= (\lambda xy. x) \ M \ N \\
 &= (\lambda y. M) \ N \\
 &= M
 \end{aligned}$$

$$\begin{aligned}
 [M, N] \text{ FALSE} &= (\lambda z. z \ M \ N) \text{ FALSE} \\
 &= \text{FALSE } M \ N \\
 &= (\lambda xy. y) \ M \ N \\
 &= (\lambda y. y) \ N \\
 &= N
 \end{aligned}$$



## NUMBERS (BARENDREGT STYLE)

Recall that predecessor, subtraction, division were difficult in the Church encoding.

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# NUMBERS (BARENDREGT STYLE)

Recall that predecessor, subtraction, division were difficult in the Church encoding.

We can use pairs to make another encoding for numbers:

- ▶  $0 = 1 = \lambda x.x$
- ▶  $n + 1 = [FALSE, n]$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

## NUMBERS (BARENDREGT STYLE)

Recall that predecessor, subtraction, division were difficult in the Church encoding.

We can use pairs to make another encoding for numbers:

- ▶  $0 = I = \lambda x.x$
- ▶  $n + 1 = [FALSE, n]$

For example:

- ▶  $1 = [FALSE, 0] = [FALSE, I] = \lambda z.z(\lambda xy.y)(\lambda x.x)$

## NUMBERS (BARENDREGT STYLE)

Recall that predecessor, subtraction, division were difficult in the Church encoding.

# Assignment Project Exam Help

We can use pairs to make another encoding for numbers:

►  $0 = I = \lambda x.x$

►  $n + 1 = [FALSE, n]$

For example:

►  $1 = [FALSE, 0] = [FALSE, I] = \lambda z.z(\lambda xy.y)(\lambda x.x)$

►  $2 = [FALSE, 1] = [FALSE, [FALSE, I]]$

<https://powcoder.com>

Add WeChat powcoder

# NUMBERS (BARENDREGT STYLE)

Recall that predecessor, subtraction, division were difficult in the Church encoding.

# Assignment Project Exam Help

We can use pairs to make another encoding for numbers:

- ▶  $0 = I = \lambda x.x$
- ▶  $n + 1 = [FALSE, n]$

For example:

- ▶  $1 = [FALSE, 0] = [FALSE, I] = \lambda z.z(\lambda xy.y)(\lambda x.x)$
- ▶  $2 = [FALSE, 1] = [FALSE, [FALSE, I]]$
- ▶  $3 = [FALSE, 2] = [FALSE, [FALSE, [FALSE, I]]]$

<https://powcoder.com>

Add WeChat powcoder

## NUMBERS (BARENDREGT STYLE)

Some of the operators are a *lot* simpler:

- ▶  $SUCC = \lambda x.[FALSE, x]$  (the next number)
  - ▶ This simply puts another FALSE in front.
  - ▶  $SUCC\ ONE = (\lambda x.[FALSE, x])\ ONE = [FALSE, ONE] = [FALSE, [FALSE, I]]$
- ▶  $PRED = \lambda x.x\ FALSE$  (the previous number)
  - ▶  $PRED\ ONE = (\lambda x.x\ FALSE)\ ONE = ONEFALSE = [FALSE, I]FALSE = I$
- ▶  $ISZERO = \lambda x.x\ TRUE$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## NUMBERS (BARENDREGT STYLE)

Some of the operators are a *lot* simpler:

- ▶  $SUCC = \lambda x.[FALSE, x]$  (the next number)
  - ▶ This simply puts another FALSE in front.
  - ▶  $SUCC\ ONE = (\lambda x.[FALSE, x])\ ONE = [FALSE, ONE] = [FALSE, [FALSE, I]]$
- ▶  $PRED = \lambda x.x\ FALSE$  (the previous number)
  - ▶  $PRED\ ONE = (\lambda x.x\ FALSE)\ ONE = ONEFALSE = [FALSE, I]FALSE = I$
- ▶  $ISZERO = \lambda x.x\ TRUE$

... recall that PRED for the Church numerals was

$$\lambda nfx.n(\lambda gh.h(gf))(\lambda y.x)(\lambda u.u)$$

## NUMBERS (BARENDREGT STYLE)

Addition is more complex, but quite intuitive

- base case:  $ADD(0, y) = y$
- recursive case:  $ADD(x, y) = 1 + ADD(x - 1, y)$

<https://powcoder.com>

Add WeChat powcoder



## NUMBERS (BARENDREGT STYLE)

Addition is more complex, but quite intuitive

# Assignment Project Exam Help

- base case:  $ADD(0, y) = y$
- recursive case:  $ADD(x, y) = 1 + ADD(x - 1, y)$

<https://powcoder.com>

To implement the recursion we can use the Y Combinator again:

$$ADD = Y \left( \lambda f. \lambda x. (ISZERO\ x) ? (SUCCE(f(PRED\ x))\ y) \right)$$

Add WeChat powcoder

- i.e.  $Y$  "if  $x$  is 0 then  $y$  else  $(1 + f(x - 1, y))$ "

## GENERALISED RECURSION

# Assignment Project Exam Help

We can generalise this idea of recursion to support an arbitrary number of variables, base and recursive cases.

<https://powcoder.com>

See section 3.11 in the reference text (Barendregt) if you're interested in the fine details of this.

Add WeChat powcoder

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$FIRST\ (PAIR\ a\ b) =$

$=$

$=$

$=$

$=$

$=$

$=$

$=$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$$FIRST\ (PAIR\ a\ b) = (\lambda p.p\ TRUE)\ (PAIR\ a\ b)$$

=

=

=

=

=

=

=

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$$FIRST\ (PAIR\ a\ b) = (\lambda p.p\ TRUE)\ (PAIR\ a\ b)$$

$$= PAIR\ a\ b\ TRUE$$

=

Add WeChat powcoder

=

=

=

=

Assignment Project Exam Help

<https://powcoder.com>

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$$FIRST\ (PAIR\ a\ b) = (\lambda p.p\ TRUE)\ (PAIR\ a\ b)$$

$$= PAIR\ a\ b\ TRUE$$

$$= (\lambda xyz.zxy)\ a\ b\ TRUE$$

Add WeChat powcoder

=  
=  
=  
=  
=  
=

Assignment Project Exam Help

<https://powcoder.com>

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$$FIRST\ (PAIR\ a\ b) = (\lambda p.p\ TRUE)\ (PAIR\ a\ b)$$

$$= PAIR\ a\ b\ TRUE$$

$$= (\lambda xyz.zxy)\ a\ b\ TRUE$$

$$= (\lambda yx.zxy)\ b\ TRUE$$

$$=$$

$$=$$

$$=$$

$$=$$

$$=$$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p \ TRUE$
- ▶  $SECOND = \lambda p.p \ FALSE$

e.g.

$$FIRST (PAIR\ a\ b) = (\lambda p.p \ TRUE) (PAIR\ a\ b)$$

$$= PAIR\ a\ b \ TRUE$$

$$= (\lambda xyz.zxy)\ a\ b \ TRUE$$

$$= (\lambda yz.zay)\ b \ TRUE$$

$$= (\lambda z.zab)\ TRUE$$

$$=$$

$$=$$

$$=$$

$$=$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$$FIRST\ (PAIR\ a\ b) = (\lambda p.p\ TRUE)\ (PAIR\ a\ b)$$

$$= PAIR\ a\ b\ TRUE$$

$$= (\lambda xyz.zxy)\ a\ b\ TRUE$$

$$= (\lambda yz.zay)\ b\ TRUE$$

$$= (\lambda z.zab)\ TRUE$$

$$= TRUE\ a\ b$$

$$=$$

$$=$$

$$=$$

Add WeChat powecoder

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$$FIRST\ (PAIR\ a\ b) = (\lambda p.p\ TRUE)\ (PAIR\ a\ b)$$

$$= PAIR\ a\ b\ TRUE$$

$$= (\lambda xyz.zxy)\ a\ b\ TRUE$$

$$= (\lambda yz.zay)\ b\ TRUE$$

$$= (\lambda z.zab)\ TRUE$$

$$= TRUE\ a\ b$$

$$= (\lambda xy.x)ab$$

$$=$$

$$=$$

Add WeChat powecoder

## PAIRS (CHURCH)

Similar idea, but not identical to the encoding Barendregt uses.

- ▶  $PAIR = \lambda xyz.zxy$
- ▶  $FIRST = \lambda p.p\ TRUE$
- ▶  $SECOND = \lambda p.p\ FALSE$

e.g.

$$FIRST\ (PAIR\ a\ b) = (\lambda p.p\ TRUE)\ (PAIR\ a\ b)$$

$$= PAIR\ a\ b\ TRUE$$

$$= (\lambda xyz.zxy)\ a\ b\ TRUE$$

$$= (\lambda yz.zay)\ b\ TRUE$$

$$= (\lambda z.zab)\ TRUE$$

$$= TRUE\ a\ b$$

$$= (\lambda xy.x)ab$$

$$= (\lambda y.a)b$$

$$= a$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

# Assignment Project Exam Help

Idea: lists are pairs of (head, tail)

- ▶ head is the *first* list entry
- ▶ tail is *everything else* in the list.

<https://powcoder.com>

Add WeChat powcoder

I will denote lists as  $\{a, b, c, d, \dots\}$

## LIST (CHURCH)

We need a way to signal if the list is empty.

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

We need a way to signal if the list is empty.

Idea: each list entry is a nested pair (isempty, (head, tail))

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

We need a way to signal if the list is empty.

Idea: each list entry is a nested pair (isempty, (head, tail))

- ▶ Empty list =  $NIL = PAIR\ TRUE\ TRUE$
- ▶ Non-empty list =  $PAIR\ FALSE\ (PAIR\ head\ tail)$
- ▶ i.e. each list entry has a boolean acting as a sentinel, signaling if this sublist is empty

Add WeChat powcoder

## LIST (CHURCH)

We need a way to signal if the list is empty.

Idea: each list entry is a nested pair (isempty, (head, tail))

- ▶ Empty list =  $NIL = PAIR\ TRUE\ TRUE$
- ▶ Non-empty list =  $PAIR\ FALSE\ (PAIR\ head\ tail)$
- ▶ i.e. each list entry has a boolean acting as a sentinel, signaling if this sublist is empty

A list containing  $\{a, b, c, d\}$  would look like:

$(PAIR\ FALSE\ (PAIR\ a$   
 $(PAIR\ FALSE\ (PAIR\ b$   
 $(PAIR\ FALSE\ (PAIR\ c$   
 $(PAIR\ FALSE\ (PAIR\ d\ NIL))))))$



## LIST (CHURCH)

# Assignment Project Exam Help

To make our lists useful, we want the following functions:

- ▶ *NIL* is an empty list
- ▶ *ISNIL* checks if the list is empty
- ▶ *HEAD* gets the first element
- ▶ *TAIL* gets the rest
- ▶ *CONS* prepends a given value to the head of a given list

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

# Assignment Project Exam Help

Encoding:

- ▶  $NIL =$
- ▶  $ISNIL =$
- ▶  $HEAD =$
- ▶  $TAIL =$
- ▶  $CONS =$

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

# Assignment Project Exam Help

Encoding:

▶  $NIL = PAIR\ TRUE\ TRUE$  (an empty list)

▶  $ISNIL =$  <https://powcoder.com>

▶  $HEAD =$

▶  $TAIL =$

▶  $CONS =$  Add WeChat powcoder

## LIST (CHURCH)

# Assignment Project Exam Help

Encoding:

►  $NIL = PAIR\ TRUE\ TRUE$  (an empty list)

►  $ISNIL = FIRST$  (is the list empty)

►  $HEAD =$

►  $TAIL =$

►  $CONS =$

<https://powcoder.com>

Add WeChat powcoder

# LIST (CHURCH)

## Assignment Project Exam Help

Encoding:

- ▶  $NIL = PAIR\ TRUE\ TRUE$  (an empty list)
- ▶  $ISNIL = FIRST$  (is the list empty)
- ▶  $HEAD = \lambda z.FIRST\ (SECONDz)$
- ▶  $TAIL =$
- ▶  $CONS =$

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

# Assignment Project Exam Help

Encoding:

►  $NIL = PAIR\ TRUE\ TRUE$  (an empty list)

►  $ISNIL = FIRST$  (is the list empty)

►  $HEAD = \lambda z.FIRST\ (SECONDz)$

►  $TAIL = \lambda z.SECOND\ (SECONDz)$

►  $CONS =$

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

# Assignment Project Exam Help

Encoding:

►  $NIL = PAIR\ TRUE\ TRUE$  (an empty list)

►  $ISNIL = FIRST$  (is the list empty)

►  $HEAD = \lambda z.FIRST\ (SECONDz)$

►  $TAIL = \lambda z.SECOND\ (SECONDz)$

►  $CONS = \lambda ht.PAIR\ FALSE\ (PAIR\ ht)$

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

Example:

*ISNIL NIL*  
=  
<https://powcoder.com>  
=  
Add WeChat powcoder  
=  
=



# LIST (CHURCH)

Example:

Assignment Project Exam Help

*ISNIL NIL*  
 = *FIRST NIL*

<https://powcoder.com>

Add WeChat powcoder

# LIST (CHURCH)

Example:

Assignment Project Exam Help

*ISNIL NIL*

*= FIRST NIL*

*= (λp.p TRUE) NIL*

<https://powcoder.com>

*=*

Add WeChat powcoder

*=*

# LIST (CHURCH)

Example:

Assignment Project Exam Help

*IS NIL NIL*

*= FIRST NIL*

*= (λp.p TRUE) NIL*

*= NIL TRUE*

*=*

*=* Add WeChat powcoder

*=*

# LIST (CHURCH)

Example:

Assignment Project Exam Help

*IS NIL NIL*

*= FIRST NIL*

*= (λp.p TRUE) NIL*

*= NIL TRUE*

*= PAIR TRUE TRUE TRUE*

Add WeChat powcoder

*=*

# LIST (CHURCH)

Example:

Assignment Project Exam Help

$IS\ NIL\ NIL$   
 $=\ FIRST\ NIL$

$= (\lambda p.p\ TRUE)\ NIL$   
 $=\ NIL\ TRUE$

$=\ PAIR\ TRUE\ TRUE\ TRUE$

$= (\lambda x y z.z\ (x\ y\ z))\ TRUE\ TRUE\ TRUE$   
 $=$   
 $=$

Add WeChat powcoder

# LIST (CHURCH)

Example:

Assignment Project Exam Help

*IS NIL NIL*

*= FIRST NIL*

*= (λp.p TRUE) NIL*

*= NIL TRUE*

*= PAIR TRUE TRUE TRUE*

*= (λxjz.zg) TRUE TRUE TRUE*

*= ... = TRUE TRUE TRUE*

*=*

<https://powcoder.com>

Add WeChat powcoder

# LIST (CHURCH)

Example:

Assignment Project Exam Help

$IS\ NIL\ NIL$

$=\ FIRST\ NIL$

$=\ (\lambda p.p\ TRUE)\ NIL$

$=\ NIL\ TRUE$

$=\ PAIR\ TRUE\ TRUE\ TRUE$

$=\ (\lambda x y z.z\ (x\ y\ z))\ TRUE\ TRUE\ TRUE$

$=\ \dots =\ TRUE\ TRUE\ TRUE$

$=\ \dots =\ TRUE$

<https://powcoder.com>

Add WeChat powcoder

# LIST (CHURCH)

Example:

Assignment Project Exam Help

$ISNIL \{a, b, c, d\}$

=

<https://powcoder.com>

=

Add WeChat powcoder

=



# LIST (CHURCH)

Example:

Assignment Project Exam Help

$$\begin{aligned}
 & ISNIL \{a, b, c, d\} \\
 &= FIRST \{a, b, c, d\}
 \end{aligned}$$

<https://powcoder.com>

=

Add WeChat powcoder

=

## LIST (CHURCH)

Example:

# Assignment Project Exam Help

 $ISNIL \{a, b, c, d\}$  $= FIRST \{a, b, c, d\}$  $= (\lambda p. p. TRUE) \{a, b, c, d\}$   
<https://powcoder.com> $=$  $=$   
[Add WeChat powcoder](#) $=$

# LIST (CHURCH)

Example:

$ISNIL \{a, b, c, d\}$

$= FIRST \{a, b, c, d\}$

$= (\lambda p. p. TRUE) \{a, b, c, d\}$

$= \{a, b, c, d\}. TRUE$

$=$

$=$   
 $=$   
 $=$

<https://powcoder.com>

Add WeChat powcoder

# LIST (CHURCH)

Example:

$$\begin{aligned}
 & ISNIL \{a, b, c, d\} \\
 &= FIRST \{a, b, c, d\} \\
 &= (\lambda p. p. TRUE) \{a, b, c, d\} \\
 &= \{a, b, c, d\}. TRUE \\
 &= PAIR FALSE (PAIR a \{b, c, d\}) TRUE \\
 &= \\
 &=
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# LIST (CHURCH)

Example:

$$\begin{aligned}
 & ISNIL \{a, b, c, d\} \\
 &= FIRST \{a, b, c, d\} \\
 &= (\lambda p.p \ TRUE) \{a, b, c, d\} \\
 &= \{a, b, c, d\} \ TRUE \\
 &= PAIR \ FALSE \ (PAIR \ a \ \{b, c, d\}) \ TRUE \\
 &= (\lambda xyz.zxy) \ FALSE \ (PAIR \ a \ \{b, c, d\}) \ TRUE \\
 &= \\
 &=
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# LIST (CHURCH)

Example:

$$\begin{aligned}
 & ISNIL \{a, b, c, d\} \\
 &= FIRST \{a, b, c, d\} \\
 &= (\lambda p.p \text{ TRUE}) \{a, b, c, d\} \\
 &= \{a, b, c, d\} \text{ TRUE} \\
 &= PAIR \text{ FALSE } (PAIR \ a \ \{b, c, d\}) \text{ TRUE} \\
 &= (\lambda xyz.zxy) \text{ FALSE } (PAIR \ a \ \{b, c, d\}) \text{ TRUE} \\
 &= \dots = \text{TRUE FALSE } (PAIR \ a \ \{b, c, d\}) \\
 &=
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH)

Example:

 $ISNIL \{a, b, c, d\}$  $= FIRST \{a, b, c, d\}$  $= (\lambda p.p \ TRUE) \{a, b, c, d\}$  $= \{a, b, c, d\} \ TRUE$  $= PAIR \ FALSE \ (PAIR \ a \ \{b, c, d\}) \ TRUE$  $= (\lambda xyz.zxy) \ FALSE \ (PAIR \ a \ \{b, c, d\}) \ TRUE$  $= \dots = TRUE \ FALSE \ (PAIR \ a \ \{b, c, d\})$  $= \dots = FALSE$ 

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH) EXAMPLE

Assignment Project Exam Help

$HEAD \{a, b, c, d\}$

=

<https://powcoder.com>

=

Add WeChat powcoder

=



## LIST (CHURCH) EXAMPLE

# Assignment Project Exam Help

$HEAD \{a, b, c, d\}$

$= (\lambda z. FIRST (SECOND z)) \{a, b, c, d\}$

<https://powcoder.com>

=

Add WeChat powcoder

=

## LIST (CHURCH) EXAMPLE

Assignment Project Exam Help

$HEAD \{a, b, c, d\}$

$= (\lambda z. FIRST (SECOND z)) \{a, b, c, d\}$

$= FIRST (SECOND \{a, b, c, d\})$

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH) EXAMPLE

Assignment Project Exam Help

$HEAD \{a, b, c, d\}$

$= (\lambda z. FIRST (SECOND z)) \{a, b, c, d\}$

$= FIRST (SECOND \{a, b, c, d\})$

$= (\lambda b.p \ TRUE) (SECOND \{a, b, c, d\})$

$=$

Add WeChat powcoder

$=$

## LIST (CHURCH) EXAMPLE

Assignment Project Exam Help

$$\begin{aligned}
 & \text{HEAD } \{a, b, c, d\} \\
 &= (\lambda z. \text{FIRST } (\text{SECOND } z)) \{a, b, c, d\} \\
 &= \text{FIRST } (\text{SECOND } \{a, b, c, d\}) \\
 &= (\lambda b. p \text{ TRUE}) (\text{SECOND } \{a, b, c, d\}) \\
 &= \text{SECOND } \{a, b, c, d\} \text{ TRUE}
 \end{aligned}$$

Add WeChat powcoder

=

## LIST (CHURCH) EXAMPLE

Assignment Project Exam Help

$$\begin{aligned}
 & \text{HEAD } \{a, b, c, d\} \\
 &= (\lambda z. \text{FIRST } (\text{SECOND } z)) \{a, b, c, d\} \\
 &= \text{FIRST } (\text{SECOND } \{a, b, c, d\}) \\
 &= (\lambda b. p \text{ TRUE}) (\text{SECOND } \{a, b, c, d\}) \\
 &= \text{SECOND } \{a, b, c, d\} \text{ TRUE} \\
 &= (\lambda p. p \text{ FALSE}) \{a, b, c, d\} \text{ TRUE} \\
 &= \\
 &=
 \end{aligned}$$

## LIST (CHURCH) EXAMPLE

Assignment Project Exam Help

$$\begin{aligned}
 & \text{HEAD } \{a, b, c, d\} \\
 &= (\lambda z. \text{FIRST } (\text{SECOND } z)) \{a, b, c, d\} \\
 &= \text{FIRST } (\text{SECOND } \{a, b, c, d\}) \\
 &= (\lambda p. p \text{ TRUE}) (\text{SECOND } \{a, b, c, d\}) \\
 &= \text{SECOND } \{a, b, c, d\} \text{ TRUE} \\
 &= (\lambda p. p \text{ FALSE}) \{a, b, c, d\} \text{ TRUE} \\
 &= \{a, b, c, d\} \text{ FALSE TRUE} \\
 &=
 \end{aligned}$$

## LIST (CHURCH) EXAMPLE

Assignment Project Exam Help

$HEAD \{a, b, c, d\}$   
 $= (\lambda z. FIRST (SECOND z)) \{a, b, c, d\}$   
 $= FIRST (SECOND \{a, b, c, d\})$   
 $= (\lambda p. p \ TRUE) (SECOND \{a, b, c, d\})$   
 $= SECOND \{a, b, c, d\} \ TRUE$   
 $= (\lambda p. p \ FALSE) \{a, b, c, d\} \ TRUE$   
 $= \{a, b, c, d\} \ FALSE \ TRUE$   
 $= PAIR \ FALSE (PAIR \ a \ \{b, c, d\}) \ FALSE \ TRUE$   
 $= \dots$

## LIST (CHURCH) EXAMPLE (CONTINUED)

Assignment Project Exam Help

= ...

=

= <https://powcoder.com>

=

=

= Add WeChat powcoder

=

=

=



## LIST (CHURCH) EXAMPLE (CONTINUED)

Assignment Project Exam Help

$HEAD \{a, b, c, d\}$   
 $= \dots$

$= (\lambda xyz. zxy) \text{ FALSE } (PAIR \ a \ \{b, c, d\}) \text{ FALSE TRUE}$

<https://powcoder.com>

=

Add WeChat powcoder

=

=

## LIST (CHURCH) EXAMPLE (CONTINUED)

Assignment Project Exam Help

$$= \dots$$

$$= (\lambda xyz.zxy) \text{ FALSE } (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE}$$

$$= (\lambda yz.z \text{ FALSE } y) (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE}$$

$$=$$

$$=$$

$$=$$

$$=$$

$$=$$

$$=$$

<https://powcoder.com>

Add WeChat powcoder

## LIST (CHURCH) EXAMPLE (CONTINUED)

Assignment Project Exam Help

$$= \dots$$

$$= (\lambda xyz.zxy) \text{ FALSE } (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE}$$

$$= (\lambda yz.z \text{ FALSE } y) (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE}$$

$$= (\lambda z.z \text{ FALSE } (\text{PAIR } a \{b, c, d\})) \text{ FALSE TRUE}$$

$$=$$

$$=$$

$$=$$

$$=$$

$$=$$

Add WeChat powcoder

## LIST (CHURCH) EXAMPLE (CONTINUED)

Assignment Project Exam Help

$\text{HEAD } \{a, b, c, d\}$   
 $= \dots$   
 $= (\lambda xyz. zxy) \text{ FALSE } (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE}$   
 $= (\lambda yz. z \text{ FALSE } y) (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE}$   
 $= (\lambda z. z \text{ FALSE } (\text{PAIR } a \{b, c, d\})) \text{ FALSE TRUE}$   
 $= \text{FALSE FALSE } (\text{PAIR } a \{b, c, d\}) \text{ TRUE}$   
 $=$   
 $=$   
 $=$

Add WeChat powcoder

## LIST (CHURCH) EXAMPLE (CONTINUED)

Assignment Project Exam Help

$$\begin{aligned}
 &= \dots \\
 &= (\lambda xyz.zxy) \text{ FALSE } (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda yz.z \text{ FALSE } y) (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda z.z \text{ FALSE } (\text{PAIR } a \{b, c, d\})) \text{ FALSE TRUE} \\
 &= \text{FALSE FALSE } (\text{PAIR } a \{b, c, d\}) \text{ TRUE} \\
 &= \dots = \text{PAIR } a \{b, c, d\} \text{ TRUE } (\text{FALSE } a b = b) \\
 &= \\
 &= \\
 &=
 \end{aligned}$$

# LIST (CHURCH) EXAMPLE (CONTINUED)

# Assignment Project Exam Help

$$\begin{aligned}
 &= \dots \\
 &= (\lambda xyz.zxy) \text{ FALSE } (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda yz.z \text{ FALSE } y) (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda z.z \text{ FALSE } (\text{PAIR } a \{b, c, d\})) \text{ FALSE TRUE} \\
 &= \text{FALSE FALSE } (\text{PAIR } a \{b, c, d\}) \text{ TRUE} \\
 &= \dots = \text{PAIR } a \{b, c, d\} \text{ TRUE} \quad (\text{FALSE } a \text{ b} = \text{b}) \\
 &= (\lambda xyz.zxy) a \{b, c, d\} \text{ TRUE} \\
 &= \\
 &=
 \end{aligned}$$

# LIST (CHURCH) EXAMPLE (CONTINUED)

# Assignment Project Exam Help

$$\begin{aligned}
 &= \dots \\
 &= (\lambda xyz.zxy) \text{ FALSE } (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda yz.z \text{ FALSE } y) (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda z.z \text{ FALSE } (\text{PAIR } a \{b, c, d\})) \text{ FALSE TRUE} \\
 &= \text{FALSE FALSE } (\text{PAIR } a \{b, c, d\}) \text{ TRUE} \\
 &= \dots = \text{PAIR } a \{b, c, d\} \text{ TRUE} \quad (\text{FALSE } a \text{ b} = \text{b}) \\
 &= (\lambda xyz.zxy) a \{b, c, d\} \text{ TRUE} \\
 &= \dots = \text{TRUE } a \{b, c, d\} \quad (3 \beta\text{-reductions}) \\
 &=
 \end{aligned}$$

# LIST (CHURCH) EXAMPLE (CONTINUED)

# Assignment Project Exam Help

$$\begin{aligned}
 &= \dots \\
 &= (\lambda xyz.zxy) \text{ FALSE } (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda yz.z \text{ FALSE } y) (\text{PAIR } a \{b, c, d\}) \text{ FALSE TRUE} \\
 &= (\lambda z.z \text{ FALSE } (\text{PAIR } a \{b, c, d\})) \text{ FALSE TRUE} \\
 &= \text{FALSE FALSE } (\text{PAIR } a \{b, c, d\}) \text{ TRUE} \\
 &= \dots = \text{PAIR } a \{b, c, d\} \text{ TRUE} \quad (\text{FALSE } a \text{ b} = \text{b}) \\
 &= (\lambda xyz.zxy) a \{b, c, d\} \text{ TRUE} \\
 &= \dots = \text{TRUE } a \{b, c, d\} \quad (3 \beta\text{-reductions}) \\
 &= \dots = a \quad (\text{TRUE } a \text{ b} = a)
 \end{aligned}$$



LIST (CHURCH) CONS

# Assignment Project Exam Help

$CONS = \lambda ht. PAIR \ FALSE \ (PAIR \ h \ t)$

$CONS \ a \ NIL$   
<https://powcoder.com>

Add WeChat powcoder

LIST (CHURCH) CONS

# Assignment Project Exam Help

$CONS = \lambda ht. PAIR\ FALSE\ (PAIR\ h\ t)$

$CONS\ a\ NIL$   
<https://powcoder.com>

$= (\lambda ht. PAIR\ FALSE\ (PAIR\ h\ t))\ a\ NIL$

$=$

Add WeChat powcoder

$=$

LIST (CHURCH) CONS

# Assignment Project Exam Help

$CONS = \lambda ht. PAIR\ FALSE\ (PAIR\ h\ t)$

$CONS\ a\ NIL$   
<https://powcoder.com>

$= (\lambda ht. PAIR\ FALSE\ (PAIR\ h\ t))\ a\ NIL$

$= (\lambda t. PAIR\ FALSE\ (PAIR\ a\ t))\ NIL$

Add WeChat powcoder

$\neq$   
 $=$

LIST (CHURCH) CONS

# Assignment Project Exam Help

$CONS = \lambda ht. PAIR\ FALSE\ (PAIR\ h\ t)$

$CONS\ a\ NIL$   
<https://powcoder.com>

$= (\lambda ht. PAIR\ FALSE\ (PAIR\ h\ t))\ a\ NIL$

$= (\lambda t. PAIR\ FALSE\ (PAIR\ a\ t))\ NIL$

$= PAIR\ FALSE\ (PAIR\ a\ NIL)$

$=$

Add WeChat powcoder

LIST (CHURCH) CONS

# Assignment Project Exam Help

$CONS = \lambda ht. PAIR\ FALSE\ (PAIR\ h\ t)$

$CONS\ a\ NIL$   
<https://powcoder.com>

$= (\lambda ht. PAIR\ FALSE\ (PAIR\ h\ t))\ a\ NIL$

$= (\lambda t. PAIR\ FALSE\ (PAIR\ a\ t))\ NIL$

$= PAIR\ FALSE\ (PAIR\ a\ NIL)$

$= \{a\}$

Add WeChat powcoder

# LIST (CHURCH) CONS

Assignment Project Exam Help

$CONS = \lambda h. \lambda t. PAIR\ FALSE\ (PAIR\ h\ t)$   
 $CONS\ b\ (CONS\ a\ NIL)$   
 = <https://powcoder.com>  
 =  
 =  
 = Add WeChat powcoder  
 =  
 =

# LIST (CHURCH) CONS

Assignment Project Exam Help

$$CONS = \lambda h. PAIR\ FALSE\ (PAIR\ h\ t)$$

$$CONS\ b\ (CONS\ a\ NIL)$$

$$= (\lambda t. PAIR\ FALSE\ (PAIR\ h\ t))\ b\ (CONS\ a\ NIL)$$

$$=$$

$$=$$

$$=$$

$$=$$

$$=$$

$$=$$

Add WeChat powcoder

# LIST (CHURCH) CONS

## Assignment Project Exam Help

$$\begin{aligned}
 &CONS\ b\ (CONS\ a\ NIL) \\
 = &(\lambda t.PAIR\ FALSE\ (PAIR\ b\ t))\ b\ (CONS\ a\ NIL) \\
 = &(\lambda t.PAIR\ FALSE\ (PAIR\ b\ t))\ (CONS\ a\ NIL) \\
 = & \\
 = & \\
 = &
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder



# LIST (CHURCH) CONS

## Assignment Project Exam Help

$$\begin{aligned}
 & \text{CONS } b \text{ (CONS } a \text{ NIL)} \\
 = & (\lambda t. \text{PAIR FALSE (PAIR } b \text{ t)}) b \text{ (CONS } a \text{ NIL)} \\
 = & (\lambda t. \text{PAIR FALSE (PAIR } b \text{ t)}) (\text{CONS } a \text{ NIL)} \\
 = & \text{PAIR FALSE (PAIR } b \text{ (CONS } a \text{ NIL))} \\
 = & \text{Add WeChat powcoder} \\
 = & \\
 = &
 \end{aligned}$$

## LIST (CHURCH) CONS

Assignment Project Exam Help

$$\begin{aligned}
 & CONS\ b\ (CONS\ a\ NIL) \\
 = & (\lambda t. PAIR\ FALSE\ (PAIR\ b\ t))\ b\ (CONS\ a\ NIL) \\
 = & (\lambda t. PAIR\ FALSE\ (PAIR\ b\ t))\ (CONS\ a\ NIL) \\
 = & PAIR\ FALSE\ (PAIR\ b\ (CONS\ a\ NIL)) \\
 = & PAIR\ FALSE\ (PAIR\ b\ (CONS\ a\ NIL)) \\
 = & \\
 = &
 \end{aligned}$$

## LIST (CHURCH) CONS

Assignment Project Exam Help

$$\begin{aligned}
 & CONS\ b\ (CONS\ a\ NIL) \\
 = & (\lambda t. PAIR\ FALSE\ (PAIR\ b\ t))\ b\ (CONS\ a\ NIL) \\
 = & (\lambda t. PAIR\ FALSE\ (PAIR\ b\ t))\ (CONS\ a\ NIL) \\
 = & PAIR\ FALSE\ (PAIR\ b\ (CONS\ a\ NIL)) \\
 = & PAIR\ FALSE\ (PAIR\ b\ (PAIR\ FALSE\ (PAIR\ a\ NIL))) \\
 = & \dots
 \end{aligned}$$

## LIST (CHURCH) CONS

Assignment Project Exam Help

$$\begin{aligned} & CONS\ b\ (CONS\ a\ NIL) \\ = & (\lambda t. PAIR\ FALSE\ (PAIR\ b\ t))\ b\ (CONS\ a\ NIL) \\ = & (\lambda t. PAIR\ FALSE\ (PAIR\ b\ t))\ (CONS\ a\ NIL) \\ = & PAIR\ FALSE\ (PAIR\ b\ (CONS\ a\ NIL)) \\ = & PAIR\ FALSE\ (PAIR\ b\ (PAIR\ FALSE\ (PAIR\ a\ NIL))) \\ = & PAIR\ FALSE\ (PAIR\ b\ (PAIR\ FALSE\ (PAIR\ a\ NIL))) \\ = & \{b, a\} \end{aligned}$$

## LIST ENCODINGS

# Assignment Project Exam Help

We now have structured data *and* recursion!

<https://powcoder.com>

Add WeChat powcoder

## LIST ENCODINGS

# Assignment Project Exam Help

We now have structured data *and* recursion!

<https://powcoder.com>

Don't forget, just as there are many ways to represent a List ADT in imperative programming, there are many possible encodings for lists and other structures in lambda calculus.

Add WeChat powcoder

## OUTLINE

# Assignment Project Exam Help

- ▶ Revision - Lambda Calculus

- ▶ Y Combinator

<https://powcoder.com>

- ▶ Encodings

- ▶ numbers (a different way)

- ▶ parsing
- ▶ lists

Add WeChat powcoder

- ▶ Functional Programming

# FIBONACCI

In the last tutorial, you probably implemented Fibonacci like this:

```
(defun fib (x)
  (if (< x 2)
      1
      (+ (fib (- x 1)) (fib (- x 2)))
  )
)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# FIBONACCI

In the last tutorial, you probably implemented Fibonacci like this:

```
(defun fib (x)
  (if (< x 2)
      1
      (+ (fib (- x 1)) (fib (- x 2)))
  )
)
```

This works, but is not very efficient (exponential time complexity!)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# FIBONACCI

In the last tutorial, you probably implemented Fibonacci like this:

```
(defun fib (x)
  (if (< x 2)
      1
      (+ (fib (- x 1)) (fib (- x 2)))))
```

This works, but is not very efficient (exponential time complexity!)

In imperative programming you would use variables to store the sequence (linear time complexity).

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# FIBONACCI

In the last tutorial, you probably implemented Fibonacci like this:

```
(defun fib (x)
  (if (< x 2)
      1
      (+ (fib (- x 1)) (fib (- x 2)))))
```

This works, but is not very efficient (exponential time complexity!)

In imperative programming you would use variables to store the sequence (linear time complexity).

A comparable approach in FP is to compute the sequence, e.g. as a list.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## LISTS IN LISP

Assignment Project Exam Help

`nil` ; an empty list  
`(cons e l)` ; prepend *e* to list *l*  
`(list a b c ...)` ; new list (*a b c ...*)  
`(car l)` ; the head element of *l*  
`(cdr l)` ; the tail list of *l*  
`(last l)` ; the last element *l*  
`(append a b)` ; combine two lists  
`(member e l)` ; first sublist starting *e* in *l*  
`(reverse l)` ; a mirror of the list

<https://powcoder.com>  
 Add WeChat powcoder

## LISTS IN LISP (EXAMPLES)

```
? (list 1 2 3)
```

```
(1 2 3)
```

```
? (cons 1 (cons 2 (cons 3 nil)))
```

```
(1 2 3)
```

```
? (member 2 (list 1 3 5))
```

```
NIL
```

```
? (member 3 (list 1 3 5))
```

```
(3 5)
```

```
? (cdr (list 1 2 3 4 5))
```

```
(2 3 4 5)
```

```
? (cdr (cdr (list 1 2 3 4 5)))
```

```
(3 4 5)
```

```
? (car (cdr (list 1 2 3 4 5)))
```

```
2
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# FIBONACCI

Idea: given part of the Fibonacci sequence and a number, add that many more elements of the sequence.

```
(defun fib (n a)
  (if (zerop n)
      a
      (fib (- n 1)
            (cons
              (+ (car a) (car (cdr a)))
              a)))
  ) ) )
```

```
(fib 100 (list 1 0))
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## FIBONACCI

Making it a bit nicer:

- We can make optional (default) arguments

► (car (cdr x)) = (cadr x)

- You can repeat the a, d as many times as required

- e.g. (caddr x) is the 4th element

```
(defun fib (n &optional (a (list 1 0)))
  (if (zerop n)
      a
      (cons
        (fib (- n 1))
        (+ (car a) (cadr a))
        a
      )
  )
)
```

```
(fib 100)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## A NOTE ON LOOPS IN LISP

I avoided using loops to keep the first example closer to lambda calculus.

# Assignment Project Exam Help

There are several ways to use loops in LISP, here's one:

<https://powcoder.com>

```
(defun fib (n)
  (loop for f1 = 0 then f2
        and f2 = 1 then (+ f1 f2)
        repeat n finally (return f1)))
```

Add WeChat powcoder

```
(fib 100)
```

```
1
```

---

<sup>1</sup>source: <https://www.clike.net/Fibonacci>



# JAVA

```

public boolean isPrime(long number) {
    return number > 1 &&
        LongStream
            .rangeClosed(2, (long) Math.sqrt(number))
            .noneMatch(index -> number % index == 0);
}
isPrime(922000000000000000039L) // Output: true
2

```

- ▶ “rangeClosed” gives a stream of values within the range
- ▶ “noneMatch” checks the stream against a predicate
- ▶ “variable -> expression” is a lambda abstraction!
  - ▶ It takes a value (index) from the range, and tests if it divides the number we’re checking.

<sup>2</sup>source: <https://www.voxxed.com/2015/12/functional-vs-imperative-programming-fibonacci-prime-and-factorial-in->

# JAVA

```

public boolean isPrime(long number) {
    return number > 1 &&
        LongStream
            .rangeClosed(2, (long) Math.sqrt(number))
            .parallel()
            .noneMatch(index -> number % index == 0);
}
isPrime(922000000000000000039L) // Output: true
3

```

Adding “.parallel()” is enough magic sauce to get an embarrassingly good speedup.

<sup>3</sup>source: [https://www.voxxed.com/2015/12/functional-vs-imperative-programming-fibonacci-prime-and-factorial-in-](https://www.voxxed.com/2015/12/functional-vs-imperative-programming-fibonacci-prime-and-factorial-in)

# PYTHON

If you write much Python, you probably write more functional programming code than you thought.

# Assignment Project Exam Help

```
>>> grades = [43, 68, 35, 89, 67, 65, 70]
>>> len(list(filter(lambda x: x>=50, grades)))
5
>>> sum(map(lambda x: x>=50, grades))
5
>>> [x + 5 for x in grades]
[48, 73, 40, 94, 72, 70, 75]
>>> max([x + 5 for x in grades])
94
```

<https://powcoder.com>

Add WeChat powcoder

## PYTHON

```
>>> from functools import reduce
>>> prices = [43, 68, 35, 89, 67, 65, 70]
>>> sales = [3, 5, 0, 3, 2, 10, 30]
>>> reduce(lambda x, y: x+y,
            map(lambda x: x[0]*x[1],
                zip(prices, sales)))
3620
```

- zip combines elements from two iterables into pairs

► e.g. [(43, 3), (68, 5), ...]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# PYTHON

```
>>> from functools import reduce
>>> prices = [43, 68, 35, 89, 67, 65, 70]
>>> sales = [3, 5, 0, 3, 2, 10, 30]
>>> reduce(lambda x, y: x+y,
            map(lambda x: x[0]*x[1],
                zip(prices, sales)))
3620
```

- ▶ zip combines elements from two iterables into pairs
  - ▶ e.g. [(43, 3), (68, 5), ...]
- ▶ map applies a function to every element of an iterable
  - ▶ e.g. [43\*3, 68\*5, ...]

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# PYTHON

```
>>> from functools import reduce
>>> prices = [43, 68, 35, 89, 67, 65, 70]
>>> sales = [3, 5, 0, 3, 2, 10, 30]
>>> reduce(lambda x, y: x+y,
            map(lambda x: x[0]*x[1],
                zip(prices, sales)))
3620
```

- ▶ zip combines elements from two iterables into pairs
  - ▶ e.g. [(43, 3), (68, 5), ...]
- ▶ map applies a function to every element of an iterable
  - ▶ e.g. [43\*3, 68\*5, ...]
- ▶ reduce combines the elements using a two parameter function
  - ▶ (((0+129) + 340) + 0) + ...

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## REVIEW

- ▶ Revision - Lambda Calculus
  - ▶ When  $\alpha$ -reductions are *required*
  - ▶  $\eta$ -reductions
- ▶ Y Combinator
  - ▶ Combinators
  - ▶ Fixed-Point Theorem
  - ▶ Y Combinator
  - ▶ Implementing recursion

- ▶ Encodings
  - ▶ numbers (a different way)
  - ▶ pairs
  - ▶ lists

- ▶ Functional Programming
  - ▶ Using lists in LISP
  - ▶ Stream processing in Java
  - ▶ Some ubiquitous Python

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder