

COMP2022: Formal Languages and Logic

2018 Semester 2, Week 2


# Assignment Project Exam Help

Joseph Godbehere

<https://powcoder.com>

9th August, 2018

Add WeChat powcoder



THE UNIVERSITY OF  
SYDNEY

# COMMONWEALTH OF AUSTRALIA

## Copyright Regulations 1969

# Assignment Project Exam Help

WARNING

This material has been reproduced and communicated to you by or on behalf of the University of Sydney pursuant to part VB of the Copyright Act 1968 (**the Act**).

The material in this communication may be subject to copyright under the Act. Any further copying or communication of this material by you may be subject of copyright protect under the Act.

**Do not remove this notice.**

## OUTLINE

# Assignment Project Exam Help

- Revision: Lambda Calculus

- Currying <https://powcoder.com>

- Encodings  
Add WeChat powcoder

- Functional Programming: LISP

## OPERATIONS

# Assignment Project Exam Help

- ▶ Application
  - ▶ Notation:  $A \cdot B$
  - ▶ Expression  $B$  is applied to expression  $A$

<https://powcoder.com>

Add WeChat powcoder

## OPERATIONS

# Assignment Project Exam Help

- ▶ Application
  - ▶ Notation:  $A \cdot B$
  - ▶ Expression  $B$  is applied to expression  $A$

<https://powcoder.com>

- ▶ Abstraction
  - ▶ Variable  $x$  is abstracted in expression  $M$

Add WeChat powcoder

## REWRITING

# Assignment Project Exam Help

- ▶  $M[x := N]$
- ▶ Expression  $M$ , but all free occurrences of  $x$  are replaced with  $N$

- ▶ e.g.
  - ▶  $(xyz \lambda x. (zzx)) [x := A] =$
  - ▶  $(xyz \lambda x. (zzx)) [y := B] =$
  - ▶  $(xyz \lambda x. (zzx)) [z := C] =$

## REWRITING

# Assignment Project Exam Help

- ▶  $M[x := N]$
- ▶ Expression  $M$ , but all free occurrences of  $x$  are replaced with  $N$

- ▶ e.g.
  - ▶  $(xyz \lambda x. (zzx)) [x := A] = (Ayz \lambda x. (zzx))$
  - ▶  $(xyz \lambda x. (zzx)) [y := B] =$
  - ▶  $(xyz \lambda x. (zzx)) [z := C] =$

## REWRITING

# Assignment Project Exam Help

- ▶  $M[x := N]$
- ▶ Expression  $M$ , but all free occurrences of  $x$  are replaced with  $N$

- ▶ e.g.
  - ▶  $(xyz \lambda x. (zzx)) [x := A] = (Ayz \lambda x. (zzx))$
  - ▶  $(xyz \lambda x. (zzx)) [y := B] = (xBz \lambda x. (zzx))$
  - ▶  $(xyz \lambda x. (zzx)) [z := C] =$



## REWRITING

# Assignment Project Exam Help

- ▶  $M[x := N]$
- ▶ Expression  $M$ , but all free occurrences of  $x$  are replaced with  $N$

- ▶ e.g.
  - ▶  $(xyz \lambda x. (zzx)) [x := A] = (Ayz \lambda x. (zzx))$
  - ▶  $(xyz \lambda x. (zzx)) [y := B] = (xBz \lambda x. (zzx))$
  - ▶  $(xyz \lambda x. (zzx)) [z := C] = (xyC \lambda x. (CxC))$

## $\alpha$ -REDUCTION

# Assignment Project Exam Help

- ▶ Rename a  $\lambda$  to remove a name conflict

- ▶ <https://powcoder.com>

- ▶ Add WeChat powcoder
  - ▶  $y$  must be a *new* variable
  - ▶ You must not choose a symbol that is already in use

## $\beta$ -REDUCTION

# Assignment Project Exam Help

- Solve an abstraction

- <https://powcoder.com>

- Add WeChat powcoder
- Note. the free occurrences of  $x$  in  $M$  is exactly the set of occurrences which bound to the  $\lambda x.$  in  $(\lambda x.M)$

## OUTLINE

# Assignment Project Exam Help

- Revision - Lambda Calculus

- ~~Currying~~ <https://powcoder.com>

- Encodings  
Add WeChat powcoder

- Functional Programming

## TWO ARGUMENTS

Assignment Project Exam Help

- Suppose we have a function  $f(x, y)$  which requires two arguments.

<https://powcoder.com>

Add WeChat powcoder

## TWO ARGUMENTS

► Suppose we have a function  $f(x, y)$  which requires two arguments.

► <https://powcoder.com>

Add WeChat powcoder

## TWO ARGUMENTS

► Suppose we have a function  $f(x, y)$  which requires two arguments.

► <https://powcoder.com>

►  $F$  is a function which takes one input, and returns a function  $F_x$ , which will take the *next* input

Add WeChat powcoder

## TWO ARGUMENTS

► Suppose we have a function  $f(x, y)$  which requires two arguments.

► <https://powcoder.com>

►  $F$  is a function which takes one input, and returns a function  $F_x$ , which will take the *next* input

► The output of the second function will be  $f(x, y)$ .



## EXAMPLE

Normal arithmetic:  $f(x, y) = (x + y)/2$

# Assignment Project Exam Help

Lambda calculus:  $(\lambda x.(\lambda y.(x + y)/2))$

<https://powcoder.com>

$((\lambda x.(\lambda y.(x + y)/2)) \cdot 5) \cdot 7$

Add WeChat powcoder

## EXAMPLE

Normal arithmetic:  $f(x, y) = (x + y)/2$

# Assignment Project Exam Help

Lambda calculus:  $(\lambda x. (\lambda y. (x + y)/2))$

<https://powcoder.com>

$((\lambda x. (\lambda y. (x + y)/2)) \cdot 5) \cdot 7$

$= (\lambda y. (5 + y)/2) \cdot 7$

Add WeChat powcoder

## EXAMPLE

Normal arithmetic:  $f(x, y) = (x + y)/2$

# Assignment Project Exam Help

Lambda calculus:  $(\lambda x.(\lambda y.(x + y)/2))$

<https://powcoder.com>

$((\lambda x.(\lambda y.(x + y)/2)) \cdot 5) \cdot 7$

$= (\lambda y.(5 + y)/2) \cdot 7$

Add WeChat powcoder

$= (5 + 7)/2$

## EXAMPLE

Normal arithmetic:  $f(x, y) = (x + y)/2$

# Assignment Project Exam Help

Lambda calculus:  $(\lambda x.(\lambda y.(x + y)/2))$

<https://powcoder.com>

$$((\lambda x.(\lambda y.(x + y)/2)) \cdot 5) \cdot 7$$

$$= (\lambda y.(5 + y)/2) \cdot 7$$

Add WeChat powcoder

$$= (5 + 7)/2$$

$$= 6$$

# CURRYING

## Assignment Project Exam Help

- ▶ A  $n$ -ary parameter function can be represented in the lambda calculus through *Currying*

<https://powcoder.com>

Add WeChat powcoder



# CURRYING

## Assignment Project Exam Help

- A  $n$ -ary parameter function can be represented in the lambda calculus through *Currying*

<https://powcoder.com>

- An  $n$  argument function returns an  $(n - 1)$  argument function, which returns an  $(n - 2)$  argument function, ...

Add WeChat powcoder

- e.g.  $(\lambda x.(\lambda y.(\lambda z.f(x, y, z)))) \cdot 1 = (\lambda y.(\lambda z.f(1, y, z)))$

# EVALUATION

Recall the example from earlier:

$$\begin{aligned}
 & ((\lambda x. (\lambda y. (x + y)/2)) \cdot 5) \cdot 7 \\
 &= (\lambda y. (5 + y)/2) \cdot 7 \\
 &= (5 + 7)/2 \\
 &= 6
 \end{aligned}$$

The function is *partially evaluated* at each step

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



# EVALUATION

Recall the example from earlier:

$$\begin{aligned}
 & ((\lambda x. (\lambda y. (x + y)/2)) \cdot 5) \cdot 7 \\
 &= (\lambda y. (5 + y)/2) \cdot 7 \\
 &= (5 + 7)/2 \\
 &= 6
 \end{aligned}$$

<https://powcoder.com>

The function is *partially evaluated* at each step

- The first function returns  $(\lambda y. (5 + y)/2)$

Add WeChat powcoder

# EVALUATION

Recall the example from earlier:

$$\begin{aligned}
 & ((\lambda x. (\lambda y. (x + y)/2)) \cdot 5) \cdot 7 \\
 &= (\lambda y. (5 + y)/2) \cdot 7 \\
 &= (5 + 7)/2 \\
 &= 6
 \end{aligned}$$

<https://powcoder.com>

The function is *partially evaluated* at each step

- The first function returns  $(\lambda y. (5 + y)/2)$
- 7 is then applied to the new function

Add WeChat powcoder

# EVALUATION

Recall the example from earlier:

$$\begin{aligned}
 & ((\lambda x. (\lambda y. (x + y)/2)) \cdot 5) \cdot 7 \\
 &= (\lambda y. (5 + y)/2) \cdot 7 \\
 &= (5 + 7)/2 \\
 &= 6
 \end{aligned}$$

The function is *partially evaluated* at each step

- ▶ The first function returns  $(\lambda y. (5 + y)/2)$
- ▶ 7 is then applied to the new function
- ▶  $(5 + 7)/2$  is evaluated and returned

## NOTATION

► Too many parentheses. Let's make it simpler:

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# NOTATION

► Too many parentheses. Let's make it simpler:

# Assignment Project Exam Help

- We can write  $(A \cdot B)$  as  $A \ B$

<https://powcoder.com>

Add WeChat powcoder

# NOTATION

► Too many parentheses. Let's make it simpler:

# Assignment Project Exam Help

- We can write  $(A \cdot B)$  as  $A \ B$

<https://powcoder.com>

- For function application we use association to the *left*:

$$ABCDEF \equiv (((((AB)C)D)E)F)$$

# Add WeChat powcoder

# NOTATION

► Too many parentheses. Let's make it simpler:

# Assignment Project Exam Help

- We can write  $(A \cdot B)$  as  $A \ B$

<https://powcoder.com>

- For function application we use association to the *left*:

$$ABCDEF \equiv (((((AB)C)D)E)F)$$

# Add WeChat powcoder

- i.e. the leftmost application happens *first*

# NOTATION

## Assignment Project Exam Help

- For function abstraction we use association to the *right*

$\lambda x_1 x_2 x_3 \dots x_k. M$   
<https://powcoder.com>

Add WeChat powcoder



# NOTATION

## Assignment Project Exam Help

- For function abstraction we use association to the *right*

$$\lambda x_1 x_2 x_3 \dots x_k. M$$

$$= \lambda x_1. \lambda x_2. \lambda x_3 \dots \lambda x_k. M$$

<https://powcoder.com>

Add WeChat powcoder

# NOTATION

## Assignment Project Exam Help

- For function abstraction we use association to the *right*

$$\begin{aligned}
 & \lambda x_1 x_2 x_3 \dots x_k . M \\
 &= \lambda x_1 . \lambda x_2 . \lambda x_3 . \dots \lambda x_k . M \\
 &= (\lambda x_1 . (\lambda x_2 . (\lambda x_3 . (\dots (\lambda x_k . M) \dots))))
 \end{aligned}$$

Add WeChat powcoder

# NOTATION

## Assignment Project Exam Help

- For function abstraction we use association to the *right*

$$\begin{aligned}
 & \lambda x_1 x_2 x_3 \dots x_k. M \\
 &= \lambda x_1. (\lambda x_2. (\lambda x_3. \dots (\lambda x_k. M) \dots)) \\
 &= (\lambda x_1. (\lambda x_2. (\lambda x_3. (\dots (\lambda x_k. M) \dots))))
 \end{aligned}$$

- Add WeChat powcoder
- This means the leftmost  $\lambda$  will match with the first input applied to the function

# NOTATION

## Assignment Project Exam Help

- ▶ Abstraction is right associative
- ▶ Application is left associative
- ▶ The abstractions and applications match up nicely:

<https://powcoder.com>

Add WeChat powcoder

# NOTATION

## Assignment Project Exam Help

- ▶ Abstraction is right associative
- ▶ Application is left associative
- ▶ The abstractions and applications match up nicely:

$$\begin{aligned}
 & (\lambda yz. ((z - 4) \times y)) 4 2 3 \\
 &= (\lambda yz. ((z - 4) \times y)) 2 3
 \end{aligned}$$

Add WeChat powcoder

# NOTATION

## Assignment Project Exam Help

- ▶ Abstraction is right associative
- ▶ Application is left associative
- ▶ The abstractions and applications match up nicely:

<https://powcoder.com>

$$\begin{aligned}
 & (\lambda yz. ((z - 4) \times y)) 4 2 3 \\
 &= (\lambda yz. ((z - 4) \times y)) 2 3 \\
 &= (\lambda z. ((z - 4) \times 2)) 3
 \end{aligned}$$

Add WeChat powcoder

# NOTATION

## Assignment Project Exam Help

- ▶ Abstraction is right associative
- ▶ Application is left associative
- ▶ The abstractions and applications match up nicely:

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}
 & (\lambda yz. ((z - 4) \times y)) 4 2 3 \\
 &= (\lambda yz. ((z - 4) \times y)) 2 3 \\
 &= (\lambda z. ((z - 4) \times 2)) 3 \\
 &= ((3 - 4) \times 2) \\
 &= -2
 \end{aligned}$$

## NOTATION

- ▶ Abstraction is right associative
- ▶ Application is left associative
- ▶ If we wrote it out in full...

$$(\lambda xyz.((z - x) \times y)) \ 4 \ 2 \ 3$$

<https://powcoder.com>

Add WeChat powcoder



## NOTATION

- ▶ Abstraction is right associative
- ▶ Application is left associative
- ▶ If we wrote it out in full...

$$(\lambda xyz.((z - x) \times y)) \ 4 \ 2 \ 3$$

$$= (\lambda x.(\lambda y.(\lambda z.((z - x) \times y)))) \ 4 \ 2 \ 3$$

<https://powcoder.com>

Add WeChat powcoder

# NOTATION

- ▶ Abstraction is right associative
- ▶ Application is left associative
- ▶ If we wrote it out in full...

$$(\lambda xyz.((z - x) \times y)) \ 4 \ 2 \ 3$$

$$= (\lambda x.(\lambda y.(\lambda z.((z - x) \times y)))) \ 4 \ 2 \ 3$$

$$= \left( \left( \left( \left( \lambda x.(\lambda y.(\lambda z.((z - x) \times y))) \right) \cdot 4 \right) \cdot 2 \right) \cdot 3 \right)$$

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

# NOTATION

- Abstraction is right associative
- Application is left associative
- If we wrote it out in full...

$$(\lambda x y z. ((z - x) \times y)) \ 4 \ 2 \ 3$$

$$= (\lambda x. (\lambda y. (\lambda z. ((z - x) \times y)))) \ 4 \ 2 \ 3$$

$$= \left( \left( \left( \left( \lambda x. (\lambda y. (\lambda z. ((z - x) \times y))) \right) \cdot 4 \right) \cdot 2 \right) \cdot 3 \right)$$

$$= ((\lambda x. (\lambda z. ((z - 4) \times 2))) \cdot 3)$$

$$= (\lambda z. ((z - 4) \times 2)) \cdot 3$$

$$= (3 - 4) \times 2$$

$$= -2$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# NOTATION

## Assignment Project Exam Help

► Question:

1. Is  $\lambda x.xy = (\lambda x.(xy))$ , or
2. is  $\lambda x.xy = (\lambda x.x)y$  ?

<https://powcoder.com>

Add WeChat powcoder

# NOTATION

## Assignment Project Exam Help

► Question:

1. Is  $\lambda x.xy = (\lambda x.(xy))$ , or
2. is  $\lambda x.xy = (\lambda x.x)y$  ?

<https://powcoder.com>

► Answer: (1), it's  $(\lambda x.(xy))$

Add WeChat powcoder

## NOTATION

# Assignment Project Exam Help

► Question:

1. Is  $\lambda x.xy = (\lambda x.(xy))$ , or
2. is  $\lambda x.xy = (\lambda x.x)y$  ?

<https://powcoder.com>

► Answer: (1), it's  $(\lambda x.(xy))$

## Add WeChat powcoder

► Use parentheses to limit the scope of the  $\lambda$  if needed

# CURRYING

- Suppose we wanted to abstract a function with  $k$  arguments:

Assignment Project Exam Help  
 $(x_1, x_2, \dots, x_k, N)$

<https://powcoder.com>

Add WeChat powcoder

# CURRYING

- Suppose we wanted to abstract a function with  $k$  arguments:

Assignment Project Exam Help

- If we apply  $k$  arguments,  $v_1 \dots v_k$ , we get this:

<https://powcoder.com>

$$(\lambda x_1 x_2 x_3 \dots x_k . N) v_1 v_2 v_3 \dots v_k$$

Add WeChat powcoder



# CURRYING

- Suppose we wanted to abstract a function with  $k$  arguments:

Assignment Project Exam Help

- If we apply  $k$  arguments,  $v_1 \dots v_k$ , we get this:

<https://powcoder.com>

$$(\lambda x_1 x_2 x_3 \dots x_k . N) v_1 v_2 v_3 \dots v_k$$

Add WeChat powcoder

- Each  $\beta$ -reduction partially evaluates the function:
  - $v_1$  replaces  $x_1$ . The resulting function takes  $k - 1$  arguments:

$$(\lambda x_2 x_3 \dots x_k . N[x_1 : v_1]) v_2 v_3 \dots v_k$$

- ... then  $v_2$  would replace  $x_2$ , etc.

## OUTLINE

# Assignment Project Exam Help

- Revision - Lambda Calculus

- <https://powcoder.com>

- **Encodings**  
Add WeChat powcoder

- Functional Programming: LISP

# Assignment Project Exam Help

But... How do we actually *do* anything?

<https://powcoder.com>

Add WeChat powcoder

# UNTYPED LAMBDA CALCULUS

- ▶ Lambda calculus does not have primitives
  - ▶ No numbers
  - ▶ No arithmetic operators
  - ▶ No aggregated data types (classes etc.)
  - ▶ No control flow (only recursion!)

<https://powcoder.com>

Add WeChat powcoder

# UNTYPED LAMBDA CALCULUS

- ▶ Lambda calculus does not have primitives

- ▶ No numbers
- ▶ No arithmetic operators
- ▶ No aggregated data types (classes etc.)
- ▶ No control flow (only recursion!)

<https://powcoder.com>

- ▶ However, I'm claiming that it is computationally equivalent to a Turing Machine!

Add WeChat powcoder

# UNTYPED LAMBDA CALCULUS

- ▶ Lambda calculus does not have primitives

- ▶ No numbers
- ▶ No arithmetic operators
- ▶ No aggregated data types (classes etc.)
- ▶ No control flow (only recursion!)

<https://powcoder.com>

- ▶ However, I'm claiming that it is computationally equivalent to a Turing Machine!

Add WeChat powcoder

- ▶ So, how can we represent data types?

# UNTYPED LAMBDA CALCULUS

- ▶ Lambda calculus does not have primitives
  - ▶ No numbers
  - ▶ No arithmetic operators
  - ▶ No aggregated data types (classes etc.)
  - ▶ No control flow (only recursion!)

<https://powcoder.com>

- ▶ However, I'm claiming that it is computationally equivalent to a Turing Machine!

Add WeChat powcoder

- ▶ So, how can we represent data types?
  - ▶ They must be expressed as functions, known as *encodings*

## ENCODINGS: TRUTH

# Assignment Project Exam Help

### ► Boolean constants:

►  $\text{TRUE} := \lambda xy.x$

►  $\text{FALSE} := \lambda xy.y$

<https://powcoder.com>

Add WeChat powcoder



## ENCODINGS: TRUTH

# Assignment Project Exam Help

### Boolean constants:

▶  $\text{TRUE} := \lambda xy.x$

▶  $\text{FALSE} := \lambda xy.y$

<https://powcoder.com>

### Now we can do conditional logic:

▶  $\text{IFELSE} := \lambda x y f. f x y$  has semantics similar to:

▶ if <cond> then <x> else <y>

▶ If <cond> is true, return result of <x>, otherwise <y>

Add WeChat powcoder

ENCODINGS: TRUTH

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

ENCODINGS: TRUTH

# Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.x) A B \quad (\text{macro substitution})$$

<https://powcoder.com>

Add WeChat powcoder

## ENCODINGS: TRUTH

# Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.x) A B$$
 (macro substitution)

$$= (\lambda fay.fay) (\lambda xy.x) A B$$
 ( $\alpha$ -reduction)

<https://powcoder.com>

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.x) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fxb.fxb) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.x) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.x)ab) A B \quad (\beta\text{-reduction})$$

Add WeChat powcoder

## ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.x) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.x)ab) A B \quad (\beta\text{-reduction})$$

$$= (\lambda b.(\lambda xy.x)Ab) B \quad (\beta\text{-reduction})$$

Add WeChat powcoder

## ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.x) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.x)ab) A B \quad (\beta\text{-reduction})$$

$$= (\lambda b.(\lambda xy.x)Ab). B \quad (\beta\text{-reduction})$$

$$= (\lambda xy..) A B \quad (\beta\text{-reduction})$$

<https://powcoder.com>

Add WeChat powcoder



## ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.x) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.x) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.x)ab) A B \quad (\beta\text{-reduction})$$

$$= (\lambda b.(\lambda xy.x)Ab) B \quad (\beta\text{-reduction})$$

$$= (\lambda xy..) AB \quad (\beta\text{-reduction})$$

$$= (\lambda y.A)B \quad (\beta\text{-reduction})$$

<https://powcoder.com>

Add WeChat powcoder

## ENCODINGS: TRUTH

Assignment Project Exam Help

$$\begin{aligned}
 & \text{TRUE} \text{ TRUE } A B \\
 &= (\lambda fxy.fxy) (\lambda xy.x) A B && \text{(macro substitution)} \\
 &= (\lambda fay.fay) (\lambda xy.x) A B && (\alpha\text{-reduction}) \\
 &= (\lambda fab.fab) (\lambda xy.x) A B && (\alpha\text{-reduction}) \\
 &= (\lambda ab.(\lambda xy.x)ab) A B && (\beta\text{-reduction}) \\
 &= (\lambda b.(\lambda xy.x)Ab). B && (\beta\text{-reduction}) \\
 &= (\lambda xy..) A B && (\beta\text{-reduction}) \\
 &= (\lambda y.A) B && (\beta\text{-reduction}) \\
 &= A && (\beta\text{-reduction})
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

ENCODINGS: TRUTH

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.y) A B$$
 (macro substitution)

<https://powcoder.com>

Add WeChat powcoder

## ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.y) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

<https://powcoder.com>

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.y) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fxb.fxb) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.y) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.y)ab) A B \quad (\beta\text{-reduction})$$

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

$$TRUE \equiv (\lambda fxy.fxy) (\lambda xy.y) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.y)ab) A B \quad (\beta\text{-reduction})$$

$$= (\lambda b.(\lambda xy.y)Ab) B \quad (\beta\text{-reduction})$$

<https://powcoder.com>

Add WeChat powcoder



## ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.y) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.y)ab) A B \quad (\beta\text{-reduction})$$

$$= (\lambda b.(\lambda xy.y)Ab) B \quad (\beta\text{-reduction})$$

$$= (\lambda xy.y) AB \quad (\beta\text{-reduction})$$

Add WeChat powcoder

<https://powcoder.com>

# ENCODINGS: TRUTH

Assignment Project Exam Help

$$= (\lambda fxy.fxy) (\lambda xy.y) A B \quad (\text{macro substitution})$$

$$= (\lambda fay.fay) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda fab.fab) (\lambda xy.y) A B \quad (\alpha\text{-reduction})$$

$$= (\lambda ab.(\lambda xy.y)ab) A B \quad (\beta\text{-reduction})$$

$$= (\lambda b.(\lambda xy.y)Ab) B \quad (\beta\text{-reduction})$$

$$= (\lambda y.y)AB \quad (\beta\text{-reduction})$$

$$= (\lambda y.y)B \quad (\beta\text{-reduction})$$

<https://powcoder.com>  
Add WeChat powcoder

## ENCODINGS: TRUTH

Assignment Project Exam Help

$$\begin{aligned}
 & \text{TRUE} \text{ FALSE } A \ B \\
 &= (\lambda fxy.fxy) (\lambda xy.y) \ A \ B && \text{(macro substitution)} \\
 &= (\lambda fay.fay) (\lambda xy.y) \ A \ B && (\alpha\text{-reduction}) \\
 &= (\lambda fab.fab) (\lambda xy.y) \ A \ B && (\alpha\text{-reduction}) \\
 &= (\lambda ab.(\lambda xy.y)ab) \ A \ B && (\beta\text{-reduction}) \\
 &= (\lambda b.(\lambda xy.y)Ab) \ B && (\beta\text{-reduction}) \\
 &= (\lambda y.y)AB && (\beta\text{-reduction}) \\
 &= (\lambda y.y)B && (\beta\text{-reduction}) \\
 &= B && (\beta\text{-reduction})
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

# ENCODINGS: TRUTH

## Assignment Project Exam Help

- ▶ Boolean constants:
  - ▶  $\text{TRUE} := \lambda xy.x$
  - ▶  $\text{FALSE} := \lambda xy.y$

- ▶ <https://powcoder.com>
- ▶  $\text{IFELSE} := \lambda fxy.fxy$

- ▶ Boolean operators
  - ▶  $\text{NOT} := \lambda fxy.fyx$
  - ▶  $\text{OR} := \lambda xy.xxy$
  - ▶  $\text{AND} := \lambda xy.xyx$

ENCODINGS: NOT

# Assignment Project Exam Help

▶ NOT :=  $\lambda fxy.fy\ x$

- ▶ NOT is a function which takes 3 arguments
  - ▶ Suppose  $f$  was a function which takes 2 arguments
  - ▶  $x, y$  would be those arguments

<https://powcoder.com>

Add WeChat powcoder

## ENCODINGS: NOT

# Assignment Project Exam Help

▶ NOT :=  $\lambda fxy.fyx$

- ▶ NOT is a function which takes 3 arguments
  - ▶ Suppose  $f$  was a function which takes 2 arguments
  - ▶  $x, y$  would be those arguments

## Add WeChat powcoder

- ▶ i.e. NOT outputs  $f$ , except its arguments have swapped around!

ENCODINGS: TRUTH

Assignment Project Exam Help  
*NOT TRUE*

<https://powcoder.com>

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

*NOT TRUE*

$= (\lambda fxy.fyx)(\lambda xy.x)$  (macro substitution)

<https://powcoder.com>

Add WeChat powcoder



# ENCODINGS: TRUTH

Assignment Project Exam Help

*NOT TRUE*

$= (\lambda fxy.fyx)(\lambda xy.x)$  (macro substitution)

$= (\lambda fxy.fyx)(\lambda ay.a)$  ( $\alpha$ -reduction)

<https://powcoder.com>

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

*NOT TRUE*

$$= (\lambda fxy.fyx)(\lambda xy.x) \quad (\text{macro substitution})$$

$$= (\lambda fxy.fyx)(\lambda ay.a) \quad (\alpha\text{-reduction})$$

$$= (\lambda fxy.fyx)(\lambda ab.a) \quad (\alpha\text{-reduction})$$

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

*NOT TRUE*

$$= (\lambda fxy.fyx)(\lambda xy.x) \quad (\text{macro substitution})$$

$$= (\lambda fxy.fyx)(\lambda ay.a) \quad (\alpha\text{-reduction})$$

$$= (\lambda fxy.yx)(\lambda ab.a) \quad (\alpha\text{-reduction})$$

$$= \lambda xy.(\lambda ab.a)yx \quad (\beta\text{-reduction})$$

Add WeChat powcoder

## ENCODINGS: TRUTH

Assignment Project Exam Help

*NOT TRUE*

$$= (\lambda fxy.fyx)(\lambda xy.x) \quad (\text{macro substitution})$$

$$= (\lambda fxy.fyx)(\lambda ay.a) \quad (\alpha\text{-reduction})$$

$$= (\lambda fxy.fyx)(\lambda ab.a) \quad (\alpha\text{-reduction})$$

$$= \lambda xy.(\lambda ab.a)yx \quad (\beta\text{-reduction})$$

$$= \lambda xy.(\lambda b.y)x \quad (\beta\text{-reduction})$$

Add WeChat powcoder

# ENCODINGS: TRUTH

Assignment Project Exam Help

*NOT TRUE*

$$= (\lambda fxy.fyx)(\lambda xy.x) \quad (\text{macro substitution})$$

$$= (\lambda fxy.fyx)(\lambda ay.a) \quad (\alpha\text{-reduction})$$

$$= (\lambda fxy.fyx)(\lambda ab.a) \quad (\alpha\text{-reduction})$$

$$= \lambda xy.(\lambda ab.a)yx \quad (\beta\text{-reduction})$$

$$= \lambda xy.(\lambda b.y)x \quad (\beta\text{-reduction})$$

$$= \lambda xy.y \quad (\beta\text{-reduction})$$

<https://powcoder.com>

Add WeChat powcoder

## ENCODINGS: TRUTH

Assignment Project Exam Help

*NOT TRUE*

$$= (\lambda fxy.fyx)(\lambda xy.x) \quad (\text{macro substitution})$$

$$= (\lambda fxy.fyx)(\lambda ay.a) \quad (\alpha\text{-reduction})$$

$$= (\lambda fxy.yx)(\lambda ab.a) \quad (\alpha\text{-reduction})$$

$$= \lambda xy.(\lambda ab.a)yx \quad (\beta\text{-reduction})$$

$$= \lambda xy.(\lambda b.y)x \quad (\beta\text{-reduction})$$

$$= \lambda xy.y \quad (\beta\text{-reduction})$$

$$= FALSE \quad (\text{macro substitution})$$

<https://powcoder.com>

Add WeChat powcoder

## ENCODINGS: NUMBERS

- ▶ The natural numbers can be thought of as a sequence, starting from 0, and successively increasing by one.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## ENCODINGS: NUMBERS

- The natural numbers can be thought of as a sequence, starting from 0, and successively increasing by one.

- More formally, we can define them inductively:

<https://powcoder.com>

Add WeChat powcoder



## ENCODINGS: NUMBERS

- ▶ The natural numbers can be thought of as a sequence, starting from 0, and successively increasing by one.

- ▶ More formally, we can define them inductively:

<https://powcoder.com>

- ▶ Basic clause: 0 is a number and is in the set

Add WeChat powcoder

# ENCODINGS: NUMBERS

- ▶ The natural numbers can be thought of as a sequence, starting from 0, and successively increasing by one.

- ▶ More formally, we can define them inductively:

<https://powcoder.com>

- ▶ Basic clause: 0 is a number and is in the set

▶ Inductive clause: for any element  $x$  in the natural numbers,  $x + 1$  is an element of the natural numbers

## ENCODINGS: NUMBERS

- ▶ The natural numbers can be thought of as a sequence, starting from 0, and successively increasing by one.

- ▶ More formally, we can define them inductively:

<https://powcoder.com>

- ▶ Basic clause: 0 is a number and is in the set

Add WeChat powcoder

- ▶ Inductive clause: for any element  $x$  in the natural numbers,  $x + 1$  is an element of the natural numbers

- ▶ Extremal clause: nothing is in the set of natural numbers unless it is obtained by the inductive clause and basis clause

## CHURCH NUMERALS

► Natural numbers in lambda calculus have two constructors:

# Assignment Project Exam Help

►  $\text{ZERO} := \lambda xy.y$

► This represents 0

► It is the same formula we used to encode FALSE

<https://powcoder.com>

# Add WeChat powcoder

## CHURCH NUMERALS

- Natural numbers in lambda calculus have two constructors:

- $\text{ZERO} := \lambda xy.y$

- This represents 0

- It is the same formula we used to encode FALSE

- $\text{SUCCESSOR} := \lambda xyz.y(xyz)$

- Returns the next number in the sequence

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## CHURCH NUMERALS

► Natural numbers in lambda calculus have two constructors:

# Assignment Project Exam Help

►  $\text{ZERO} := \lambda xy. y$

► This represents 0

► It is the same formula we used to encode FALSE

►  $\text{SUCCESSOR} := \lambda xyz. y(xyz)$

► Returns the next number in the sequence

► We're now ready to start constructing the natural numbers!

<https://powcoder.com>

Add WeChat powcoder

## CHURCH NUMERALS

# Assignment Project Exam Help

*ONE*

*= SUCCESSOR ZERO*

<https://powcoder.com>

Add WeChat powcoder

# CHURCH NUMERALS

# Assignment Project Exam Help

*ONE*

*= SUCCESSOR ZERO*

<https://powcoder.com> (macro)

# Add WeChat powcoder



# CHURCH NUMERALS

## Assignment Project Exam Help

*ONE*

*= SUCCESSOR ZERO*

<https://powcoder.com> (macro)

*= (λxyz.y(xyz))(λab.b)* (α)

Add WeChat powcoder

# CHURCH NUMERALS

## Assignment Project Exam Help

*ONE*

*= SUCCESSOR ZERO*

<https://powcoder.com> (macro)

*= (λxyz.y(xyz))(λab.b)* (α)

*= λyz.y((λab.b)yz)* (β)

Add WeChat powcoder

# CHURCH NUMERALS

## Assignment Project Exam Help

*ONE*

*= SUCCESSOR ZERO*

<https://powcoder.com> (macro)

*= (λxyz.y(xyz))(λab.b)* (α)

*= λyz.y((λab.b)yz)* (β)

*= λyz.y((λb.b)z)* (β)

# CHURCH NUMERALS

## Assignment Project Exam Help

ONE

= *SUCCESSOR ZERO*

<https://powcoder.com> (macro)

=  $(\lambda xyz.y(xyz))(\lambda ab.b)$  ( $\alpha$ )

=  $\lambda yz.y((\lambda ab.b)yz)$  ( $\beta$ )

Add WeChat powcoder ( $\beta$ )

=  $\lambda yz.yz$  ( $\beta$ )

## CHURCH NUMERALS

# Assignment Project Exam Help

*TWO*

*= SUCCESSOR ONE*

<https://powcoder.com> (macro)

# Add WeChat powcoder

## CHURCH NUMERALS

# Assignment Project Exam Help

*TWO*

*= SUCCESSOR ONE*

<https://powcoder.com> (macro)

*= (λxyz.y(xyz))(λab.ab)* (α)

# Add WeChat powcoder

## CHURCH NUMERALS

# Assignment Project Exam Help

*TWO*

*= SUCCESSOR ONE*

<https://powcoder.com> (macro)

*= (λxyz.y(xyz))(λab.ab)*  $(\alpha)$

*= λyz.y((λab.ab)yz)*  $(\beta)$

Add WeChat powcoder

# CHURCH NUMERALS

## Assignment Project Exam Help

*TWO*

*= SUCCESSOR ONE*

<https://powcoder.com> (macro)

*= (λxyz.y(xyz))(λab.ab)* ( $\alpha$ )

*= λyz.y((λab.ab)yz)* ( $\beta$ )

Add WeChat powcoder ( $\beta$ )



# CHURCH NUMERALS

## Assignment Project Exam Help

*TWO*

*= SUCCESSOR ONE*

<https://powcoder.com> (macro)

$= (\lambda xyz. y(xyz))(\lambda ab. ab)$  ( $\alpha$ )

$= \lambda yz. y((\lambda ab. ab)yz)$  ( $\beta$ )

Add WeChat powcoder ( $\beta$ )

$= \lambda yz. y(yz)$  ( $\beta$ )

## CHURCH NUMERALS

Assignment *THREE* Project Exam Help  
 = *SUCCESSOR TWO*

= ...

<https://powcoder.com>  
 =  $\lambda yz. y(y(z))$

Add WeChat powcoder

# CHURCH NUMERALS

Assignment *THREE* Project Exam Help  
 = *SUCCESSOR TWO*

= ...

<https://powcoder.com>  
 =  $\lambda yz.y(y(yz))$

Add WeChat powcoder  
 = *SUCCESSOR THREE*

= ...

=  $\lambda yz.y(y(y(yz)))$

# ARITHMETIC?

## Assignment Project Exam Help

- We have numbers. Do they work?

<https://powcoder.com>

Add WeChat powcoder

# ARITHMETIC?

## Assignment Project Exam Help

- We have numbers. Do they work?

<https://powcoder.com>

- Arithmetic:

- $ADD := \lambda x y p q . x p (y p q)$

- $MULT := \lambda x y z . x (y z)$

- $EXP := \lambda x y . y x$

Add WeChat powcoder

# ADDITION EXAMPLE

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## ADDITION EXAMPLE

Assignment Project Exam Help

$$= (\lambda xypq.xp(y pq)) (\lambda yz.y(yz)) (\lambda yz.y(y(yz)))$$

<https://powcoder.com>

Add WeChat powcoder

## ADDITION EXAMPLE

Assignment Project Exam Help

$$= (\lambda xypq.xp(y pq)) (\lambda yz.y(yz)) (\lambda yz.y(y(yz)))$$

$$= (\lambda xypq.xp(y pq)) (\lambda ab.a(ab)) (\lambda cd.c(c(cd))) \quad (\alpha)$$

<https://powcoder.com>

Add WeChat powcoder



## ADDITION EXAMPLE

# Assignment Project Exam Help

$$\begin{aligned}
 & \text{ADD TWO THREE} \\
 &= (\lambda x y p q. x p (y p q)) (\lambda y z. y (y z)) (\lambda y z. y (y (y z))) \\
 &= (\lambda x y p q. x p (y p q)) (\lambda a b. a (a b)) (\lambda c d. c (c (c d))) \quad (\alpha) \\
 &= (\lambda x y p q. (\lambda a b. a (a b)) p (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)
 \end{aligned}$$

<https://powcoder.com>

## Add WeChat powcoder

## ADDITION EXAMPLE

# Assignment Project Exam Help

$$\begin{aligned}
 & \text{ADD TWO THREE} \\
 &= (\lambda x y p q. x p (y p q)) (\lambda y z. y (y z)) (\lambda y z. y (y (y z)))
 \end{aligned}$$

$$= (\lambda x y p q. x p (y p q)) (\lambda a b. a (a b)) (\lambda c d. c (c (c d))) \quad (\alpha)$$

$$= (\lambda y p q. (\lambda a b. a (a b)) p (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q. (\lambda b. p (p b)) (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

# Add WeChat powcoder

## ADDITION EXAMPLE

# Assignment Project Exam Help

*ADD TWO THREE*

$$= (\lambda x y p q. x p (y p q)) (\lambda y z. y (y z)) (\lambda y z. y (y (y z)))$$

$$= (\lambda x y p q. x p (y p q)) (\lambda a b. a (a b)) (\lambda c d. c (c (c d))) \quad (\alpha)$$

$$= (\lambda y p q. (\lambda a b. a (a b)) p (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q. (\lambda b. p (p b)) (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q. p (p (y p q))) (\lambda c d. c (c (c d))) \quad (\beta)$$

# Add WeChat powcoder

## ADDITION EXAMPLE

# Assignment Project Exam Help

$$= (\lambda x y p q . x p (y p q)) (\lambda y z . y (y z)) (\lambda y z . y (y (y z)))$$

$$= (\lambda x y p q . x p (y p q)) (\lambda a b . a (a b)) (\lambda c d . c (c (c d))) \quad (\alpha)$$

$$= (\lambda y p q . (\lambda a b . a (a b)) p (y p q)) (\lambda c d . c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q . (\lambda b . p (p b)) (y p q)) (\lambda c d . c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q . p (p (y p q))) (\lambda c d . c (c (c d))) \quad (\beta)$$

$$= \lambda q . p (p ((\lambda c d . c (c (c d))) p q)) \quad (\beta)$$

Add WeChat powcoder

## ADDITION EXAMPLE

Assignment Project Exam Help

$$= (\lambda x y p q. x p (y p q)) (\lambda y z. y (y z)) (\lambda y z. y (y (y z)))$$

$$= (\lambda x y p q. x p (y p q)) (\lambda a b. a (a b)) (\lambda c d. c (c (c d))) \quad (\alpha)$$

$$= (\lambda y p q. (\lambda a b. a (a b)) p (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q. (\lambda b. p (p b)) (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q. p (p (y p q))) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= \lambda q. p (p ((\lambda c d. c (c (c d))) p q)) \quad (\beta)$$

$$= \lambda p q. p (p ((\lambda d. p (p (p d))) q)) \quad (\beta)$$

Add WeChat powcoder

<https://powcoder.com>

## ADDITION EXAMPLE

# Assignment Project Exam Help

$$= (\lambda x y p q. x p (y p q)) (\lambda y z. y (y z)) (\lambda y z. y (y (y z)))$$

$$= (\lambda x y p q. x p (y p q)) (\lambda a b. a (a b)) (\lambda c d. c (c (c d))) \quad (\alpha)$$

$$= (\lambda y p q. (\lambda a b. a (a b)) p (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q. (\lambda b. p (p b)) (y p q)) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= (\lambda y p q. p (p (y p q))) (\lambda c d. c (c (c d))) \quad (\beta)$$

$$= \lambda p q. p (p ((\lambda d. c (c (c d))) p q)) \quad (\beta)$$

$$= \lambda p q. p (p ((\lambda d. p (p (p d))) q)) \quad (\beta)$$

$$= \lambda p q. p (p (p (p q))) \quad (\beta)$$

<https://powcoder.com>

Add WeChat powcoder

## ADDITION EXAMPLE

# Assignment Project Exam Help

$$\begin{aligned}
 & \lambda x y z. x y z \text{ TWO THREE} \\
 &= (\lambda x y p q. x p (y p q)) (\lambda y z. y (y z)) (\lambda y z. y (y (y z))) \\
 &= (\lambda x y p q. x p (y p q)) (\lambda a b. a (a b)) (\lambda c d. c (c (c d))) \quad (\alpha) \\
 &= (\lambda y p q. (\lambda a b. a (a b)) p (y p q)) (\lambda c d. c (c (c d))) \quad (\beta) \\
 &= (\lambda y p q. (\lambda b. p (p b)) (y p q)) (\lambda c d. c (c (c d))) \quad (\beta) \\
 &= (\lambda y p q. p (p (y p q))) (\lambda c d. c (c (c d))) \quad (\beta) \\
 &= \lambda p q. p (p ((\lambda d. c (c (c d))) p q)) \quad (\beta) \\
 &= \lambda p q. p (p ((\lambda d. p (p (p d))) q)) \quad (\beta) \\
 &= \lambda p q. p (p (p (p q))) \quad (\beta) \\
 &= \text{FIVE}
 \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

# Assignment Project Exam Help

*MULT EIGHT THIRTEEN*

<https://powcoder.com>

Add WeChat powcoder



## MULTIPLICATION EXAMPLE

# Assignment Project Exam Help

*MULT EIGHT THIRTEEN*

<https://powcoder.com>

# Add WeChat powcoder

## MULTIPLICATION EXAMPLE

# Assignment Project Exam Help

*MULT EIGHT THIRTEEN*

$$= (\lambda xyz.x(yz))(\lambda fx.f(f(f(f(f(f(f(fx))))))))$$
  

$$(\lambda fx.f(f(f(f(f(f(f(f(f(f(f(f(f(f(fx))))))))))))))$$

= ...

# Add WeChat powcoder

Just kidding

## MULTIPLICATION EXAMPLE

*MULT TWO THREE*

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

$$\begin{array}{l} \text{MULT TWO THREE} \\ = (\lambda x y z. x(yz)) \text{ TWO THREE} \end{array}$$

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

*MULT TWO THREE*  
 $= (\lambda xyz.x(yz)) \text{ TWO THREE}$

$= (\lambda yz.TWO (yz)) \text{ THREE}$

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

Assignment Project Exam Help

$$\begin{aligned} & \text{MULT TWO THREE} \\ &= (\lambda xyz.x(yz)) \text{ TWO THREE} \end{aligned}$$

$$= (\lambda yz.\text{TWO } (yz)) \text{ THREE}$$

$$= \lambda z.\text{TWO } (\text{THREE } z)$$

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

Assignment Project Exam Help

$$\text{MULT TWO THREE}$$

$$= (\lambda x y z. x (y z)) \text{ TWO THREE}$$

$$= (\lambda y z. \text{TWO } (y z)) \text{ THREE}$$

$$= \lambda z. \text{TWO } (\text{THREE } z)$$

<https://powcoder.com>

$$= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z)$$

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

Assignment Project Exam Help

$$\begin{aligned} & \text{MULT TWO THREE} \\ &= (\lambda x y z. x (y z)) \text{ TWO THREE} \end{aligned}$$

$$= (\lambda y z. \text{TWO } (y z)) \text{ THREE}$$

$$= \lambda z. \text{TWO } (\text{THREE } z)$$

$$= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z)$$

$$= \lambda z. (\lambda x. (\text{THREE } z) ((\text{THREE } z) x))$$

Add WeChat powcoder



## MULTIPLICATION EXAMPLE

$$\begin{aligned}
 & \text{MULT TWO THREE} \\
 &= (\lambda x y z. x (y z)) \text{ TWO THREE} \\
 &= (\lambda y z. \text{TWO } (y z)) \text{ THREE} \\
 &= \lambda z. \text{TWO } (\text{THREE } z) \\
 &= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z) \\
 &= \lambda z. (\lambda x. (\text{THREE } z) ((\text{THREE } z) x)) \\
 &= \lambda x. (\text{THREE } z) ((\text{THREE } z) x)
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

$$\begin{aligned}
 & \text{MULT TWO THREE} \\
 &= (\lambda x y z. x (y z)) \text{ TWO THREE} \\
 &= (\lambda y z. \text{TWO } (y z)) \text{ THREE} \\
 &= \lambda z. \text{TWO } (\text{THREE } z) \\
 &= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z) \\
 &= \lambda z. (\lambda x. (\text{THREE } z) ((\text{THREE } z) x)) \\
 &= \lambda x. (\text{THREE } z) ((\text{THREE } z) x) \\
 &= \lambda z x. (((\lambda f x. f (f (f x))) z) (((\lambda f x. f (f (f x))) z) x))
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

$$\begin{aligned}
 & \text{MULT TWO THREE} \\
 &= (\lambda x y z. x (y z)) \text{ TWO THREE} \\
 &= (\lambda y z. \text{TWO } (y z)) \text{ THREE} \\
 &= \lambda z. \text{TWO } (\text{THREE } z) \\
 &= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z) \\
 &= \lambda z. (\lambda x. (\text{THREE } z) ((\text{THREE } z) x)) \\
 &= \lambda x. (\text{THREE } z) ((\text{THREE } z) x) \\
 &= \lambda z x. (((\lambda f x. f (f (f x))) z) (((\lambda f x. f (f (f x))) z) x)) \\
 &= \lambda z x. (\lambda x. z (z (z x))) ((\lambda x. z (z (z x))) x)
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

$$\begin{aligned}
 & \text{MULT TWO THREE} \\
 &= (\lambda x y z. x (y z)) \text{ TWO THREE} \\
 &= (\lambda y z. \text{TWO } (y z)) \text{ THREE} \\
 &= \lambda z. \text{TWO } (\text{THREE } z) \\
 &= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z) \\
 &= \lambda z. (\lambda x. (\text{THREE } z) ((\text{THREE } z) x)) \\
 &= \lambda x. (\text{THREE } z) ((\text{THREE } z) x) \\
 &= \lambda z x. (((\lambda f x. f (f (f x))) z) (((\lambda f x. f (f (f x))) z) x)) \\
 &= \lambda z x. (\lambda x. z (z (z x))) ((\lambda x. z (z (z x))) x) \\
 &= \lambda z x. (\lambda x. z (z (z x))) (z (z (z x)))
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## MULTIPLICATION EXAMPLE

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$\begin{aligned}
 & \text{MULT TWO THREE} \\
 &= (\lambda x y z. x (y z)) \text{ TWO THREE} \\
 &= (\lambda y z. \text{TWO } (y z)) \text{ THREE} \\
 &= \lambda z. \text{TWO } (\text{THREE } z) \\
 &= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z) \\
 &= \lambda z. (\lambda x. (\text{THREE } z) ((\text{THREE } z) x)) \\
 &= \lambda x. (\text{THREE } z) ((\text{THREE } z) x) \\
 &= \lambda z x. (((\lambda f x. f (f (f x))) z) (((\lambda f x. f (f (f x))) z) x)) \\
 &= \lambda z x. (\lambda x. z (z (z x))) ((\lambda x. z (z (z x))) x) \\
 &= \lambda z x. (\lambda x. z (z (z x))) (z (z (z x))) \\
 &= \lambda z x. z (z (z (z (z (z x)))))
 \end{aligned}$$

## MULTIPLICATION EXAMPLE

$$\begin{aligned}
 & \text{MULT TWO THREE} \\
 &= (\lambda x y z. x (y z)) \text{ TWO THREE} \\
 &= (\lambda y z. \text{TWO } (y z)) \text{ THREE} \\
 &= \lambda z. \text{TWO } (\text{THREE } z) \\
 &= \lambda z. (\lambda f x. f (f x)) (\text{THREE } z) \\
 &= \lambda z. (\lambda x. (\text{THREE } z) ((\text{THREE } z) x)) \\
 &= \lambda x. (\text{THREE } z) ((\text{THREE } z) x) \\
 &= \lambda z x. (((\lambda f x. f (f (f x))) z) (((\lambda f x. f (f (f x))) z) x)) \\
 &= \lambda z x. (\lambda x. z (z (z x))) ((\lambda x. z (z (z x))) x) \\
 &= \lambda z x. (\lambda x. z (z (z x))) (z (z (z x))) \\
 &= \lambda z x. z (z (z (z (z (z x))))) \\
 &= \text{SIX}
 \end{aligned}$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

# RECURSION

In imperative languages, we can easily write recursive code:

```
def factorial(x):
```

```
    if x == 1:
```

```
        return 1
```

```
    return x*factorial(x-1)
```

<https://powcoder.com>

Add WeChat powcoder

... by referencing the method itself by name.

So far, we haven't directly seen iteration or recursion in the lambda calculus.

# RECURSION

In the last tutorial you tried to reduce:

Assignment Project Exam Help  
 $(\lambda x.xx)(\lambda x.xx)$

<https://powcoder.com>

Add WeChat powcoder



# RECURSION

In the last tutorial you tried to reduce:

Assignment Project Exam Help  
 $(\lambda x.xx)(\lambda x.xx)$

... and discovered that it looped forever.

<https://powcoder.com>

Add WeChat powcoder

# RECURSION

In the last tutorial you tried to reduce:

**Assignment Project Exam Help**  
 $(\lambda x.xx)(\lambda x.xx)$

... and discovered that it looped forever.

**<https://powcoder.com>**

This is related to a slightly more useful construct called the Y Combinator:

**Add WeChat powcoder**  
 $Y \equiv \lambda f.(\lambda x.f(xx))(\lambda x.f(xx))$

# RECURSION

In the last tutorial you tried to reduce:

Assignment Project Exam Help

$$(\lambda x.xx)(\lambda x.xx)$$

... and discovered that it looped forever.

<https://powcoder.com>

This is related to a slightly more useful construct called the Y Combinator:

Add WeChat powcoder

$$Y \equiv \lambda f.(\lambda x.f(xx))(\lambda x.f(xx))$$

Next week, we'll use this to compute recursive functions in the lambda calculus.

## OUTLINE

# Assignment Project Exam Help

- Revision - Lambda Calculus

- Curryng <https://powcoder.com>

- Encodings  
Add WeChat powcoder

- Functional Programming: LISP

# LISP

## Assignment Project Exam Help

- ▶ LISP is the second oldest programming language in common use
- ▶ Invented in 1958 by John McCarthy
- ▶ Was very popular in the AI boom
- ▶ Is a functional programming language
- ▶ Is a practical implementation of the Lambda Calculus
- ▶ Has many dialects (e.g. Clojure, Common Lisp, Racket, Scheme, etc.)

<https://powcoder.com>

Add WeChat powcoder

# LISP = LIST PROCESSING

- ▶ LISP has atoms

- ▶ Numbers, e.g. 10
- ▶ Identifiers, e.g. Foo
- ▶ Strings, e.g. "filename"

- ▶ LISP has lists

- ▶ can contain other lists
- ▶ can contain atoms
- ▶ can contain nothing (empty)

- ▶ very small syntax:

```
<object> ::= <atoms> | <list>
<list>  ::= "(" { <object> } ")"
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## LIST EXAMPLES IN LISP

Assignment Project Exam Help

```

(1 2 3)
()
(+ 1 2)
(* (+ 1 2) (- 2 3))
(sq 1 2)
(setq a 100)
(defun sq (n) (* n n))
(let ((a 6)) a)
(if t 5 6)
(cons 5 6)
(cons (cons 6 7))

```

<https://powcoder.com>

Add WeChat powcoder

## CONCEPTS OF LISP

# Assignment Project Exam Help

- ▶ LISP has a data structure model

- ▶ Lists

- ▶ Atoms

- ▶ Even programs are written as lists.

- ▶ Even *LISP* is written as a list.

- ▶ No other data structures

<https://powcoder.com>

Add WeChat powcoder



# EVALUATION

## Assignment Project Exam Help

- ▶ Prefix notation of function calls as lists
  - ▶ Operation is first element
  - ▶ Second and following elements are arguments
  - ▶ `(<operation> <arg1> ... <argn>)`
- ▶ Examples:

```
(+ 4 2)
(+ 3 (+ 3 2))
(sq (* 4 2))
```

Add WeChat powcoder

# NUMERICAL FUNCTIONS

- ▶ Numerical operations:
  - ▶ Addition: (+ 1 2)
  - ▶ Subtraction: (- 1 2)
  - ▶ Multiplication: (\* 1 2)
  - ▶ Division: (/ 1 2)
- ▶ Square root: (sqrt x)
- ▶ Base Exponent: (expt x y)
- ▶ Trigonometric Functions: (sin x)
- ▶ Absolute Value: (abs x)
- ▶ Modulo: (mod x y)
- ▶ Rounding: (round x)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## INTERACTION

# Assignment Project Exam Help

- ▶ Interaction with lisp is done in a *read-eval-print loop*
- ▶ Loop consists of the following steps:
  - ▶ Parse input and construct LISP object
  - ▶ Evaluate LISP object to produce output
  - ▶ Print output object
- ▶ Example:

$$\frac{2}{3} (+ 1 2)$$
 Add WeChat powcoder

# VARIABLES

- Variables can be defined by:

(set! <var> <value>)

- Semantics

<var> := <value>

- Occurrence of variable symbol replaces variable symbol by the value of the variable

- Example:

```
>> (set! a (+ 5 3))
```

```
8
```

```
>> a
```

```
8
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## QUOTE

# Assignment Project Exam Help

- If lists should not be evaluated, use function quote

```
>> (setq a (+ 1 2))
```

```
3
>> (setq a (quote (+ 1 2)))
(+ 1 2)
```

- There is a short-hand form, using a single quotation mark

```
>> (setq a '(+ 1 2))
(+ 1 2)
```

## CONDITION FUNCTION

# Assignment Project Exam Help

► Definition: `(if <cond> <true-value> <false-value>)`

► Boolean values in LISP are given by two symbols

► Symbol `nil` (equal to the empty list) represents false

► `T` represents true

<https://powcoder.com>

```
>> (if nil 1 2)
```

```
2
```

```
>> (if (= 10 10) 1 2)
```

```
1
```

```
>> (if () 1 2)
```

```
2
```

Add WeChat powcoder

## PREDICATES

- ▶ Type checking predicates
  - ▶ (atom x) checks whether x is not a list
  - ▶ (integer? x) checks whether x is an integer
  - ▶ (number? x) checks whether x is a number
  - ▶ (string? x) checks whether x is a string
- ▶ Numerical predicates
  - ▶ (odd? x) checks whether x is integer and odd
  - ▶ (even? x) checks whether x is integer and even
- ▶ Equality
  - ▶ (equal? x y) checks structural equality
  - ▶ (eq? x y) checks atom equality
  - ▶ (eq x y) checks identity
  - ▶ (= x y) checks numerical equality
- ▶ Logical operators
  - ▶ (or x y) logical OR
  - ▶ (and x y) logical AND

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## FUNCTIONS

- Function declaration:

```
(defun <name> (<arg1> ... <argn>) body)
```

- Translates to:

```
(setq <name> '(lambda (<arg1> ... <argn>) body))
```

```
>> (defun factorial (x)
      (if (= x 0)
          1
          (* x (factorial (- x 1)))))
```

```
FACTORIAL
>> (factorial 4)
24
```

- Next week we'll do this in lambda calculus directly - without the impurity of defining variables

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## BINDINGS

# Assignment Project Exam Help

```
(let ((<name1> <value1>) ... (<namen> <valuen>))
  body)
```

<https://powcoder.com>

```
>>> let ((a 3) (b 4) (c 5))
      (+ (* a b) c))
```

# Add WeChat powcoder

add WeChat powered by

Error: variable A is unbound

## BINDINGS (2)

# Assignment Project Exam Help

- Let allows local bindings of variables
- Bindings might be nested – innermost variable is taken

>> (let  
((a 3))  
 (let  
 ((a 5))  
 a  
 )  
 )  
5

<https://powcoder.com>

Add WeChat powcoder

5

## LIST CONSTRUCTION

# Assignment Project Exam Help

- # Signiment Project Exam 1
- Construction with cons: (cons <element> <list>)
  - Cons returns a new list with <element> as first element, followed by elements in <list>

- **Construction with list:** (list <elem1> ... <elemn>)

Construction with list: (list <elem1> ... <elemn>)

```
>> (cons 1 nil)
```

(1)

```
>> (cons 'a (b c))
```

$$(a \ b \ c)$$

```
>> (list 1 2 3)
```

$$(1 \ 2 \ 3)$$

# Add WeChat powcoder

## LIST ACCESS

# Assignment Project Exam Help

- ▶ Access first element: `(first <list>)`
- ▶ Access all but first element: `(rest <list>)`

<https://powcoder.com>

```
>> (first '(a b c))
```

```
a
```

```
>> (rest '(a b c))
```

```
(b c)
```

Add WeChat powcoder

## $\lambda$ IN LISP

# Assignment Project Exam Help

```
>> ((lambda (x) (+ x 1)) 4)
5
>> ((lambda (x y z) (* (+ x x) z)) 1 3 5)
10
```

Add WeChat powcoder

# λ IN HASKELL

## Assignment Project Exam Help

```
>> (\x -> x + 1) 4
5
>> (\x y z -> (x + x) * z) 1 3 5
10
```

<https://powcoder.com>

Add WeChat powcoder

# λ IN PYTHON

```

>>> (lambda x: x + 1) 4
5
>>> (lambda x: lambda y: lambda z: (x + x) * z)(1)(1)
10
>>> f = lambda x: lambda y: lambda z: (x + x) * z
>>> f
<function <lambda> at 0x02F66270>
>>> f(1)
<function <lambda>.<locals>.<lambda> at 0x02F66150>
>>> f(1)(3)
<function <lambda>.<locals>.<lambda>.<locals>.<lambda> at 0x02F66150>
>>> f(1)(3)(5)
10

```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## λ IN PYTHON

# Assignment Project Exam Help

```
>>> NOT = lambda f: lambda x: lambda y: f(y)(x)
>>> TRUE = lambda x: lambda y: x
>>> FALSE = lambda x: lambda y: y
>>> IF = lambda f: lambda x: lambda y: f(x)(y)
>>> IF (NOT(TRUE)) ("a") ("b")
'a'
>>> IF (NOT(NOT(TRUE))) ("a") ("b")
'b'
```

<https://powcoder.com>

Add WeChat powcoder



# REVIEW

- ▶ Lambda Calculus revision
  - ▶ Application, Abstraction
  - ▶ Rewriting
  - ▶  $\alpha$  and  $\beta$  reductions
- ▶ Currying
  - ▶ Multiple arguments
  - ▶ Associativity
- ▶ Encodings
  - ▶ Boolean logic
  - ▶ Church numerals, arithmetic
- ▶ Functional programming
  - ▶ Introduction to LISP
  - ▶ Brief look  $\lambda$  in other languages

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder