


## Week 8 Workshop – Query Processing and Optimisation

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





## Housekeeping

# Assignment Project Exam Help

Assignment 2 (Database Theory) for both COMP2400/6240 students

- The submission deadline is 23:59, Oct 12, 2021.
- This assignment must be done individually (no group work). Please join the special drop-in sessions if you need any clarifications.

<https://powcoder.com>

Add WeChat powcoder



## Housekeeping

# Assignment Project Exam Help

- 1 Assignment 2 (Database Theory) for both COMP2400/6210 students
  - The submission deadline is 23:59, Oct 12, 2021.
  - This assignment must be done individually (no group work). Please join the special drop-in sessions if you need any clarifications.
- 2 All the labs on Oct 4 (Monday, public holiday) in Week 9 will be moved to the same timeslots on Oct 11 (Monday) in Week 10.

<https://powcoder.com>

## Add WeChat powcoder



## Housekeeping

# Assignment Project Exam Help

- 1 Assignment 2 (Database Theory) for both COMP2400/6240 students
  - The submission deadline is 23:59, Oct 12, 2021.
  - This assignment must be done individually (no group work). Please join the special drop-in sessions if you need any clarifications.
- 2 All the labs on Oct 4 (Monday, public holiday) in Week 9 will be moved to the same timeslots on Oct 11 (Monday) in Week 10.
- 3 Lab 8 is optional (no associated with any assessment items)
  - We will open a separate sign-up page on Wattle at 12pm Oct 6.
  - All the optional labs will be scheduled from Oct 12 to Oct 15.
  - Three options are available
    - (1) Database Programming with Java
    - (2) Database Programming with Python
    - (3) Database Exercises on IMDB

<https://powcoder.com>

Add WeChat powcoder



## Query Processing – Example

SELECT name FROM Person WHERE age < 21

High-level language  
(SQL)



$\pi_{\text{name}}(\sigma_{\text{age} < 21}(\text{Person}))$

Low-level language  
(Relational Algebra)



$\pi_{\text{name}}$

$\sigma_{\text{age} < 21}$

Person



name
Rickon
Bran

Execution plan  
(Query tree)

Query result



## From SQL to RA Expressions

```
Students(matNr, firstName, lastName, email)  
Exams(matNr, crsNr, result, semester)  
Courses(crsNr, title, unit)
```

```
SELECT lastName, result, title
```

```
FROM STUDENTS, EXAMS, COURSES
```

```
WHERE STUDENTS.matNr=EXAMS.matNr AND
```

```
EXAMS.crsNr=COURSES.crsNr AND result≤1.3;
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## From SQL to RA Expressions

Students(matNr, firstName, lastName, email)  
Exams(matNr, crsNr, result, semester)  
Courses(crsNr, title, unit)

```
SELECT lastName, result, title
```

```
FROM STUDENTS, EXAMS, COURSES
```

```
WHERE STUDENTS.matNr=EXAMS.matNr AND
```

```
EXAMS.crsNr=COURSES.crsNr AND result≤1.3;
```

<https://powcoder.com>

### RA Expressions:

- 1  $\pi_{lastName, result, title}(\sigma_{result \leq 1.3}((Students \bowtie_{Students.matNr=Exams.matNr} Exams) \bowtie_{Exams.crsNr=Courses.crsNr} Courses))$
- 2  $\pi_{lastName, result, title}(\sigma_{result \leq 1.3}(\sigma_{EXAMS.crsNr=Courses.crsNr}(\sigma_{Students.matNr=Exams.matNr}(Students \times Exams \times Courses))))$
- 3  $\pi_{lastName, result, title}((Students \bowtie_{Students.matNr=Exams.matNr}(\sigma_{result \leq 1.3}(Exams))) \bowtie_{Exams.crsNr=Courses.crsNr} Courses)$
- 4 ...

Add WeChat powcoder




## From RA Expressions to Query Trees

- Each RA expression can be represented as a **query tree**:

- leaf nodes** represent the input relations;
- internal nodes** represent the intermediate result;
- the root node** represents the resulting relation.

- Example:**

$\pi_{\text{lastName}, \text{result}, \text{title}} (\sigma_{\text{result} \leq 1.3} ((\text{Students} \bowtie_{\text{students.matNr} = \text{Exams.matNr}} \text{Exams}) \bowtie_{\text{Exams.crsNr} = \text{Courses.crsNr}} \text{Courses}))$



Add WeChat powcoder




## Query Tree Example

- For each query tree, computation proceeds **bottom-up**:
  - child nodes must be executed before their parent nodes
  - but there can exist multiple methods of executing sibling nodes.

- Example:**



$\pi_{lastName, result, title}(\sigma_{result \leq 1.3}(\sigma_{Exams.crsNr=Courses.crsNr}(\sigma_{Students.matNr=Exams.matNr}(Students \times Exams \times Courses))))$



## Equivalent Query Trees (Query Optimisation)

# Assignment Project Exam Help

<https://powcoder.com>



Add WeChat powcoder

## Execution Plan


(Slide 8-27 will not be assessed in our course)

- A query execution plan consists of an (extended) query tree with additional annotation at each node indicating:

- (1) the *access method* to use for each table, and
- (2) the *implementation method* for each RA operator.

<https://powcoder.com>

Add WeChat powcoder






## Execution Plan

- **Materialized**: The intermediate result of an operator may be saved in a temporary table for processing by the next operator.
- **Pipelined**: the intermediate result of an operator is directly sent to another operator without creating a temporary table (also called **on-the-fly**).

<https://powcoder.com>

Add WeChat powcoder



**Note:** Pipelined evaluation may have significant saving on I/O cost, while materialized evaluation can avoid repeated computations.



## Execution Plan

Assignment Project Exam Help

- Question: Which execution plan is "optimal" in terms of processing efficiency?

<https://powcoder.com>

Add WeChat powcoder



## Execution Plan

# Assignment Project Exam Help

- Question: Which execution plan is "optimal" in terms of processing efficiency?

- This is determined by the query optimiser using a variety of algorithms (Fact: there is no true optimal solution in general!).

<https://powcoder.com>

- Realistically, we cannot expect to always find the best plan, but we expect to **consistently find a plan that is good.**

Add WeChat powcoder



## Execution Plan

# Assignment Project Exam Help

- Question: Which execution plan is "optimal" in terms of processing efficiency?

- This is determined by the query optimiser using a variety of algorithms (**Fact:** there is no true optimal solution in general!).

<https://powcoder.com>

- Realistically, we cannot expect to always find the best plan, but we expect to **consistently find a plan that is good.**

Add WeChat powcoder

- The **performance** of different execution plans for the same query may differ considerably (e.g., seconds vs. hours vs. days):
  - different but equivalent **RA expressions**;
  - different algorithms for **each RA operator**.



## Execution Plan

- Basic ideas of algorithms used for RA operators

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





## Execution Plan

- Basic ideas of algorithms used for RA operators
- **Selection:** If there is no index, we have to scan the table. Otherwise, we scan the indexes to retrieve matching tuples and apply remaining selection conditions to further restrict the tuples.

<https://powcoder.com>

Add WeChat powcoder



## Execution Plan

- Basic ideas of algorithms used for RA operators

- **Selection:** If there is no index, we have to scan the table. Otherwise, we scan the indexes to retrieve matching tuples and apply remaining selection conditions to further restrict the tuples.

- **Projection** retrieves a subset of attributes from each tuple of the table (similar to selection). If requiring duplicate elimination, then we have to do sorting additionally (expensive part!)

Add WeChat powcoder



## Execution Plan

- Basic ideas of algorithms used for RA operators

- **Selection:** If there is no index, we have to scan the table. Otherwise, we scan the indexes to retrieve matching tuples and apply remaining selection conditions to further restrict the tuples.

- **Projection** retrieves a subset of attributes from each tuple of the table (similar to selection). If requiring duplicate elimination, then we have to do sorting additionally (expensive part!)

- **Join:** We may use *nested loops join*, or *sort-merge join*, *hash joins*, *block nested loops join*, etc.



## Execution Plan

- Basic ideas of algorithms used for RA operators

- **Selection:** If there is no index, we have to scan the table. Otherwise, we scan the indexes to retrieve matching tuples and apply remaining selection conditions to further restrict the tuples.

- **Projection** retrieves a subset of attributes from each tuple of the table (similar to selection). If requiring duplicate elimination, then we have to do sorting additionally (expensive part!)

- **Join:** We may use *nested loops join*, or *sort-merge join*, *hash joins*, *block nested loops join*, etc.

- **Group by** and **order by** are typically implemented using sorting.



## Execution Plan

- Basic ideas of algorithms used for RA operators

- **Selection:** If there is no index, we have to scan the table. Otherwise, we scan the indexes to retrieve matching tuples and apply remaining selection conditions to further restrict the tuples.

- **Projection** retrieves a subset of attributes from each tuple of the table (similar to selection). If requiring duplicate elimination, then we have to do sorting additionally (expensive part!)

- **Join:** We may use *nested loops join*, or *sort-merge join*, *hash joins*, *block nested loops join*, etc.

- **Group by** and **order by** are typically implemented using sorting.

- **Aggregation operators** use temporary counters in main memory when retrieving tuples.



## Execution Plan

- Basic ideas of algorithms used for RA operators

- **Selection:** If there is no index, we have to scan the table. Otherwise, we scan the indexes to retrieve matching tuples and apply remaining selection conditions to further restrict the tuples.

- **Projection** retrieves a subset of attributes from each tuple of the table (similar to selection). If requiring duplicate elimination, then we have to do sorting additionally (expensive part!)

- **Join:** We may use *nested loops join*, or *sort-merge join*, *hash joins*, *block nested loops join*, etc.

- **Group by** and **order by** are typically implemented using sorting.

- **Aggregation operators** use temporary counters in main memory when retrieving tuples.

- **Set operators** can use the same approach as projection to eliminate duplicates.



## Estimating Query Costs - Example

- Which movies got a non-US award for one of its actors playing an agent?

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example

- Which movies got a non-US award for one of its actors playing an 'agent'?

$\pi_{\text{title}, \text{production\_year}} (\sigma_{\text{role\_description}='agent'} (\text{ROLE} \bowtie \text{ACTOR\_AWARD} \bowtie (\text{AWARD} \\ - \sigma_{\text{award\_country}='USA'} (\text{AWARD}))))$

<https://powcoder.com>

Add WeChat powcoder




## Estimating Query Costs - Example

- Which movies got a non-US award for one of its actors playing an agent?

$\pi_{\text{title}, \text{production\_year}} (\sigma_{\text{role\_description}='agent'} (\text{ROLE} \bowtie \text{ACTOR\_AWARD} \bowtie (\text{AWARD} - \sigma_{\text{award\_country}='USA'} (\text{AWARD}))))$

<https://powcoder.com>

Add WeChat powcoder



## Size of Relations

# Assignment Project Exam Help

• How to determine the size of a relation  $r$  over  $R(A_1, \dots, A_k)$ ?

- Let  $n$  denote the average number of tuples in  $r$ , and  $\ell_j$  the the average space (e.g., in bits) for attribute  $A_j$ .

<https://powcoder.com>

	$R$			
	$A_1$	$A_2$	$\dots$	$A_k$
1	...	...	...	...
$\dots$	...	...	...	...
$n$	...	...	...	...
	$\ell_1$	$\ell_2$	$\dots$	$\ell_k$

Add WeChat powcoder

## Size of Relations

# Assignment Project Exam Help

• How to determine the size of a relation  $r$  over  $R(A_1, \dots, A_k)$ ?

- Let  $n$  denote the average number of tuples in  $r$ , and  $\ell_j$  the the average space (e.g., in bits) for attribute  $A_j$ .

<https://powcoder.com>

	$A_1$	$A_2$	$\dots$	$A_k$
1	...	...	...	...
$\dots$	...	...	...	...
$n$	...	...	...	...
$\ell_1$	$\ell_2$	$\dots$	$\ell_k$	

Add WeChat powcoder

- Then,  $n \cdot \sum_{j=1}^k \ell_j$  is the size of the relation  $r$ .

- We use this formula to assign sizes to leaf nodes in the query tree.



## Estimating Query Costs - Example (Relation Sizes)

**Assignment Project Exam Help**

```
AWARD(Award_name:varchar(30),Institution:varchar(50),Award_country:  
      varchar(20))
```

<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example (Relation Sizes)

Assignment Project Exam Help

- `AWARD(Award_name:varchar(30),Institution:varchar(50),Award_country:varchar(20))`

- Estimate the average number of tuples as 15.

<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example (Relation Sizes)

Assignment Project Exam Help

```
AWARD(Award_name:varchar(30),Institution:varchar(50),Award_country:  
      varchar(20))
```

- Estimate the average number of tuples as 15.
- Estimate the average space for attributes:

Add WeChat powcoder



## Estimating Query Costs - Example (Relation Sizes)

**Assignment Project Exam Help**

• `AWARD(Award_name: varchar(30), Institution: varchar(50), Award_country: varchar(20))`

- Estimate the average number of tuples as 15.

- Estimate the average space for attributes:

- Award\_name:  $8 \cdot 20 = 160$  bits (the mean length is 20);

- Institution:  $8 \cdot 30 = 240$  bits (the mean length is 30);

- Award\_country:  $8 \cdot 10 = 80$  bits (the mean length is 10).

**Add WeChat powcoder**



## Estimating Query Costs - Example (Relation Sizes)

# Assignment Project Exam Help

• `AWARD(Award_name: varchar(30), Institution: varchar(50), Award_country: varchar(20))`

- Estimate the average number of tuples as 15.

- Estimate the average space for attributes:

- Award\_name:  $8 \cdot 20 = 160$  bits (the mean length is 20);

- Institution:  $8 \cdot 30 = 240$  bits (the mean length is 30);

- Award\_country:  $8 \cdot 10 = 80$  bits (the mean length is 10).

- The average size of a tuple is  $160 + 80 + 240 = 480$  bits.

# Add WeChat powcoder



## Estimating Query Costs - Example (Relation Sizes)

# Assignment Project Exam Help

• `AWARD(Award_name:varchar(30),Institution:varchar(50),Award_country:varchar(20))`

- Estimate the average number of tuples as 15.

- Estimate the average space for attributes:

- Award\_name:  $8 \cdot 20 = 160$  bits (the mean length is 20);

- Institution:  $8 \cdot 30 = 240$  bits (the mean length is 30);

- Award\_country:  $8 \cdot 10 = 80$  bits (the mean length is 10).

- The average size of a tuple is  $160 + 80 + 240 = 480$  bits.
- The average size of a relation is estimated to be  $15 \cdot 480 = 7,200$  bits.



## Estimating Query Costs - Example (Relation Sizes)

Assignment Project Exam Help

- ROLE\_ID:char(3), title:varchar(40), Production\_year:number(4),  
Role\_description:varchar(100),Credits:varchar(40))

<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example (Relation Sizes)

Assignment Project Exam Help

- `ROLE_ID:char(8), title:varchar(40), Production_year:number(4),  
Role_description:varchar(100),Credits:varchar(40))`

- Estimate the average number of tuples as 500.

<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example (Relation Sizes)

Assignment Project Exam Help

• ROLE\_ID:char(8), title:varchar(40), Production\_year:number(4),  
Role\_description:varchar(100),Credits:varchar(40))

- Estimate the average number of tuples as 500.

- Estimate the average space for attributes.

<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example (Relation Sizes)

• `ROLE_ID:char(8), Title:varchar(40), Production_year:number(4),  
Role_description:varchar(100),Credits:varchar(40))`

- Estimate the average number of tuples as 500.
- Estimate the average space for attributes:
  - Id:  $8 \cdot 8 = 64$  bits (as the domain is `char(8)`);
  - Title:  $8 \cdot 25 = 200$  bits (the mean length is 25);
  - Production\_year: 13 bits (as the domain is `number(4)`);
  - Role\_description:  $8 \cdot 50 = 400$  bits (the mean length is 50);
  - Credits:  $8 \cdot 20 = 160$  bits (the mean length is 20).



## Estimating Query Costs - Example (Relation Sizes)

• `ROLE_ID:char(8), title:varchar(40), Production_year:number(4),  
Role_description:varchar(100),Credits:varchar(40))`

- Estimate the average number of tuples as 500.

- Estimate the average space for attributes.

- Id:  $8 \cdot 8 = 64$  bits (as the domain is `char(8)`);
- Title:  $8 \cdot 25 = 200$  bits (the mean length is 25);
- Production\_year: 13 bits (as the domain is `number(4)`);
- Role\_description:  $8 \cdot 50 = 400$  bits (the mean length is 50);
- Credits:  $8 \cdot 20 = 160$  bits (the mean length is 20).

- The average size of a tuple is  $64 + 200 + 13 + 400 + 160 = 837$  bits

## Estimating Query Costs - Example (Relation Sizes)

• `ROLE(id:char(8), title:varchar(40), Production_year:number(4),  
Role_description:varchar(100),Credits:varchar(40))`

- Estimate the average number of tuples as 500.

- Estimate the average space for attributes:

- Id:  $8 \cdot 8 = 64$  bits (as the domain is char(8));
- Title:  $8 \cdot 25 = 200$  bits (the mean length is 25);
- Production\_year: 13 bits (as the domain is number(4));
- Role\_description:  $8 \cdot 50 = 400$  bits (the mean length is 50);
- Credits:  $8 \cdot 20 = 160$  bits (the mean length is 20).

- The average size of a tuple is  $64 + 200 + 13 + 400 + 160 = 837$  bits
- The average size of a relation is to be  $500 \cdot 837 = 418,500$  bits



## Estimating Query Costs - Example (Relation Sizes)

- `ACTOR_AWARD(Title:varchar(40),Production_year:number(4),  
Role_description:varchar(100),Award_name:varchar(30),  
Year_of_award:number(4),Category:varchar(100),Result:varchar(20))`

- Estimate the average number of tuples as 40

- Estimate the average space for attributes:

- Title: 200 bits (as before);
- Production\_year: 13 bits (as before);
- Role\_description: 400 bits (as before);
- Award\_name: 160 bits (as before);
- Year\_of\_award: 13 bits (as the domain is number(4));
- Category:  $8 \cdot 40 = 320$  bits (the mean length is 40);
- Result:  $8 \cdot 7 = 56$  bits (the mean length is 7).

- The average size of a tuple is  $200 + 13 + 400 + 160 + 13 + 320 + 56 = 1,162$  bits.
- The average size of a relation is  $40 \cdot 1162 = 46,480$  bits.




## Estimating Query Costs - Example (Query Tree)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





## Size of Selection Node

# Assignment Project Exam Help

• Selection  $\sigma_{\varphi}$  is linear in the number  $n$  of tuples of the involved relation

- Scan the relation one tuple after another (if there is no index);
- Check for each tuple whether the condition  $\varphi$  is satisfied or not;
- Keep exactly those tuples satisfying  $\varphi$ .

<https://powcoder.com>

Add WeChat powcoder

## Size of Selection Node

# Assignment Project Exam Help

- Selection  $\sigma_{\varphi}$  is linear in the number  $n$  of tuples of the involved relation

- Scan the relation one tuple after another (if there is no index);
- Check for each tuple whether the condition  $\varphi$  is satisfied or not;
- Keep exactly those tuples satisfying  $\varphi$ .

- Let  $s$  be the size of its single relevant node.

- The size of a selection node  $\sigma_{\varphi}$  is

$$a_{\varphi} \cdot s,$$

where  $a_{\varphi}$  is the average percentage of tuples satisfying  $\varphi$ .

# Assignment Project Exam Help

- For selection (award.country='USA' assume  $\alpha_{\varphi} = 0.4$  i.e., 40% of the movie awards from the USA). Hence, we have:  $\alpha_{\varphi}$ 's =  $0.4 \cdot 7,206 = 2,880$ .



# Add WeChat powcoder



## Size of Difference Node

# Assignment Project Exam Help

- Let  $s_1$  and  $s_2$  be the sizes of the two relevant nodes.
- Again, we need to consider the probability that tuples occur in both relations.

<https://powcoder.com>

Add WeChat powcoder



## Size of Difference Node

# Assignment Project Exam Help

- Let  $s_1$  and  $s_2$  be the sizes of the two relevant nodes.
- Again, we need to consider the probability that tuples occur in both relations.
- The **size of a difference node** is


**Add WeChat**  $s_1(1 - p)$  **powcoder**

where  $(1 - p)$  is the probability that tuples from  $s_1$  does not occur in  $s_2$ .

- Since 40% of the movie awards from the USA, the probability of an award to be a US-award is  $p = 0.4$ . We have:  $S_1 \cdot (1 - p) = 7,200 \cdot (1 - 0.4) = 4,320$ .

<https://powercoder.com>

# Add WeChat powcoder





## Size of Natural Join Node

# Assignment Project Exam Help

- Let  $s_1$  and  $s_2$  be the sizes of the two relevant nodes, and  $r_1$  and  $r_2$  be the size of a tuple in these two nodes.  $\frac{s_1}{r_1}$  and  $\frac{s_2}{r_2}$  are the estimated number of tuples in these two nodes.

<https://powcoder.com>

Add WeChat powcoder



## Size of Natural Join Node

# Assignment Project Exam Help

- Let  $s_1$  and  $s_2$  be the sizes of the two relevant nodes, and  $r_1$  and  $r_2$  be the size of a tuple in these two nodes.  $\frac{s_1}{r_1}$  and  $\frac{s_2}{r_2}$  are the estimated number of tuples in these two nodes.

<https://powcoder.com>

- The **size of a natural join node** is

**Add WeChat powcoder**

where  $r$  is the size of a tuple over the **common attributes**, and  $p$  is the **matching probability** (for any tuple of the first relevant node to match with any tuples in the second relevant relation). Note that  $r_1 + r_2 - r$  is the size of a tuple after the natural join operation.


## Estimating Query Costs - Example (Natural Join)

- For join with ACTOR\_AWARD assume  $p = 0.08$ , i.e., 8% of the actor awards are non-US awards. By  $\frac{s_1}{r_1} \cdot p \cdot \frac{s_2}{r_2} \cdot (r_1 + r_2 - r)$ , we have:

$$\frac{46,480}{1,162} \cdot 0.08 \cdot \frac{4,320}{480} \cdot (1,162 + 480 - 160) = 42,682.$$

<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example (Natural Join)


Assignment Project Exam Help

Assume  $p = 0.002$ . By  $\frac{s_1}{r_1} \cdot p \cdot \frac{s_2}{r_2} \cdot (r_1 + r_2 - r)$ , we have:

$$\frac{418,500}{837} \cdot 0.002 \cdot \frac{42,682}{1,482} \cdot (837 + 1,482 - 200 - 400 - 13) = 49,133.$$


<https://powcoder.com>

Add WeChat powcoder



## Estimating Query Costs - Example (Selection)

- For selection  $\sigma_{\text{role\_description}=\text{'agent'}}$ , assume  $a_{c,s} = 0.05$  (i.e., non-US awards for "agent" roles are 5%). Hence, we have:  $a_{c,s} \cdot s = 0.05 \cdot 491133 = 2,457$ .





## Size of Projection Node

# Assignment Project Exam Help

• Projection  $\pi_{A_1, \dots, A_n}$ :

- Project each tuple to the attributes in  $\{A_1, \dots, A_n\}$
- Eliminate duplicates (**Note:** SQL does not eliminate tuples unless DISTINCT is used).

<https://powcoder.com>

Add WeChat powcoder



## Size of Projection Node

# Assignment Project Exam Help

- Projection  $\pi_{A_1, \dots, A_n}$ :
  - Project each tuple to the attributes in  $\{A_1, \dots, A_n\}$
  - Eliminate duplicates (**Note**: SQL does not eliminate tuples unless DISTINCT is used).
- Let  $s$  be the size of its single relevant node with  $s = n \cdot r$  for its average number  $n$  of tuples and its average size  $r$  of a tuple.
- The **size of a projection node**  $\pi_{A_1, \dots, A_n}$  is

<https://powcoder.com>


Add WeChat powcoder

$$(1 - p_i) \cdot s \frac{r_i}{r},$$

where  $r_i$  is the average size of a tuple over  $\{A_1, \dots, A_n\}$ , and  $p_i$  is the probability that two tuples coincide on  $A_1, \dots, A_n$  (i.e., the same values on all attributes  $A_1, \dots, A_n$ ).

## Estimating Query Costs - Example (Projection)

- For projection  $\pi_{\text{title, production\_year}}$  assume that there are 1% of duplicates i.e.,  $p_i = 0.01$ . By  $(1 - p_i) \cdot s \cdot \frac{r_i}{r}$ , we have  $(1 - 0.01) \cdot 2,457 \cdot \frac{213}{1706} = 304$



## Query Optimisation

# Assignment Project Exam Help

I can remember song lyrics from  
2006 but not whatever maths  
formula we were learning yesterday

<https://powcoder.com>

Add WeChat powcoder




©santabanta.com



## Relational Algebra $\Rightarrow$ Query Optimisation

Assignment Project Exam Help

<https://powcoder.com>




- Which RA query should be chosen for a given SQL query?

Add WeChat powcoder

## Relational Algebra $\Rightarrow$ Query Optimisation

Assignment Project Exam Help

<https://powcoder.com>



- Which RA query should be chosen for a given SQL query?


- Who choose?

Add WeChat powcoder

## Relational Algebra $\Rightarrow$ Query Optimisation

Assignment Project Exam Help

<https://powcoder.com>



- Which RA query should be chosen for a given SQL query?


• Who choose? Query optimiser!

Add WeChat powcoder

## Relational Algebra $\Rightarrow$ Query Optimisation

Assignment Project Exam Help

<https://powcoder.com>



- Which RA query should be chosen for a given SQL query?

• Who choose? Query optimiser!


• How to choose?

Add WeChat powcoder

## Relational Algebra $\Rightarrow$ Query Optimisation

Assignment Project Exam Help

<https://powcoder.com>



- Which RA query should be chosen for a given SQL query?

• Who choose? Query optimiser!

• How to choose?

- Semantic query optimisation
- Rule-based optimisation
- Cost-based optimisation

Add WeChat powcoder



## Query Optimisation

# Assignment Project Exam Help

- In practice, query optimisers incorporate elements of the following three optimisation approaches:

<https://powcoder.com>

Add WeChat powcoder



## Query Optimisation

# Assignment Project Exam Help

- In practice, query optimisers incorporate elements of the following three optimisation approaches:

- **Semantic query optimisation**

<https://powcoder.com>  
Use application specific semantic knowledge to transform a query into the one with a lower cost (they return the same answer).

# Add WeChat powcoder



## Query Optimisation

# Assignment Project Exam Help

- In practice, query optimisers incorporate elements of the following three optimisation approaches:

- **Semantic query optimisation**

<https://powcoder.com>  
Use application specific semantic knowledge to transform a query into the one with a lower cost (they return the same answer).

- **Rule-based query optimisation**

[Add WeChat powcoder](https://powcoder.com)  
Use heuristic rules to transform a relational algebra expression into an equivalent one with a possibly lower cost.





## Query Optimisation

# Assignment Project Exam Help

- In practice, query optimisers incorporate elements of the following three optimisation approaches:

- **Semantic query optimisation**

<https://powcoder.com>  
Use application specific semantic knowledge to transform a query into the one with a lower cost (they return the same answer).

- **Rule-based query optimisation**

[Add WeChat powcoder](#)  
Use heuristic rules to transform a relational algebra expression into an equivalent one with a possibly lower cost.

- **Cost-based query optimisation**

Use a cost model to estimate the costs of plans, and then select the most cost-effective plan. This will not be assessed in our course.



## Semantic Query Optimisation

# Assignment Project Exam Help

- Example:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

WRITER(id, title, production\_year, credits) where

$[id] \subseteq \text{PERSON}[id]$   
 $[title, production\_year] \subseteq \text{MOVIE}[title, production\_year]$

- List the ids of the writers who have written movies produced in 2000.

Add WeChat powcoder



## Semantic Query Optimisation

# Assignment Project Exam Help

- Example:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

WRITER(id, title, production\_year, credits) where

$[id] \subseteq \text{PERSON}[id]$   
 $[title, production\_year] \subseteq \text{MOVIE}[title, production\_year]$

<https://powcoder.com>

- List the ids of the writers who have written movies produced in 2000.

$\pi_{id} \sigma_{production\_year=2000} (\text{WRITER} \bowtie \text{PERSON} \bowtie \text{MOVIE})$

$\pi_{id} \sigma_{production\_year=2000} (\text{WRITER} \bowtie \text{PERSON})$

$\pi_{id} \sigma_{production\_year=2000} (\text{WRITER} \bowtie \text{MOVIE})$

Add WeChat powcoder

## Semantic Query Optimisation

# Assignment Project Exam Help

- Example:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

WRITER(id, title, production\_year, credits) where

$[id] \subseteq \text{PERSON}[id]$   
 $[title, production\_year] \subseteq \text{MOVIE}[title, production\_year]$

<https://powcoder.com>

- List the ids of the writers who have written movies produced in 2000.

$\pi_{id} \sigma_{production\_year=2000} (\text{WRITER} \bowtie \text{PERSON} \bowtie \text{MOVIE})$

$\pi_{id} \sigma_{production\_year=2000} (\text{WRITER} \bowtie \text{PERSON})$

$\pi_{id} \sigma_{production\_year=2000} (\text{WRITER} \bowtie \text{MOVIE})$

- $\pi_{id} \sigma_{production\_year=2000} \text{WRITER}$   $\longleftarrow$  the optimised RA

Add WeChat powcoder



## Rule-based Query Optimisation

# Assignment Project Exam Help

- A rule-based optimisation transforms the RA expression by using a set of heuristic rules that typically improve the execution performance.

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Query Optimisation

# Assignment Project Exam Help

- A rule-based optimisation transforms the RA expression by using a set of heuristic rules that typically improve the execution performance.
- **Key ideas:** apply the most restrictive operation before other operations, which can reduce the size of intermediate results.

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Query Optimisation

# Assignment Project Exam Help

- A rule-based optimisation transforms the RA expression by using a set of heuristic rules that typically improve the execution performance.
- **Key ideas:** apply the most restrictive operation before other operations, which can reduce the size of intermediate results:

- **Push-down selection:**

Apply as early as possible to reduce the number of tuples:

# Add WeChat powcoder



## Rule-based Query Optimisation

# Assignment Project Exam Help

- A rule-based optimisation transforms the RA expression by using a set of heuristic rules that typically improve the execution performance.
- **Key ideas:** apply the most restrictive operation before other operations, which can reduce the size of intermediate results:

<https://powcoder.com>

- **Push-down selection:**

Apply as early as possible to reduce the number of tuples:

- **Push-down projection:**

Apply as early as possible to reduce the number of attributes.

Add WeChat powcoder





## Rule-based Query Optimisation

# Assignment Project Exam Help

- A rule-based optimisation transforms the RA expression by using a set of heuristic rules that typically improve the execution performance.
- **Key ideas:** apply the most restrictive operation before other operations, which can reduce the size of intermediate results:

<https://powcoder.com>

- **Push-down selection:**

Apply as early as possible to reduce the number of tuples:

- **Push-down projection:**

Apply as early as possible to reduce the number of attributes.

Add WeChat powcoder

## Rule-based Query Optimisation

# Assignment Project Exam Help

- A rule-based optimisation transforms the RA expression by using a set of heuristic rules that typically improve the execution performance.
- **Key ideas:** apply the most restrictive operation before other operations, which can reduce the size of intermediate results:

- **Push-down selection:**

Apply as early as possible to reduce the number of tuples:

- **Push-down projection:**

Apply as early as possible to reduce the number of attributes.

- But we must ensure that the resulting query tree gives the same result as the original query tree, i.e., **the equivalence of RA expressions**.



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators.

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\hookrightarrow$  Merging RA operators.

- $\sigma_{\varphi}(\sigma_{\psi}(R)) \equiv \sigma_{\varphi \wedge \psi}(R);$

- $\pi_{\chi}(\pi_{\gamma}(R)) \equiv \pi_{\chi}(\pi_{\gamma \wedge \psi}(R));$

<https://powcoder.com>

- $\sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2;$

- $\sigma_{\varphi_1}(R_1 \bowtie_{\varphi_2} R_2) \equiv R_2 \bowtie_{\varphi_1 \wedge \varphi_2} R_1;$

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

- $\sigma_{\varphi}(\sigma_{\psi}(R)) \equiv \sigma_{\varphi \wedge \psi}(R);$

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

- $\sigma_{\varphi}(\sigma_{\psi}(R)) \equiv \sigma_{\varphi \wedge \psi}(R);$

$\sigma_{CourseNo='COMP2400'}(\sigma_{UID=111}(STUDY))$  v.s.  $\sigma_{(Course='COMP2400') \wedge (UID=111)}(STUDY)$

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\hookrightarrow$  Merging RA operators

$$\sigma_{\varphi}(\sigma_{\psi}(R)) \equiv \sigma_{\varphi \wedge \psi}(R);$$

$\sigma_{\text{CourseNo}='COMP2400'}(\sigma_{\text{UID}=111}(\text{STUDY}))$  v.s.  $\sigma_{(\text{Course}='COMP2400') \wedge (\text{UID}=111)}(\text{STUDY})$

STUDY		
UID	CourseNo	Hours
111	COMP2400	120
222	COMP2400	115
333	STAT2001	120
111	BUSN2011	110
111	ECON2102	120
333	BUSN2011	130

STUDY		
UID	CourseNo	Hours
111	COMP2400	120
111	BUSN2011	110
111	ECON2102	120

STUDY		
UID	CourseNo	Hours
111	COMP2400	120

<https://powcoder.com>

Add WeChat powcoder





## Rule-based Optimisation

- Can they be executed in one go?  $\hookrightarrow$  Merging RA operators

$$\sigma_{\varphi}(\sigma_{\psi}(R)) \equiv \sigma_{\varphi \wedge \psi}(R);$$

$\sigma_{CourseNo='COMP2400'}(\sigma_{UID=111}(STUDY))$  v.s.  $\sigma_{(Course='COMP2400') \wedge (UID=111)}(STUDY)$

STUDY		
UID	CourseNo	Hours
111	COMP2400	120
222	COMP2400	115
333	STAT2001	120
111	BUSN2011	110
111	ECON2102	120
333	BUSN2011	130

STUDY		
UID	CourseNo	Hours
111	COMP2400	120
111	BUSN2011	110
111	ECON2102	120

STUDY		
UID	CourseNo	Hours
111	COMP2400	120

STUDY		
UID	CourseNo	Hours
111	COMP2400	120
222	COMP2400	115
333	STAT2001	120
111	BUSN2011	110
111	ECON2102	120
333	BUSN2011	130



(without any intermediate relation)

STUDY		
UID	CourseNo	Hours
111	COMP2400	120

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

- $\pi_X(\pi_Y(R)) \equiv \pi_X(R)$  if  $X \subseteq Y$ ,

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

- $\pi_X(\pi_Y(R)) \equiv \pi_X(R)$  if  $X \subseteq Y$ ,

$$\pi_{UID}(\pi_{UID, CourseNo}(Study)) \quad \text{v.s.} \quad \pi_{UID}(Study)$$

<https://powcoder.com>

Add WeChat powcoder

## Rule-based Optimisation

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

$$\pi_X(\pi_Y(R)) \equiv \pi_X(R) \text{ if } X \subseteq Y,$$

$\pi_{UID}(\pi_{UID, CourseNo}(Study))$

v.s.  $\pi_{UID}(Study)$

Study		
UID	CourseNo	Hours
111	COMP2400	120
222	COMP2400	115
333	STAT2001	120
111	BUSN2011	110
111	ECON2102	120
333	BUSN2011	130

Study	
UID	CourseNo
111	COMP2400
222	COMP2400
333	STAT2001
111	BUSN2011
111	ECON2102
333	BUSN2011

UID
111
222
333

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can they be executed in one go?  $\hookrightarrow$  Merging RA operators

$$\pi_X(\pi_Y(R)) \equiv \pi_X(R) \text{ if } X \subseteq Y,$$

$\pi_{UID}(\pi_{UID, CourseNo}(Study))$

v.s.  $\pi_{UID}(Study)$

Study		
UID	CourseNo	Hours
111	COMP2400	120
222	COMP2400	115
333	STAT2001	120
111	BUSN2011	110
111	ECON2102	120
333	BUSN2011	130

Study	
UID	CourseNo
111	COMP2400
222	COMP2400
333	STAT2001
111	BUSN2011
111	ECON2102
333	BUSN2011

UID
111
222
333

STUDY		
UID	CourseNo	Hours
111	COMP2400	120
222	COMP2400	115
333	STAT2001	120
111	BUSN2011	110
111	ECON2102	120
333	BUSN2011	130



(without any intermediate relation)

UID
111
222
333

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\leftrightarrow$  Merging RA operators

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\rightarrow$  Merging RA operators

- $\sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$

<https://powcoder.com>

Add WeChat powcoder





## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\rightarrow$  Merging RA operators

- $\sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$

$$\sigma_{Course.No=Enrol.CoureNo}(Course \times Enrol)$$

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\rightarrow$  Merging RA operators

- $\sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$

$$\sigma_{Course.No=Enrol.CourseNo}(Course \times Enrol)$$

<https://powcoder.com>

Course		
No	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Enrol			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

• Can they be executed in one go?  $\rightarrow$  Merging RA operators

$$\bullet \sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$$

$$\sigma_{Course.No=Enrol.CourseNo}(Course \times Enrol)$$

<https://powcoder.com>

Course		
No	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Enrol			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder

No	Cname	Unit	StudentID	CourseNo	Semester	Status
COMP2400	Relational Databases	6	111	BUSN2011	2016 S1	active
COMP2400	Relational Databases	6	222	COMP2400	2016 S1	active
COMP2400	Relational Databases	6	111	COMP2400	2016 S2	active
BUSN2011	Management Accounting	6	111	BUSN2011	2016 S1	active
BUSN2011	Management Accounting	6	222	COMP2400	2016 S1	active
BUSN2011	Management Accounting	6	111	COMP2400	2016 S2	active



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\rightarrow$  Merging RA operators

- $\sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$

$$\sigma_{Course.No=Enrol.CourseNo}(Course \times Enrol)$$

<https://powcoder.com>

Course		
No	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Enrol			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder

No	Cname	Unit	StudentID	CourseNo	Semester	Status
COMP2400	Relational Databases	6	111	BUSN2011	2016 S1	active
COMP2400	Relational Databases	6	222	COMP2400	2016 S1	active
COMP2400	Relational Databases	6	111	COMP2400	2016 S2	active
BUSN2011	Management Accounting	6	111	BUSN2011	2016 S1	active
BUSN2011	Management Accounting	6	222	COMP2400	2016 S1	active
BUSN2011	Management Accounting	6	111	COMP2400	2016 S2	active



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\rightarrow$  Merging RA operators

$$\sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$$

*Course*  $\bowtie_{Course.No=Enrol.CourseNo}$  *Enrol*

<https://powcoder.com>

Course		
No	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Enrol			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can they be executed in one go?  $\rightarrow$  Merging RA operators

$$\sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$$

*Course*  $\bowtie_{Course.No=Enrol.CourseNo}$  *Enrol*

<https://powcoder.com>

Course		
No	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Enrol			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder

Inner Join on *Course.No=Enrol.CourseNo* (no intermediate Cartesian product)

No	Cname	Unit	StudentID	CourseNo	Semester	Status
COMP2400	Relational Databases	6	222	COMP2400	2016 S1	active
COMP2400	Relational Databases	6	111	COMP2400	2016 S2	active
BUSN2011	Management Accounting	6	111	BUSN2011	2016 S1	active



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;

- $\sigma_{\varphi_1 \wedge \varphi_2}(R_1 \bowtie R_2) \equiv \sigma_{\varphi_1}(R_1) \bowtie \sigma_{\varphi_2}(R_2)$  if  $\varphi_1$  contains only attributes in  $R_1$  and  $\varphi_2$  contains only attributes in  $R_2$ ;

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition contains attributes not in  $X$ , where  $X_i$  contains attributes both in  $R_i$  and  $X$ , and ones both in  $R_i$  and  $R_2$ ;

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , where  $X_i$  contains attributes both in  $R_i$  and  $X$ , and ones both in  $R_1$  and  $R_2$ ;





## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\rightarrow$  Push select/project before join

- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;  
 $\sigma_{Cname='ManagementAccounting'}(Course \bowtie Enrol)$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

# Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\rightarrow$  Push select/project before join

- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;

$\sigma_{Cname='ManagementAccounting'}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentNo	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\rightarrow$  Push select/project before join

- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;

$\sigma_{Cname='ManagementAccounting'}(Course \bowtie Enrol)$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder

CourseNo	Cname	Unit	StudentID	Semester	Status
COMP2400	Relational Databases	6	222	2016 S1	active
COMP2400	Relational Databases	6	111	2016 S2	active
BUSN2011	Management Accounting	6	111	2016 S1	active

## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\rightarrow$  Push select/project before join

- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;  
 $\sigma_{Cname='ManagementAccounting'}(Course \bowtie Enrol)$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

CourseNo	Cname	Unit	StudentID	Semester	Status
COMP2400	Relational Databases	6	222	2016 S1	active
COMP2400	Relational Databases	6	111	2016 S2	active
BUSN2011	Management Accounting	6	111	2016 S1	active

CourseNoNo	Cname	Unit	StudentID	Semester	Status
BUSN2011	Management Accounting	6	111	2016 S1	active



## Rule-based Optimisation

# Assignment Project Exam Help

• Can join be executed last?  $\leftrightarrow$  Push select/project before join

- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;  
 $\sigma_{Cname='ManagementAccounting'}(Course) \bowtie Enrol$

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join
- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;  
 $\sigma_{Cname='ManagementAccounting'}(Course) \bowtie Enrol$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

<https://powcoder.com>

Add WeChat powcoder

## Rule-based Optimisation

# Assignment Project Exam Help

• Can join be executed last?  $\leftrightarrow$  Push select/project before join

- $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;  
 $\sigma_{Cname='ManagementAccounting'}(Course) \bowtie Enrol$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

COURSE		
CourseNo	Cname	Unit
BUSN2011	Management Accounting	6

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

• Can join be executed last?  $\leftrightarrow$  Push select/project before join

•  $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;

$\sigma_{Cname='ManagementAccounting'}(Course) \bowtie Enrol$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

COURSE		
CourseNo	Cname	Unit
BUSN2011	Management Accounting	6

<https://powcoder.com>

Add WeChat powcoder





## Rule-based Optimisation

# Assignment Project Exam Help

• Can join be executed last?  $\leftrightarrow$  Push select/project before join

•  $\sigma_{\varphi}(R_1 \bowtie R_2) \equiv \sigma_{\varphi}(R_1) \bowtie R_2$ , if  $\varphi$  contains only attributes in  $R_1$ ;

$\sigma_{Cname='ManagementAccounting'}(Course) \bowtie Enrol$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

COURSE		
CourseNo	Cname	Unit
BUSN2011	Management Accounting	6

Add WeChat powcoder

CourseNo	Cname	Unit	StudentID	Semester	Status
BUSN2011	Management Accounting	6	111	2016 S1	active



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

<https://powcoder.com>

Add WeChat powcoder

## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

$\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

CourseNo	Cname	Unit	StudentID	Semester	Status
COMP2400	Relational Databases	6	222	2016 S1	active
COMP2400	Relational Databases	6	111	2016 S2	active
BUSN2011	Management Accounting	6	111	2016 S1	active

## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

CourseNo	Cname	Unit	StudentID	Semester	Status
COMP2400	Relational Databases	6	222	2016 S1	active
COMP2400	Relational Databases	6	111	2016 S2	active
BUSN2011	Management Accounting	6	111	2016 S1	active

CourseNo	Cname	StudentID
COMP2400	Relational Databases	222
COMP2400	Relational Databases	111
BUSN2011	Management Accounting	111



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol)$

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol)$

<https://powcoder.com>

Course		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

$\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

$\pi_{CourseNo, Cname}(Course)$	
CourseNo	Cname
COMP2400	Relational Databases
BUSN2011	Management Accounting

## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

$\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo, Cname}(Course)$	
CourseNo	Cname
COMP2400	Relational Databases
BUSN2011	Management Accounting

<https://powcoder.com>

Add WeChat powcoder

## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol)$

Course		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo, Cname} Course$		
CourseNo	Cname	
COMP2400	Relational Databases	
BUSN2011	Management Accounting	

$\pi_{CourseNo, StudentID} ENROL$	
StudentID	CourseNo
111	BUSN2011
222	COMP2400
111	COMP2400

## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

$\pi_X(R_1 \bowtie R_2) \equiv \pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)$ , if the join condition involves only attributes in  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol)$

Course		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo, Cname} Course$	
CourseNo	Cname
COMP2400	Relational Databases
BUSN2011	Management Accounting

$\pi_{CourseNo, StudentID} ENROL$	
StudentID	CourseNo
111	BUSN2011
222	COMP2400
111	COMP2400

CourseNo	Cname	StudentID
COMP2400	Relational Databases	222
COMP2400	Relational Databases	111
BUSN2011	Management Accounting	111



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder





## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

# Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

Add WeChat powcoder

## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

$\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

CourseNo	Cname	Unit	StudentID	Semester	Status
COMP2400	Relational Databases	6	222	2016 S1	active
COMP2400	Relational Databases	6	111	2016 S2	active
BUSN2011	Management Accounting	6	111	2016 S1	active



## Rule-based Optimisation

- Can join be executed last?  $\Rightarrow$  Push select/project before join.

$\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

CourseNo	Cname	Unit	StudentID	Semester	Status
COMP2400	Relational Databases	6	222	2016 S1	active
COMP2400	Relational Databases	6	111	2016 S2	active
BUSN2011	Management Accounting	6	111	2016 S1	active

Cname	StudentID
Relational Databases	222
Relational Databases	111
Management Accounting	111



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join
- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Course, studentID}(Course \bowtie Enrol) = \pi_{name}(Course) \times \pi_{StudentID}(Enrol)?$

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

• Can join be executed last?  $\leftrightarrow$  Push select/project before join

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, studentID}(Course \bowtie Enrol) = \pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)?$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Add WeChat powcoder





## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join
- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, studentID}(Course \bowtie Enrol) = \pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)?$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

$\pi_{Cname} COURSE$
Cname
Relational
Management

Add WeChat powcoder

## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join

- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol) = \pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)?$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{Cname} COURSE$
Cname
Relational
Management

Add WeChat powcoder

## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join
- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, StudentID}(Course \bowtie Enrol) = \pi_{CourseNo}(Course) \bowtie \pi_{StudentID}(Enrol)?$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo} COURSE$
Cname
Relational
Management

$\pi_{StudentID} ENROL$
StudentID
111
222

Add WeChat powcoder



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join
- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{CourseNo, StudentID}(Course \bowtie Enrol) = \pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)?$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{Cname} COURSE$
Cname
Relational
Management

$\pi_{StudentID} ENROL$
StudentID
111
222

Add WeChat powcoder

Is  $\pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)$  our desired result?



## Rule-based Optimisation

# Assignment Project Exam Help

- Can join be executed last?  $\leftrightarrow$  Push select/project before join
- $\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol) \neq \pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)?$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{Cname} COURSE$
Cname
Relational
Management

$\pi_{StudentID} ENROL$
StudentID
111
222

Is  $\pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)$  our desired result?

No.  $\pi_{Cname, StudentID}(Course \bowtie Enrol) \neq \pi_{Cname}(Course) \bowtie \pi_{StudentID}(Enrol)$



## Rule-based Optimisation

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) = \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

$\pi_{Cname, StudentID}(\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol))$

<https://powcoder.com>

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) = \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

$\pi_{Cname, StudentID}(\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol))$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

Add WeChat powcoder

## Rule-based Optimisation

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) = \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

$\pi_{Cname, StudentID}(\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol))$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

$\pi_{CourseNo, Cname}(COURSE)$	
CourseNo	Cname
COMP2400	Relational Databases
BUSN2011	Management Accounting

Add WeChat powcoder



## Rule-based Optimisation

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

•  $\pi_X(R_1 \bowtie R_2) = \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

$\pi_{Cname, StudentID}(\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol))$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo, Cname}(Course)$	
CourseNo	Cname
COMP2400	Relational Databases
BUSN2011	Management Accounting

Add WeChat powcoder

## Rule-based Optimisation

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) = \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

$\pi_{Cname, StudentID}(\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol))$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo, Cname}(COURSE)$	
CourseNo	Cname
COMP2400	Relational Databases
BUSN2011	Management Accounting

$\pi_{CourseNo, StudentID}(ENROL)$	
StudentID	CourseNo
111	BUSN2011
222	COMP2400
111	COMP2400

Add WeChat powcoder

## Rule-based Optimisation

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) = \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

$\pi_{Cname, StudentID}(\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol))$

<https://powcoder.com>

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo, Cname}(COURSE)$		
CourseNo	Cname	
COMP2400	Relational Databases	
BUSN2011	Management Accounting	

$\pi_{CourseNo, StudentID}(ENROL)$	
StudentID	CourseNo
111	BUSN2011
222	COMP2400
111	COMP2400

CourseNo	Cname	StudentID
COMP2400	Relational Databases	222
COMP2400	Relational Databases	111
BUSN2011	Management Accounting	111

Add WeChat powcoder

## Rule-based Optimisation

- Can join be executed last?  $\leftrightarrow$  Push select/project before join.

- $\pi_X(R_1 \bowtie R_2) = \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2))$ , if the join condition involves attributes outside  $X$ , how could we derive  $X_1$  and  $X_2$ ?

$\pi_{Cname, StudentID}(Course \bowtie Enrol)$

$\pi_{Cname, StudentID}(\pi_{CourseNo, Cname}(Course) \bowtie \pi_{CourseNo, StudentID}(Enrol))$

COURSE		
CourseNo	Cname	Unit
COMP2400	Relational Databases	6
BUSN2011	Management Accounting	6

$\pi_{CourseNo, Cname}(COURSE)$	
CourseNo	Cname
COMP2400	Relational Databases
BUSN2011	Management Accounting

CourseNo	Cname	StudentID
COMP2400	Relational Databases	222
COMP2400	Relational Databases	111
BUSN2011	Management Accounting	111

ENROL			
StudentID	CourseNo	Semester	Status
111	BUSN2011	2016 S1	active
222	COMP2400	2016 S1	active
111	COMP2400	2016 S2	active

$\pi_{CourseNo, StudentID}(ENROL)$	
StudentID	CourseNo
111	BUSN2011
222	COMP2400
111	COMP2400

Cname	StudentID
Relational Databases	222
Relational Databases	111
Management Accounting	111



## Heuristic Rules and Query Trees

(\*)  $\sigma_\varphi(\sigma_\psi(R)) \equiv \sigma_{\varphi \wedge \psi}(R)$

$\sigma_\varphi$

|

$\sigma_\psi$

|

$R$

$\sigma_{\varphi \wedge \psi}$

|

$R$

<https://powcoder.com>

Add WeChat powcoder




## Heuristic Rules and Query Trees

Assignment Project Exam Help

<https://powcoder.com>

(2)  $\pi_X(\pi_Y(R)) \equiv \pi_X(R)$  if  $X \subseteq Y$ ;

Add WeChat powcoder





## Heuristic Rules

$$(3) \sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$$

$$\sigma_{\varphi}$$

$$\times$$

$$\bowtie_{\varphi}$$

$$R_1$$

$$R_2$$

$$R_1$$

$$R_2$$

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Heuristic Rules

$$(3) \sigma_{\varphi}(R_1 \times R_2) \equiv R_1 \bowtie_{\varphi} R_2$$

 $\sigma_{\varphi}$ 
 $\times$ 
 $R_1$ 
 $R_2$ 
 $\bowtie_{\varphi}$ 
 $R_1$ 
 $R_2$ 

<https://powcoder.com>

$$(4) \sigma_{\varphi_1}(R_1 \bowtie_{\varphi_2} R_2) \equiv R_1 \bowtie_{\varphi_1 \wedge \varphi_2} R_2$$

 $\sigma_{\varphi_1}$ 
 $\bowtie_{\varphi_2}$ 
 $R_1$ 
 $R_2$ 
 $\bowtie_{\varphi_1 \wedge \varphi_2}$ 
 $R_1$ 
 $R_2$ 

Add WeChat powcoder





## Push-down Selection – Example

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query: List all war movies that are performed by Tom Cruise.

$$\pi_{\text{title, production\_year}}(\sigma_{\text{title}=\text{mtitle} \wedge \text{production\_year}=\text{mprod\_year}}(\sigma_{\text{major\_genre}=\text{'war'} \wedge \text{first\_name}=\text{'Tom'} \wedge \text{last\_name}=\text{'Cruise'}}(\text{MOVIE} \times (\text{PERSON} \bowtie \text{ROLE}))))$$

Add WeChat powcoder

## Push-down Selection – Example

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query: List all war movies that are performed by 'Tom Cruise'.

$\pi_{\text{title, production\_year}}(\sigma_{\text{title}=m\text{title} \wedge \text{production\_year}=m\text{prod\_year}}(\sigma_{\text{major\_genre}='war' \wedge \text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{MOVIE} \times (\text{PERSON} \bowtie \text{ROLE}))))$

- Question: Can we apply the following rule to optimise the query?  
 $\sigma_{\varphi_1 \wedge \varphi_2}(R_1 \bowtie R_2) \equiv \sigma_{\varphi_1}(R_1) \times \sigma_{\varphi_2}(R_2)$  if  $\varphi_1$  contains only attributes in  $R_1$  and  $\varphi_2$  contains only attributes in  $R_2$

## Push-down Selection – Example

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query** List all 'war' movies that are performed by 'Tom Cruise'.

$$\pi_{\text{title, production\_year}}(\sigma_{\text{title}=m\text{title} \wedge \text{production\_year}=m\text{prod\_year}}(\sigma_{\text{major\_genre}='war' \wedge \text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{MOVIE} \times (\text{PERSON} \bowtie \text{ROLE}))))$$


- Question** Can we apply the following rule to optimise the query?  
 $\sigma_{\varphi_1 \wedge \varphi_2}(R_1 \cup R_2) \equiv \sigma_{\varphi_1}(R_1) \times \sigma_{\varphi_2}(R_2)$  if  $\varphi_1$  contains only attributes in  $R_1$  and  $\varphi_2$  contains only attributes in  $R_2$
- We would have

$$\pi_{\text{title, production\_year}}(\sigma_{\text{title}=m\text{title} \wedge \text{production\_year}=m\text{prod\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE}) \times \sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE})))$$



## Push-down Selection – Example

# Assignment Project Exam Help



## Push-down Selection – Example

# Assignment Project Exam Help

- Given the relation schema:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query: List all war movies that are performed by 'Tom Cruise'.

$$\pi_{\text{title, production\_year}}(\sigma_{\text{title}=\text{mtitle} \wedge \text{production\_year}=\text{mprod\_year}}(\sigma_{\text{major\_genre}=\text{'war'}}(\text{MOVIE}))$$

$$\times \sigma_{\text{first\_name}=\text{'Tom'} \wedge \text{last\_name}=\text{'Cruise'}}(\text{PERSON} \bowtie \text{ROLE}))$$

# Add WeChat powcoder

## Push-down Selection – Example

- Given the relation schema:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query: List all war movies that are performed by 'Tom Cruise'.

$$\pi_{\text{title, production\_year}}(\sigma_{\text{title}=\text{mtitle} \wedge \text{production\_year}=\text{mprod\_year}}(\sigma_{\text{major\_genre}=\text{'war'}}(\text{MOVIE}))$$
$$\times \sigma_{\text{first\_name}=\text{'Tom'} \wedge \text{last\_name}=\text{'Cruise'}}(\text{PERSON} \bowtie \text{ROLE}))$$

- Can we apply  $\sigma_{\varphi}(R_1 \times R_2) = R_1 \bowtie_{\varphi} R_2$ ?

Add WeChat powcoder

## Push-down Selection – Example

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query: List all war movies that are performed by 'Tom Cruise'.

$$\pi_{\text{title, production\_year}}(\sigma_{\text{title}=m\text{title} \wedge \text{production\_year}=m\text{prod\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE}))$$

$$\times \sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE}))$$


- Can we apply  $\sigma_{\varphi}(R_1 \times R_2) = R_1 \bowtie_{\varphi} R_2$ ?
- We would have

$$\pi_{\text{title, production\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE}) \bowtie_{\text{title}=m\text{title} \wedge \text{production\_year}=m\text{prod\_year}} ($$

$$\sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE})))$$

## Push-down Selection – Example

# Assignment Project Exam Help







## Push-down Projection – Example

# Assignment Project Exam Help

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query:** List all war movies that are performed by 'Tom Cruise'.

$$\pi_{\text{title, production\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE}) \bowtie_{\text{title}=m\text{title} \wedge \text{production\_year}=m\text{prod\_year}} (\sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE})))$$

Add WeChat powcoder



## Push-down Projection – Example

# Assignment Project Exam Help

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query:** List all war movies that are performed by 'Tom Cruise'.

$\pi_{\text{title, production\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE}) \bowtie_{\text{title}=m\text{title} \wedge \text{production\_year}=m\text{prod\_year}} (\sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE})))$

- Question:** Can we apply the following rule to optimise the query?

$$\pi_X(R_1 \bowtie R_2) \equiv \pi_X(\pi_{X_1}(R_1) \bowtie \pi_{X_2}(R_2)),$$

where  $X_i$  contains attributes both in  $R_i$  and  $X$ , and ones both in  $R_1$  and  $R_2$

## Push-down Projection – Example

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query: List all war movies that are performed by 'Tom Cruise'.

$\pi_{\text{title, production\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE}) \bowtie_{\text{title}=\text{mtitle} \wedge \text{production\_year}=\text{mprod\_year}} ($

$\sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE})))$

Add WeChat powcoder

## Push-down Projection – Example

- Given the relation schemas:

PERSON(id, first\_name, last\_name, year\_born)

MOVIE(title, production\_year, country, run\_time, major\_genre)

ROLE(id, mtitle, mprod\_year, description, credits)

- Query: List all war movies that are performed by 'Tom Cruise'.

$$\pi_{\text{title}, \text{production\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE}) \bowtie_{\text{title}=\text{mtitle} \wedge \text{production\_year}=\text{mprod\_year}} (\sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE})))$$


- We would have:

$$\pi_{\text{title}, \text{production\_year}}(\pi_{\text{title}, \text{production\_year}}(\sigma_{\text{major\_genre}='war'}(\text{MOVIE})))$$
$$\bowtie_{\text{title}=\text{mtitle} \wedge \text{production\_year}=\text{mprod\_year}}$$
$$(\pi_{\text{mtitle}, \text{mprod\_year}}(\sigma_{\text{first\_name}='Tom' \wedge \text{last\_name}='Cruise'}(\text{PERSON} \bowtie \text{ROLE}))))$$

We further apply some rules to optimise the query ...

## Push-down Projection – Example

Assignment Project Exam Help



## Cost-based Optimisation (not assessed)

- Consider CHARTS = {Rank, Artist, Song} with 100 tuples and 3 attributes.

Rank	Artist	Song
1	Chingy	Right Thurr
2	Scribe	Stand up
3	Aguilera and Kim	Can't hold us down
4	Evanescence	Going under
5	Justin Timberlake	Senorita
6	Brooke Fraser	Better
7	Black Eyed Peas	Where is the love?
...	...	...
...	...	...

- Compare two strategies of evaluating "Who is top of the pops?":
  - $\sigma_{\text{Rank}=1}(\pi_{\text{Rank, Artist}}(\text{CHARTS}))$
  - $\pi_{\text{Rank, Artist}}(\sigma_{\text{Rank}=1}(\text{CHARTS}))$

## Cost-based Optimisation (not assessed)

- Consider CHARTS = {Rank, Artist, Song} with 10 tuples and 3 attributes.

Rank	Artist	Song
1	Chingy	Right Thurr
2	Scribe	Stand up
3	Aguilera and Kim	Can't hold us down
4	Evanescence	Going under
5	Justin Timberlake	Senorita
6	Brooke Fraser	Better
7	Black Eyed Peas	Where is the love?
...	...	...
...	...	...

- Compare two strategies of evaluating "Who is top of the pops?":

- $\sigma_{\text{Rank}=1}(\pi_{\text{Rank, Artist}}(\text{CHARTS}))$
- $\pi_{\text{Rank, Artist}}(\sigma_{\text{Rank}=1}(\text{CHARTS}))$

Selection before Projection is preferred.

## Cost-based Optimisation (not assessed)

- Consider CHARTS = {Rank, Artist, ...} with 100 tuples and 50 attributes:

Rank	Artist	Song	...	...	...
1	Chingy	Right Thurr	...	...	...
2	Scribe	Stand up	...	...	...
3	Aguilera and Kim	Can hold us down	...	...	...
4	Evanescence	Going under	...	...	...
5	Justin Timberlake	Senorita	...	...	...
6	Brooke Fraser	Better	...	...	...
7	Black Eyed Peas	Where is the love?	...	...	...
...	...	...	...	...	...

- Compare two strategies of evaluating?
  - $\sigma_{\text{Rank} > 10}(\pi_{\text{Rank, Artist}}(\text{CHARTS}))$
  - $\pi_{\text{Rank, Artist}}(\sigma_{\text{Rank} > 10}(\text{CHARTS}))$



## Cost-based Optimisation (not assessed)

- Consider CHARTS = {Rank, Artist, ...} with 100 tuples and 50 attributes:


Rank	Artist	Song	...	...	...
1	Chingy	Right Thurr	...	...	...
2	Scribe	Stand up	...	...	...
3	Aguilera and Kim	Can hold us down	...	...	...
4	Evanescence	Going under	...	...	...
5	Justin Timberlake	Senorita	...	...	...
6	Brooke Fraser	Better	...	...	...
7	Black Eyed Peas	Where is the love?	...	...	...
...	...	...	...	...	...

- Compare two strategies of evaluating?
  - $\sigma_{\text{Rank} > 10}(\pi_{\text{Rank, Artist}}(\text{CHARTS}))$
  - $\pi_{\text{Rank, Artist}}(\sigma_{\text{Rank} > 10}(\text{CHARTS}))$

Projection before Selection is preferred.

## Query Optimisation

# Assignment Project Exam Help



Add WeChat powcoder

- Trade-off:

**Time for executing a RA query vs Time for finding a better RA query**

(credit cookie) memorising vs understanding

# Assignment Project Exam Help

I can remember song lyrics from  
2006 but not whatever maths  
formula we were learning yesterday

<https://powcoder.com>

Add WeChat powcoder



©santabanta.com