

COMP 250

INTRODUCTION TO COMPUTER SCIENCE

Assignment Project Exam Help

<https://powcoder.com>

Week 10-11 Recursion 3 (Mergesort and Quicksort)

Add WhatsApp powcoder

Giulia Alberini, Fall 2020

WHAT ARE WE GOING TO DO IN THIS VIDEO?



- Merge sort
- Quick sort

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

TIME COMPLEXITY

$O(\log n)$	$O(n)$	$O(n^2)$
<ul style="list-style-type: none">convert to binarybinary search.....	<p>Assignment Project Exam Help https://powcoder.com Add WeChat powcoder</p> <ul style="list-style-type: none">List operations: findMax, removegrade school addition.....	<ul style="list-style-type: none">insertion/selection/bubble sortgrade school multiplication.....

Assignment Project Exam Help

MERGE SORT

<https://powcoder.com>

Add WeChat powcoder

MERGE SORT

Merge Sort is a divide and conquer algorithm.


- GOAL: Sort an list.
- IDEA:
 - Partition the list into two halves.
 - Sort each half recursively
 - Merge the sorted half maintaining the order.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

IDEA



IMPLEMENTATION

```
mergesort(list) {  
    if (list.size() == 1)  
        return list  
    else {  
        mid = (list.size() - 1) / 2  
        list1 = list.getElements(0, mid)  
        list2 = list.getElements(mid+1, list.size()-1)  
        list1 = mergesort(list1)  
        list2 = mergesort(list2)  
        return merge(list1, list2)  
    }  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

IMPLEMENTATION

```
mergesort(list) {
```

```
    if (list.size() == 1)
```

```
        return list
```

```
    else {
```

```
        mid = (list.size() - 1) / 2
```

```
        list1 = list.getElements(0, mid)
```

```
        list2 = list.getElements(mid+1, list.size()-1)
```

```
        list1 = mergesort(list1)
```

```
        list2 = mergesort(list2)
```

```
        return merge(list1, list2)
```

```
    }
```

```
}
```

Base case

Partition

Recursive sort


Merge

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

MERGING PRESERVING ORDER



MERGING PRESERVING ORDER

Iterate through the elements of the two sorted list. Depending on how they compare decide which element comes first in the merged list.



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder merge

1
3
6
8
10
11

2
4
5
7
13
16




MERGING PRESERVING ORDER

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder merge




MERGING PRESERVING ORDER

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder merge




MERGING PRESERVING ORDER

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder merge



MERGING PRESERVING ORDER

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder merge

1
3
6
8
10
11

1
2
3

2
4
5
7
13
16



MERGING PRESERVING ORDER

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder merge

1
3
6
8
10
11

1
2
3
4

2
4
5
7
13
16



MERGING PRESERVING ORDER

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder merge

1
3
6
8
10
11

1
2
3
4
5

2
4
5
7
13
16



MERGING PRESERVING ORDER

Assignment Project Exam Help



<https://powcoder.com>

Add WeChat powcoder merge

1
3
6
8
10
11

1
2
3
4
5
6

2
4
5
7
13
16




MERGING PRESERVING ORDER

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder merge




MERGING PRESERVING ORDER

And so on until one list is empty!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder merge



MERGING PRESERVING ORDER

Then copy the remaining
elements!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder merge

1
3
6
8
10
11

2
4
5
7
13
16

1
2
3
4
5
6
7
8
10
11
13
16

IMPLEMENTATION OF MERGE

```
merge(list1, list2){  
    list = ...initialize with empty list...  
    while (!list1.isEmpty() && !list2.isEmpty()){  
        if (list1.get(0) < list2.get(0))  
            list.addlast(list1.removeFirst())  
        else  
            list.addlast(list2.removeFirst())  
    }  
    while (!list1.isEmpty())  
        list.addlast(list1.removeFirst())  
    while (!list2.isEmpty())  
        list.addlast(list2.removeFirst())  
    return list  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

IMPLEMENTATION OF MERGE

```
merge(list1, list2){  
    list = ...initialize with empty list...  
    while (!list1.isEmpty() && !list2.isEmpty()){  
        if (list1.get(0) < list2.get(0))  
            list.addlast(list1.removeFirst())  
        else  
            list.addlast(list2.removeFirst())  
    }  
    while (!list1.isEmpty())  
        list.addlast(list1.removeFirst())  
    while (!list2.isEmpty())  
        list.addlast(list2.removeFirst())  
    return list  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Pick elements to
add until one of the
two lists is empty

Then add the
remaining elements

1) Partitions into list and call mergesort until base case is reached.

EXAMPLE OF EXECUTION

8
10
3
11
6
1
7
16
2
5
4
13

```
mergesort(list) {  
    if (list.size() == 1)  
        return list  
    else {  
        mid = (list.size() - 1) / 2  
        list1 = list.getElements(0, mid)  
        list2 = list.getElements(mid+1, list.size()-1)  
        list1 = mergesort(list1)  
        list2 = mergesort(list2)  
        return merge(list1, list2)  
    }  
}
```


Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1) Partitions into list and call mergesort until base case is reached.

EXAMPLE OF EXECUTION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1) Partitions into list and call mergesort until base case is reached.

EXAMPLE OF EXECUTION




Assignment Project Exam Help

list2 <https://powcoder.com>

Add WeChat powcoder

1) Partitions into list and call mergesort until base case is reached.

EXAMPLE OF EXECUTION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

1) Partitions into list and call mergesort until base case is reached.

EXAMPLE OF EXECUTION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Then start to merge!

EXAMPLE OF EXECUTION




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


Then start to merge!

EXAMPLE OF EXECUTION




Then start to merge!

EXAMPLE OF EXECUTION




Then start to merge!

EXAMPLE OF EXECUTION




Then start to merge!

EXAMPLE OF EXECUTION



Then start to merge!


EXAMPLE OF EXECUTION



Q: How many operations are required to mergesort a list of size n ?

A: $O(n \log_2 n)$

This will become more clear in the next video when we discuss recurrences.



COMPLEXITY

$n \log_2 n$ is much closer to n than to n^2

$\log_2 n$	n	$n \log_2 n$	n^2
10	$2^{10} \approx 10^3$	10^4	10^6
20	$2^{20} \approx 10^6$	$\sim 10^7$	10^{12}
30	$2^{30} \approx 10^9$	$\sim 10^{10}$	10^{18}

COMPLEXITY

$n \log_2 n$ is much closer to n than to n^2

$\log_2 n$	n	$n \log_2 n$	n^2
10	$2^{10} \approx 10^3$	10^4	10^6
20	$2^{20} \approx 10^6$	$\sim 10^7$	10^{12}
30	$2^{30} \approx 10^9$	$\sim 10^{10}$	10^{18}

milliseconds

seconds

minutes/hours

centuries

Assignment Project Exam Help

QUICK SORT
<https://powcoder.com>

Add WeChat powcoder

QUICK SORT

- Quick Sort is a divide and conquer algorithm.

- GOAL: Sort a list.

Assignment Project Exam Help

- IDEA:

<https://powcoder.com>

- Pick an element of the array (the pivot).
- Partition the list moving the pivot to its correct position making sure that all the lower elements are on its left and all the larger elements are on its right.
- Sort the left part AND the right part of the list recursively.
- Keep doing it until there's nothing left to sort.

Add WeChat powcoder

IDEA

IDEA:

- Pick an element of the array (the pivot).
- Move the pivot to its correct position making sure that all the smaller elements are on its left and all the larger elements are on its right.
- Sort the left part AND the right part
- Keep doing it until there's nothing left to sort.

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

This is the crucial process of the algorithm!

Recursive Step

Base case

IDEA



THE PIVOT

Different versions of Quick Sort pick the pivot in different ways:

- Always pick the first element as the pivot
- Always pick the last element as the pivot
- Pick a random element
- Pick the median as pivot

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

THE PIVOT

Different versions of Quick Sort pick the pivot in different ways:

- Always pick the first element as the pivot
- Always pick the last element as the pivot
- Pick a random element
- Pick the median as pivot

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

QUICK SORT EXAMPLE

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

1. Pick the pivot.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $5 < 3$ false \rightarrow do nothing!

QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $1 < 3$ true

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:

$1 < 3$ true \rightarrow move the wall


QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $1 < 3$ true \rightarrow move the element

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $4 < 3$ false \rightarrow do nothing

QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $2 < 3$ true

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder


QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left

3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $2 < 3$ true \rightarrow move wall

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

QUICK SORT EXAMPLE

1. Pick the pivot.

2. Set the wall on the left


3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




swap

compare:

$2 < 3$ true \rightarrow move element

QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.
 - If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
 - Otherwise, do nothing.
4. Move the pivot next to the wall.




Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.
 - If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
 - Otherwise, do nothing.
4. Move the pivot next to the wall.
5. Use Quick sort on left part and then on the right part




QUICK SORT EXAMPLE

1. Pick the pivot.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left

Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder



QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $1 < 2$ true

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.




compare:
 $1 < 2$ true \rightarrow move wall

QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.

- If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
- Otherwise, do nothing.



compare:
 $1 < 2$ true \rightarrow element
already in position.


QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left.
3. Go through all the elements of the list that are not the pivot.
 - If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
 - Otherwise, do nothing.
4. Move the pivot next to the wall.
5. Use Quick Sort on left part and then on the right part.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

- In this case the left part and the right part are base cases.
- The left part has 1 element → already sorted!
- The right part is empty → sorted!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

- It is left to sort the part of the list to the right of the first pivot.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

1. Pick the pivot.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left

Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder



QUICK SORT EXAMPLE


1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.
 - If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
 - Otherwise, do nothing.



compare:
 $5 < 4$ false \rightarrow do nothing!

QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.
 - If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
 - Otherwise, do nothing.
4. Move the pivot next to the wall.




QUICK SORT EXAMPLE

1. Pick the pivot.
2. Set the wall on the left
3. Go through all the elements of the list that are not the pivot.
 - If the element is smaller than the pivot, move the wall right by 1, and place the element just behind the wall.
 - Otherwise, do nothing.
4. Move the pivot next to the wall.
5. Use Quick Sort on left part and then on the right part.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



QUICK SORT EXAMPLE

- Once again, both the left part and the right part are base cases.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




QUICK SORT EXAMPLE

- Once again, both the left part and the right part are base cases.
- The array is sorted

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



QUICK SORT EXAMPLE

- Once again, both the left part and the right part are base cases.
- The array is sorted
- The original array is sorted!

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder



QUICK SORT – IMPLEMENTATION

What do we need to implement this algorithm?

- A method that swaps two elements
- A way to refer to parts of the list
- A method that places the pivot in its correct position and moves the elements around so that all the lower elements are on the left, and all the larger elements are on the right. Call it `placeAndDivide`
- A method that implements the Quick Sort, that is:
 - Pick a pivot
 - `placeAndDivide`
 - `quickSort` left part
 - `quickSort` right part

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

PARTS OF THE LIST

What can we use to denote a part of the list?

- We can use the same idea used from binary search → keep track of the left and right index denoting where the part begins and ends.
- Consider for example the list $\{5, 3, 6, 1, 2\}$. Then:
 - The indices 0 and 4 denote the entire list.
 - The indices 0 and 2 denote the part of the list with the 3 left most elements.
 - The indices 1 and 3 denote the part of the list with the 3 middle elements.

quickSort – PSEUDO CODE

```
quickSort(list, leftIndex, rightIndex) {  
    // Base case:  
    if (leftIndex >= rightIndex)  
        return; // done!  
}  
  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

quickSort – PSEUDO CODE

```
quickSort(list, leftIndex, rightIndex) {  
    // Base case:  
    if (leftIndex >= rightIndex)  
        return; // done!  
    } else { // recursive step:  
        i ← placeAndDivide(list, leftIndex, rightIndex)  
        // i = index where the pivot is placed  
        quickSort(list, leftIndex, i-1)  
        quickSort(list, i+1, rightIndex)  
    }  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

placeAndDivide – PSEUDO CODE

```
placeAndDivide(list, leftIndex, rightIndex) {
```

```
    // pick the right most element
```

```
    pivot ← list.get(rightIndex)
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

```
}
```

placeAndDivide – PSEUDO CODE

```
placeAndDivide(list, leftIndex, rightIndex) {
```

```
    // pick the right most element
```

```
    pivot ← list.get(rightIndex)
```

```
    // place the wall to the left
```

```
    wall ← leftIndex - 1
```

```
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

placeAndDivide – PSEUDO CODE

```
placeAndDivide(list, leftIndex, rightIndex) {  
    // pick the right most element  
    pivot ← list.get(rightIndex)  
    // place the wall to the left  
    wall ← leftIndex - 1  
    // go through all elements and compare them to the pivot  
    for(int i=leftIndex; i< rightIndex; i++) {  
  
    }  
  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

placeAndDivide – PSEUDO CODE

```
placeAndDivide(list, leftIndex, rightIndex) {  
    // pick the right most element  
    pivot ← list.get(rightIndex)  
    // place the wall to the left  
    wall ← leftIndex - 1  
    // go through all elements and compare them to the pivot  
    for(int i=leftIndex; i< rightIndex; i++) {  
        if(list.get(i)<pivot) {  
            wall++; // move wall  
            swap list.get(i) list.get(wall) // move element behind wall  
        }  
    }  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

placeAndDivide – PSEUDO CODE

```
placeAndDivide(list, leftIndex, rightIndex) {  
    // pick the right most element  
    pivot ← list.get(rightIndex)  
    // place the wall to the left  
    wall ← leftIndex - 1  
    // go through all elements and compare them to the pivot  
    for(int i=leftIndex; i< rightIndex; i++) {  
        if(list.get(i)<pivot) {  
            wall++; // move wall  
            swap list.get(i) list.get(wall) // move element behind wall  
        }  
    }  
    swap list.get(rightIndex) list.get(wall+1) // move pivot next to wall  
    return wall+1;  
}
```

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

MERGESORT VS. QUICKSORT

- Mergesort typically uses an extra list. More space can hurt performance for big lists.

Assignment Project Exam Help

<https://powcoder.com>

- We will discuss worst case performance of quicksort later in the course.

Add WeChat powcoder

- See stackoverflow if you want opinions on which is better. The answer is, it depends ...



Coming Soon

Assignment Project Exam Help

In the next video:

- Recurrences

<https://powcoder.com>
Add WeChat powcoder