

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help  
COMP251: Network flows (2)

<https://powcoder.com>

Add WeChat powcoder

Jérôme Waldispühl

School of Computer Science

McGill University

Based on slides from M. Langer (McGill)

# Assignment Project Exam Help

## Recap Network Flows

Add WeChat powcoder

$G = (V, E)$  directed.

Each edge  $(u, v)$  has a **capacity**  $c(u, v) \geq 0$ .


If  $(u, v) \notin E$ , then  $c(u, v) = 0$ .

**Source** vertex  $s$ , **sink** vertex  $t$ , assume  $s \rightsquigarrow v \rightsquigarrow t$  for all  $v \in V$ .

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder




**Problem:** Given  $G$ ,  $s$ ,  $t$ , and  $c$ , find a flow whose value is maximum.

# Assignment Project Exam Help

## Application

Add WeChat powcoder




Maximize flow of supplies in eastern europe!

# Assignment Project Exam Help

## Recap (residual graphs)

Add WeChat powcoder


Flow



<https://powcoder.com>

Add WeChat powcoder

Residual  
graph



# Assignment Project Exam Help

## Recap (Ford-Fulkerson algorithm)

Add WeChat powcoder

```
f ← 0
```

```
Gf ← G
```

Assignment Project Exam Help




```
While (there is a s-t path in Gf) do
```

```
  f.augment(P)
```

```
  update Gf based on new f
```

<https://powcoder.com>

Add WeChat powcoder




# Assignment Project Exam Help

## Recap graph cuts

Add WeChat powcoder

A graph cut is a partition of the graph vertices into two sets.



The crossing edges from S to V-S are  $\{ (u,v) \mid u \in S, v \in V-S \}$ , also called the cut set.

# Assignment Project Exam Help

## Cuts in flow networks

Add WeChat powcoder

**Definition:** An s-t cut of a flow network is a cut  $A, B$  such that  $s \in A$  and  $t \in B$ .

<https://powcoder.com>


**Notation:** We write  $\text{cut}(A, B)$  the set of edges from  $A$  to  $B$ .

Add WeChat powcoder

**Definition:** The capacity of an s-t cut is 
$$\sum_{e \in \text{cut}(A, B)} c(e)$$

# Assignment Project Exam Help

## Examples




Add WeChat powcoder


Assignment Project Exam Help

$$1+5=6$$

<https://powcoder.com>




$$1+2=3$$



Add WeChat powcoder

$$5+3+4=12$$



$$2+4=6$$



Assignment Project Exam Help

# Objectives

Add WeChat powcoder

For any flow network:


Assignment Project Exam Help

- Maximum value of a flow = the minimum capacity of any cut.  
<https://powcoder.com>  
Add WeChat powcoder
- Ford-Fulkerson gives the “max flow” and the “min cut”.

# Assignment Project Exam Help

## Application

Add WeChat powcoder



How to cut supplies if cold war turns into real war!

# Assignment Project Exam Help

## Flow through a cut

Add WeChat powcoder


**Claim:** Given a flow network. Let  $f$  be a flow and  $A, B$  be a s-t cut. Then,

$$|f| = \sum_{e \in \text{cut}(A,B)} f(e) - \sum_{e \in \text{cut}(B,A)} f(e)$$

Assignment Project Exam Help  
<https://powcoder.com>

**Notation:**  $|f| = f^{\text{out}}(A) - f^{\text{in}}(A)$

Add WeChat powcoder



$$|f| = 9 - 4 = 5$$

# Assignment Project Exam Help

## Flow through a cut

Add WeChat powcoder

### Proof:

- for any  $u \in V - \{s, t\}$ , we have  $f^{out}(u) = f^{in}(u)$ .
- Summing over  $u \in A - \{s\}$ :
$$\sum_{u \in A - \{s\}} f^{out}(u) = \sum_{u \in A - \{s\}} f^{in}(u)$$
- $|f| = f^{out}(s) = \sum_{u \in A} f^{out}(u) - \sum_{u \in A} f^{in}(u)$
- Each edge  $e = (u, v)$  with  $u, v \in A$  contributes to both sums, and can be removed (Note:  $f^{in}(s) = 0$ ).

$$\begin{aligned} |f| &= \sum_{e \in cut(A, B)} f(e) - \sum_{e \in cut(B, A)} f(e) \\ &\equiv f^{out}(A) - f^{in}(A) \end{aligned}$$

<https://powcoder.com>

Add WeChat powcoder

## Assignment Project Exam Help

# Upper bound on flow through cuts

Add WeChat powcoder

**Claim:** For any network flow  $f$ , and any s-t cut(A,B)

$$|f| \leq \sum_{e \in \text{cut}(A,B)} c(e)$$

Assignment Project Exam Help

<https://powcoder.com>

**Proof:**

$$|f| = f^{\text{out}}(A) - f^{\text{in}}(A)$$

Add WeChat powcoder

$$\leq f^{\text{out}}(A)$$

$$\leq \sum_{e \in \text{cut}(A,B)} c(e)$$

# Assignment Project Exam Help

## Observations

Add WeChat powcoder

- Some cuts have greater capacities than others.
- Some flows are greater than others.
- **But every flow must be  $\leq$  capacity of every s-t cut.**
- Thus, the value of the maximum flow is less than capacity of the minimum cut.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

## Assignment Project Exam Help

# Value of flow in Ford-Fulkerson

Add WeChat powcoder

- Ford-Fulkerson terminates when there is no augmenting path in the residual graph  $G_f$ .
- Let  $A$  be the set of vertices reachable from  $s$  in  $G_f$ , and  $B = V - A$ .
- $A, B$  is a s-t cut in  $G_f$ .
- $A, B$  is an s-t cut in  $G$  ( $G$  and  $G_f$  have the same vertices).
- $|f| = f^{\text{out}}(A) - f^{\text{in}}(A)$
- We want to show:  $|f| = \sum_{e \in \text{cut}(A, B)} c(e)$
- And in particular:

$$\textcircled{1} \quad f^{\text{out}}(A) = \sum_{e \in \text{cut}(A, B)} c(e)$$

$$\textcircled{2} \quad f^{\text{in}}(A) = 0$$

# Assignment Project Exam Help

## Value of flow in Ford-Fulkerson

Add WeChat powcoder

(1) For any  $e=(u,v) \in \text{cut}(A,B)$ ,  $f(e)=c(e)$ .

Assignment Project Exam Help

- $f(e)<c(e) \Rightarrow e=(u,v)$  would be a forward edge in the residual graph  $G_f$  with capacity  $c_f(e)=c(e)-f(e)>0$ .
- $v$  reachable from  $s$  in  $G_f \Rightarrow$  contradiction. ■

<https://powcoder.com>

Add WeChat powcoder

(2)  $f^{\text{in}}(A)=0$ :  $\forall e=(v,u) \in E$  such that  $v \in B$ ,  $u \in A$ , we have  $f(e)=0$ .

- $f(e)>0 \Rightarrow \exists$  backward edge  $(u,v)$  in  $G_f$  such that  $c_f(e)=f(e)$
- $v$  is reachable from  $s$  in  $G_f \Rightarrow$  contradiction. ■



# Assignment Project Exam Help

## Max flow = Min cut

Add WeChat powcoder

- Ford-Fulkerson terminates when there is no path s-t in the residual graph  $G_f$

- This defines a cut in A B in G (A = nodes reachable from s)

Assignment Project Exam Help

- $|f| = f^{out}(A) - f^{in}(A)$

<https://powcoder.com>

$$= \sum_{e \in cut(A,B)} f(e) - \sum_{e \in cut(B,A)} f(e)$$

Add WeChat powcoder

- Ford-Fulkerson flow =  $\sum_{e \in cut(A,B)} c(e) - 0$

= capacity of cut(A,B)

**Note:** We did not proved uniqueness.

## Assignment Project Exam Help

# Computing the min cut

Add WeChat powcoder

Q: Given a flow network, how can we compute a minimum cut?

Answer: **Assignment Project Exam Help**

- Run Ford-Fulkerson to compute a maximum flow (it gives us  $G_f$ )
- Run BFS or DFS of  $s$ .
- The reachable vertices define the set  $A$  for the cut


<https://powcoder.com>

Add WeChat powcoder


# Assignment Project Exam Help

## Example (min cut with Ford-Fulkerson)


(1) Initial flow net  $G$




(2) Compute max flow (FF)



(3) Compute  $G_f$  and vertices accessible from  $s$



(4) Vertices accessible from  $s$  in  $G_f$  determine the min cut




# Assignment Project Exam Help


## Bipartite matching

Add WeChat powcoder

Suppose we have an undirected graph bipartite graph  $G=(V,E)$ .



Q: How can we find the maximal matching? (Recall Lecture 11)



## Assignment Project Exam Help


# Bipartite matching with network flows

Add WeChat powcoder

Define a flow network  $G'=(V',E')$  such that:

- $V' = V \cup \{s,t\}$
- $E' = \{ (u,v) \mid u \in A, v \in B, (u,v) \in E \} \cup \{ (s,u) \mid u \in A \} \cup \{ (v,t) \mid v \in B \}$
- Capacities of every edge = 1.


Assignment Project Exam Help



Motivation: Max flow  $\Rightarrow$  max matching.

# Assignment Project Exam Help

## Max flow in bipartite graphs




Exercise: The maximal flow found by Ford-Fulkerson defines a maximal matching in the original graph  $G$  (the maximal set of edges  $(u,v)$   $u \in A$  &  $v \in B$  such that  $f(u,v)=1$ ).

## Assignment Project Exam Help

# Max matching with Ford-Fulkerson

Add WeChat powcoder

Ford-Fulkerson will find an augmenting path with  $\beta=1$  at each iteration. They are of the form:



Or have more than one zig-zag in  $G_f$

Note:

- No edge from  $B$  to  $A$  in  $E'$ . The back edges are in the residual graph.
- Edges  $e$  such that  $c(e)=0$  are not shown.

# Assignment Project Exam Help

## Running time

Add WeChat powcoder

Q: How long will it take to find a maximal matching with Ford-Fulkerson?

# Assignment Project Exam Help

- The general complexity of Ford-Fulkerson is  $O(C \cdot |E|)$ , where

$$C = \sum_u c(s, u)$$

<https://powcoder.com>

Add WeChat powcoder

- Suppose  $|A| = |B| = n$
- Then,  $C = |A| = n$  and  $|E'| = |E| + 2n = m + 2n$  (Assume  $m > n$ )
- Thus,  $C \cdot |E'| = n \cdot (m + 2n)$
- Running time is  $O(nm)$




# Assignment Project Exam Help

## Example

Add WeChat powcoder

What is max flow? What is min cut?




# Assignment Project Exam Help

## Example

Add WeChat powcoder

What is the max flow? What is the min cut?



Max flow  $|f|=2$ .

Note: there are other flows with  $|f|=2$ .



What is the minimum cut?

# Assignment Project Exam Help

## Example

Add WeChat powcoder

Find any min cut with capacity 2.




# Assignment Project Exam Help

## Example


Add WeChat powcoder

To find a min cut compute a max flow.

Flow



Residual  
graph




# Assignment Project Exam Help

## Example

Add WeChat powcoder

To find the cut run BFS (or DFS) from  $s$  on the residual graph.  
The reachable vertices define the (min) cut.

Residual  
graph  
with DFS



Min cut  
(in  $G$ !)

