

Assignment Project Exam Help

Add WeChat powcoder

COMP251: Dynamic programming (2)

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Jérôme Waldispühl

School of Computer Science

McGill University

Based on (Kleinberg & Tardos, 2005) & Slides by K. Wayne

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

SINGLE SOURCE SHORTEST PATHS

Assignment Project Exam Help

Modeling as graphs

Input:

- Directed graph $G = (V, E)$
- Weight function $w : E \rightarrow \mathbb{R}$

Weight of path $p = \langle v_0, v_1, \dots, v_k \rangle$

$$= \sum_{k=1}^n w(v_{k-1}, v_k)$$

= sum of edge weights on path p

Shortest-path weight u to v :

$$\delta(u, v) = \begin{cases} \min \left\{ w(p) : u \xrightarrow{p} v \right\} & \text{If there exists a path } u \rightsquigarrow v. \\ \infty & \text{Otherwise.} \end{cases}$$

Shortest path u to v is any path p such that $w(p) = \delta(u, v)$.

Generalization of breadth-first search to weighted graphs.



Assignment Project Exam Help

Dijkstra's algorithm

- No negative-weight edges.
- Weighted version of BFS:
 - Instead of a FIFO queue, uses a **priority queue**.
 - Keys are shortest-path weights ($d[v]$).
- Greedy choice: At each step we choose the light edge.

How to deal with negative weight edges?

- Allow re-insertion in queue? \Rightarrow Exponential running time...
- Add constant to each edge?



Not working...

Assignment Project Exam Help

Bellman-Ford Algorithm

Add WeChat powcoder

- Allows negative-weight edges.
- Computes $d[v]$ and $\pi[v]$ for all $v \in V$.
- Returns TRUE if no negative-weight cycles reachable from s , FALSE otherwise.

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

If Bellman-Ford has not converged after $V(G) - 1$ iterations, then there cannot be a shortest path tree, so there must be a negative weight cycle.

Assignment Project Exam Help

Bellman-Ford Algorithm

Add WeChat powcoder

- Can have negative-weight edges.
- Will “detect” **reachable** negative-weight cycles.

Assignment Project Exam Help

```
Initialize(G, s);  
for i = 1 to |V[G]| - 1 do  
    for each (u, v) in E[G] do  
        Relax(u, v, w)  
for each (u, v) in E[G] do  
    if d[v] > d[u] + w(u, v) then  
        return false  
return true
```

<https://powcoder.com>


Add WeChat powcoder

Time
Complexity
is $O(VE)$.

Assignment Project Exam Help

Example

Add WeChat powcoder




Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 1




Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 1



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 1



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 1



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 2



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 2



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 2



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example

Add WeChat powcoder

Iteration 2



Assignment Project Exam Help


<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder




Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 1



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 1



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 1



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 1



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 2



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 2




Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 2



Assignment Project Exam Help

<https://powcoder.com>


Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder

Iteration 2



Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Assignment Project Exam Help

Example 2

Add WeChat powcoder


Check

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

$$d[y] > d[s] + w(s, y) \\ \Rightarrow \text{FALSE}$$



Assignment Project Exam Help

Another Look at Bellman-Ford

Note: This is essentially **dynamic programming**.

Let $d(i, j)$ = cost of the shortest path from s to i that is at most j hops.

$$d(i, j) = \begin{cases} 0 & \text{if } i = s \wedge j = 0 \\ \infty & \text{if } i \neq s \wedge j = 0 \\ \min(\{d(k, j-1) + w(k, i) : i \in \text{Adj}(k)\} \cup \{d(i, j-1)\}) & \text{if } j > 0 \end{cases}$$

Add WeChat powcoder

		$i \rightarrow$				
		z	u	v	x	y
		1	2	3	4	5
$j \downarrow$	0	0	∞	∞	∞	∞
	1	0	6	∞	7	∞
	2	0	6	4	7	2
	3	0	2	4	7	2
	4	0	2	4	7	-2

Assignment Project Exam Help

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

KNAPSACK PROBLEM

Assignment Project Exam Help

Knapsack problem

Add WeChat powcoder

- Given n objects and a "knapsack."
- Item i weighs $w_i > 0$ and has value $v_i > 0$.
- Knapsack has capacity of W .
- Goal: fill knapsack so as to maximize total value.

Assignment Project Exam Help

Ex. $\{1, 2, 5\}$ has value 35.

Ex. $\{3, 4\}$ has value 40.

Ex. $\{3, 5\}$ has value 46 (but exceeds weight limit).

<https://powcoder.com>

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

knapsack instance
(weight limit $W = 11$)

Greedy by value. Repeatedly add item with maximum v_i .

Greedy by weight. Repeatedly add item with minimum w_i .

Greedy by ratio. Repeatedly add item with maximum ratio v_i / w_i .

Observation. None of greedy algorithms is optimal.

Assignment Project Exam Help

False start...

Add WeChat powcoder

Def. $OPT(i)$ = max profit subset of items $1, \dots, i$.

Case 1. OPT does not select item i .

- OPT selects best of $\{1, 2, \dots, i-1\}$.

<https://powcoder.com>

optimal substructure property
(proof via exchange argument)

Case 2. OPT selects item i .

Add WeChat powcoder

- Selecting item i does not immediately imply that we will have to reject other items.
- Without knowing what other items were selected before i , we don't even know if we have enough room for i .

Conclusion. Need more subproblems!

Assignment Project Exam Help

New variable

Add WeChat powcoder

Def. $OPT(i, w)$ = max profit subset of items $1, \dots, i$ with weight limit w .

Case 1. OPT does not select item i .

- OPT selects best of $\{1, 2, \dots, i-1\}$ using weight limit w .

Assignment Project Exam Help

<https://powcoder.com>

Case 2. OPT selects item i .

- New weight limit = $w - w_i$.
- OPT selects best of $\{1, 2, \dots, i-1\}$ using this new weight limit.

optimal substructure property
(proof via exchange argument)

Add WeChat powcoder

$$OPT(i, w) = \begin{cases} 0 & \text{if } i = 0 \\ OPT(i-1, w) & \text{if } w_i > w \\ \max\{OPT(i-1, w), v_i + OPT(i-1, w - w_i)\} & \text{otherwise} \end{cases}$$

Assignment Project Exam Help

Dynamic programming algorithm

Add WeChat powcoder

KNAPSACK ($n, W, w_1, \dots, w_n, v_1, \dots, v_n$)

FOR $w = 0$ TO W

$M[0, w] \leftarrow 0.$

Assignment Project Exam Help

<https://powcoder.com>

FOR $i = 1$ TO n

Add WeChat powcoder

FOR $w = 1$ TO W

IF ($w_i > w$) $M[i, w] \leftarrow M[i-1, w].$

ELSE $M[i, w] \leftarrow \max \{ M[i-1, w], v_i + M[i-1, w - w_i] \}.$

RETURN $M[n, W].$

Assignment Project Exam Help

Example

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Max weight $W = 11$

Example

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

W

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0											
{1,2}	0											
{1,2,3}	0											
{1,2,3,4}	0											
{1,2,3,4,5}	0											

i

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}	0											
{1,2,3}	0											
{1,2,3,4}	0											
{1,2,3,4,5}	0											

<https://powcoder.com>

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}	0	1										
{1,2,3}	0											
{1,2,3,4}	0											
{1,2,3,4,5}	0											

<https://powcoder.com>

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}	0	1	6									
{1,2,3}	0											
{1,2,3,4}	0											
{1,2,3,4,5}	0											

$V_2 + M(i-1, w-w_2)$

$M(i-1, w)$

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}												
{1,2,3}	0											
{1,2,3,4}	0											
{1,2,3,4,5}	0											

$V_2 + M(i-1, w-w_2)$

$M(i-1, w)$

7

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}	0	1	6	7	7	7	7	7	7	7	7	7
{1,2,3}	0											
{1,2,3,4}	0											
{1,2,3,4,5}	0											

<https://powcoder.com>

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}	0	1	6	7	7	7	7	7	7	7	7	7
{1,2,3}	0	1	6	7	7	18	19	24	25	25	25	25
{1,2,3,4}	0											
{1,2,3,4,5}	0											

<https://powcoder.com>

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}	0	1	6	7	7	7	7	7	7	7	7	7
{1,2,3}	0	1	6	7	7	18	19	24	25	25	25	25
{1,2,3,4}	0	1	6	7	7	18	22	24	28	29	29	40
{1,2,3,4,5}	0											

<https://powcoder.com>

Add WeChat powcoder

i	v_i	w_i
1	1	1
2	6	2
3	18	5
4	22	6
5	28	7

Assignment Project Exam Help

Example

Add WeChat powcoder

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

M	0	1	2	3	4	5	6	7	8	9	10	11
{}	0	0	0	0	0	0	0	0	0	0	0	0
{1}	0	1	1	1	1	1	1	1	1	1	1	1
{1,2}	0	1	7	7	7	7	7	7	7	7	7	7
{1,2,3}	0	1	6	7	7	18	19					25
{1,2,3,4}	0	1	6	7	7	18	22	24	28	29	29	40
{1,2,3,4,5}	0	1	6	7	7	18	22	28	29	34	35	40

Item 3 in solution

Item 4 in solution

Assignment Project Exam Help

Analysis

Add WeChat powcoder

Theorem. There exists an algorithm to solve the knapsack problem with n items and maximum weight W in $\Theta(nW)$ time and $\Theta(nW)$ space.

Pf.

weights are integers
between 1 and W

- Takes $O(1)$ time per table entry.
- There are $\Theta(nW)$ table entries.
- After computing optimal values, can trace back to find solution:
take item i in $OPT(i, w)$ iff $M[i, w] < M[i-1, w]$. ■

Assignment Project Exam Help

<https://powcoder.com>

Add WeChat powcoder

Remarks.

- Not polynomial in input size! ← "pseudo-polynomial"
- Decision version of knapsack problem is NP-COMPLETE. [CHAPTER 8]
- There exists a poly-time algorithm that produces a feasible solution that has value within 1% of optimum. [SECTION 11.8]