COMP2610/6261 - Information Theory

Lecture 17: Noisy Channels

Bob Williamson

Research School of Computer Science

Australian
National
University

2 October, 2018

1 Communication over Noisy Channels: Big Picture
2 Noisy Channels: Formally
3 Examples of Channels
4 Probability of Error

The Big Picture



The Big Picture



Concept: Expected code length

Theorem: Source coding theorem

Algorithms: { Huffman, Arithmetic } codes

The Big Picture



Concept: Channel capacity

Theorem: Channel coding theorem

Algorithms: Repetition codes, Hamming codes

Communication over Noisy Channels

A channel is some medium for transmitting messages

A noisy channel is a channel that potentially introduces errors in the sender's message

The Problem of Communication

"The fundamental problem of communication is that of reproducing at one point either exactly or approximately a message selected at another point." (Claude Shannon, 1948)

Example: Telephone Network



Source : Aditya

Encoder : Telephone handset

Channel : Analogue telephone line

Decoder : Telephone handset

Destination : Mark

Key Questions

How do we model noisy communication abstractly?

What are the theoretical limits of noise correction?

What are the practical approaches to noise correction?

1 Communication over Noisy Channels: Big Picture
2 Noisy Channels: Formally
3 Examples of Channels
4 Probability of Error

Encoder/Decoder Pairs

Suppose we have some set $\mathcal{S} = \{1, 2, \ldots, S\}$ of possible messages

- e.g. codewords from Huffman coding on some ensemble
- Sender and receiver agree on what these are

Encoder/Decoder Pairs

Suppose we have some set $\mathcal{S} = \{1, 2, \ldots, S\}$ of possible messages

- e.g. codewords from Huffman coding on some ensemble
- Sender and receiver agree on what these are

When communicating over a channel, the sender must encode messages into some input alphabet $\mathcal{X}$

Encoder/Decoder Pairs

Suppose we have some set $\mathcal{S} = \{1, 2, \ldots, S\}$ of possible messages

- e.g. codewords from Huffman coding on some ensemble

- Sender and receiver agree on what these are

When communicating over a channel, the sender must encode messages into some input alphabet $\mathcal{X}$

The receiver then receives some (possibly corrupted) element from an output alphabet $\mathcal{Y}$

- Simple case: $\mathcal{X} = \mathcal{Y} = \{0, 1\}$

- The bit the sender transmits may not be what the receiver sees

Encoder/Decoder Pairs

Formally, the sender encodes messages via

$$\mathtt{enc} : \mathcal{S} \to \mathcal{X}^N$$

Encoder/Decoder Pairs

Formally, the sender encodes messages via

$$\texttt{enc}: \mathcal{S} \to \mathcal{X}^N$$

The receiver then decodes messages via

$$\texttt{dec}: \mathcal{Y}^N \to \mathcal{S}$$

Encoder/Decoder Pairs

Formally, the sender encodes messages via

$$\texttt{enc} : \mathcal{S} \to \mathcal{X}^N$$

The receiver then decodes messages via

$$\texttt{dec} : \mathcal{Y}^N \to \mathcal{S}$$

Isn't the compressor already "encoding" a message?

- Yes, but we might want to add something for noise tolerance

Might have $\mathcal{X} \neq \mathcal{Y}$

- e.g. if we allow a special "erased" symbol

$N > 1$ can be thought of as multiple uses of a channel

- e.g. use a bitstring of length 4 to represent messages

Channels: Informally

A **discrete channel** Q will:

- accept an **input** from $\mathcal{X}$
- produce an **output** from $\mathcal{Y}$

Channels: Informally

A **discrete channel** Q will:

- accept an **input** from $\mathcal{X}$
- produce an **output** from $\mathcal{Y}$

There is a **probability** of observing various outputs, given an input

- This represents some inherent noise
- Noise could depend on the input

Channels: Formally

A **discrete channel** Q consists of:

- an *input alphabet* $\mathcal{X} = \{a_1, \ldots, a_I\}$
- an *output alphabet* $\mathcal{Y} = \{b_1, \ldots, b_J\}$
- *transition probabilities* $P(y|x)$

Channels: Formally

A **discrete channel** Q consists of:

- an *input alphabet* $\mathcal{X} = \{a_1, \ldots, a_I\}$
- an *output alphabet* $\mathcal{Y} = \{b_1, \ldots, b_J\}$
- *transition probabilities* $P(y|x)$

The channel Q can be expressed as a matrix

$$Q_{j,i} = P(y = b_j | x = a_i)$$

This represents the probability of observing b_j given that we transmit a_i

Channels: Example

Example: A channel Q with inputs $\mathcal{X} = \{a_1, a_2, a_3\}$, outputs $\mathcal{Y} = \{b_1, b_2\}$, and transition probabilities expressed by the matrix

$$Q = \begin{bmatrix} 0.8 & 0.5 & 0.2 \\ 0.2 & 0.5 & 0.8 \end{bmatrix}$$

So $P(b_1|a_1) = 0.8 = P(b_2|a_3)$ and $P(b_1|a_2) = P(b_2|a_2) = 0.5$.

Channels: Example

Example: A channel Q with inputs $\mathcal{X} = \{a_1, a_2, a_3\}$, outputs $\mathcal{Y} = \{b_1, b_2\}$, and transition probabilities expressed by the matrix

$$Q = \begin{bmatrix} 0.8 & 0.5 & 0.2 \\ 0.2 & 0.5 & 0.8 \end{bmatrix}$$

So $P(b_1|a_1) = 0.8 = P(b_2|a_3)$ and $P(b_1|a_2) = P(b_2|a_2) = 0.5$.

We arrange the inputs along the columns, and outputs along the rows

Actual details of alphabet are abstracted away

1. Communication over Noisy Channels: Big Picture
2. Noisy Channels: Formally
3. Examples of Channels
4. Probability of Error

The Binary Noiseless Channel

One of the simplest channels is the **Binary Noiseless Channel**. The received symbol is always equal to the transmitted symbol – there is no probability of error, hence *noiseless*.

Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, 1\}$;
Transition probabilities

$$Q = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

The Binary Noiseless Channel

One of the simplest channels is the **Binary Noiseless Channel**. The received symbol is always equal to the transmitted symbol – there is no probability of error, hence *noiseless*.

Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, 1\}$;
Transition probabilities

$$Q = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

What was transmitted over the channel if `0000 1111` was received?

$$\xrightarrow{Q} \texttt{0000 1111}$$

The Binary Noiseless Channel

One of the simplest channels is the **Binary Noiseless Channel**. The received symbol is always equal to the transmitted symbol – there is no probability of error, hence *noiseless*.

Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, 1\}$;
Transition probabilities

$$Q = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

What was transmitted over the channel if `0000 1111` was received?

$$\texttt{0000 1111} \xrightarrow{Q} \texttt{0000 1111}$$

The Noisy Non-overlapping Channel

Even if there is some uncertainty about the output given the input, it may still be possible to perfectly infer what was transmitted.

Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{\mathtt{a}, \mathtt{b}, \mathtt{c}, \mathtt{d}\}$; Transition probabilities

$$Q = \begin{bmatrix} 0.5 & 0 \\ 0.5 & 0 \\ 0 & 0.5 \\ 0 & 0.5 \end{bmatrix}$$

The Noisy Non-overlapping Channel

Even if there is some uncertainty about the output given the input, it may still be possible to perfectly infer what was transmitted.

Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{\mathtt{a}, \mathtt{b}, \mathtt{c}, \mathtt{d}\}$; Transition probabilities

$$Q = \begin{bmatrix} 0.5 & 0 \\ 0.5 & 0 \\ 0 & 0.5 \\ 0 & 0.5 \end{bmatrix}$$

What was transmitted over the channel if `abba ddcd` was received?

$$\xrightarrow{Q} \texttt{abba ddcd}$$

The Noisy Non-overlapping Channel

Even if there is some uncertainty about the output given the input, it may still be possible to perfectly infer what was transmitted.

Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{\mathtt{a}, \mathtt{b}, \mathtt{c}, \mathtt{d}\}$; Transition probabilities

$$Q = \begin{bmatrix} 0.5 & 0 \\ 0.5 & 0 \\ 0 & 0.5 \\ 0 & 0.5 \end{bmatrix}$$

What was transmitted over the channel if `abba ddcd` was received?

$$0000\ 1111 \xrightarrow{Q} \mathtt{abba\ ddcd}$$

The Binary Symmetric Channel

Each symbol sent across a **binary symmetric channel** has a chance of being "flipped" to its counterpart ($0 \to 1$; $1 \to 0$)



Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, 1\}$;
Transition probabilities with $P(\text{flip}) = f$

$$Q = \begin{bmatrix} 1-f & f \\ f & 1-f \end{bmatrix}$$

The Binary Symmetric Channel

Each symbol sent across a **binary symmetric channel** has a chance of being "flipped" to its counterpart ($0 \to 1$; $1 \to 0$)



Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, 1\}$;
Transition probabilities with $P(\text{flip}) = f$

$$Q = \begin{bmatrix} 1-f & f \\ f & 1-f \end{bmatrix}$$

What was most likely transmitted over the channel if 0010 1001 was received, assuming $f = 0.1$ and $P(x = 0) = P(x = 1) = 0.5$?

$$\xrightarrow{Q} 0010\,1001$$

The Binary Symmetric Channel

Each symbol sent across a **binary symmetric channel** has a chance of being "flipped" to its counterpart ($0 \to 1$; $1 \to 0$)



Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, 1\}$;
Transition probabilities with $P(\text{flip}) = f$

$$Q = \begin{bmatrix} 1-f & f \\ f & 1-f \end{bmatrix}$$

What was most likely transmitted over the channel if 0010 1001 was received, assuming $f = 0.1$ and $P(x = 0) = P(x = 1) = 0.5$?

$$0010\,1001 \xrightarrow{Q} 0010\,1001$$

Inferring the Input

Suppose we know the $P(x)$ — the probability x is transmitted.

Given a particular output $y \in \mathcal{Y}$ received over a channel Q, how likely was it that input $x \in \mathcal{X}$ was transmitted?

Inferring the Input

Suppose we know the $P(x)$ — the probability x is transmitted.

Given a particular output $y \in \mathcal{Y}$ received over a channel Q, how likely was it that input $x \in \mathcal{X}$ was transmitted?

$$P(x|y) = \frac{P(y|x)P(x)}{P(y)} = \frac{P(y|x)P(x)}{\sum_{x' \in \mathcal{X}} P(y|x')P(x')}$$

Inferring the Input: Example

Suppose $P(x = 0) = P(x = 1) = 0.5$. What are the probability that a $x = 0$ was transmitted over a *binary symmetric channel* Q with $f = 0.1$ given that a $y = 0$ was received?

Inferring the Input: Example

Suppose $P(x = 0) = P(x = 1) = 0.5$. What are the probability that a $x = 0$ was transmitted over a *binary symmetric channel* Q with $f = 0.1$ given that a $y = 0$ was received?

$$P(x = 0|y = 0) = \frac{0.9 \times 0.5}{0.9 \times 0.5 + 0.1 \times 0.5} = 0.9$$

Similarly, $P(x = 1|y = 1) = 0.9$.

Inferring the Input: Example

Suppose $P(x = 0) = P(x = 1) = 0.5$. What are the probability that a $x = 0$ was transmitted over a *binary symmetric channel* Q with $f = 0.1$ given that a $y = 0$ was received?

$$P(x = 0|y = 0) = \frac{0.9 \times 0.5}{0.9 \times 0.5 + 0.1 \times 0.5} = 0.9$$

Similarly, $P(x = 1|y = 1) = 0.9$.

What if $P(x = 0) = 0.01$?

Inferring the Input: Example

Suppose $P(x = 0) = P(x = 1) = 0.5$. What are the probability that a $x = 0$ was transmitted over a *binary symmetric channel* Q with $f = 0.1$ given that a $y = 0$ was received?

$$P(x = 0|y = 0) = \frac{0.9 \times 0.5}{0.9 \times 0.5 + 0.1 \times 0.5} = 0.9$$

Similarly, $P(x = 1|y = 1) = 0.9$.

What if $P(x = 0) = 0.01$?

$$P(x = 0|y = 0) = \frac{0.9 \times 0.01}{0.9 \times 0.01 + 0.1 \times 0.99} \approx 0.0833.$$

The Z Channel

Symbols may be corrupted over the channel asymmetrically.

Inputs $\mathcal{A} = \{0, 1\}$; Outputs $\mathcal{B} = \{0, 1\}$

Transition probabilities



$$Q = \begin{bmatrix} 1 & f \\ 0 & 1-f \end{bmatrix}$$

The Z Channel

Symbols may be corrupted over the channel asymmetrically.

Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, 1\}$

Transition probabilities



$$Q = \begin{bmatrix} 1 & f \\ 0 & 1-f \end{bmatrix}$$

Inferring the input: Clearly $P(x = 1|y = 1) = 1$ but

$$P(x = 0|y = 0) = \frac{P(y = 0|x = 0)P(x = 0)}{\sum_{x' \in \mathcal{X}} P(y = 0|x')P(x')} = \frac{P(x = 0)}{P(x = 0) + f\,P(x = 1)}$$

So $P(x = 0|y = 0) \to 1$ as $f \to 0$, and goes to $P(x = 0)$ as $f \to 1$

The Binary Erasure Channel

We can model a channel which “erases” bits by letting one of the output symbols be the symbol ’?’ with associated probability f. The receiver knows which bits are erased.



Inputs $\mathcal{X} = \{0, 1\}$; Outputs $\mathcal{Y} = \{0, ?, 1\}$;
Transition probabilities

$$Q = \begin{bmatrix} 1-f & 0 \\ f & f \\ 0 & 1-f \end{bmatrix}$$

Example:

$$0000\,1111 \xrightarrow{Q} 00?0\,?11?$$

The Noisy Typewriter Channel

This channel simulates a noisy "typewriter". Inputs and outputs are 26 letters A through Z plus space. With probability $\frac{1}{3}$, each letter is either: unchanged; changed to the next letter; changed to the previous letter.

The Noisy Typewriter Channel

This channel simulates a noisy "typewriter". Inputs and outputs are 26 letters A through Z plus space. With probability $\frac{1}{3}$, each letter is either: unchanged; changed to the next letter; changed to the previous letter.



Inputs $\mathcal{X} = \{\mathtt{A}, \mathtt{B}, \ldots, \mathtt{Z}, \_\}$;

Outputs $\mathcal{Y} = \{\mathtt{A}, \mathtt{B}, \ldots, \mathtt{Z}, \_\}$;

Transition probabilities

$$Q = \begin{bmatrix} \frac{1}{3} & \frac{1}{3} & 0 & 0 & \cdots & 0 & \frac{1}{3} \\ \frac{1}{3} & \frac{1}{3} & \frac{1}{3} & 0 & \cdots & 0 & 0 \\ 0 & \frac{1}{3} & \frac{1}{3} & \frac{1}{3} & \cdots & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots & \vdots \\ \frac{1}{3} & 0 & 0 & & \cdots & \frac{1}{3} & \frac{1}{3} \end{bmatrix}$$

The Noisy Typewriter Channel

This channel simulates a noisy "typewriter". Inputs and outputs are 26 letters A through Z plus space. With probability $\frac{1}{3}$, each letter is either: unchanged; changed to the next letter; changed to the previous letter.



Inputs $\mathcal{X} = \{\mathtt{A}, \mathtt{B}, \ldots, \mathtt{Z}, \_\}$;

Outputs $\mathcal{Y} = \{\mathtt{A}, \mathtt{B}, \ldots, \mathtt{Z}, \_\}$;

Transition probabilities

$$Q = \begin{bmatrix} \frac{1}{3} & \frac{1}{3} & 0 & 0 & \cdots & 0 & \frac{1}{3} \\ \frac{1}{3} & \frac{1}{3} & \frac{1}{3} & 0 & \cdots & 0 & 0 \\ 0 & \frac{1}{3} & \frac{1}{3} & \frac{1}{3} & \cdots & 0 & 0 \\ \vdots & \vdots & \vdots & \vdots & \ddots & \vdots & \vdots \\ \frac{1}{3} & 0 & 0 & & \cdots & \frac{1}{3} & \frac{1}{3} \end{bmatrix}$$

The transition matrix for this channel has a diagonal structure: all of the probability mass is concentrated around the diagonal.

The Noisy Typewriter Channel

This channel simulates a noisy "typewriter". Inputs and outputs are 26 letters A through Z plus space. With probability $\frac{1}{3}$, each letter is either: unchanged; changed to the next letter; changed to the previous letter.

Inputs $\mathcal{X} = \{\mathtt{A}, \mathtt{B}, \ldots, \mathtt{Z}, \_\}$;

Outputs $\mathcal{Y} = \{\mathtt{A}, \mathtt{B}, \ldots, \mathtt{Z}, \_\}$;

Transition probabilities





The transition matrix for this channel has a diagonal structure: all of the probability mass is concentrated around the diagonal.

1 Communication over Noisy Channels: Big Picture
2 Noisy Channels: Formally
3 Examples of Channels
4 Probability of Error

Communicating over Noisy Channels

Suppose we know we have to communicate over some channel Q and we want build an *encoder*/*decoder* pair to reliably send a message $\mathbf{s}$ over Q.



Communicating over Noisy Channels

Suppose we know we have to communicate over some channel Q and we want build an *encoder*/*decoder* pair to reliably send a message $\mathbf{s}$ over Q:



Reliability is measured via **probability of error** — that is, the probability of incorrectly decoding $\mathbf{s}_{out}$ given $\mathbf{s}_{in}$ as input:

$$P(\mathbf{s}_{out} \neq \mathbf{s}_{in}) = \sum_{\mathbf{s}} P(\mathbf{s}_{out} \neq \mathbf{s}_{in} | \mathbf{s}_{in} = \mathbf{s}) P(\mathbf{s}_{in} = \mathbf{s})$$

Probability of Error: Example

Let $S = \{a, b\}$ and $S' = \mathcal{Y} = \{0, 1\}$

Assume *encoder*: $\mathtt{a} \to 0$; $\mathtt{b} \to 1$, *decoder*: $0 \to \mathtt{a}$; $1 \to \mathtt{b}$.

Consider binary symmetric Q,

$$Q = \begin{bmatrix} 1-f & f \\ f & 1-f \end{bmatrix}$$

with $f = 0.1$

Probability of Error: Example

If base probabilities of symbol transmission are $(p_{\mathtt{a}}, p_{\mathtt{b}}) = (0.5, 0.5)$,

$$P(\mathbf{s}_{in} \neq \mathbf{s}_{out}) = P(\mathbf{s}_{in} = \mathtt{a}, \mathbf{s}_{out} = \mathtt{b}) + P(\mathbf{s}_{in} = \mathtt{b}, \mathbf{s}_{out} = \mathtt{a})$$

Probability of Error: Example

If base probabilities of symbol transmission are $(p_{\mathtt{a}}, p_{\mathtt{b}}) = (0.5, 0.5)$,

$$P(\mathbf{s}_{in} \neq \mathbf{s}_{out}) = P(\mathbf{s}_{in} = \mathtt{a}, \mathbf{s}_{out} = \mathtt{b}) + P(\mathbf{s}_{in} = \mathtt{b}, \mathbf{s}_{out} = \mathtt{a})$$
$$= P(\mathbf{s}_{out} = \mathtt{b}|\mathbf{s}_{in} = \mathtt{a})P(\mathbf{s}_{in} = \mathtt{a}) +$$
$$P(\mathbf{s}_{out} = \mathtt{a}|\mathbf{s}_{in} = \mathtt{b})P(\mathbf{s}_{in} = \mathtt{b})$$

Probability of Error: Example

If base probabilities of symbol transmission are $(p_a, p_b) = (0.5, 0.5)$,

$$P(\mathbf{s}_{in} \neq \mathbf{s}_{out}) = P(\mathbf{s}_{in} = a, \mathbf{s}_{out} = b) + P(\mathbf{s}_{in} = b, \mathbf{s}_{out} = a)$$
$$= P(\mathbf{s}_{out} = b|\mathbf{s}_{in} = a)P(\mathbf{s}_{in} = a) +$$
$$P(\mathbf{s}_{out} = a|\mathbf{s}_{in} = b)P(\mathbf{s}_{in} = b)$$
$$= P(y = 1|x = 0)\, p_a + P(y = 0|x = 1)\, p_b$$

Probability of Error: Example

If base probabilities of symbol transmission are $(p_a, p_b) = (0.5, 0.5)$,

$$P(\mathbf{s}_{in} \neq \mathbf{s}_{out}) = P(\mathbf{s}_{in} = a, \mathbf{s}_{out} = b) + P(\mathbf{s}_{in} = b, \mathbf{s}_{out} = a)$$
$$= P(\mathbf{s}_{out} = b|\mathbf{s}_{in} = a)P(\mathbf{s}_{in} = a) +$$
$$P(\mathbf{s}_{out} = a|\mathbf{s}_{in} = b)P(\mathbf{s}_{in} = b)$$
$$= P(y = 1|x = 0)\, p_a + P(y = 0|x = 1)\, p_b$$
$$= f$$

Probability of Error: Example

If base probabilities of symbol transmission are $(p_a, p_b) = (0.5, 0.5)$,

$$
\begin{aligned}
P(\mathbf{s}_{in} \neq \mathbf{s}_{out}) &= P(\mathbf{s}_{in} = a, \mathbf{s}_{out} = b) + P(\mathbf{s}_{in} = b, \mathbf{s}_{out} = a) \\
&= P(\mathbf{s}_{out} = b|\mathbf{s}_{in} = a)P(\mathbf{s}_{in} = a) + \\
&\quad P(\mathbf{s}_{out} = a|\mathbf{s}_{in} = b)P(\mathbf{s}_{in} = b) \\
&= P(y = 1|x = 0)\, p_a + P(y = 0|x = 1)\, p_b \\
&= f \\
&= 0.1
\end{aligned}
$$

A Simple Coding Scheme

Suppose $\mathbf{s} \in \{\mathtt{a}, \mathtt{b}\}$ and we encode by $\mathtt{a} \to \mathtt{000}$ and $\mathtt{b} \to \mathtt{111}$.
To decode we count the number of $\mathtt{1}$s and $\mathtt{0}$s and set all bits to the majority count to determine $\mathbf{s}$.

$$\underbrace{\mathtt{000}, \mathtt{001}, \mathtt{010}, \mathtt{100}}_{A} \to \mathtt{a} \quad \text{and} \quad \underbrace{\mathtt{111}, \mathtt{110}, \mathtt{101}, \mathtt{011}}_{B} \to \mathtt{b}$$

A Simple Coding Scheme

Suppose $\mathbf{s} \in \{\mathtt{a}, \mathtt{b}\}$ and we encode by $\mathtt{a} \to \mathtt{000}$ and $\mathtt{b} \to \mathtt{111}$.
To decode we count the number of $\mathtt{1}$s and $\mathtt{0}$s and set all bits to the majority count to determine $\mathbf{s}$

$$\underbrace{\mathtt{000}, \mathtt{001}, \mathtt{010}, \mathtt{100}}_{A} \to \mathtt{a} \quad \text{and} \quad \underbrace{\mathtt{111}, \mathtt{110}, \mathtt{101}, \mathtt{011}}_{B} \to \mathtt{b}$$

If the channel Q is binary symmetric with $f = 0.1$ again

$$\begin{aligned} P(\mathbf{s}_{in} \neq \mathbf{s}_{out}) &= P(\mathbf{y} \in B|000)\, p_{\mathtt{a}} + P(\mathbf{y} \in A|111)\, p_{\mathtt{b}} \\ &= [f^3 + 3f^2(1-f)]p_{\mathtt{a}} + [f^3 + 3f^2(1-f)]p_{\mathtt{b}} \\ &= f^3 + 3f^2(1-f) = 0.028 \end{aligned}$$

A Simple Coding Scheme

Suppose $\mathbf{s} \in \{\mathtt{a}, \mathtt{b}\}$ and we encode by $\mathtt{a} \to \mathtt{000}$ and $\mathtt{b} \to \mathtt{111}$.
To decode we count the number of $\mathtt{1}$s and $\mathtt{0}$s and set all bits to the majority count to determine $\mathbf{s}$.

$$\underbrace{\mathtt{000}, \mathtt{001}, \mathtt{010}, \mathtt{100}}_{A} \to \mathtt{a} \quad \text{and} \quad \underbrace{\mathtt{111}, \mathtt{110}, \mathtt{101}, \mathtt{011}}_{B} \to \mathtt{b}$$

If the channel Q is binary symmetric with $f = 0.1$ again

$$\begin{aligned} P(\mathbf{s}_{in} \neq \mathbf{s}_{out}) &= P(\mathbf{y} \in B|000)\, p_{\mathtt{a}} + P(\mathbf{y} \in A|111)\, p_{\mathtt{b}} \\ &= [f^3 + 3f^2(1-f)]p_{\mathtt{a}} + [f^3 + 3f^2(1-f)]p_{\mathtt{b}} \\ &= f^3 + 3f^2(1-f) = 0.028 \end{aligned}$$

So the *error* has dropped from 0.1 to 0.028
but so has the *rate*: from 1 symbol/bit to 1/3 symbol/bit.

A Simple Coding Scheme



A Simple Coding Scheme



Can we make the error arbitrarily small without the rate going to zero?

Summary and Reading

Main Points:

- Modelling Noisy Channels
  - Noiseless, Overlap, Symmetric, Z, Erasure
- Simple Coding via Repetition
  - Probability of Error vs Transmission Rate

Reading:

- MacKay §9.1 - §9.5
- Cover & Thomas §7.1 - §7.3